

CSS JAVASCRIPT SQL PYTHON JAVA PHP HOW TO W3.CSS C

JavaScript Window Location

Previous

Next >

The window.location object can be used to get the current page address (URL) and to redirect the browser to a new page.

Window Location

The window.location object can be written without the window prefix.

Some examples:

- window.location.href returns the href (URL) of the current page
- window.location.hostname returns the domain name of the web host
- window.location.pathname returns the path and filename of the current page
- window.location.protocol returns the web protocol used (http: or https:)
- window.location.assign() loads a new document

Window Location Href

The window.location.href property returns the URL of the current page.

Example

Display the href (URL) of the current page:

```
document.getElementById("demo").innerHTML =
"Page location is " + window.location.href;
```



Try it Yourself »

Window Location Hostname

The window.location.hostname property returns the name of the internet host (of the current page).

Example

Display the name of the host:

```
document.getElementById("demo").innerHTML =
"Page hostname is " + window.location.hostname;
```

Result is:

Page hostname is www.w3schools.com

Try it Yourself »

PYTHON

JAVA

PHP

HOW TO

W3.CSS

SQL

Example

CSS

Display the path name of the current URL:

JAVASCRIPT

```
document.getElementById("demo").innerHTML =
"Page path is " + window.location.pathname;
```

Result is:

```
Page path is /js/js_window_location.asp
```

Try it Yourself »

Window Location Protocol

The window.location.protocol property returns the web protocol of the page.

Example

Display the web protocol:

```
document.getElementById("demo").innerHTML =
"Page protocol is " + window.location.protocol;
```

Result is:

Page protocol is https:

Try it Yourself »

Window Location Port

JAVASCRIPT SQL PYTHON JAVA PHP HOW TO

W3.CSS

Example

CSS

Display the name of the host:

```
document.getElementById("demo").innerHTML =
   "Port number is " + window.location.port;

Result is:
   Port number is

   Try it Yourself »
```

Most browsers will not display default port numbers (80 for http and 443 for https)

Window Location Assign

The window.location.assign() method loads a new document.

Example

Load a new document:

```
<html>
<head>
<script>
function newDoc() {
   window.location.assign("https://www.w3schools.com")
}
</script>
</head>
<body>
<input type="button" value="Load new document" onclick="newDoc()">
```



Try it Yourself »

< Previous</p>

Next >

Track your progress - it's free!

Sign Up Log in



COLOR PICKER











PLUS SPACES

GET CERTIFIED

FOR TEACHERS

Log in

FOR BUSINESS

CONTACT US

Top Tutorials

HTML Tutorial
CSS Tutorial
JavaScript Tutorial
How To Tutorial
SQL Tutorial
Python Tutorial
W3.CSS Tutorial
Bootstrap Tutorial
PHP Tutorial
Java Tutorial
C++ Tutorial
jQuery Tutorial

Top References

HTML Reference
CSS Reference
JavaScript Reference
SQL Reference
Python Reference
W3.CSS Reference
Bootstrap Reference
PHP Reference
HTML Colors
Java Reference
Angular Reference
jQuery Reference

Top Examples

HTML Examples CSS Examples JavaScript Examples How To Examples SQL Examples Python Examples W3.CSS Examples

Get Certified

HTML Certificate
CSS Certificate
JavaScript Certificate
Front End Certificate
SQL Certificate
Python Certificate
PHP Certificate



=

Tutorials **▼** Exercises **▼** Services **▼** Q Sign Up Log in

CSS JAVASCRIPT

SQL PYTHON JAVA PHP

HOW TO W3.CSS

С





FORUM ABOUT ACADEMY

W3Schools is optimized for learning and training. Examples might be simplified to improve reading and learning.

Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness

of all content. While using W3Schools, you agree to have read and accepted our terms of use, cookie and privacy policy.

Copyright 1999-2025 by Refsnes Data. All Rights Reserved. W3Schools is Powered by W3.CSS.