# JavaScript Object Prototypes

\ Previous

Next >

All JavaScript objects inherit properties and methods from a prototype.

In the previous chapter we learned how to use an **object constructor**:

## Example

```
function Person(first, last, age, eyecolor) {
   this.firstName = first;
   this.lastName = last;
   this.age = age;
   this.eyeColor = eyecolor;
}

const myFather = new Person("John", "Doe", 50, "blue");
const myMother = new Person("Sally", "Rally", 48, "green");
```

We also learned that you can **not** add a new property to an existing object constructor:

### Example

Try it Yourself »

```
Person.nationality = "English";
```

CSS JAVASCRIPT SQL PYTHON JAVA

PHP

To add a new property to a constructor, you must add it to the constructor function:

### Example

```
function Person(first, last, age, eyecolor) {
 this.firstName = first;
 this.lastName = last;
 this.age = age;
 this.eyeColor = eyecolor;
 this.nationality = "English";
```

Try it Yourself »

## Prototype Inheritance

All JavaScript objects inherit properties and methods from a prototype:

- Date objects inherit from Date.prototype
- Array objects inherit from Array.prototype
- Person objects inherit from Person.prototype

The Object.prototype is on the top of the prototype inheritance chain:

JAVASCRIPT SQL PYTHON JAVA PHP HOW TO W3.CSS

## Adding Properties and Methods to Objects

Sometimes you want to add new properties (or methods) to all existing objects of a given type.

Sometimes you want to add new properties (or methods) to an object constructor.

## Using the **prototype** Property

The JavaScript prototype property allows you to add new properties to object constructors:

## Example

```
function Person(first, last, age, eyecolor) {
 this.firstName = first;
 this.lastName = last;
 this.age = age;
 this.eyeColor = eyecolor;
}
Person.prototype.nationality = "English";
```

Try it Yourself »

The JavaScript prototype property also allows you to add new methods to objects constructors:

## Example

```
function Person(first, last, age, eyecolor) {
 this.firstName = first;
 this.lastName = last;
  this.age = age;
  this.eyeColor = eyecolor;
```



Try it Yourself »

Only modify your **own** prototypes. Never modify the prototypes of standard JavaScript objects.

\ Previous

Next >

Track your progress - it's free!

Sign Up Log in



**COLOR PICKER** 



Tutorials **▼** 

Exercises **▼** 

Services ▼ Q

Sign Up

Log in

= .

CSS JAVASCRIPT SQL

PYTHON

JAVA

PHP

HOW TO

W3.CSS

C













**PLUS** 

**SPACES** 

**GET CERTIFIED** 

**FOR TEACHERS** 

**FOR BUSINESS** 

**CONTACT US** 

### **Top Tutorials**

**HTML Tutorial CSS Tutorial** JavaScript Tutorial How To Tutorial **SQL Tutorial Python Tutorial W3.CSS Tutorial Bootstrap Tutorial PHP Tutorial** Java Tutorial C++ Tutorial jQuery Tutorial

#### **Top References**

**HTML Reference CSS Reference** JavaScript Reference **SQL** Reference **Python Reference W3.CSS** Reference **Bootstrap Reference** PHP Reference **HTML Colors** Java Reference



CSS JAVASCRIPT

SQL

PYTHON

JAVA

PHP

HOW TO

W3.CSS

C

 $\equiv$ 

CSS Examples
JavaScript Examples
How To Examples
SQL Examples
Python Examples
W3.CSS Examples
Bootstrap Examples
PHP Examples
Java Examples

XML Examples

jQuery Examples

VA PI

CSS Certificate
JavaScript Certificate
Front End Certificate
SQL Certificate
Python Certificate
PHP Certificate
jQuery Certificate
Java Certificate
C++ Certificate
C# Certificate
XML Certificate



#### FORUM ABOUT ACADEMY

W3Schools is optimized for learning and training. Examples might be simplified to improve reading and learning.

Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness

of all content. While using W3Schools, you agree to have read and accepted our <u>terms of</u> <u>use</u>, <u>cookie and privacy policy</u>.

Copyright 1999-2025 by Refsnes Data. All Rights Reserved. W3Schools is Powered by W3.CSS.