



Luigi Berrettini May 26
@luigiberrettini

Follow

Deep dive on [#permissions](#) and [@docker #volumes](#)
[github.com/rocker-org/roc ...](#)
[github.com/rocker-org/roc ...](#)
[denibertovic.com/posts/handling ...](#)



rocker-org/rocker


R configurations for Docker. Contribute to rocker development by creating an ac...
[github.com](#)

12:14 AM - 26 May 2016



Luigi Berrettini @luigiberrettini · May 26

Creating a container user and group from the docker-entrpoint.sh passing their IDs as [@docker](#) run environment vars



kylemanna/docker-aosp

docker-aosp - Minimal build environment for AOSP with handy automation wra...
[github.com](#)



Luigi Berrettini @luigiberrettini · May 26

Most elegant solution (similar) in [@microsoft #dotnetcore](#) CLI tools [@docker](#) scripts
[github.com/docker/docker/...](#)



dotnet/cli

cli - This repo contains the .NET Core command-line (CLI) tools, used for buildi...
[github.com](#)





Luigi Berrettini @luigiberrettini · May 26

Using chown [@docker](#)



Make uid & gid configurable for shared volumes · Issue #7198 · docker/d...

Please provide an option to make ownership of shared volumes configurable. F...
[github.com](#)



Luigi Berrettini @luigiberrettini · May 26

Setting user with [@docker](#) run



Volumes are created in container with root ownership and strict permissi...

The emptyDir volumeMount is owned by root:root and permissions set to 750 h...
[github.com](#)



Luigi Berrettini @luigiberrettini · May 26

Set gid not to have a [@docker](#) container's root user owning host files
[renzok.github.io/2015/09/20/doc...](#)

