Whistle and Wrong Lyrics: Synthetic Queries Are Not Enough for Real-World Query-by-Melody

Luigi Rivolta
Independent Researcher
EMAIL@PLACEHOLDER

October 2026

Abstract

People look up a song by humming it, but also by whistling it or singing it with the wrong words. Published query-by-humming systems and benchmarks focus on hums and sung queries; whistles and wrong-lyrics singing are rarely studied, and no public dataset pairs them with song recordings. We study both query types with a melody-only retrieval system: a key-normalized pitch track (F0) embedded by a 5.2M-parameter contour encoder, with a spectral-peak tracker for whistles. We make three contributions. First, a physics-grounded synthetic query generator that renders whistles (a near-sinusoid with a weak second harmonic, placed in the human whistle register) and nonsense-syllable singing (a source-filter voice) from the vocal melodies of 11,083 songs, then re-tracks each rendering with the tracker a real query would get. Second, a controlled study over three training rounds. Training on these queries raises top-1 retrieval of held-out synthetic queries against an 11,050-song gallery from 0.180 to 0.251 for whistles and from 0.193 to 0.264 for wrong-lyrics singing, at a hum cost of under one point. The gain does not transfer to real whistles: on the MLEnd test performers the best synthetic-only model gets 210 of 339 whistles right at top-1, against 214 for the baseline. Adding real whistles of 6 of the 8 test tunes to training helps those tunes and drops the 2 held-out tunes from 53 to 41 of 90, and a saturated selection metric silently returned the starting weights in the first round. Third, a scoped, closed-set real-whistle evaluation on MLEnd's 8 songs. Code is public; models and data will be released.

1 Introduction

When a tune is stuck in your head you often do not know the words. You whistle it, or sing it with whatever words come to mind. The retrieval problem is the same each time: find the recording whose melody matches the query's melody, whatever the timbre, words, key and tempo.

Google's Hum to Search reports that a model trained mostly on sung clips "worked well enough for people singing, but not for people humming or whistling" [6]. The open query-by-humming (QbH) literature, including CHAD [1] and ByteHum [5], evaluates hummed and sung queries, not whistles. We found no public dataset of whistled or wrong-lyrics queries paired with the song recordings.

Why whistles are hard. A whistle is a different sound source from the voice (Section 3): it is close to a pure tone and sits about three octaves above a hum. A vocal pitch model can report it an octave low, and people whistle a compressed version of the tune.

Why wrong lyrics matter. A spectrogram model can learn to use lyrics and timbre, which a wrong-lyrics query does not share with the recording. A melody-only model cannot use them by design. What stays hard is that made-up words change the voiced/unvoiced pattern and add consonant breaks that a pitch tracker turns into gaps and glitches.

Contributions.

1. A physics-grounded synthetic query generator for whistles and nonsense-syllable singing, locked frame by frame to the vocal melody of real songs and re-tracked with the tracker a real query would get (Section 5).
2. A controlled study of synthetic-query training over three rounds (D-040, D-041, D-042). It improves synthetic-query retrieval by about 7 top-1 points across 11k songs but does not transfer to real whistles. It also documents two pitfalls: training on real whistles of the test tunes teaches the tunes, not whistling, and a saturated selection metric returns the starting checkpoint (Sections 7–8).
3. A scoped, closed-set real-whistle evaluation on the 8 songs of MLEnd Hums and Whistles [13] (Section 7.3).
4. An open-source release (Section 10).

Throughout, results on generated queries are marked [SYNTHETIC], results on recordings of people are marked [REAL], and single hand-picked examples are marked [BEST CASE]. Every number comes from a result file in the repository; decision identifiers (D-xxx) refer to entries in the project's decision log.

2 Related work

Commercial and large-scale QbH. Google Hum to Search [6] (a blog post, with no published accuracy) embeds spectrograms of queries and recordings with metric learning. Its first training set was mostly sung; synthetic hums were then generated from SPICE pitch [7], first as discrete tones and later with an unpublished neural generator. ByteHum [5] trains a CNN on raw audio with weak supervision from source-separated cover songs and unsupervised domain adaptation toward hums, and re-annotates three QbH benchmarks with original recordings. We could not read its full text and report none of its numbers.

CHAD. Amatov et al. [1] collect time-aligned cover fragments with a semi-supervised pipeline plus crowdsourced hums, and train ResNet18 on CREPE [10] F0 activations or CQT with NT-Xent. With CREPE features they report top-10 0.921 on MIR-QBSH against about 2,600 MIDI references and 0.883 on MTG-QBH with 1,886 imposter songs. They note that "the pure search-by-humming setup requires adding a portion of real humming data". Our negative result is the whistle analogue of that remark.

Query-by-whistling. Shen and Lee [18] built "Whistle for Music", which transcribes whistles to MIDI and uses approximate string matching. Dias et al. [4] compare pitch detectors for whistle transcription. Nilsson et al. [14] report a typical human whistle range of 500–5,000 Hz. These systems transcribe to notes and match symbols; none learns a joint embedding with real song recordings.

Datasets. HumTrans [12]: about 56 hours of hums of 1,000 segments with MIDI labels and official splits. MIR-QBSH [8, 9]: 4,431 hummed or sung queries of 48 MIDI songs. MLEnd Hums and Whistles [13]: hums and whistles of 8 songs from about 200 people, with no song recordings. MTG-QBH [16]: 118 sung queries; the collection audio is not distributed.

Models and losses. MERT [11] is a self-supervised music audio model; we use MERT-v1-95M as a baseline. RMVPE [19] estimates vocal pitch from mixtures. CLEWS [17] is a segment-level contrastive loss for version matching, which we use for query-to-song windows. Neural singing synthesizers such as SoulX-Singer [15], whose melody-control mode takes lyrics and a continuous F0 contour, and Vevo2 [20] could replace our simple singer; neither was used here.

3 Signals

All signal physics used in the paper is defined here once and referenced as S1–S8.

S1. F0 and pitch. A periodic sound has a fundamental frequency f_0 and harmonics at kf_0. Pitch in semitones is $p = 12\log_2(f_0/440\,\text{Hz}) + 69$. An F0 track is p (or unvoiced) every 10 ms.

S2. Two sources. A voice (sung, hummed) is a harmonic source shaped by a vocal-tract filter: many harmonics with resonances (formants). A whistle is a near-sinusoid: on 1,702 MLEnd whistles the median second harmonic is -45.0 dB relative to the fundamental.

S3. Spectral peak. For a whistle the strongest spectral peak is f_0. For a voice it is often a formant-boosted harmonic, so the peak is not f_0.

S4. Ranges. Human whistles typically lie in 500–5,000 Hz [14]. On MLEnd the median hum is 178.7 Hz and the median whistle about 1.34–1.36 kHz; the same performer whistles a median +35.8 st (about three octaves) above their hum. The 5–95% pitch range of a whistle is 6.5 st against 9.7 st for hums of the same songs: people compress the tune when they whistle.

S5. Key normalization. The encoder sees p minus the median voiced pitch of the crop. This makes it exactly invariant to transposition and removes whole-clip octave errors, but not intermittent ones.

S6. Octave error. RMVPE at normal speed reports a lower octave on a median 55.4% of a whistle's voiced frames, which makes whistle-to-hum retrieval chance-level (AUC 0.49–0.53). Running it on audio slowed to half speed ("RMVPE-fix") moves the whistle into its range.

S7. DTW. Contour pairs are compared with slope-constrained dynamic time warping in re-ranking.

S8. Whistle tracker validation. Our whistle tracker takes the spectral peak in 200–6,000 Hz with a 6 dB tonal-ratio voicing gate. On all 1,702 usable MLEnd whistles it agrees with RMVPE-fix on a median 99.7% of jointly voiced frames (Figure 1). RMVPE-fix degrades above about 2 kHz, and at 0 dB SNR the peak tracker voices nothing.




Figure 1: Whistle F0 validation on MLEnd (S8): spectral-peak tracker vs. half-speed RMVPE. [REAL]

4 Retrieval system

Front ends. Hums and singing: RMVPE at 10 ms, voiced where salience ≥ 0.3, then cleaning (short runs dropped, isolated octave jumps folded, median filter). Whistles: the spectral-peak tracker (S3, S8). Songs: an htdemucs [3] vocal stem, then RMVPE, with the mixture as fallback.

Contour encoder. Input is key-normalized pitch (S5) plus a voicing flag at 20 ms. A convolutional front end halves the frame rate; a 6-layer pre-norm transformer (d=256, 4 heads) and a masked attention pool give one L2-normalized 256-d vector (about 5.2M parameters, one tower for queries and songs). The baseline, E2b, was trained with symmetric InfoNCE on HumTrans hum–MIDI pairs and then fine-tuned with the CLEWS loss on cover–original windows from CHAD.

Search. For the experiments below, each query is scored against up to 24 windows of 8 s of every song in memory, and a song's score is its best window.

5 Synthetic whistle and wrong-lyrics queries

Design principle. An earlier attempt (D-031) edited contours directly (interval compression, octave folding, gaps). It never passed through a tracker, gave no gain on all 8 MLEnd songs, and cost 4.2 top-1 points on MTG-QBH. We therefore render *audio* and re-track it, so training contours carry the errors a real tracker makes on that kind of sound. Each rendering is locked to a real song's vocal F0, so the positive pair is known exactly.

Source melodies. The cached vocal-stem F0 of 11,083 open songs (FMA [2] and chart songs used only as features; evaluation-target titles removed). Four windows per song, each rendered in both styles, gave 86,110 query contours. Songs are split by `crc32(song_id) mod 10`: 0 test, 1 validation, otherwise train (68,714 training pairs).

Human errors (both styles). Before rendering: one note moved by ± 1 or ± 2 st (p=0.5), one note dropped (p=0.4), then tempo stretch 0.5–1.9, local warp 0.3, interval scale 0.25, drift 1 st, jitter 0.25 st, voicing dropout 0.6, octave slips 0.15, glides and vibrato.

Whistle. Register: add 2 or 3 octaves, then shift by whole octaves until the median lies in 500–4,000 Hz (lower edge S4; upper edge where the peak tracker stayed correct, S8). Tone: a sinusoid at f_0 plus a second harmonic drawn uniformly in -50 to -40 dB, centered on the MLEnd median

(S2). Breath: high-passed noise 30–40 dB below the tone. Room: one reflection (12–35 ms, gain 0.04–0.18) plus noise at 18–36 dB SNR. Re-tracked with the spectral peak (S8).

Wrong-lyrics singing. Source: 16 harmonics of f_0 with a $1/k$ tilt (S2). Filter: three fixed resonances per vowel (a, e, i, o, u), separate settings for nasals and liquids, a short burst for "d". Words: syllables of 180–280 ms drawn at random from *la, na, ma, du, lu, ni, me, lo*; no lyric text is an input, so the words can never be the song's words. Same room. Re-tracked with RMVPE, the tracker real sung queries get.

Renderer check [best case]. On one invented tune, the rendered whistle (median 1,558 Hz) re-tracks with a median absolute error of 0.045 st, and the rendered singing (median 390 Hz) with 0.106 st. This checks the renderer on one clip; it is not a dataset error rate.

6 Training rounds and evaluation

All rounds start from E2b and use one seed. The loss is CLEWS (weight 1.0) between a synthetic query and 4 vocal-melody windows of the same song within ±3 s (64 songs per batch), plus 0.15× InfoNCE on HumTrans hum–MIDI pairs to keep hums intact. The 0.15 was fixed in advance.

D-040. 3,000 steps, LR 3×10^{-5}. Selection on HumTrans validation top-1 (query shifted +7 st). We report the final checkpoint (step 3,000); Section 8.1 explains why.

D-041. Selection on the synthetic validation split (mean whistle and wrong-lyrics top-1, with a HumTrans guard), about 4× longer training, per-epoch query augmentation, and real MLEnd whistle–hum pairs from *training* performers of 6 of the 8 songs. Best checkpoint: step 9,500.

D-042. D-041 with all MLEnd data removed. Best checkpoint: step 11,250 of 12,000.

Evaluation sets.

- **Synthetic hold-out** [SYNTHETIC]: 8,526 queries (4,263 per style) from test-split songs never trained on, against an 11,050-song gallery (training songs stay as distractors).
- **Hum baseline** [REAL]: HumTrans test (769 hums) and MIR-QBSH (4,431 queries, 48 MIDI songs, windows anywhere in the song, no distractors), MIDI references.
- **MLEnd closed set** [REAL]: Section 7.3.

Metrics are top-1, top-10 (top-3 for 8-way MLEnd) and mean reciprocal rank (MRR).

7 Results

7.1 Synthetic queries [synthetic]

Table 1 shows a clear, steady gain: D-042 adds 0.071 to 0.072 top-1 over E2b in both styles. With 4,263 queries per style, the binomial standard error of a top-1 near 0.2 is about 0.006, so the gain is far outside query-sampling noise (seed variance is not measured). Removing the MLEnd pairs (D-041 → D-042) costs at most 0.005, so D-041's synthetic gain came from selection, length and augmentation. These queries come from the same generator used in training, on new melodies: the table measures fit to the generator, not robustness to people.




Figure 2: Top-1 by model and query set, generated from the committed result files. Left: synthetic hold-out queries [SYNTHETIC]. Right: MLEnd real whistles against other people's hums [REAL]. D-041's all-8 bar is not clean (it trained on real whistles of 6 of those songs); its held-out bar is.

Table 1: Synthetic hold-out [SYNTHETIC]: 4,263 queries per style, 11,050-song gallery. Top-1 / top-10 / MRR. One seed.

Model	Whistle	Wrong lyrics	Both (8,526)
E2b (baseline)	0.180 / 0.291 / 0.220	0.193 / 0.314 / 0.235	0.186 / 0.303 / 0.227
D-040 (step 3,000)	0.226 / 0.342 / 0.267	0.238 / 0.365 / 0.283	0.232 / 0.354 / 0.275
D-041 best (9,500)	0.253 / 0.378 / 0.297	0.269 / 0.401 / 0.314	0.261 / 0.389 / 0.305
D-042 best (11,250)	0.251 / 0.374 / 0.295	0.264 / 0.399 / 0.312	0.258 / 0.387 / 0.303

7.2 Hum baseline [real]

The small hum term keeps hums nearly intact (Table 2). D-042 costs 0.004 HumTrans top-1 (763 vs. 766 of 769) and 0.005 MIR-QBSH (4,209 vs. 4,232 of 4,431).

7.3 Closed-set real whistles on MLEnd [real]

Protocol. MLEnd has no song recordings, so we cannot score a real whistle against the song itself. Instead, each test performer's whistle (spectral-peak tracker) is scored against the centroid embedding of *other people's* hums of each of the 8 songs; the query's own performer is excluded. This is an 8-way closed set (chance top-1 0.125) over 339 whistles from 26 test whistlers. Hakuna and Potter are the two songs held out from every MLEnd training pair. Neither E2b, D-040 nor D-042 trained on MLEnd, so every row is a clean test for them; for D-041 only the held-out row is clean.

No transfer. On the full clean test, D-042 gets 210 of 339 whistles right against 214 for E2b (Table 3). Its +3 of 90 on the held-out pair is inside the binomial standard error (about 0.05) and is offset by −7 of 249 on the other six. D-040 shows the same pattern. Three rounds of synthetic training raised synthetic whistle top-1 by 0.07 and did not move real whistles beyond noise.

Table 2: Real hums against MIDI [REAL]. Top-1 / top-10.

Set	E2b	D-040	D-041 best	D-042 best
HumTrans test (769)	0.996 / 1.000	0.991 / 1.000	0.993 / 1.000	0.992 / 1.000
HumTrans test, +7 st	0.996 / 1.000	0.995 / 1.000	0.995 / 1.000	0.993 / 1.000
MIR-QBSH 48 (4,431)	0.955 / 0.993	0.944 / 0.991	0.949 / 0.991	0.950 / 0.992

Table 3: MLEnd test whistles → other people's hums, 8-way closed set [REAL]. Top-1 / top-3 / MRR, with correct top-1 counts in parentheses.

Model	Hakuna + Potter (90)	Other 6 songs (249)	All 8 (339)
E2b	0.589 / 0.711 / 0.698 (53)	0.647 / 0.791 / 0.742 (161)	0.631 / 0.770 / 0.731 (214)
D-040	0.656 / 0.789 / 0.741 (59)	0.594 / 0.779 / 0.720 (148)	0.611 / 0.782 / 0.725 (207)
D-041 best[†]	0.456 / 0.700 / 0.620 (41)	0.707 / 0.863 / 0.803 (176)	0.640 / 0.820 / 0.754 (217)
D-042 best	0.622 / 0.722 / 0.709 (56)	0.618 / 0.763 / 0.724 (154)	0.619 / 0.752 / 0.720 (210)

[†]Trained on real whistles of the other 6 songs: only the Hakuna + Potter column is clean.

Real whistles of the test tunes teach the tunes. D-041, which also trained on real whistles of 6 of the 8 songs from other performers, gains 0.060 top-1 on those 6 songs but falls to 41 of 90 on the 2 it never saw, against 53 for E2b and 59 for D-040. Removing the pairs (D-042) recovers 56 of 90. The same pattern appeared in an earlier experiment (D-015/D-016: held-out songs 0.630 → 0.456). In a closed set this small, real pairs teach song identity rather than the whistle-to-hum mapping, and an all-8 number that mixes trained and untrained songs (0.640 for D-041) should not be read as a whistle gain.

Tracker matters more than training. With the same E2b weights, whistle top-1 over all 8 songs is 0.631 with the spectral-peak tracker, 0.584 with RMVPE-fix and 0.159 with plain RMVPE, consistent with S6.

7.4 Closed-set real-whistle training

Following the scoped design, a model is trained and tested on real whistles within MLEnd's 8 songs, with test performers disjoint from training performers. This is a closed-set result by construction: it says how well real whistle training works when the song set is fixed and known, not how it generalizes to new songs.

Pending. Results from the closed-set real-whistle training run will be added to Table 4.

Table 4: Closed-set real-whistle training on MLEnd's 8 songs [REAL]. Test performers are disjoint from training performers.

Model	Top-1	Top-3	MRR
E2b (no MLEnd training)	0.631	0.770	0.731
Closed-set real-whistle model	–	–	–

7.5 MERT baseline [real]

A fine-tuned MERT-v1-95M encoder (8,000 further steps on 13,080 HumTrans hums) reaches HumTrans test top-1 / top-10 0.947 / 0.999 but only 0.169 / 0.602 on MIR-QBSH (48 songs, first 10 s of each reference). The contour encoder E2b scores 0.996 / 1.000 and 0.949 / 0.990 on the same sets. MERT learns HumTrans but does not transfer to MIR-QBSH; the F0 encoder does, which motivates the contour design. The two evaluation scripts differ, so the HumTrans rows are close but not guaranteed identical protocols.

8 Lessons

8.1 The checkpoint-selection pitfall

D-040 selected checkpoints on HumTrans validation top-1 with a +7 st shift. That metric was 0.9948 at step 0 (the E2b weights) and never exceeded it, drifting to 0.9922. The first run early-stopped at step 500 with "best step 0"; the second run, with patience off, also selected step 0, so its "best" checkpoint was the baseline and every number in its result file equals E2b's exactly. We report the fixed-schedule final checkpoint instead. The fix (D-041) selects on the synthetic validation split with HumTrans as a guard; that metric does move, from 0.288 at step 0 to 0.374 at the best step in both D-041 and D-042, with the guard holding at every validation (0.9908–0.9948). The rule works, but the metric it optimizes is synthetic, so it cannot see the real-whistle behavior in Table 3. A selection metric must be able to move on what is being trained *and* track the target domain.

8.2 Other results that shaped the method

- Hum fine-tuning with positives built from each song's own distorted F0 (D-039) gave no real gain: CHAD validation top-1 0.4359 at best vs. 0.4341 at step 0.
- Rendering and re-tracking audio (D-040) costs hums far less than editing contours (D-031: −4.2 MTG-QBH top-1).
- The largest real-hum gains in this project came from matching (multi-window voting and re-ranking), not from training.

9 Limitations

1. **No real whistle or wrong-lyrics query is scored against the actual song recording.** MLEnd ships whistles but not the songs, and MTG-QBH ships sung queries but not the recordings. Our real-whistle evidence is whistle → other people's hums.
2. **No real wrong-lyrics test.** The wrong-lyrics results are synthetic only.
3. **MLEnd is small:** 8 songs and 26 test whistlers; the held-out pair is 2 songs, 90 whistles. Per-song effects dominate.
4. **The renderer is simple:** a one-reflection room, fixed formants, an 8-syllable inventory and no learned timbre. Its gap to real queries is the likely cause of the failure to transfer, but we have not measured that gap directly.
5. **One seed** per round; differences of one or two points are not resolved.

6. **Song side:** melody comes from the vocal stem, so instrumental hooks are unreachable.
7. **Whistles above about 2 kHz** and very noisy whistles are tracked poorly (S8).
8. **No direct comparison** with Google (no published numbers) or ByteHum (full text not read).

10 Release

Code, configuration files, decision log and every result file cited here are on GitHub at `https://github.com/luiginotmario/hum2song`. Model checkpoints (E2b, D-040 to D-042, MERT runs) and the search index will be released on Hugging Face as `luigir5/hum2song-models`; derived data (melody features, song catalog, result files) will be released as `luigir5/hum2song-data`. Both repositories exist and are private at the time of writing; they are to be released.

11 Conclusion and future work

A melody-only contour encoder with a whistle-specific tracker is a sound base for whistle and wrong-lyrics search: lyrics and timbre cannot mislead it, and key is removed exactly. Rendering whistles and nonsense-syllable singing from real song melodies and re-tracking them improves retrieval of such queries on new songs by about 7 top-1 points at under one point of hum cost. It does not improve retrieval of real whistles, and real whistles of the test tunes teach the tunes rather than whistling. As CHAD found for hums, synthetic or proxy data is not enough: what is missing is real whistled and wrong-lyrics queries paired with recordings. Next steps are (i) collecting such queries for songs whose audio we can hold, (ii) selecting checkpoints on a real-query validation set, (iii) replacing the source-filter singer with a neural singer and measuring the synthetic-to-real gap before training, and (iv) more seeds.

References

[1] A. Amatov, D. Lamanov, M. Titov, I. Vovk, I. Makarov, and M. Kudinov. A semi-supervised deep learning approach to dataset collection for query-by-humming task, 2023.

[2] Michaël Defferrard, Kirell Benzi, Pierre Vandergheynst, and Xavier Bresson. FMA: A dataset for music analysis. In *Proc. International Society for Music Information Retrieval Conference (ISMIR)*, pages 316–323, 2017.

[3] Alexandre Défossez. Hybrid spectrogram and waveform source separation. In *Proc. ISMIR 2021 Workshop on Music Source Separation*, 2021. arXiv:2111.03600.

[4] B. Dias, R. Ventura, and J. Gaspar. Automatic transcription of musical whistling: Comparing pitch detection methods. Institute for Systems and Robotics, Instituto Superior Técnico, Lisbon, 2008.

[5] Xingjian Du, Pei Zou, Mingyu Liu, Xia Liang, Minghang Chu, and Bilei Zhu. ByteHum: Fast and accurate query-by-humming in the wild. In *Proc. IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 1111–1115, 2024. doi: 10.1109/ICASSP48485.2024.10448117.

[6] Christian Frank. The machine learning behind hum to search. Google Research Blog, November 2020. `https://research.google/blog/the-machine-learning-behind-hum-to-search/`.

[7] Beat Gfeller, Christian Frank, Dominik Roblek, Matt Sharifi, Marco Tagliasacchi, and Mihajlo Velimirović. SPICE: Self-supervised pitch estimation. *IEEE/ACM Transactions on Audio, Speech, and Language Processing*, 28, 2020. arXiv:1910.11664.

[8] Jyh-Shing Roger Jang. MIR-QBSH corpus. MIR Lab, National Taiwan University. `http://mirlab.org/dataset/public/`.

[9] Jyh-Shing Roger Jang and Hong-Ru Lee. A general framework of progressive filtering and its application to query by singing/humming. *IEEE Transactions on Audio, Speech, and Language Processing*, 16(2):350–358, 2008. doi: 10.1109/TASL.2007.913035.

[10] Jong Wook Kim, Justin Salamon, Peter Li, and Juan Pablo Bello. CREPE: A convolutional representation for pitch estimation. In *Proc. IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 161–165, 2018. arXiv:1802.06182.

[11] Yizhi Li, Ruibin Yuan, Ge Zhang, et al. MERT: Acoustic music understanding model with large-scale self-supervised training. In *Proc. International Conference on Learning Representations (ICLR)*, 2024. arXiv:2306.00107.

[12] Shansong Liu, Xu Li, Dian Li, and Ying Shan. HumTrans: A novel open-source dataset for humming melody transcription and beyond. In *Proc. IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, 2024. arXiv:2309.09623.

[13] MLEnd. MLEnd hums and whistles dataset. Queen Mary University of London. `https://mlenddatasets.github.io/hums_whistles/`.

[14] Mikael Nilsson, Josef Ström Bartůněk, Jörgen Nordberg, and Ingvar Claesson. Human whistle detection and frequency estimation. In *Proc. Congress on Image and Signal Processing (CISP)*, volume 5, pages 737–741, 2008. doi: 10.1109/CISP.2008.415.

[15] Jiale Qian, Hao Meng, et al. SoulX-Singer: Towards high-quality zero-shot singing voice synthesis, 2026.

[16] Justin Salamon, Joan Serrà, and Emilia Gómez. Tonal representations for music retrieval: From version identification to query-by-humming. *International Journal of Multimedia Information Retrieval*, 2:45–58, 2013. doi: 10.1007/s13735-012-0026-0.

[17] Joan Serrà, R. Oguz Araz, Dmitry Bogdanov, and Yuki Mitsufuji. Supervised contrastive learning from weakly-labeled audio segments for musical version matching. In *Proc. International Conference on Machine Learning (ICML)*, volume 267 of *PMLR*, pages 53923–53939, 2025. arXiv:2502.16936.

[18] Hung-Che Shen and Chungnan Lee. Whistle for music: Using melody transcription and approximate string matching for content-based query over a MIDI database. *Multimedia Tools and Applications*, 35(3):259–283, 2007. doi: 10.1007/s11042-007-0128-5.

[19] Haojie Wei, Xueke Cao, Tangpeng Dan, and Yueguo Chen. RMVPE: A robust model for vocal pitch estimation in polyphonic music. In *Proc. Interspeech*, pages 5421–5425, 2023. arXiv:2306.15412.

[20] Xueyao Zhang, Junan Zhang, Yuancheng Wang, Chaoren Wang, Yuanzhe Chen, Dongya Jia, Zhuo Chen, and Zhizheng Wu. Vevo2: Bridging controllable speech and singing voice generation via unified prosody learning, 2025.