

JavaScript Constructors

Example

```
function Person(first, last, age, eye) {  
  this.firstName = first;  
  this.lastName = last;  
  this.age = age;  
  this.eyeColor = eye;  
}
```

[Try it yourself »](#)

It is considered good practice to name constructor functions with an upper-case first letter.

Object Types (Blueprints) (Classes)

The examples from the previous chapters are limited. They only create single objects.

Sometimes we need a **"blueprint"** for creating many objects of the same "type".

The way to create an "object type", is to use an **object constructor function**.

In the example above, `function Person()` is an object constructor function.

Objects of the same type are created by calling the constructor function with the `new` keyword:

```
var myFather = new Person("John", "Doe", 50, "blue");  
var myMother = new Person("Sally", "Rally", 48, "green");
```

[Try it yourself »](#)

The this Keyword

In JavaScript, the thing called `this` is the object that "owns" the code.

The value of `this`, when used in an object, is the object itself.

In a constructor function `this` does not have a value. It is a substitute for the new object. The value of `this` will become the new object when a new object is created.

Note that `this` is not a variable. It is a keyword. You cannot change the value of `this`.

Adding a Property to an Object

Adding a new property to an existing object is easy:

The property will be added to `myFather`. Not to `myMother`. (Not to any other person objects).

Adding a Method to an Object

Adding a new method to an existing object is easy:

Example

```
myFather.name = function () {  
  return this.firstName + " " + this.lastName;  
};
```

[Try it Yourself »](#)

The method will be added to myFather. Not to myMother. (Not to any other person objects).

Adding a Property to a Constructor

You cannot add a new property to an object constructor the same way you add a new property to an existing object:

To add a new property to a constructor, you must add it to the constructor function:

Example

```
function Person(first, last, age, eyecolor) {  
  this.firstName = first;  
  this.lastName = last;  
  this.age = age;  
  this.eyeColor = eyecolor;  
  this.nationality = "English";  
}
```

[Try it Yourself »](#)

This way object properties can have default values.

Adding a Method to a Constructor

Your constructor function can also define methods:

Example

```
function Person(first, last, age, eyecolor) {  
  this.firstName = first;  
  this.lastName = last;  
  this.age = age;  
  this.eyeColor = eyecolor;  
  this.name = function() {return this.firstName + " " + this.lastName;};  
}
```

[Try it Yourself »](#)

You cannot add a new method to an object constructor the same way you add a new method to an existing object.

Adding methods to an object must be done inside the constructor function:

Example

```
function Person(firstName, lastName, age, eyeColor) {  
  this.firstName = firstName;  
  this.lastName = lastName;  
  this.age = age;  
  this.eyeColor = eyeColor;  
  this.changeName = function (name) {  
    this.lastName = name;  
  };  
}
```

The changeName() function assigns the value of name to the person's lastName property.

JavaScript knows which person you are talking about by "substituting" **this** with **myMother**.

Built-in JavaScript Constructors

JavaScript has built-in constructors for native objects:

Example

```
var x1 = new Object(); var x2 = new String(); var x3 = new Number(); var x4 = new Boolean(); var x5 = new Array(); var x6 = new RegExp(); var x7 = new Function(); var x8 = new Date();
```

[Try it Yourself »](#)

The `Math()` object is not in the list. `Math` is a global object. The `new` keyword cannot be used on `Math`.

Did You Know?

As you can see above, JavaScript has object versions of the primitive data types `String`, `Number`, and `Boolean`. But there is no reason to create complex objects. Primitive values are much faster.

ALSO:

Use object literals `{}` instead of `new Object()`.

Use string literals `" "` instead of `new String()`.

Use number literals `12345` instead of `new Number()`.

Use boolean literals `true` / `false` instead of `new Boolean()`.

Use array literals `[]` instead of `new Array()`.

Use pattern literals `/()/` instead of `new RegExp()`.

Use function expressions `() {}` instead of `new Function()`.

Example

```
var x1 = {};      var x2 = "";      var x3 = 0;      var x4 = false;      var x5 = [];      var x6 = /O/      var x7 = function(){};
```

[Try it Yourself »](#)

String Objects

Normally, strings are created as primitives: `var firstName = "John"`

But strings can also be created as objects using the `new` keyword: `var firstName = new String("John")`

Learn why strings should not be created as object in the chapter [JS Strings](#).

Number Objects

Normally, numbers are created as primitives: `var x = 123`

But numbers can also be created as objects using the `new` keyword: `var x = new Number(123)`

Learn why numbers should not be created as object in the chapter [JS Numbers](#).

Boolean Objects

Normally, booleans are created as primitives: `var x = false`

https://www.w3schools.com/js/js_object_constructors.asp

But booleans can also be created as objects using the `new` keyword: `var x = new Boolean(false)`

Learn why booleans should not be created as object in the chapter [JS Booleans](#).