



JavaScript Booleans

[< Previous](#)

[Next >](#)

A JavaScript Boolean represents one of two values: **true** or **false**.

Boolean Values

Very often, in programming, you will need a data type that can only have one of two values, like

- YES / NO
- ON / OFF
- TRUE / FALSE

For this, JavaScript has a **Boolean** data type. It can only take the values **true** or **false**.

The Boolean() Function

You can use the **Boolean()** function to find out if an expression (or a variable) is true:

Example

```
Boolean(10 > 9)    // returns true
```

[Try it Yourself »](#)

Or even easier:

Example

```
(10 > 9)           // also returns true  
10 > 9             // also returns true
```

[Try it Yourself »](#)

Comparisons and Conditions

The chapter JS Comparisons gives a full overview of comparison operators.

The chapter JS Conditions gives a full overview of conditional statements.

Here are some examples:

| Operator | Description | Example |
|----------|--------------|----------------------|
| == | equal to | if (day == "Monday") |
| > | greater than | if (salary > 9000) |
| < | less than | if (age < 18) |

The Boolean value of an expression is the basis for all JavaScript comparisons and conditions.

Everything With a "Value" is True

Examples

100

3.14

-15

"Hello"

"false"

7 + 1 + 3.14

Try it Yourself »

Everything Without a "Value" is False

The Boolean value of **0** (zero) is **false**:

```
var x = 0;  
Boolean(x);    // returns false
```

Try it Yourself »

The Boolean value of **-0** (minus zero) is **false**:

```
var x = -0;  
Boolean(x);    // returns false
```

Try it Yourself »

The Boolean value of **""** (empty string) is **false**:

```
var x = "";  
Boolean(x);    // returns false
```

Try it Yourself »

The Boolean value of **undefined** is **false**:

```
var x;  
Boolean(x);    // returns false
```

Try it Yourself »

The Boolean value of **null** is **false**:

```
var x = null;  
Boolean(x);    // returns false
```

Try it Yourself »

The Boolean value of **false** is (you guessed it) **false**:

```
var x = false;  
Boolean(x);    // returns false
```

Try it Yourself »

The Boolean value of **NaN** is **false**:

```
var x = 10 / "H";  
Boolean(x);      // returns false
```

Try it Yourself »

Booleans Can be Objects

Normally JavaScript booleans are primitive values created from literals:

```
var x = false;
```

But booleans can also be defined as objects with the keyword `new`:

```
var y = new Boolean(false);
```

Example

```
var x = false;  
var y = new Boolean(false);  
  
// typeof x returns boolean  
// typeof y returns object
```

Try it yourself »

Do not create Boolean objects. It slows down execution speed.

The `new` keyword complicates the code. This can produce some unexpected results:

When using the `==` operator, equal booleans are equal:

Example

```
var x = false;  
var y = new Boolean(false);  
  
// (x == y) is true because x and y have equal values
```

Try it Yourself »

When using the `===` operator, equal booleans are not equal, because the `===` operator expects equality in both type and value.

Example

```
var x = false;
```

```
var y = new Boolean(false);

// (x === y) is false because x and y have different types
```

Try it Yourself »

Or even worse. Objects cannot be compared:

Example

```
var x = new Boolean(false);
var y = new Boolean(false);

// (x == y) is false because objects cannot be compared
```

Try it Yourself »

Note the difference between (x==y) and (x===y).
Comparing two JavaScript objects will always return false.

Complete Boolean Reference

For a complete reference, go to our [Complete JavaScript Boolean Reference](#).

The reference contains descriptions and examples of all Boolean properties and methods.

◀ Previous

Next ▶