

Critical: Bind Shell Backdoor Detection

Description

A shell is listening on the remote port without any authentication being required. An attacker may use it by connecting to the remote port and sending commands directly.

Descrizione

Una shell è in ascolto sulla porta remota senza che sia richiesta alcuna autenticazione. Un utente malintenzionato può utilizzarlo collegandosi alla porta remota e inviando direttamente i comandi.

Solution

Verify if the remote host has been compromised, and reinstall the system if necessary.

Soluzione

Verifica se l'host remoto è stato compromesso e, se necessario, reinstalla il sistema.

Output

- Nessus was able to execute the command "id" using the following request :

```
This produced the following truncated output (limited to 10 lines) :
----- snip -----
root@metasploitable:/# uid=0(root) gid=0(root) groups=0(root)
root@metasploitable:/#
----- snip -----
```

Critical: Debian OpenSSH/OpenSSL Package Random Number Generator Weakness (SSL check)

Description

The remote x509 certificate on the remote SSL server has been generated on a Debian or Ubuntu system which contains a bug in the random number generator of its OpenSSL library.

The problem is due to a Debian packager removing nearly all sources of entropy in the remote version of OpenSSL.

An attacker can easily obtain the private part of the remote key and use this to decipher the remote session or set up a man in the middle attack.