

Buckets Explorer Database Schema

Django stores application metadata, tenant activation state, sharing records, file upload records, and admin configuration. Ceph RGW stores objects. RGWSquared owns bucket lifecycle and upstream permission state. In the buckets table, **name** is the generated bare bucket name; RGWSquared maps it to the tenant-prefixed physical bucket in Ceph.

users		
bigint	id	PK
string	username	
string	display_username	UK
string	email	UK
string	external_id	UK
string	idp_source	
string	institution	
string	department	
string	affiliation_status	
string	orcid	UK
url	profile_picture_url	
datetime	last_idp_sync	
boolean	is_approved	
text	notes	

tenant_memberships		
bigint	id	PK
bigint	user_id	FK
bigint	tenant_id	FK
string	ceph_username	
string	role	
string	uo_code	
boolean	is_active	
unique	user_id + tenant_id	UK
unique	active tenant + ceph_username	UK

tenants		
bigint	id	PK
string	code	UK
string	name	
string	rgwsquared_structure	
string	bucket_name_prefix	
boolean	is_active	

buckets		
bigint	id	PK
string	name	
string	display_name	
bigint	tenant_id	FK
bigint	owner_id	FK
string	bucket_type	
boolean	is_deletable	
text	description	
datetime	created_at	
datetime	updated_at	
unique	name + tenant_id	UK

bucket_permissions		
bigint	id	PK
bigint	bucket_id	FK
bigint	user_id	FK
string	permission	
string	source	
datetime	granted_at	
unique	bucket_id + user_id	UK

file_upload_records		
bigint	id	PK
bigint	bucket_id	FK
string	file_key	
bigint	uploaded_by_id	FK
bigint	file_size	
datetime	uploaded_at	
unique	bucket_id + file_key	UK