1. O que nos diz?git status

2. O que nos diz?git log -p

```
C:\Users\luisg\git-katas>git log -p
commit b5dc244a03d7e02931d1ead4103bb93d410a4a8b (HEAD -> main)
Author: Luís Gustavo Silva <luisgustavos949@gmail.com>
Date: Thu Mar 6 16:24:08 2025 -0300
   Adiciona file1.txt
diff --git a/file1.txt b/file1.txt
new file mode 100644
index 0000000..8d1c8b6
--- /dev/null
+++ b/file1.txt
@@ -0,0 +1 @@
commit b556d50a9d1b10abc442e72ded42da1100efdf51
Author: Luís Gustavo Silva <luisgustavos949@gmail.com>
       Thu Mar 6 16:22:20 2025 -0300
   Adiciona .gitignore para ignorar arquivos .s
diff --git a/.gitignore b/.gitignore
new file mode 100644
index 0000000..ed37726
--- /dev/null
+++ b/.gitignore
@@ -0,0 +1 @@
```

3. Encenar a adição de bar.txt

```
C:\Users\luisg\git-katas>echo .> bar.txt
```

4. Correr git commit -amend

```
C:\Users\luisg\git-katas>git commit --amend
[main 2c9dc36] Adiciona file1.txt
Date: Thu Mar 6 16:24:08 2025 -0300
1 file changed, 1 insertion(+)
create mode 100644 file1.txt
```

5. O que aconteceu? O que nos diz?git log -p

```
C:\Users\luisg\git-katas>git log -p
commit 2c9dc36d4c7fe1fa6d3dcdad5e7984b33dd8c7aa (HEAD -> main)
Author: Luís Gustavo Silva <luisgustavos949@gmail.com>
Date:
       Thu Mar 6 16:24:08 2025 -0300
    Adiciona file1.txt
diff --git a/file1.txt b/file1.txt
new file mode 100644
index 0000000..8d1c8b6
--- /dev/null
+++ b/file1.txt
00 -0,0 +1 00
commit b556d50a9d1b10abc442e72ded42da1100efdf51
Author: Luís Gustavo Silva <luisgustavos949@gmail.com>
Date: Thu Mar 6 16:22:20 2025 -0300
   Adiciona .gitignore para ignorar arquivos .s
diff --git a/.gitignore b/.gitignore
new file mode 100644
index 0000000..ed37726
--- /dev/null
+++ b/.gitignore
@@ -0,0 +1 @@
```