

Bioinformatic methods for the design of antimicrobial peptides

Luis H. Reyes^a and Juan C. Cruz^b

^aDepartment of Chemical and Food Engineering, Universidad de los Andes, Bogotá, Colombia, ^bDepartment of Biomedical Engineering, Universidad de los Andes, Bogotá, Colombia

1 Introduction

1.1 The significance of bioinformatics in accelerating the discovery and optimization of AMPs

Bioinformatics represents a milestone in modern biomedical research, particularly in the search for novel therapeutic agents such as antimicrobial peptides (AMPs). This computational field merges biology, computer science, and mathematics to analyze biological data efficiently, speeding up the discovery, design, and optimization processes for AMPs. Bioinformatics offers tools for *in silico* analysis of AMP sequences, structures, and functions, facilitating an understanding of their mechanisms of action, interactions with microbial membranes, therapeutic potential, and resistance mechanisms against existing treatments for infectious diseases. The threat of antibiotic-resistant pathogens necessitates new antimicrobials to maintain efficacy against future outbreaks.

Rodriguez-Cerdeira et al. demonstrate bioinformatics' power in discovering antifungal peptides, highlighting its potential to expand our antimicrobial arsenal (Rodríguez-Cerdeira et al., 2023). Computational screening quickly identifies antifungal compounds from genomic databases, saving time and resources compared with traditional wet lab methods. Similarly, Wang et al. use computer screening to find promising antifungal peptides in large genomic databases (Wang, 2020). Oei's exhaustive bioinformatic analysis of amphibian-derived AMPs uncovered length-dependent correlations that could inform the design and prediction of effective AMPs, showing how bioinformatics reveals principles that define peptide efficacy.

Dedicated bioinformatics resources for antimicrobial research have significantly expedited discovery efforts. The database of antimicrobial activity and structure of peptides (DBAASP), created by Hammami et al., consolidates experimental data regarding the activity and structure of peptide antimicrobial agents. DBAASP can be a valuable resource in designing novel AMPs (Hammami et al., 2010). This database illustrates how bioinformatics resources enable researchers to capitalize on existing knowledge for new antimicrobial strategies through standardization, ultimately aiding discovery (Hammami et al., 2010).

Beyond identification, bioinformatics tools offer predictive abilities that extend to optimizing therapeutic properties. Porto et al. highlighted how machine learning algorithms could predict the antimicrobial activity of peptide sequences (Porto et al., 2018). Using such computational models, the potential efficacy of candidates before synthesis could be assessed, thus streamlining the development pipeline.

Structural analysis of AMPs using bioinformatics tools has provided crucial insights into their relationship to antimicrobial activity. Understanding this aspect is central to creating AMPs with increased specificity, potency, and lower toxicity toward human cells. Bioinformatics enables the prediction of peptide structures from their amino acid sequences, providing clues as to their mode of action, interactions with microbial membranes, and therapeutic applications (Richter et al., 2022). For example, Richter et al. demonstrated the significance of linking predicted structures of AMPs with their biological activities, showing how certain structural features correlate closely to antimicrobial efficacy (Richter et al., 2022). This correlation aids designers in crafting AMPs that target and neutralize pathogenic organisms effectively.

Structure-activity relationships (SARs) of AMPs can be investigated using bioinformatics approaches, providing the ability to identify sequence motifs and structural characteristics essential for antimicrobial function. Torrent et al. detailed how bioinformatics is instrumental in unmasking mechanisms underlying their antimicrobial activity, while computational

models help comprehend interactions with bacterial membranes (Torrent et al., 2012). Such insights are crucial when engineering antimicrobial agents with optimal properties yet minimal side effects.

The stability and formulation potential of AMPs have also been studied using bioinformatics methods. Understanding their stability in biological fluids is paramount for their therapeutic development; its impact determines efficacy and half-life. Bioinformatics tools simulate physiological conditions to figure out how stable peptides are. Changes can then be made to make them more resistant to proteolytic degradation. Hancock and Sahl highlighted the significance of bioinformatics optimization of AMPs for clinical use as an essential means to increase stability while simultaneously decreasing toxicity (Hancock & Sahl, 2006).

Analyzing AMPs using bioinformatics is also very important for making AMPs that can be used in medicine. Computer programs can predict how these peptides interact with pharmaceutical ingredients and model their behavior in delivery systems. They are both very important for making antimicrobial therapies that work. Deslouches and Di demonstrated this application of bioinformatics when formulating AMPs; their computational predictions helped inform the selection of appropriate delivery vehicles and administration routes (Deslouches & Di, 2017). Bioinformatics forms the cornerstone of structural analysis and optimization for AMPs, providing researchers with an enhanced understanding of their molecular architecture and functional mechanisms. Researchers can develop new AMPs with targeted antimicrobial activity, enhanced stability, and superior therapeutic profiles by employing computational tools to predict and analyze peptide structures.

As an innovative force, bioinformatics provides powerful computational strategies that have transformed AMP research. Predictive modeling plays a pivotal role in this domain by enabling researchers to predict the antimicrobial potential of synthetic peptides even before their synthesis is completed, speeding up the discovery process while drastically decreasing the resources needed for experimental validation.

An excellent illustration of this approach is provided by Porto et al., who utilized machine learning algorithms to predict the antimicrobial activity of peptides based on sequence information (Porto et al., 2018). Veltri et al. successfully employed bioinformatics models to identify sequences with high antimicrobial potential, demonstrating their strength in finding effective AMPs. Furthermore, they developed software capable of identifying sequences with antimicrobial activity more quickly than by hand searching. Veltri et al. also created a deep-learning model to directly predict AMPs from amino acid sequences. This model is a high-throughput screening tool that can quickly check peptide libraries (Veltri et al., 2018). These advancements highlight the transformative impact predictive modeling can have on AMP research and its efficacy in finding potential therapeutic candidates.

Sequence analysis using bioinformatics plays an integral part in understanding the factors governing antimicrobial activity and specificity. By looking at sequence motifs linked to antimicrobial activity, it is possible to make AMPs with specific properties. Gabere and Noble utilized motif analysis to identify conserved regions within AMPs that contribute significantly to the targeting and killing of microbes (Gabere & Noble, 2017). Such molecular-level insights provide invaluable knowledge into antimicrobial action mechanisms while designing peptides optimized against specific pathogens (Gabere & Noble, 2017).

Integrating bioinformatics in sequence analysis extends to optimizing AMP sequences for increased biological activity and decreased cytotoxicity. By studying the relationship between sequence features and peptide function, researchers can engineer AMPs that offer an ideal balance of antimicrobial potency versus selectivity for targeting only bacteria over human cells. Using computational approaches, Pirtskhalava et al. utilized bioinformatics tools to design an AMP with enhanced activity and stability, further demonstrating bioinformatics' capabilities (Pirtskhalava et al., 2021).

These advancements in predictive modeling and sequence analysis demonstrate the profound influence of bioinformatics on antimicrobial research. By employing computational tools and methodologies, scientists can more easily navigate the vast complexity of peptide sequence space, discovering novel AMPs with potential antimicrobial activity that meet current market needs.

Tools and databases tailored specifically for AMP research represent bioinformatics' transformative power in this science area. These databases serve as comprehensive repositories of AMP information, such as their sequence, structure, activity mechanisms, and therapeutic potential, providing invaluable resources that help with discovery.

The antimicrobial peptide database (APD), created by Wang et al. (2016), is an invaluable tool for researchers. With more than 3000 AMPs from various organisms represented, APD provides tools for analysis, prediction, and design, as well as genetic determinant information (Wang et al., 2016), making it an indispensable resource in the field (Hammami et al., 2010). Furthermore, the BACTIBASE database offers in-depth coverage of bacteriocins, a subclass of AMPs containing their genetic determinants and bioactivity profiles (Hammami et al., 2010). These databases facilitate comparative analyses and the identification of candidates for further study (Waghu et al., 2016).

Derived from these databases, bioinformatics tools enable the *in silico* design and optimization of AMPs. Computational algorithms can predict their antimicrobial activity, toxicity, and stability, ultimately creating more effective and safer therapeutic agents. One such bioinformatics tool that utilizes machine learning models to predict whether a given peptide will act against pathogens is the CAMPR3 tool, which utilizes machine learning models to predict this likelihood based on sequence features (Waghu et al., 2016), which allows bioinformatics tools to go from vast spaces of potential sequences down to those that hold the greatest therapeutic promise.

Bioinformatics methodologies have made studying how AMPs interact with microbes and host cells possible, which have become an invaluable asset. Simulations, docking studies, and molecular dynamics (MD) simulations offer insight into the mechanisms underlying antimicrobial activity and selectivity. These provide crucial knowledge that allows designers to create antimicrobial agents that effectively target pathogens while limiting adverse side effects on host cells. Bioinformatics resources and tools have exponentially accelerated AMP research. By harnessing computational analysis power to unlock the therapeutic potential of antimicrobials more effectively, researchers can more efficiently discover novel antimicrobial strategies to combat drug-resistant infections.

Formulating AMPs for therapeutic applications can be a complex and time-consuming task that benefits immensely from bioinformatics analysis. You must find potency antimicrobial activity peptides and ensure their solubility, compatibility with delivery systems, and stability before administration can take place effectively. Bioinformatics tools offer solutions by simulating behavior under various physiological conditions, predicting interactions with pharmaceutical excipients, and assessing immunogenicity potential—all crucial analyses for formulating formulations that are both effective and safe enough for clinical use.

Computational modeling can predict the structural stability of AMPs in the presence of serum proteins, an essential requirement for maintaining their activity in bloodstream environments. Studies have also utilized MD simulations to study their folding in different environments and give insights into their behavior *in vivo* (Gupta et al., 2013; Mooney et al., 2012; Smith & Smith, 2020). Furthermore, bioinformatics tools such as PeptideRanker and ToxinPred provide predictions regarding bioactivity and toxicity, respectively, to help guide the selection of optimal therapeutic peptides (Gupta et al., 2013; Mooney et al., 2012).

Designing delivery systems for AMPs is another area in which bioinformatics is integral. Nanoparticle-based delivery systems, for instance, can improve efficacy by protecting them from degradation and aiding target cell uptake. Bioinformatics tools can model interactions between peptides and nanoparticle surfaces to predict loading/release efficiency; this ability provides a valuable means of optimizing delivery systems that maximize therapeutic potential while mitigating the side effects (Almeida & Martins, 2019).

Bioinformatics analysis can also assist researchers in selecting suitable administration routes based on predicted peptide pharmacokinetics and pharmacodynamics. By simulating absorption, distribution, metabolism, and excretion (ADME) profiles of AMPs, researchers can quickly and effectively identify effective routes of administration that are likely to meet desired therapeutic outcomes (Kola & Landis, 2004). Researchers can develop more effective and safer AMP-based therapies faster by employing computational tools to simulate and predict peptide behavior in various physiological and pharmacological contexts. Furthermore, this approach accelerates the development of novel antimicrobial agents faster and enhances our capacity to address antibiotic-resistant infections more effectively.

Researchers can develop more effective and safer AMP-based therapies faster by employing computational tools to simulate and predict peptide behavior in various physiological and pharmacological contexts. Furthermore, this approach accelerates the development of novel antimicrobial agents faster and enhances our capacity to address antibiotic-resistant infections more effectively.

The role of bioinformatics in AMP research and drug development cannot be overstated in modern biomedical research and drug development. Combining computational power with biological data has opened new horizons in our search for antimicrobial agents to combat antibiotic resistance. Through its lens, bioinformatics allows researchers to navigate precisely between pathogens and antimicrobials with unprecedented precision, revolutionizing how we discover, optimize, and deploy them as therapeutic agents.

Bioinformatics not only deepen our understanding of AMP mechanisms but also provide us with personalized medicine approaches to tackle infections. By tailoring peptide therapies specifically to individual patients or infections, we can achieve greater efficacy and safety—an approach powered by bioinformatics that provides hope of an antimicrobial future optimized for maximum therapeutic benefit while mitigating the risks of resistance development.

The collaboration of bioinformatics with other technological advancements, such as genomics, proteomics, and nanotechnology, ushers in a new era of antimicrobial therapy. Interdisciplinary efforts such as these are integral to breaking through current limitations on antimicrobial strategies while supporting future therapeutic innovations.

As we approach a postantibiotic era, the role of bioinformatics in driving forward antibiotic research cannot be over-emphasized. The discovery, design, and development efforts of antibiotics provide hope of meeting one of our greatest health challenges; its continued investment and advancement are vital components to winning this war against infectious disease.

Bioinformatics has proven itself a key ally in AMP research and development, from its groundbreaking role as a tool to its transformational impact in shaping the understanding of function and mechanism at both molecular and global levels. As we explore their vast potential further, bioinformatics will remain essential in harnessing natural defense mechanisms for human health benefits.

2 Foundations of AMP design

2.1 Bioinformatics-driven peptide engineering

Bioinformatics has proven invaluable in the field of peptide engineering. Bioinformatics offers tools enabling researchers to model, analyze, and predict AMP structures and functions [Fig. 1.1](#). By simulating amino acid substitution effects on peptide structures through bioinformatics simulation, researchers can optimize properties such as charge, hydrophobic moment,




FIG. 1.1 Bioinformatics workflow for antimicrobial peptide discovery and optimization. (No permission required.)

and amphipathicity critical for interactions with microbial membranes. Studies have demonstrated how increasing the positive charges on AMPs increases attraction to negatively charged bacterial membranes, thus increasing antimicrobial activity (Melo et al., 2009).

Rosetta and MODELLER have proven instrumental in accurately predicting the three-dimensional structures of AMPs based on their amino acid sequences, making these predictions essential to comprehending how AMPs act; their structure determines much of their interaction with microbial membranes (Fiser & Šali, 2003; Rohl et al., 2004). Bioinformatics tools also assist in optimizing strategies such as cyclization to boost stability and activity, including by simulating its impact on overall structure/dynamics (Gentilucci et al., 2010; Haney et al., 2015).

Dimerization or multimerization of AMPs, which can produce synergistic antimicrobial effects, is yet another area where bioinformatics plays an instrumental role. Computational analyses can pinpoint potential sites for dimerization and predict its effect on biological activity (Haney et al., 2015). Ultimately, this strategy allows for designing more potent AMPs with reduced toxicity profiles and better pharmacokinetic profiles.

2.2 Computational tools for AMP discovery

Bioinformatics has transformed AMP research, drastically speeding up discovery. Employing algorithms and databases to sift through genetic and protein sequences and identify those matching typical AMP characteristics, such as sequence similarity. Machine learning models trained using known AMPs, such as the Antimicrobial Peptide Database (APD) or CAMP (collection of AMPs), now have an abundance of existing AMPs against which novel peptides can be evaluated (Waghu et al., 2016; Wang et al., 2016).

MD simulations are pivotal in understanding how potential antimicrobial agents (AMPs) interact with microbial membranes. Such computational models help demonstrate how specific peptide structures allow them to insert and disrupt the membranes of bacteria, an important mechanism of action for many AMPs. Their use has demonstrated the significance of such interactions in antimicrobial activity and assisted researchers with selecting future development candidates (Marrink et al., 2007).

Quantitative structure-activity relationship (QSAR) models facilitate AMP discovery by correlating certain molecular features with their antimicrobial potency. By identifying structural and physicochemical properties that contribute to antimicrobial activity, QSAR models inform the design of peptides with optimized characteristics (Veltri et al., 2018). This approach streamlines discovery by helping researchers focus on only those candidates most likely for synthesis and experimental validation.

2.3 Bioinformatic resources for AMP discovery

AMPs represent an invaluable weapon against increasing antibiotic resistance worldwide. Their discovery and optimization represent one key area of focus in this fight against increased resistance. Bioinformatic resources are central, offering necessary tools and databases for discovering, assessing, and refining potential antimicrobial candidates. These resources tap into massive amounts of biological data, enabling researchers to rapidly identify novel peptides with therapeutic potential from diverse organisms and environments. They assist in analyzing sequence composition, structural motifs, and physicochemical properties, which are essential in predicting AMP efficacy and safety. Bioinformatic platforms also provide insights into the evolutionary relationships and functional mechanisms of these peptides, providing direction for the rational design of next-generation antimicrobials. Integrating bioinformatics in antimicrobial research not only accelerates discovery processes but also expands knowledge on mechanisms of action, resistance, and interactions with membranes (Porto et al., 2018; Tossi et al., 2000; Wang et al., 2016).

2.3.1 Databases and repositories: A comprehensive guide to specialized AMP resources

The discovery and development of AMPs as potential therapeutic agents have been greatly advanced with the emergence of dedicated databases and repositories. These resources have become essential in AMP research, providing invaluable information regarding sequences, structures, functional activities, therapeutic potential, and even sequence similarities among AMPs. We examine key features of notable databases such as APD3, CAMP, and DRAMP while outlining their unique contributions to our field.

APD3: The antimicrobial peptide database

The APD3 is an invaluable AMP research resource. Established to facilitate its study, design, and therapeutic application, APD3 has grown into one of the most comprehensive and user-friendly databases today, encompassing information on over

3000 naturally occurring AMPs from six kingdoms of life with sequence data, molecular targets, source information, and functional activities; each entry is meticulously curated, so researchers have access to accurate and pertinent information (Wang et al., 2016).

APD3 organizes its database by categorizing peptides according to different criteria, including the animal source (animal, plant, or bacteria), structure (a-helix, b-sheet extended loop, or extended helix), and function (antibacterial, antifungal, antiviral, or anticancer). This multifaceted classification system allows users to perform targeted searches that meet their research requirements (Wang, 2010).

In addition to its expansive repository of peptide data, APD3 offers analytical tools designed to assess essential properties critical for the antimicrobial function and therapeutic potential of peptides. These include algorithms for calculating molecular weight, charge, hydrophobicity, potential toxicity, and molecular weight ratio; such calculations help predict behavior and efficacy in biological systems. APD3's user-friendly interface facilitates quick data retrieval, allowing for identifying and designing novel AMPs with optimized characteristics (Harris et al., 2009).

APD3 has had an immense effect on the AMP research community, facilitating discovery and optimization processes significantly faster while simultaneously offering researchers access to peptides with desired properties for analysis quickly. Furthermore, APD3 is an educational resource that spreads knowledge and deepens comprehension of AMP mechanisms and therapeutic applications (Zasloff, 2002).

To remain at the forefront of AMP research, APD3 is continuously updated and expanded to reflect the most up-to-date discoveries and advancements. User-submitted data and feedback from the scientific community contribute to the database's growth and relevance, making APD3 an indispensable resource for researchers worldwide (Lazzaro et al., 2020; Yeaman & Yount, 2003).

CAMP: Collection of antimicrobial peptides

The CAMP database stands out by utilizing machine learning algorithms to classify and predict the antimicrobial nature of peptide sequences. This powerful feature allows researchers to assess potential antimicrobial activity before conducting in vitro testing, saving valuable time and resources. CAMP's extensive database houses thousands of AMP sequences from various organisms, encompassing information on their source, structure, activity level, and efficacy against different strains (Thomas et al., 2010; Waghu et al., 2016).

In addition to its predictive capabilities, CAMP offers a suite of bioinformatics tools specifically tailored for antimicrobial research. These tools include algorithms for sequence alignment, similarity searches, and analysis of physicochemical properties, enabling researchers to compare novel peptides with known antimicrobials. These analytical tools play a vital role in identifying key features responsible for antimicrobial activity while aiding in optimizing sequences to maximize therapeutic potential (Hammami et al., 2010; Porto et al., 2018).

One of the strengths of CAMP is its user-friendly interface and the ability for researchers to submit new data, making it a dynamic database that constantly reflects the latest advances and discoveries within the field. This collaborative nature fosters the continuous improvement of database content and the development of an active research community dedicated to exploring and developing AMPs. Regular updates ensure that CAMP remains a reliable and up-to-date scientific resource (Seebah et al., 2007).

CAMP strongly emphasizes educational outreach, providing tutorials and documentation to assist new researchers in understanding the complexities of AMP design and function. This educational component is crucial for training future scientists in antimicrobial research, ensuring the continued expansion and innovation of this important field (Hancock & Lehrer, 1998).

DRAMP: Data repository of antimicrobial peptides

The data repository of antimicrobial peptides (DRAMP) is an all-inclusive platform that supports global efforts in AMP research and development. DRAMP stands out from other databases' comprehensive collection and categorization of AMP data from general and patent literature, making this unique resource indispensable for researchers and developers.

The purpose of DRAMP is to provide an in-depth view of AMPs, including annotations, sequences, structures, functions, and sources. The database organizes these records into categories for general, patent, and clinical AMPs so users can filter out relevant information based on research interests or development needs; its general dataset covers naturally occurring and synthetic peptides from across organisms and conditions (Fan et al., 2016; Kang et al., 2019).

One of the standout features of DRAMP is its patent dataset, which provides researchers with an in-depth perspective of AMPs' commercial and developmental status. This section can help researchers navigate the intellectual property landscape, bypass potential patent barriers, and identify opportunities for collaboration and innovation. Furthermore, clinical

data enhance DRAMP's utility further, providing details of those that have progressed to clinical trials and their therapeutic targets, efficacy profiles, and safety profiles (Hancock & Sahl, 2006; Zasloff, 2002).

DRAMP provides an intuitive user experience featuring an easy interface and advanced search capabilities. Users can conduct detailed queries based on peptide properties, biological activity, and structural characteristics and use tools for sequence alignment analysis that facilitate comparative studies by highlighting conserved motifs essential to antimicrobial function (Bulet et al., 2004).

This database actively encourages community involvement, permitting researchers to submit new AMP data directly, thus keeping it fresh and comprehensive. This collaborative approach enhances database content and fosters a sense of belonging among AMP researchers as they collaborate to advance progress within their respective fields (Wang, 2020; Wu et al., 1999).

Databases and repositories in AMP research

Creating specialized databases and repositories has transformed AMP research. These resources have revolutionized how scientists discover, characterize, and optimize AMPs to progress significantly. Their central collection of data, combined with the analytical and predictive tools provided by these databases, has made research workflows smoother while encouraging collaboration—all of which helps translate basic science research into potential therapeutic applications faster.

Specialized databases have significantly simplified the discovery process by offering comprehensive collections of AMP sequences and structures from various organisms and environments, identifying novel antimicrobials faster than ever (Hancock & Sahl, 2006; Zasloff, 2002). With greater accessibility comes reduced time and resources needed for initial discovery phases and more focused experimental validation and characterization (Tossi et al., 2000; Zasloff, 2002).

These databases go beyond mere repositories to offer analytical tools for rational design and optimization of AMPs. Researchers can predict how sequence modifications impact peptide structure, charge, hydrophobicity, toxicity levels, and other properties essential to antimicrobial efficacy and toxicity; using bioinformatic approaches allows systematic modification of peptides with increased therapeutic potential and minimized adverse effects; modeling interactions between host cell membranes and microbe membranes is also essential to guide the development of AMPs with greater specificity while decreasing resistance development (Jenssen et al., 2006; Tossi et al., 2000).

Databases such as APD3, CAMP, and DRAMP provide platforms for global collaboration by breaking down geographical and disciplinary barriers. By permitting researchers worldwide to contribute data and access shared resources, these databases foster an environment that accelerates scientific discovery and innovation. Moreover, these resources serve as valuable educational tools for newcomers entering the field by spreading knowledge and best practices regarding AMP research (Porto et al., 2018; Waghu et al., 2016).

AMP databases include clinical trials and patent literature information, bridging the gap between basic research and clinical development. Researchers can track AMPs from bench to bedside, understanding the challenges associated with successful therapeutic applications as they develop (Brown & Wright, 2016; Spellberg & Gilbert, 2014). Furthermore, academic-industrial collaboration enables the creation of clinically relevant peptides and helps identify promising candidates for further investigation (Brown & Wright, 2016; Spellberg & Gilbert, 2014).

These repositories contain comprehensive data that improve our understanding of AMP mechanisms of action and the emergence of resistance in microbes. By studying different AMPs from diverse collections, researchers can identify common features and mechanisms, leading to deeper insight into how these peptides interact with microbial targets and host cells; such knowledge is critical in designing new antimicrobial treatments against resistant strains (Bechinger & Gorr, 2017; Perron et al., 2006).

2.3.2 Sequence and structure analysis tools for AMPs

The development and application of sequence and structure analysis tools have marked a substantial advance in AMP research. These software and algorithms play a pivotal role in comprehending the intricate relationship among sequences, three-dimensional structures, biological functions, and biological sequences. By enabling prediction of structure from sequences, identification of conserved motifs, and alignment of AMP sequences, these tools allow for improved identification and design of novel therapeutic AMPs with increased therapeutic potential.

Peptide structure prediction

Predicting peptide structure from amino acid sequences is at the core of AMP research, underpinning rational design and optimization of novel therapeutic agents. With advances in computational biology come sophisticated algorithms and

software capable of modeling these complex three-dimensional structures of linear sequence peptides. This invaluable ability directly informs understanding of mechanisms of action, specificity, and interactions with microbe membranes or immune cells.

Modern computational approaches for peptide structure prediction encompass various techniques, such as *ab initio* modeling, homology modeling, and MD simulation. *Ab initio* techniques, like those implemented by the Rosetta software suite, use physical principles and statistical analyses of known protein structures as templates to predict new structures from scratch (Simons et al., 1997). Homology modeling uses similar structures from databases as templates to assemble the three-dimensional structures of target peptides, as demonstrated by tools such as MODELLER (Šali & Blundell, 1993).

Combining machine learning and artificial intelligence has significantly enhanced accuracy and speed in peptide structure prediction. Algorithms trained on large datasets of known protein structures recognize patterns that indicate likely conformation changes for novel peptides. Deep learning models developed by DeepMind, such as AlphaFold, provide predictions with extraordinary accuracy (Jumper et al., 2021; Senior et al., 2020).

Tools specifically developed for predicting secondary structures, such as PSIPRED and JPred, provide valuable insight into the peptide's α -helices, β -sheets, and turns. Understanding these elements is vital since they play key roles in antimicrobial activity and the membrane interaction of AMP therapeutics (Cole et al., 2008; Jones, 1999).

Alongside structural prediction, analyzing physicochemical properties using tools such as ExPASy's ProtParam can help understand a peptide's behavior. Parameters such as hydrophobicity, charge, and amphipathicity play an integral part in how peptides interact with and disrupt microbial membranes (Gasteiger et al., 2005).

Application in Antimicrobial Peptide Research Structure prediction tools has become indispensable in AMP research, helping researchers discover and create antimicrobial agents with enhanced antimicrobial properties and reduced toxicity. By anticipating how peptides fold and interact with microbial membranes, researchers can modify sequences to enhance efficacy, increase specificity for target bacteria cells, and decrease resistance development risks (Hancock & Lehrer, 1998; Marr et al., 2006). Furthermore, structure prediction provides important insight into how antimicrobials avoid protease degradation or immune recognition—something structure prediction facilitates by understanding how they evade protease degradation or immune recognition, which is crucial when designing long-acting therapeutic agents (Hancock & Lehrer, 1998; Marr et al., 2006).

2.3.3 AMP prediction and classification tools

Motif discovery

Motif discovery is an integral step in AMP research. This process entails locating repeating patterns or sequences within peptide structures that contribute to their antimicrobial function and are essential for their mode of action, target specificity, and overall efficacy. As bioinformatics has advanced significantly over recent years, tools and algorithms have been created to facilitate motif discovery and analysis, contributing significantly to AMP research.

Tools such as MEME Suite and HMMER have revolutionized motif discovery in AMP research. MEME Suite identifies conserved motifs within an unaligned dataset of sequences, offering insight into potential functional regions shared among all AMPs (Bailey et al., 2009; Bailey & Elkan, 1994). HMMER utilizes hidden Markov models (HMMs) to detect sequence motifs with greater structural and functional relevance (Eddy & Pearson, 2011; Finn et al., 2011), providing a greater understanding of their structural and functional relevance as well as patterns that might govern antimicrobial activity, such as cationic and amphipathic regions essential for membrane interaction (Eddy & Pearson, 2011; Finn et al., 2011). These tools serve AMP researchers effectively in uncovering patterns that might influence antimicrobial activity, such as regions containing amphipathic regions essential for membrane interaction.

Motifs within AMPs often correspond with specific biological functions. For example, defensins have become popular antimicrobials for their broad-spectrum antimicrobial activity and stability (Ganz, 2003; Lehrer & Ganz, 2002). Understanding these motifs enables researchers to correlate specific structural features with antimicrobial potency and the spectrum for designing more potency-specific peptides for novel applications with increased activity and specificity.

Databases such as APD3 and CAMP integrate motif discovery tools that allow users to compare newly identified motifs with those in known AMPs (Waghu et al., 2016; Wang et al., 2016). This comparative analysis can uncover potential new AMPs or suggest modifications that improve existing ones' efficacy; similarly, researchers can utilize these databases to systematically assess their significance across various microbial targets and host environments.

Motif discovery provides critical insight for designing and optimizing AMPs. By identifying key functional motifs, researchers can engineer synthetic AMPs with essential antimicrobial features while limiting host cell toxicity—ultimately leading to synthetic AMPs with enhanced therapeutic profiles (Hancock & Sahl, 2006; Zasloff, 2002).

Sequence alignment and comparative analysis

Sequence alignment and comparative analysis are fundamental AMP research processes. They provide key insight into evolutionary relationships, functional conservation, and identifying novel candidates for antimicrobial molecules. These bioinformatic methods compare sequences across species and families to reveal structural and functional diversity within this class of molecules, offering further insight into AMP research. Advanced software has also been created to facilitate these analyses, significantly impacting this field of investigation.

BLAST, Clustal Omega, and MAFFT are essential for conducting sequence alignments and comparative analyses. BLAST (Basic Local Alignment Search Tool) allows researchers to compare an AMP sequence against known sequences from databases, identifying similar peptides as potential functional analogs (Altschul et al., 1997; Katoh & Standley, 2013; Sievers et al., 2011). Clustal Omega and MAFFT allow simultaneous alignments across multiple sequences while simultaneously revealing conserved regions or motifs indicative of shared functions or evolutionary origins.

Comparative analysis is invaluable in unraveling the evolution of AMPs, showing how structural variations impact antimicrobial activity and specificity. By comparing AMPs from diverse biological sources, researchers can trace the evolutionary conservation of specific sequences or motifs that might play a significant role in antimicrobial function; such insights enable the rational design of new AMPs by protecting essential functional elements while making modifications that enhance therapeutic properties (Hancock & Sahl, 2006; Wang et al., 2016).

Sequence alignment and comparative analysis are effective approaches for discovering novel antimicrobial agents (AMPs). Researchers can uncover hidden potential otherwise overlooked by matching sequences from nontraditional or understudied organisms to known AMPs. This leads them to discover novel compounds with distinct structures and mechanisms of action, expanding our arsenal of antimicrobial strategies (Tossi et al., 2000; Zasloff, 2002).

Integrating sequence alignment tools with AMP databases such as APD3, CAMP, and DRAMP enhances their usefulness for researchers. By directly comparing newly discovered sequences against documented AMPs from these collections, researchers can rapidly characterize and predict new sequences more efficiently for quick functional prediction. Furthermore, this integrated approach streamlines discovery while speeding the transition from sequence identification to experimental validation and application (Fan et al., 2016; Waghu et al., 2016).

2.4 Theoretical frameworks for AMP structure-activity relationship (SAR)

The antimicrobial activity of AMPs depends upon their structural features, including amphipathicity, charge, hydrophobicity, and specific secondary structures such as motifs or secondary structures such as α -helices and β -sheets. These elements determine how easily an AMP targets and penetrates microbial membranes to disrupt or inhibit intracellular processes. Antimicrobial pPeptides (AMPs) are distinguished by their amphipathic nature. They consist of hydrophobic and hydrophilic regions that allow them to enter lipid bilayers by disrupting membrane integrity. Their positive charge allows electrostatic attraction with negatively charged components of microbial membranes, such as lipopolysaccharides or lipoteichoic acids (Brogden, 2005; Matsuzaki, 1999).

AMP hydrophobic domains are essential to their integration into lipid bilayers, leading to transmembrane pores or membrane destabilization. Research has demonstrated that an optimal balance of hydrophobicity must be maintained for effective antimicrobial activity, as excessive hydrophobicity could increase mammalian cell toxicity (Dathe & Wieprecht, 1999). α -Helical peptides may form pore-like structures to disrupt membrane integrity, while β -sheet peptides aggregate into fibrils that damage cell membranes (Shai, 2002).

Peptides of smaller molecular size tend to act more quickly against target membranes due to their ability to quickly diffuse through biological fluids and interact with them. Incorporating glycine or proline residues also assists AMPs in adopting conformations that maximize interactions with microbiome membranes (Tossi et al., 2000).

2.4.1 Bioinformatic approaches to SAR

Bioinformatics offers a suite of tools that simulate the complex interactions between antimicrobial molecules (AMPs) and microbial membranes, predicting how variations in sequence affect antimicrobial activity. This computational approach to SAR analysis employs several key strategies, including sequence analysis and alignment, MD simulations, machine learning models, and QSAR models.

Bioinformatic tools such as BLAST can be used to compare AMP sequences against databases of known antimicrobials, identifying conserved motifs associated with antimicrobial activity. This allows designers to create peptides with improved or retained activities (Pearson, 2013). MD simulations provide researchers with insights into the behavior of AMPs at an atomic level, enabling them to observe how AMPs interact with lipid bilayers and disrupt membranes. Tools such as

GROMACS allow researchers to visualize membrane disruption mechanisms, offering evidence for structural features contributing to antimicrobial efficacy (Abraham et al., 2015).

Cutting-edge machine learning algorithms can accurately predict the antimicrobial activity of novel AMP sequences using training data from existing peptides. These models utilize patterns and correlations between sequence features and antimicrobial potency to optimize the design of AMPs (Porto et al., 2018). QSAR models, on the other hand, use statistical analysis to correlate chemical structure with biological activity. By identifying key structural descriptors that influence antimicrobial activity, these models can predict the effects of modifications to peptides, helping to select candidates with enhanced properties (Cherkasov et al., 2009).

The combination of these bioinformatic approaches enables researchers to gain a comprehensive understanding of the SARs of AMPs. By leveraging sequence analysis, MD simulations, machine learning models, and QSAR models, scientists can design and optimize AMPs with improved antimicrobial activity, specificity, and stability. This computational approach accelerates the discovery and development of novel antimicrobial agents, which is crucial in the fight against the growing threat of antibiotic-resistant infections.

2.4.2 Case studies illustrating successful applications of SAR analysis in AMP design

SAR analysis has proven useful in optimizing antimicrobials derived from frog skin. Researchers utilized sequence analysis and molecular modeling techniques to identify specific amino acid substitutions that increased charge, amphipathicity, and antimicrobial potency against resistant strains (Conlon et al., 2014). Another example of synthetic analog development for antimicrobial drugs is their SAR analysis-guided modification to reduce hemolytic activity while maintaining antimicrobial function; the analogs created from this modification exhibited improved safety profiles that made them promising candidates for therapeutic development (Wang, 2014).

2.4.3 Environment's role in AMP analysis

Analysis of AMPs often depends on understanding how environmental conditions influence their biological activity, especially regarding pH levels, ionic strength, and biological fluids that could impact an AMP's efficacy or structure conformation—making their consideration essential to SAR studies.

Environmental pH can enormously impact AMPs' ionization states, changing their charge, amphipathicity, and ability to interact with microbial membranes. Therefore, SAR analysis must consider pH-dependent structural changes to accurately predict the activity spectrum of AMPs under various physiological conditions. Understanding their pH responsiveness enables researchers to tailor peptides specifically for infection sites with distinct pH profiles (Dathe & Wieprecht, 1999; Georgescu et al., 2020).

The ionic strength of the surrounding medium can either hinder or enhance interactions between AMPs and microbial cell membranes. As part of an SAR analysis, considering both divalent cations such as Mg^{2+} and Ca^{2+} is essential in predicting AMP efficacy; high ionic environments reduce the binding affinity of AMPs with negatively charged membranes, which should be factored into computational models that assess peptide-membrane interactions (Brogden, 2005; Yeaman & Yount, 2003).

Since biological fluids may contain proteolytic enzymes capable of degrading an AMP or binding proteins capable of inactivating it, SAR analysis must go beyond mere sequence and structure assessments in various biological matrices; instead, it must include stability assessments as well as interaction testing within these different environments to produce antimicrobials with both increased antimicrobial potency and improved stability and bioavailability (Lai & Gallo, 2009; Schmidtchen et al., 2001).

Modern SAR models are now beginning to incorporate environmental variables for more accurate predictions of antimicrobial performance. Machine learning algorithms and MD simulations enhanced with environmental information provide more precise predictions on how antimicrobial agents behave under various physiological conditions, ultimately leading to more targeted and effective antimicrobial strategies (Porto et al., 2018).

Strategic approaches for improving AMP therapeutic potential involve creating antimicrobial AMP analogs and derivatives through SAR analysis. This process involves modifying sequences based on SAR insights to increase efficacy while decreasing toxicity levels and improving stability.

2.4.4 Rational design of AMP analogs

SAR analysis provides a powerful means for the rational design of antimicrobial drug analogs by identifying key molecular determinants of antimicrobial activity and host cell toxicity. By changing specific amino acids or peptide motifs, researchers can optimize desirable properties while attenuating undesirable ones. For example, increasing cationicity

may increase potency while improving membrane selectivity, and decreasing hydrophobicity could lower cytotoxicity against mammalian cells. This approach has resulted in the development of antimicrobial drug analogs with improved therapeutic indexes (Hancock & Sahl, 2006; Marr et al., 2006).

The development of AMP derivatives typically requires more substantial changes than analogs. These include incorporating nonnatural amino acids or conjugating with other molecules to form new structures that improve stability, bioavailability, and resistance to proteolytic degradation. SAR analysis is essential in ensuring the derivative retains or exceeds antimicrobial activity while meeting any unique pharmacological challenges (Seo et al., 2012; Zasloff, 2002).

SAR analysis in AMP research has resulted in numerous successes. For instance, derivatives of human cathelicidin LL-37 that undergo SAR analyses have produced antimicrobial activity against resistant bacteria, while modifications made based on SAR studies of magainin and melittin peptides yield analogs with increased specificity and decreased hemolytic activity (Dathe & Wieprecht, 1999; Tossi et al., 2000).

Although SAR-based design offers an effective means for developing AMP therapeutics, it poses considerable difficulties. Ensuring that modifications do not disrupt functional conformation changes or interact with microbe targets requires great caution. Translating in vitro SAR results into in vivo efficacy can also present difficulties that require thorough pharmacokinetic and pharmacodynamic studies (Jenssen et al., 2006; Porto et al., 2018).

Technological advances have greatly advanced SAR analysis capabilities. Molecular modeling, machine learning algorithms, and QSAR models facilitate high-throughput screening and predictive modeling of AMP sequences using virtual testing of thousands of variants to identify promising candidates for synthesis and experimental validation rapidly (Dürr et al., 2006; Schneider & Sahl, 2010).

2.4.5 Integrating SAR analysis into drug development pipelines

Integrating SAR analysis into AMP drug development pipelines represents an integral step in translating theoretical models and experimental data into therapeutic solutions that are both cost-effective and safe for patients. By streamlining the discovery and optimization processes of potential drugs as they move through development phases, this comprehensive approach expedites the discovery and optimization of new antimicrobial agents. It enhances their efficacy and safety profiles along their development pathway.

SAR analysis is integral to drug discovery by helping researchers quickly identify lead compounds with desirable antimicrobial properties. By studying the relationship between the chemical structure of peptides and their biological activities, researchers can more quickly prioritize candidates with potent antimicrobial effects with minimal toxicity. Early integration of SAR insights helps direct resources toward those that offer the greatest promise, thus speeding up drug development processes while decreasing the time and costs associated with them (Brown & Wright, 2016; Hancock & Chapple, 1999; Rennie et al., 2019).

Once an AMP candidate enters the optimization phase, SAR analysis becomes increasingly sophisticated as more data from computational models, high-throughput screening, biochemical and microbiological assays, and detailed biochemical and microbiological assays are incorporated (Melo et al., 2009; Rennie et al., 2019). At this stage, findings from SAR analyses guide modifications of peptide sequences to enhance stability, reduce resistance potential, and selectivity toward bacteria over human cells—essential steps toward refining lead AMPs before preclinical trials to ensure they meet stringent safety and efficacy standards (Teixeira et al., 2012).

Moving an AMP candidate from preclinical to clinical development is pivotal in drug development. SAR analysis can play a crucial role in designing clinical trials by providing insight into potential outcomes and biomarkers of efficacy and safety (Spellberg & Gilbert, 2014). Furthermore, its insights enable the stratification of patient populations and modification of dosage regimens, thereby optimizing the clinical evaluation of an AMP candidate. This tailored approach increases the likelihood of positive clinical outcomes and regulatory approval (Payne et al., 2007).

Once an AMP has received regulatory approval, SAR analysis continues to inform postmarketing surveillance and the development of next-generation analogs. Ongoing SAR studies can detect resistance emergence mechanisms, which helps design derivative compounds that remain effective against resistant bacterial strains (Lewis, 2013). Similarly, continuous SAR-driven research supports the life cycle management of AMP-based drugs, guaranteeing their efficacy and safety over their long life cycles.

3 Stability and toxicity prediction

Developing AMPs as therapeutic agents requires in-depth knowledge of their stability and toxicity profiles. This knowledge is crucial in transitioning them from bench to bedside and impacts both efficacy and safety. This section investigates factors impacting biological stability and strategies to reduce mammalian cell toxicity.

3.1 Stability of AMPs in biological contexts

Stability is fundamental to AMP therapeutic potential and efficacy. Environmental influences, including proteolytic enzymes, pH variations, and serum protein presence or degradation, lead to rapid degradation or inactivation in physiological conditions.

One of the primary challenges in maintaining AMP stability is their susceptibility to proteolytic degradation by host and microbial proteases. This reduces effective concentration at infection sites while diminishing antimicrobial activity. Strategies to counter protease degradation may include including D-amino acids in AMP molecules or using nonnatural amino acid substitutions, which prevent proteases from recognizing and cleaving (Craik et al., 2013; Hamamoto et al., 2002).

The activity and stability of AMPs depend on their environment's pH level and ionic strength. Fluctuations in pH may alter their charge, altering their interaction with microbial membranes and susceptibility to degradation. High ionic strength conditions can block electrostatic interactions essential for their mechanism of action, thereby decreasing efficacy. Designing pH-responsive peptides or employing buffer systems can mitigate such adverse effects and maintain stability in various physiological environments (Marrink & Vries, 2004; Nguyen et al., 2010).

Bindings between AMPs and serum proteins can significantly impact their bioavailability and antimicrobial efficacy. When in the bloodstream or present on wound exudates, AMPs can bind with various serum components, sequestering away their targets or leading to rapid clearance from the body. This interaction must be minimized by developing more stable formulations or employing delivery systems that protect AMPs from such interactions (Brandenburg et al., 2012).

Modifications such as oxidation, deamidation, and disulfide bond disruption may harm AMPs' structural integrity and function, while thermal instability limits their storage and shelf-life. Chemical modifications, including stable disulfide analogs or antioxidants and formulation strategies such as lyophilization, can help increase chemical and thermal stability (Deslouches & Di, 2017; Rosenfeld et al., 2006).

3.2 Toxicity toward mammalian cells

When developing AMPs as therapeutic agents, striking an optimal balance between their efficacy against pathogenic organisms and their safety for mammalian host cells is critical. Toxicity toward nontarget mammalian cells poses a considerable challenge when applied as antimicrobial treatments; understanding and mitigating this toxicity are crucial components of AMP therapies' clinical success.

AMPs typically exert their antimicrobial effects by disrupting membranes through amphipathic and cationic interactions with bacteria. Unfortunately, however, at higher concentrations, these properties can also disrupt mammalian cell membranes, leading to hemolysis (destruction of red blood cells), apoptosis, or necrosis in nontarget cells; their degree of toxicity usually correlates with hydrophobicity, charge density, and propensity to form amphipathic structures (Matsuzaki, 2009).

One of its major objectives is peptide design strategies that decrease antimicrobial efficacy without increasing mammalian cell toxicity. Strategies include changing peptide structure to lower hydrophobicity, optimizing the distribution of cationic charges and thus decreasing affinity with mammalian cell membranes, or including unnatural amino acids, cyclization, or truncation to increase selectivity against bacteria (Melo et al., 2009). Targeted delivery systems may minimize systemic exposure and associated toxicity (Deslouches & Di, 2017).

Advancements in computational models and high-throughput screening technologies have significantly contributed to our understanding of AMP toxicity in mammalian cells. These tools enable rapid assessment of large peptide libraries, quickly identifying candidates with optimal therapeutic indices. Computational models can predict toxicity based on sequence and structure analysis for safer design. At the same time, high-throughput assays provide empirical data regarding cell viability, membrane integrity, and hemolytic activity, validating computational predictions while informing future optimization (Porto et al., 2018).

SAR studies provide invaluable insight into the molecular factors governing AMP toxicity in mammalian cells. By altering peptide sequences systematically and monitoring antimicrobial activity and toxicity simultaneously, researchers can identify key features contributing to cell selectivity. SAR insights enable the rational design of antibacterial agents with potency and minimal adverse side effects (Haney et al., 2015).

3.3 Predictive models for stability and toxicity

Advancements in computational methodologies have resulted in the creation of predictive models, which significantly aid in assessing AMPs' stability and toxicity profiles. These models play a pivotal role in the rational design of antimicrobials by providing early information about biological system behavior before testing and expediting drug development processes.

Computational tools that accurately forecast AMP stability across various biological environments can significantly shorten the time and resources necessary for their optimization. MD simulations, for instance, provide valuable insight into the structural resilience of AMPs under physiological conditions such as pH fluctuations, temperature variations, and variations in ionic strength (Wang et al., 2016). Machine learning approaches utilizing datasets of experimentally verified stable and unstable peptides have also been developed to predict AMP stability using sequence and structural characteristics, such as sequence data. Such models allow researchers to identify potential degradation hotspots and suggest modifications that extend durability without diminishing antimicrobial activity (Torrent et al., 2011).

Assessing the cytotoxicity of AMPs against mammalian cells is an integral aspect of their use as therapeutic agents. Predictive models for toxicity have been employed to estimate the hemolytic and cytotoxic potential of AMPs based on their physical-chemical properties and sequence information (Maccari et al., 2013; Müller et al., 2018). These QSAR models and machine learning algorithms serve as reliable estimates. These models enable high-throughput screening of peptide libraries for candidates that exhibit minimal toxicity toward mammalian cells. Combining SAR analysis with these computational tools enables the identification of structural features associated with reduced toxicity, ultimately leading to safer AMP design (Melo et al., 2009; Porto et al., 2018).

Integrating predictive models for stability and toxicity into AMP drug development pipelines enhances efficiency and effectiveness in discovering peptide therapeutics. By applying these models early in development, researchers can prioritize candidates with ideal stability/toxicity profiles for further testing/development. Their iterative use allows continuous refinement to optimize candidates and increase accuracy and predictive power (Hancock & Sahl, 2006; Koo & Seo, 2019).

Although predictive modeling for AMP stability and toxicity has significantly improved, several obstacles must be overcome to provide accurate long-term and in vivo toxicity predictions. Current efforts aim to expand and diversify training datasets, improve algorithmic methodologies, and integrate multiomics data sources into these models to increase their predictive accuracy; future AMP development may increasingly rely on such computational tools, further emphasizing their importance (Gabere & Noble, 2017; Pirtskhalava et al., 2021).

3.4 Computational methods for predicting peptide stability

The stability of AMPs is an integral factor in their therapeutic efficacy. Computational methods are vital in predicting AMPs' resistance to proteolytic degradation, chemical instability, and aggregation, ultimately leading to more stable and effective peptide designs. This subsection explores various computational tools and approaches for assessing and improving AMPs' stability.

3.4.1 Resistance to proteolytic degradation

Proteolytic degradation poses a substantial barrier to the therapeutic application of AMPs, as enzymes in biological fluids and tissues can rapidly break them down and diminish their efficacy. Recognizing and improving AMPs' resistance to proteolytic degradation are critical to maintaining their antimicrobial activity in vivo.

AMPs can be degraded through proteolysis by various proteases, including endo- and exopeptidases that cleave peptide bonds within or at either terminus of their chains, respectively. Their susceptibility to degradation by these enzymes depends on factors such as sequence composition, structure accessibility, and binding to serum proteins or microbiological targets that influence the rate and extent of proteolytic degradation (Powers & Hancock, 2003; Sieprawska-Lupa et al., 2004).

Multiple approaches have been employed to strengthen the proteolytic resistance of AMPs:

- Amino acid substitution: D-amino or nonnatural amino acids can significantly lower proteases' susceptibility, as most proteolytic enzymes target L-amino acids. Computational predictions can then help devise substitutions that maintain antimicrobial properties while being recognized by proteases (Craik et al., 2013; Hamamoto et al., 2002).
- Peptide cyclization: Cyclization can protect against protease cleavage by restricting access to potential cleavage sites and stabilizing conformational change. Head-to-tail and side-chain-to-side-chain cyclization have both been demonstrated to increase proteolytic stability without impairing antimicrobial activity (Rosengren et al., 2003; Tam & Lu, 1998).
- Peptidomimetics: Formulating peptidomimetics that mimic the structure and function of AMPs while having altered backbones (e.g., peptoids, β -peptides) can provide resistance to proteolysis while maintaining or increasing antimicrobial efficacy. Since natural proteases don't recognize such molecules, so they remain highly stable within biological environments (Scott et al., 2008).

Computational tools play a crucial role in predicting the protease resistance of AMPs. Algorithms such as PeptideCutter and PROSPER can identify potential protease cleavage sites within sequences, guiding designers for modifications that increase stability and resistance. Molecular modeling and dynamics simulations further assist by providing insight into modifications' impact on structure/function relationships within an AMP (Gasteiger et al., 2005; Song et al., 2012).

Although significant strides have been made, significant obstacles remain when it comes to accurately predicting and achieving protease resistance without impairing the therapeutic properties of AMPs. Future research should integrate multifaceted approaches, combining experimental data with advanced computational models, to systematically design and validate protease-resistant AMPs. Creating comprehensive databases detailing peptide stability data, protease specificity information, successful modifications, and other useful details could further advance this field (Agrawal et al., 2016).

3.4.2 Assessing chemical stability

Assessing the chemical stability of AMPs is essential for therapeutic effectiveness. Unstable properties, such as oxidation, deamidation, racemization, or disulfide bond reshuffling, can reduce activity and, subsequently, therapeutic potential; computational techniques play a key role in anticipating and mitigating such instabilities, contributing to more robust AMPs in development.

- **Oxidation susceptibility:** Amphiphiles with methionine, cysteine, or tryptophan residues are particularly vulnerable to oxidation reactions that alter their structure and function. Computational tools such as MassPred and MetOx can predict the oxidation susceptibility of peptides by replacing potentially reactive amino acids with less reactive ones without impacting antimicrobial activity, providing an additional level of chemical stability and shelf life extension (Kessler, 1982; Metanis et al., 2010).
- **Deamidation and racemization:** Deamidation and racemization can result in structural changes that compromise peptide bioactivity, with asparagine and glutamine residues becoming deamidated and racemization of chiral amino acids leading to instabilities that prevent normal functioning (Patel et al., 2001; Robinson & Robinson, 2004). Computational platforms such as the Deamidation Predictor can estimate the probability of deamidation occurring early enough in design to make necessary modifications. Similarly, an analysis of primary sequence and structure can identify potential sites of racemization and replace potentially unstable residues.
- **Disulfide bond formation:** Disulfide bonds play an essential role in maintaining the structural integrity and functioning of many AMPs, yet incorrect formation can cause misfolded peptides with reduced activity. Computational tools such as Disulfide by Design and CYSPRED provide insights to determine the most advantageous disulfide bonding patterns to optimize conformational stability and support proper pairing (Thorpe & Hooper, 1996).
- **Chemical stability in formulation:** Peptide properties alone do not determine their chemical stability; the formulation can have a large influence. Computational models that simulate different formulation conditions (pH, solvent composition, and ionic strength) can accurately predict how AMPs will perform under specific environments; this information can then be used to develop formulations that maintain stability during storage and administration (Voss et al., 2001).
- **Integration of experimental data:** Computational predictions offer valuable insight, but to fully evaluate chemical stability, it is crucial that these predictions be combined with experimental data obtained through techniques such as high-performance liquid chromatography (HPLC), mass spectrometry, and circular dichroism spectroscopy. Such tests confirm whether modifications to an AMP cause improved stability without impacting efficacy (Bennett et al., 1995; Pace et al., 2014).

3.4.3 Preventing peptide aggregation

Peptide aggregation poses a formidable challenge to developing AMPs as therapeutic agents. It could lead to reduced efficacy, increased toxicity, and compromised bioavailability. Preventing this issue is imperative to maintaining the clinical viability of AMPs.

Peptide aggregation often results from the self-assembly of amphipathic or hydrophobic segments within peptides, usually through β -sheet formation, hydrophobic interactions, or electrostatic attractions. This leads to insoluble fibrils or amorphous aggregates being formed in solution. Aggregation may also be affected by concentration, temperature, pH level, the ionic strength of the solution, and the presence or absence of certain ions or molecules (Almeida & Brito, 2020; Meli et al., 2008).

Many computational tools have been created to accurately predict areas prone to peptide aggregation. AGGRESCAN, TANGO, and Zyggregator are notable examples that analyze sequences to detect segments with a high propensity for aggregation, such as AGGRESCAN or Zyggregator (Conchillo-Solé et al., 2007; Fernandez-Escamilla et al., 2004; Tartaglia et al., 2007). Furthermore, MD simulations and in silico mutagenesis allow further evaluations of how sequence changes impact aggregation behavior and overall stability (Zhou & Pang, 2018).

To reduce aggregation, several strategies derived from computational predictions can be utilized:

- Amino acid substitutions: Substituting hydrophilic or charged amino acids for those likely to aggregate can help minimize their presence without significantly impacting antimicrobial activity (Chiti & Dobson, 2006; Dobson, 2003).
- Cyclization of peptides: Cycling AMPs may help alter their conformation, decreasing access to regions that lead to aggregation and thus lessening their likelihood (Smith et al., 2006).
- Cosolvents and additives: When used in combination with peptide formulations, cosolvents or additives such as glycerol, arginine, or polyethylene glycol can help stabilize and prevent aggregate formation by interfering with non-specific interactions that lead to aggregate formation (Kelly, 1998; Manning et al., 2010).
- Peptide engineering: By designing peptides with balanced hydrophobic and hydrophilic regions or by including amino acids known as “b-breakers” in their design, engineers can avoid creating b-sheet structures that lead to aggregation (Luheshi & Dobson, 2009; Selkoe, 2003).

While computational predictions provide a foundation for designing less-aggregation-prone peptides, experimental validation is critical. Techniques such as dynamic light scattering, circular dichroism spectroscopy, and atomic force microscopy can characterize the aggregation behavior of AMPs under various conditions; using experimental feedback with computational models helps refine predictions further as well as guide iterative optimization of sequences for reduced aggregation (Wetzel, 2006; Young et al., 2015).

3.4.4 Integrating stability predictions into AMP design

Integrating stability predictions into AMPs design is an innovative strategy to accelerate the development of effective and durable therapeutic agents. This process utilizes computational models to predict how modifications to sequences affect proteolytic degradation, chemical instability, and aggregation before applying this knowledge in the AMP design phase.

Computational tools and algorithms play an integral part in predicting AMP stability. For instance, MD simulations provide detailed insight into how sequence changes or structural modifications might alter their stability (Dror et al., 2010; Kuhlman & Baker, 2000). MD and bioinformatics platforms such as PeptideCutter or AGGRESCAN allow designers to identify potential cleavage sites or aggregate-prone regions for modification, providing designers with a comprehensive basis for AMP stability predictions (Gasteiger et al., 2005). When taken together, these tools provide an accurate basis for predicting their stability (Craik et al., 2013).

Specific sequences and structural modifications can be made to the AMP sequence to increase stability by utilizing computational predictions. Strategies such as amino acid substitution, cyclization, and incorporating nonnatural or D-amino acids are commonly implemented to increase resistance against proteolytic enzymes, reduce susceptibility to chemical degradation, and prevent aggregation. Unfortunately, designing such changes often necessitates iterative rounds of design, prediction, and testing before success (Rosengren et al., 2003).

Rational AMP design employing stability predictions involves an organized, methodical approach to optimize their therapeutic properties. By considering protease resistance, chemical stability, aggregation propensity predictions, and bioavailability predictions, researchers can develop antimicrobials with increased bioavailability and longer half-lives, contributing significantly to clinical efficacy. This integrated approach ensures potency for antimicrobial activity and stability for therapeutic use (Hancock & Sahl, 2006; Zasloff, 2002).

While *in silico* predictions are valuable, experimental validation remains equally essential. Techniques such as mass spectrometry, circular dichroism spectroscopy, and HPLC are used to verify AMP designs under physiological conditions. Feedback from these experiments then helps refine computational models, resulting in an ongoing cycle of prediction, testing, and optimization that continuously enhances accuracy predictions and their efficacy over time (Mann & Jensen, 2003; Pace et al., 2014).

Integrating stability predictions with AMP design is an ongoing field that faces numerous hurdles, such as accurately simulating complex biological environments and forecasting long-term stability. Future advancements could involve the creation of more sophisticated predictive models with multiomics data integration; this would improve our capacity to design stable yet effective AMPs tailored specifically for particular pathogens or therapeutic contexts (Dobson, 2003).

3.5 Toxicity prediction models

Developing AMPs requires striking a balance between effectiveness and toxicity. *In silico* toxicity prediction models play an integral part in the early design stages of an AMP, enabling researchers to assess potential hemolytic activity and cytotoxicity toward mammalian cells before experimental validation. This subsection reviews various computational methods employed in this domain, such as QSAR models and machine learning approaches used for these assessments.

3.5.1 Quantitative structure-activity relationship (QSAR) models

QSAR models form the cornerstone of computational toxicology and drug design, providing insights into chemical structures' relationships and biological activities' relationships. QSAR models have proven especially valuable when used to study AMPs. QSAR models allow users to predict hemolytic activity, cytotoxicity levels, and therapeutic index values to optimize antimicrobials for safe therapeutic applications.

QSAR models utilize statistical techniques to correlate certain features of chemical structures with biological activity, or “molecular descriptors,” such as physical-chemical properties, geometric characteristics, electronic features, or even hydrophobicity that correlates to hydrophobicity charge distribution, amphipathicity, or molecular weight, which play key roles in AMP research (Hansch & Fujita, 1964; Verma et al., 2010). Developing QSAR models for AMPs requires collecting large datasets containing activities known to each molecular descriptor, selecting relevant features from them, and employing statistical methods (multiple linear regression (MLR), partial least squares (PLS), principal component analysis (PCA), etc.) to form the model. Cross-validation, external validation, and assessments of predictive accuracy are often employed to ensure reliability and applicability (Roy et al., 2015; Tropsha, 2010).

QSAR models have become indispensable tools in designing AMPs to anticipate potential human cell toxicity while still achieving antimicrobial efficacy. By identifying molecular features associated with undesired toxic effects, researchers can modify peptide sequences to mitigate them and produce safer AMPs for clinical development (Maccari et al., 2013; Porto et al., 2018).

While QSAR models have proven invaluable for research, they also present significant hurdles, including accurately representing complex peptide structures and dynamic interactions between cells and peptides. Recent advancements in QSAR modeling involve machine learning algorithms such as support vector machines (SVM) or neural networks that can handle nonlinear relationships and complex patterns in large datasets for more accurate and robust predictions (Durrant & McCammon, 2011; Melo et al., 2009).

Combining QSAR models with other computational approaches, such as molecular docking and MD simulations, provides a holistic method for understanding and predicting the behavior of antimicrobial drugs (AMPs). This integrated framework permits simultaneous optimization of antimicrobial potency and minimization of toxicity, ultimately leading to next-generation antimicrobials with increased therapeutic potential (Schneider & Fechner, 2005).

3.5.2 Machine learning approaches

Machine learning (ML) approaches have revolutionized computational biology, offering powerful tools for predicting the activity and toxicity of AMPs. From traditional algorithms to cutting-edge deep learning models, these approaches facilitate the analysis of complex relationships between peptide sequences and biological functions in an unsupervised fashion.

Supervised learning models such as SVMs, decision trees, and random forests have become widely utilized to classify AMPs based on their hemolytic activity and cytotoxicity. By training these models on datasets of known toxic peptides with known toxic profiles, researchers can identify patterns and features crucial for toxicology prediction (Ruiz Puentes et al., 2022). Tools such as ToxiPred use SVM for this task, which gives valuable insights into designing safer AMPs (Porto et al., 2018). Deep learning models, particularly convolutional neural networks (CNNs) and recurrent neural networks (RNNs), have proven adept at accurately representing the complex properties of peptides that interact with biological membranes. CNNs and RNNs process sequential data well, enabling the analysis of linear structures within an AMPs sequence. Learning from large datasets through deep learning approaches allows users to discover subtle sequence-toxicity relationships and more accurately predict AMP toxicity (Spencer et al., 2015).

An integral aspect of using machine learning in AMP research is accurately representing peptides to capture their biological properties. Techniques such as one-hot encoding, physicochemical property encoding, and natural language processing-inspired embeddings convert amino acid sequences into numerical formats suitable for machine learning models; feature selection methods further refine these representations by selecting descriptors relevant to toxicological prediction, thus improving model performance and interpretability (Loperena et al., 2001). Integrating machine learning-based toxicity predictions into the AMP development process enables iterative optimization of peptide sequences to achieve antimicrobial efficacy while minimizing toxic side effects, streamlining the development of therapeutic antimicrobials. In addition, these models may identify nonobvious modifications that reduce toxicity without hindering antimicrobial activity, thereby discovering novel AMP candidates (Veltri et al., 2018).

While ML approaches offer considerable advantages, several challenges remain, such as data scarcity, generalizability, and interpretability of results. Addressing these obstacles requires continuous collection and integration of experimental data and the development of more robust transferable models using AI techniques for AI use. Further developments include

multiomics data integration and transfer learning, with experimental biologists working collaboratively to maximize the predictive power and utility of ML models used for AMP research (Alipanahi et al., 2015).

3.5.3 Integrating MD and toxicity predictions

Integrating MD simulations with toxicity prediction models represents a substantial advancement in the design of AMPs. This combined approach enhances our knowledge of interactions between antimicrobials and biological membranes and offers more in-depth knowledge about structural determinants of toxicology for creating safer therapeutic agents.

MD simulations provide a detailed, atomistic view of the interactions between AMPs and lipid bilayers, providing crucial insight into their mechanism of action and potential cytotoxicity. By simulating their behavior in different membrane environments, researchers can identify factors contributing to membrane disruption, insertion depth changes associated with toxic effects, and any modifications in structure that influence interaction with mammalian or microbial membranes, guiding their development accordingly (Ruiz Puentes et al., 2022). Integrating MD simulations and computational toxicity prediction models allows for a comprehensive assessment of AMP safety profiles. By feeding structural and dynamic data from MD simulations into machine learning or QSAR models, researchers can increase accuracy in toxicity predictions. Furthermore, this integration permits the correlation of specific molecular interactions or conformations observed during simulations with empirical toxicity data, leading to a more nuanced understanding of how design influences toxicological outcomes (Periole & Marrink, 2013).

Many studies have successfully employed this integrated approach to identify nontoxic variants of naturally occurring or synthetic AMPs. By analyzing membrane binding modes through MD simulations and correlating these findings with cytotoxicity data, researchers could design peptides that decreased hemolysis while still offering antimicrobial efficacy (Maleš & Zoranić, 2022).

Although MD simulations with toxicity predictions offer great promise, their use can present several obstacles, such as computational demands and accurately representing complex biological environments. With advances in computational power, simulation methodologies, and the creation of more sophisticated models in mind, the challenges associated with their integration may eventually be surmounted. As future research progresses, it may look into automating this integration method and developing standard protocols to apply these methods across more AMPs with potential off-target effects (Adelusi et al., 2022).

Experimental validation, such as toxicity assays and biophysical measurements, must be included to increase this integrated approach's predictive accuracy and clinical relevance. Feedback between computational predictions and experimental data will refine models, leading to more reliable and clinically relevant predictions. Furthermore, broadening membrane models used for simulations to account for various cell types and pathological conditions will enhance generalizability (Durrant & McCammon, 2011).

3.5.4 Database and web-based tools for toxicity prediction

With the proliferation of databases and web-based tools for toxicity prediction, assessing AMPs and other therapeutic agents has become significantly simpler. These resources compile massive amounts of experimental data, enabling researchers to predict potential toxic effects based on established patterns or relationships.

Databases such as the APD and CAMP_R3 provide more than just sequence and structure data on AMPs; they also include information on their toxicity and therapeutic indices, making these resources invaluable for researchers who want to compare new AMP candidates against an extensive library of known peptides to identify structural features associated with reduced toxicity, which in turn aid in the design of safer AMPs (Waghu et al., 2016; Wang et al., 2016).

Various online platforms specialize in this area and offer tools designed specifically to predict peptides' toxicity, such as ToxiPred and ADMETox. ToxiPred utilizes machine learning algorithms to assess potential cytotoxic effects against mammalian cells; ADMETox offers more general predictions relating to ADME and toxicity as a more thorough assessment of safety profiles (Gupta et al., 2013). Platforms such as SwissADME and pkCSM combine physical property predictions with pharmacokinetic and toxicity evaluation. Researchers can quickly generate profiles that include potential toxicities by entering peptide or small-molecule sequences into these platforms. Such integrative platforms are particularly helpful during the early drug development stages to speed up screening processes (Pires et al., 2015). Web services such as Pred-Skin and Derek Nexus offer online toxicity predictions using QSAR models and machine learning approaches. These predictions are based on QSAR models regularly updated with new data to increase predictive accuracy over time. Their user-friendly interfaces allow nonexperts to use complex computational models for accurate toxicity prediction (Raies & Bajic, 2016).

While databases and tools such as these provide invaluable resources, their limitations must be considered when making predictions. Prediction accuracy may be restricted by data quality and quantity limitations and biological relevance validation experiments conducted before computational predictions are made. Future developments will likely focus on expanding databases with additional diverse datasets while improving algorithms to increase predictive performance.

4 Formulation and delivery system design

4.1 Challenges in AMP formulation: Addressing stability, bioavailability, and controlled release in therapeutic applications

Formulating AMPs for therapeutic applications presents several difficulties, including stability, bioavailability, and controlled release issues. Bioinformatic and computational methods are critical in meeting these challenges, helping design and develop effective AMP-based therapies.

4.1.1 Stability challenges in AMP formulation

Stability is one of the primary obstacles to formulating AMPs. Maintaining their structure and function from manufacturing to administration is vital for their therapeutic effectiveness; bioinformatic and computational approaches have proven invaluable in meeting this challenge.

AMPs may lose activity through thermal denaturation or proteolytic degradation. Bioinformatic tools help identify stable motifs and resistant sequences through comparative analysis and molecular evolution studies, while computational studies such as MD simulations give insight into thermal stability by simulating structural changes at various temperatures; databases such as MEROPS provide additional knowledge; and tools such as PeptideCutter allow prediction and mitigation of proteolytic degradation by identifying cleavage sites and suggesting modifications ([Rawlings et al., 2014](#)).

Chemical degradation such as oxidation, deamidation, and racemization presents additional challenges to AMP stability. Computational chemistry techniques aid in designing AMPs with less susceptibility to chemical degradation while maintaining their antimicrobial properties ([Patel et al., 2001](#); [Xie et al., 2021](#)). In silico models can predict vulnerable sites within peptide sequences, suggesting chemical modifications (for instance, replacing unstable residues or adding nonnatural amino acids). Computational models also assist designers by suggesting appropriate modifications that improve stability. Computational techniques also aid AMP design by helping designers predict which sites within its sequence may present risks; in silico models can predict these sites, which allows more informed decisions.

The formulation can play an essential role in an AMP's stability. Computational tools evaluate interactions between AMPs and various formulation components to predict possible instabilities. This may involve testing for surface adsorption, interactions between excipients, or aggregation tendencies in solution. Simulation software such as GROMACS or CHARMM can model these interactions, leading to formulations that increase stability ([Abraham et al., 2015](#); [Sato & Feix, 2006](#)).

Aggregation and poor solubility can drastically diminish AMP bioavailability and efficacy. Computational screenings to identify regions prone to aggregation and hydrophobicity analysis help identify sequences that could cause solubility issues. At the same time, algorithms such as AGGRESCAN and FoldAmyloid offer insight into aggregate behavior, providing tools that allow the redesign of peptides with improved solubility and reduced self-association ([Conchillo-Solé et al., 2007](#); [Tartaglia et al., 2008](#)).

Unfortunately, creating stable AMP formulations remains challenging due to the complex interrelationships among molecules, environments, and each other. Future developments will likely utilize multiscale simulation techniques that include quantum mechanics, MD, and continuum models; further fostering correlations between computational predictions and experimental validation will also be important for meeting stability challenges in formulation ([Freire et al., 1990](#); [Kamerlin & Warshel, 2010](#)).

4.1.2 Bioavailability issues

Bioavailability issues of AMPs play an essential role in treating infections caused by microbes; their therapeutic efficacy depends heavily on bioavailability—how quickly and completely their active ingredients are absorbed and released at their sites of action. Tackling bioavailability concerns is critical to creating successful AMP-based therapies.

Various factors may reduce the bioavailability of AMPs, such as poor membrane permeability, rapid degradation by proteolytic enzymes, and binding with serum proteins. Computational approaches such as MD simulations and physico-chemical property analyses can predict these interactions and suggest modifications that increase bioavailability (Deslouches & Di, 2017; Lien et al., 2020).

Enhancing AMP stability in biological fluids extends their half-life. It increases bioavailability through techniques such as peptide cyclization, D-amino acids, and the incorporation of nonnatural amino acids. These techniques are tested using in silico models to predict their effects on stability and membrane permeability (Craik et al., 2013). In addition, computational tools are being used to simulate how an AMP interacts with biological membranes to identify sequences that facilitate cell uptake while still possessing antimicrobial activity (Róg & Pasenkiewicz-Gierula, 2001; Tieleman & Marrink, 2006).

Proteolytic degradation significantly diminishes AMP bioavailability. Computational tools such as PeptideCutter can predict potential cleavage sites of peptides to guide resistant sequence design; additionally, molecular docking and QSAR models assist in creating inhibitors against proteases present in biological fluids (Di, 2015; Saravanan et al., 2019).

Effective delivery systems are key to increasing the bioavailability of antimicrobials (AMPs). Computational approaches have proven invaluable in designing nanoparticle carriers, liposomes, or hydrogel matrices tailored specifically for AMP delivery with regard to their encapsulation efficiency, release profiles, and interactions with biological membranes. In silico models can evaluate different formulations of pharmacokinetics and tissue distribution (Immordino et al., 2006; Mahlapuu et al., 2016).

Due to their complex biological systems, accurately predicting and increasing the bioavailability of antimicrobial drugs remain difficult. Future efforts should involve multiscale modeling approaches, from molecular-level interactions to whole-organism pharmacokinetics, for a more comprehensive understanding of bioavailability factors. Coupling computational predictions with high-throughput experimental assays will accelerate optimizing antimicrobials for increased bioavailability and therapeutic efficacy.

4.1.3 Controlled release strategies

A controlled release strategy for AMPs is essential to maintaining therapeutic drug concentrations at the infection site while minimizing toxicity and decreasing the frequency of administration. Bioinformatics and computational methodologies are crucial in designing and evaluating these strategies to ensure sustained effectiveness and greater patient compliance.

When developing delivery systems such as liposomes, nanoparticles, micelles, and hydrogels for controlled release of AMPs, computational modeling is extensively used to predict their encapsulation efficiency, release kinetics, and interaction with biological membranes. Applications such as GROMACS and NAMD simulate such delivery systems within biological environments, which provides insights into mechanisms related to release/stability within carriers (Marrink & Tieleman, 2013; Phillips et al., 2005).

Bioinformatic tools can assist in optimizing AMP encapsulation to protect them from degradation while maintaining antimicrobial activity. Computational screening identifies suitable materials and formulations as carriers of these antimicrobial agents. QSAR models and machine learning algorithms predict the release profiles of different formulations of these agents for easy design of systems that release them when exposed to specific triggers such as pH changes, enzyme activity, or temperature variations (Maurya et al., 2019; Tiwari et al., 2012).

Understanding how controlled release systems interact with target membranes is critical to effectively delivering AMPs. Computational docking and MD simulations provide useful insight into the affinity and orientation of carriers containing AMP-loaded carriers toward microbes' membranes; such studies assist designers in creating delivery systems that efficiently target pathogens while sparing host cells, thus reducing cytotoxicity and side effects (Labouta & Schneider, 2013; Lee et al., 2019).

Bioinformatics and computational modeling technologies have made significant strides toward designing smart delivery systems capable of targeted and stimuli-responsive release of AMPs. For instance, computational studies have allowed for the design of nanocarriers capable of shifting their conformations in response to bacterial enzymes or acidic environments commonly seen at infection sites; this ensures AMPs reach exactly where needed (Yoo et al., 2019).

Although computational approaches have greatly advanced the field of controlled release for AMPs, challenges still remain. One such difficulty is accurately predicting in vivo behavior from in silico models. Future research could concentrate on improving prediction accuracy with multiscale modeling techniques or machine learning and understanding biological barriers to delivery that hinder controlled release systems.

4.2 Integration of computational approaches

Integrating computational approaches transforms the AMP formulation field by optimizing stability, bioavailability, and controlled release. This multidisciplinary strategy harnesses various computational tools, from MD simulations to machine learning algorithms, to address the multifaceted challenges associated with AMP development.

The synergy between MD simulations and bioinformatic analyses facilitates a deeper understanding of AMP mechanisms and interactions at the molecular level. By combining these methods, researchers can predict how AMP modifications affect their structure, dynamics, and interactions with biological membranes or formulation components. This integrated approach aids in designing AMPs with enhanced stability and bioavailability, paving the way for more effective therapeutic formulations (Marrink & Mark, 2003).

Machine learning models are increasingly used to predict AMP properties, including toxicity, efficacy, and pharmacokinetic profiles. By integrating these models with data from molecular simulations and experimental studies, researchers can rapidly screen and optimize vast libraries of peptide sequences, identifying candidates with the most desirable therapeutic properties. This accelerates the development process and reduces the reliance on costly and time-consuming laboratory experiments (Durrant & McCammon, 2011).

QSAR models and computational chemistry techniques are critical for understanding the relationships between AMP structure and formulation outcomes. By integrating these computational models, scientists can identify key physico-chemical properties influencing AMP stability in various formulations and predict the most suitable delivery systems for specific peptides. This approach enables the rational design of AMP formulations that ensure optimal therapeutic performance (Drayton et al., 2020).

Multiscale modeling techniques allow examining AMP-related phenomena across scales, from atomic-level interactions to whole-body pharmacokinetics. This comprehensive analysis is vital for understanding the complexities of AMP behavior in biological systems and developing formulations that address specific therapeutic needs. By integrating data and insights across scales, researchers can create more accurate and predictive models for AMP development (Allen & Cullis, 2013).

Despite significant advancements, integrating computational approaches in AMP formulation still faces challenges, particularly in data integration, model validation, and translation from *in silico* predictions to real-world applications. Future research will likely focus on improving the interoperability of different computational tools, enhancing the accuracy of models through better data and algorithms, and fostering closer collaboration between computational scientists and experimental researchers. The ongoing development of standardized databases and open-source tools will facilitate knowledge sharing and promote innovation in AMP formulation.

4.3 Bioinformatics in formulation design

Bioinformatics-driven formulation design represents an innovative new strategy for developing AMPs. Computational methods provide an effective framework for predicting and optimizing interactions among formulation components and delivery systems that enhance the efficacy, stability, and bioavailability of therapeutic AMPs.

4.3.1 Predictive modeling for peptide-formulation interactions

The application of predictive modeling techniques to understand peptide-formulation interactions has dramatically contributed to drug design, particularly with AMPs. Specifically, predictive modeling utilizes several computational techniques that forecast how different components of pharmaceutical formulations react with each other based on how AMPs interact with them, thus facilitating personalized drug delivery systems with increased therapeutic efficacy and stability.

MD simulations and docking studies represent a cornerstone of predictive modeling, providing detailed insight into physical and chemical interactions between AMPs and formulation constituents. These computational methods enable dynamic visualization of peptide behavior in different environments, including conformational changes, binding affinity interactions with carriers or excipients, and interaction sites between carriers or excipients. Through simulating different formulation conditions, scientists can predict stable yet effective configurations and formulate optimized formulations (Marrink et al., 2007).

Bioinformatic platforms integrate large datasets from experimental peptide studies, providing a holistic view of the behaviors and trends associated with them. By tapping databases such as the Protein Data Bank (PDB) or the APD, researchers can use machine learning algorithms to detect patterns within interactions between various peptide sequences and formulation variables, effectively speeding up formulation design (Waghu et al., 2016; Wang et al., 2016).

QSAR models contribute significantly to predictive modeling by establishing correlations between the chemical structures of peptides and their observed effects in various formulations. By identifying critical physicochemical properties affecting performance, QSAR analyses allow the modification of sequences for improved stability and compatibility with delivery systems. With machine learning capabilities, advanced QSAR techniques produce reliable predictive models that guide AMP formulation development with improved solubility, reduced toxicity, and specific delivery characteristics (Yap, 2011).

For accurate predictive models to be refined and validated by experiment, their predictions must be corroborated with laboratory results to be evaluated against reality. This iterative process between computational modeling and laboratory validation leads to continuous improvements in predictive accuracy and more effective AMP formulations being created over time. Integration also validates computational approaches and provides new insight into interactions between peptide-formulation interactions that could guide future research (Oliveira et al., 2022).

Challenges and future prospects for predictive modeling: While predictive modeling has made great strides, challenges remain in accurately simulating biological systems' complex and dynamic nature. Future advancements should focus on creating more sophisticated computational models for interactions among various peptide formulations; incorporating omics data and systems biology approaches could open new pathways in predictive modeling by providing holistic understandings of peptide behaviors (Allen & Cullis, 2013).

4.3.2 *Optimizing peptide-encapsulation efficiency*

Optimization of peptide encapsulation efficiency is central to increasing the therapeutic potential of AMPs. Advancements in computational modeling and bioinformatics have transformed this aspect of formulation design, enabling precise engineering of delivery systems that preserve integrity while increasing the efficacy of AMPs.

Cutting-edge computational screening methods enable the identification of optimal conditions for peptide encapsulation. By simulating interactions between AMPs and various carrier materials, researchers can predict encapsulation outcomes based on both peptide properties and the composition of the carrier materials. Materials that offer maximum protection of AMPs from degradation should be chosen while simultaneously providing for controlled release at sites of infection. MD simulations offer invaluable insight into the structural compatibility between peptides and potential encapsulants, aiding in designing nanoparticle, liposome, or polymer carriers tailored specifically for each peptide (Marrink et al., 2019).

Bioinformatics is integral in understanding AMPs' structural and functional attributes that influence their encapsulation. By analyzing sequence motifs and physical/chemical properties associated with successful encapsulation, bioinformatic tools provide valuable information for optimizing interactions with delivery systems, such as altering hydrophobicity, charge distribution, or molecular size, to increase effectiveness without impacting antimicrobial activity. Databases such as the APD provide extensive resources for trend identification and designing peptides with favorable encapsulation characteristics (Porto et al., 2018).

Machine learning algorithms have become increasingly popular as predictive models to predict the success of different encapsulation approaches across a broad range of variables. By training models with data from successful and unsuccessful encapsulation attempts, these algorithms can recognize patterns to predict optimal combinations of peptides and carriers; this approach significantly decreases the time and resources required for empirical testing, streamlining the creation of effective AMP formulations (Mooney et al., 2012).

Although advances have been made, challenges still exist when translating computational predictions into practical encapsulation strategies. Due to biological system complexity and variability among individual peptide behaviors, further refining and validation of computational models must occur through experimental studies. Future research may include multiscale modeling approaches ranging from atomic interactions to macropharmacokinetics for a more comprehensive insight into factors impacting encapsulation efficiency (Allen & Cullis, 2013).

As computational and bioinformatic methodologies progress, their integration with experimental pharmacology and materials science will become more crucial. Collaborative efforts that draw upon each field's expertise could speed the creation of AMP formulations with optimized encapsulation efficiency—something that would boost their therapeutic potential and broaden their applicability across various infections.

4.3.3 *Enhancing peptide-delivery system interactions*

Pharmaceutical scientists must prioritize optimizing the interactions between AMPs and their delivery mechanisms to ensure efficient and safe therapeutic action. Due to the complexity of such interactions, bioinformatics and computational methods must be utilized to refine and optimize these mechanisms, assuring targeted, efficient, and safe therapeutic action.

An in-depth knowledge of how peptides interact with biological membranes is central to optimizing delivery system interactions. Computational techniques such as MD simulations provide deep insights into these biophysical interactions between AMPA receptors (AMPs) and lipid bilayers, with modifications of sequence or structure influencing affinity or permeability of membranes; such information allows designers to design delivery systems that target and breach microbial membranes effectively without unintended interactions with mammalian cells, thus minimizing cytotoxicity or off-target effects (Marrink & Tieleman, 2013).

Bioinformatics-aided targeted delivery systems allow the specific administration of antimicrobial medicines (AMPs) directly to infection sites while limiting systemic exposure and side effects. Computational models help design targeting ligands or functionalization strategies that bind specifically to specific receptors or structures on cells or microbes; simulations of endosomal escape mechanisms help optimize nanoparticle formulations to release more AMPs into the target cell cytoplasm, increasing therapeutic efficacy (Torchilin, 2014).

Computational approaches provide significant improvements in designing nanocarriers such as liposomes, polymeric nanoparticles, or micelles for AMP delivery. Bioinformatic analyses and molecular simulations inform the selection of materials and design parameters that improve stability, loading capacity, and release profiles. Machine learning algorithms trained on experimental data can predict optimal nanoparticle sizes, surface charges, and hydrophobicity for increased cell uptake while decreasing immunogenicity. Carriers can be customized to specific therapeutic needs (Gref et al., 2000).

Innovative computational strategies also facilitate the creation of synergistic formulations in which antimicrobial medicines (AMPs) are combined with other therapeutic agents to increase their antimicrobial efficacy. Docking simulation and synergy prediction models identify possible interactions between antibiotics or adjuvants and AMPs, as well as potential codelivery systems that may overcome bacteria's resistance mechanisms. Combined with experimental validation, such computational insights accelerate the development of effective synergistic antimicrobial therapies (Zhang et al., 2010).

4.4 QSAR models in formulation optimization

QSAR models are essential in optimizing pharmaceutical formulations, particularly AMPs. These computational models elucidate the intricate relationship between molecular structures and their pharmacological effects, aiding in formulating effective and safe AMP formulations.

QSAR models use statistical and mathematical techniques to correlate specific molecular descriptors such as hydrophobicity, charge distribution, and molecular volume with biological activities or physical-chemical properties that are of interest. QSAR models allow formulators to optimize solubility, stability, and permeability—three crucial characteristics essential for therapeutic peptide success—by predicting them using QSAR models and identifying structural features that influence these characteristics. QSAR models enable improved formulation characteristics without impacting potency.

Integrating QSAR models with MD simulations enhances formulation optimization's predictive power and reliability. MD simulations offer detailed atomic-level insights into interactions between active pharmaceutical ingredients (APIs) and formulation components and show how different molecular configurations influence peptide behavior. By including MD simulation results in QSAR analyses, researchers can create more accurate and robust models that reflect the dynamic nature of PPI-formulation interactions and develop more targeted delivery systems (Cherkasov et al., 2009).

Advances in QSAR methodologies, particularly their integration of machine learning and artificial intelligence, have dramatically broadened their applications in formulation optimization. These advanced models can manage large datasets while identifying nonlinear relationships more accurately than ever. Furthermore, machine learning algorithms such as neural networks and SVMs facilitate analyzing complex relationships between peptide structures and formulation-dependent behaviors to facilitate faster design of optimal AMP formulations (Madhavi Sastry et al., 2013).

QSAR models used in formulation optimization still face obstacles due to data quality and diversity issues. Increasing attention is focused on building more representative datasets for analysis to increase the predictive accuracy and generalizability of QSAR analyses. For this reason, experimental validation remains integral to turning computational insights into practical formulation strategies (Vapnik & Vapnik, 1998).

QSAR models' future in formulation optimization lies in collaborative efforts that bridge computational chemistry, pharmaceutical sciences, and clinical research. Researchers combining computational predictions with experimental studies and clinical insights can create well-balanced and effective AMP formulations utilizing QSAR models. Such an interdisciplinary approach ensures that QSAR models advance theoretical understandings and drive practical advancements in therapeutic peptide delivery.

4.5 Innovations in AMP delivery: Bioinformatic tools and design of advanced delivery systems

At the forefront of AMP therapeutic innovation, delivery systems are key to increasing therapeutic efficacy and improving patient outcomes. Bioinformatic tools and computational methodologies play a crucial role in this revolution by creating sophisticated delivery vehicles such as nanoparticle carriers, hydrogels, and other advanced systems for targeting patient treatment efficacy and outcomes.

4.5.1 Nanoparticle carriers and computational design

Nanoparticle carriers for AMP delivery represent an innovative step forward in nanomedicine. Utilizing computational design and bioinformatic tools, researchers have created sophisticated nanoparticle systems tailored specifically for improved delivery and efficacy of AMPs, helping overcome traditional obstacles encountered during therapeutic applications.

Computational design forms the cornerstone of nanoparticle carriers, employing sophisticated simulations and modeling techniques to predict interactions between AMPs and nanoparticles. MD simulations offer insights into the structural and dynamic behaviors of nanoparticles interacting with AMPs at an atomic level—thus providing opportunities to optimize properties such as size, charge, and surface chemistry to increase encapsulation efficiency, stability, and cell membrane penetration (Allen & Cullis, 2013).

Bioinformatic approaches supplement computational design by examining biological data related to AMPs and their targets. By employing algorithms that examine the sequences, structures, and biological activities of AMPs and their targets, researchers can identify key features that should be considered during nanoparticle design, including selecting antimicrobial potency, resistance degradation, and compatibility (Porto et al., 2018).

Nanoparticle carriers designed with computational models are tightly intertwined with the principles of drug delivery. By taking into account factors such as targeted delivery, controlled release, biocompatibility, and targeted release strategies when engineering nanoparticles for antimicrobial drug delivery (AMP), QSAR models and machine learning algorithms further refine this process by providing predictions about the outcomes of various formulation strategies, resulting in efficient nanoparticle-based AMP delivery systems (Torchilin, 2014).

Although advances have been made in computational and bioinformatic methodologies, accurate prediction of nanoparticle behavior remains challenging in biological systems. Ongoing efforts aim to increase model fidelity through multi-scale modeling approaches and the incorporation of experimental data. Furthermore, future research directions include investigating novel materials and functionalization strategies to enhance the specificity and efficiency of AMP delivery, as well as creating personalized nanoparticle systems based on patient-specific data and needs (Peppas et al., 2006; Torres-Vanegas et al., 2021).

Nanoparticle carriers' success in antimicrobial therapy delivery relies upon multidisciplinary collaboration and translational research. This collaborative approach will enable safe, effective AMP therapies capable of combating antibiotic resistance by connecting computational design, bioinformatic analysis, clinical application, and theoretical models faster into practical solutions.

4.5.2 Hydrogels and bioinformatics in sustained release

Hydrogels have become an effective technology in the sustained release of AMPs, providing a versatile platform for therapeutic applications. Bioinformatics and computational modeling have revolutionized hydrogel design, permitting precise control over release kinetics while furthering therapeutic efficacy.

Bioinformatics has dramatically impacted the designing of responsive hydrogels capable of adapting their behavior in response to environmental stimuli such as pH, temperature, or enzyme presence. Computational tools model these interactions within hydrogel matrices and with their encapsulated AMPs; these predictions allow engineers to engineer hydrogels that release peptides precisely when and where needed, increasing therapeutic effect while decreasing side effects (Peppas et al., 2006).

Molecular simulations, including MD and Monte Carlo simulations, offer insight into the molecular architecture of hydrogels and their interactions with AMPs at a granular level. By simulating the diffusion of peptides through the matrix of hydrogels, researchers can optimize pore sizes and cross-linking densities for efficient encapsulation and sustained release—ultimately leading to more effective therapies that combine the mechanical properties required for application with release characteristics essential for effective therapy. These simulations help identify ideal formulations that combine the mechanical properties needed for application with the release characteristics necessary for effective therapy applications (Lee & Mooney, 2001).

Bioinformatics tools are vital in evaluating the compatibility between hydrogels and AMPs. By analyzing the sequence and structure of AMPs, these tools can predict how changes to their design might alter encapsulation efficiency, stability within the hydrogel, release kinetics, or release rates of an AMP. Furthermore, analyses of peptide databases may identify features linked to successful hydrogel delivery, which facilitate the selection or modification of AMPs to achieve enhanced therapeutic results (Hoffman, 2012).

Although significant advancement has been achieved, difficulties still exist when accurately predicting in vivo behavior from in vitro and computational models. Future research should focus on creating more sophisticated simulation models that accurately simulate complex interactions among hydrogels, AMPs, biological systems, and their components. Integrating high-throughput experimental data with computational predictions should increase hydrogel design reliability while exploring novel bioactive compounds for hydrogel synthesis. This will broaden the clinical applications of such delivery systems (Highley et al., 2015; Seliktar, 2012).

4.5.3 *Liposomal and polymeric delivery systems*

Liposomal and polymeric delivery systems represent a revolution in AMP therapy, providing innovative solutions to stability, specificity, bioavailability, and bioinformatics challenges. Computational design tools and bioinformatic analyses have proven essential to optimizing these vehicles for delivering AMPs with improved efficacy and delivery timeframes.

Liposomes have emerged as an efficient platform for AMP delivery due to their biocompatibility and ability to encase hydrophilic and hydrophobic molecules, making them especially suited for the task. Computational modeling plays a key role in designing liposomes; simulation of interactions between liposomes and their target molecules allows for the simulation of interactions, formation, and stability under physiological conditions, and MD simulations provide insights into optimal composition/surface modifications that ensure optimal cell targeting, thereby increasing efficiency while simultaneously minimizing off-target effects (Allen & Cullis, 2013).

Polymeric delivery systems incorporating biodegradable polymers such as nanoparticles, micelles, or hydrogels provide controlled release and protection of AMPs from enzymatic degradation. Bioinformatics and computational chemistry assist in selecting polymers with desirable degradation rates, mechanical properties, and biocompatibility properties; advanced modeling techniques predict how chain length and functionalization can influence encapsulation efficiency and release kinetics to design polymeric systems that release AMPs gradually over time to optimize therapeutic outcomes (Langer & Tirrell, 2004).

Bioinformatic tools play a central role in the rational design of both liposomal and polymeric systems. By analyzing large datasets of peptide sequences and structures, these tools can identify critical properties required for effective delivery, such as charge distribution, hydrophobicity, size, and charge distribution motifs and properties that facilitate effective delivery. When integrated with computational models, these data enable targeted delivery systems with increased encapsulation stability and superior antimicrobial activity (Torchilin, 2014).

As advances have increased, designing liposomal and polymeric delivery systems still presents challenges, particularly translating in silico models into in vivo successes. Future efforts will likely focus on creating multiscale models to accurately predict the behavior of these systems in biological environments, bridging theoretical predictions with clinical efficacy; also, exploring novel materials or surface modifications can further improve targeting/release profiles (Oliveira et al., 2022).

Implementing liposomal and polymeric delivery systems designed through computational means into clinical applications requires an interdisciplinary effort, combining computational insights with experimental pharmacology and clinical trials. Collaboration among computational scientists, materials engineers, biologists, and clinicians is vital for addressing the remaining challenges associated with innovative delivery systems for antimicrobial therapy (AMP), such as improving antibiotic resistance. Together, this effort could result in more targeted and safe antimicrobial treatments to meet the rising antibiotic resistance challenge (Highley et al., 2015).

4.5.4 *Integration with experimental data and clinical insights*

Effective translation of bioinformatic predictions and computational designs into effective AMP delivery systems depends upon their integration with experimental data and clinical insights. This convergence forms the cornerstone of translational research approaches, guaranteeing that theoretical models meet real-world therapeutic needs and outcomes.

Integrating laboratory validation of computational models is integral to their refinement. Experimental studies provide essential feedback about the bioavailability, toxicity, and efficacy of designed AMP delivery systems, thus enabling further refinement of computational predictions. Techniques such as in vitro release studies, cell culture assays, and animal models provide vital data that enable scientists to optimize nanoparticle carriers, hydrogels, and other delivery systems for increased performance. Furthermore, advanced imaging and analytical methods further elucidate how these systems

behave within biological environments by directly comparing simulation results and pinpointing areas that need improvement (Lammers et al., 2016; Mitragotri et al., 2015).

The ultimate aim of combining computational design with experimental validation is the successful translation of these technologies into clinical applications. Clinical trials play a central role in this process, providing direct insights into the safety and efficacy of AMP delivery systems in human subjects. Data collected during phase I through III trials not only validate their therapeutic potential but also provide crucial feedback that allows further refinement of computational models, ensuring that they accurately predict clinical outcomes (Etheridge et al., 2013).

While computational design holds great promise for clinical application, translation to practice remains fraught with difficulty. Differences in biological complexity between model systems and humans, individual patient responses, and regulatory hurdles all impede the direct translation of bioinformatically designed therapies directly into patients. To overcome this difficulty, it requires adaptive computational models capable of accommodating a broad array of biological variables as well as factors unique to patients, as well as regulatory strategies that facilitate efficient evaluation and approval processes for novel therapeutic delivery systems (Hafner et al., 2014).

Looking ahead, the integration of computational models with experimental and clinical data should see increased benefit due to advances in data analytics, machine learning, and personalized medicine. Enhancing clinical outcome predictability requires sophisticated computational tools capable of simulating interactions among therapeutic agents, delivery systems, and biological systems. Collaboration among various disciplines—combining computational scientists, bioengineers, pharmacologists, and clinicians—is essential to successfully navigate translational research and realize AMP delivery systems' full potential in clinical settings (Tinkle et al., 2014; Wagner et al., 2006).

5 Conclusion

5.1 Summary of key points: The vital role of bioinformatics in the discovery and development of next-generation AMPs

Bioinformatics has completely transformed the discovery and development of AMPs, signaling an important change in strategies employed to fight microbial resistance. At its core, bioinformatics uses computational power to analyze complex biological data, providing invaluable insight that is instrumental in identifying novel AMP candidates while optimizing therapeutic potential. Furthermore, this interdisciplinary field incorporates information from genomics, proteomics, and molecular biology to gain greater insight into the mechanisms underlying antimicrobial activity as well as resistance mechanisms.

Bioinformatics has revolutionized AMP discovery through data mining from genomic and proteomic databases. Sophisticated algorithms utilize these vast repositories of information to quickly find sequences with characteristics similar to known AMPs, revealing potential new candidates at an unprecedented scale and speed. Tools such as the APD have proven invaluable resources, cataloging AMPs from various sources while providing bioinformatic analyses aimed at finding new peptides.

Optimizing AMP Therapeutic Properties: Beyond discovery, bioinformatics plays an integral part in optimizing the therapeutic properties of AMPs. Computational modeling and simulation techniques assess their SARs, providing a roadmap for how alterations to sequence can alter antimicrobial potency, selectivity, toxicity, or efficacy. Such predictive capabilities help designers craft AMPs with improved efficacy yet reduced side effects, creating therapeutic peptides that are both powerful against pathogens and safe enough for human use.

Addressing antibiotic resistance requires developing novel antimicrobials. Bioinformatics plays a vital role here by identifying antimicrobial mechanisms of action and potential resistance pathways, leading to the design of AMPs capable of bypassing or overpowering microbial defense mechanisms. Furthermore, genetic variations between pathogen populations help predict resistance development as well as select durable AMPs.

Integrating multiomics data—comprising genomics, transcriptomics, proteomics, and metabolomics—offers an unparalleled view into how AMPs interact with microbial cells. Bioinformatics plays an integral part in deciphering this complex data set to understand its multiple impacts on physiology as well as potential targets for antimicrobial action and minimizing resistance development. This holistic approach enhances our knowledge about AMPs within their larger context, thus supporting the development of tailored therapies that minimize resistance development.

Bioinformatics' continued evolution promises to further advance antimicrobial discovery and development. With machine learning and artificial intelligence being adopted into bioinformatic analyses, the predictive accuracy of computational models should increase significantly and enable more efficient identification/optimization of antimicrobials with

even greater efficiency. As bioinformatics tools become more sophisticated, their incorporation into multidisciplinary research efforts will become essential to exploiting their full potential as next-generation antimicrobials.

5.2 Future directions: Emerging trends and technologies in bioinformatics that could revolutionize the design and application of AMPs

Emerging bioinformatics technologies and trends are revolutionizing AMP development, promising to revolutionize how we discover, optimize, and deploy these vital therapeutic agents. By employing advanced computational methods, machine learning algorithms, and new bioinformatics tools in research involving AMPs, precision and efficiency will increase significantly while aiding advances against antibiotic resistance.

Artificial intelligence and machine learning applications in bioinformatics have revolutionized AMP discovery by facilitating the analysis of complex datasets beyond human capabilities. AI algorithms can predict activity, structure-function relationships, and resistance mechanisms with high accuracy, while deep learning models trained on vast databases of AMP sequences and structures are revealing novel peptides with unique mechanisms of action, quickly enabling candidates with potency antimicrobial properties with minimal toxicity.

Systems biology approaches provide unparalleled insights into the complex relationships among antimicrobials (AMPs), microbes, hosts, pathogens (microbiota), antimicrobial-resistant bacteria (biofilms), host organisms (hosts), and pathogens. By integrating data from genomics, proteomics, and metabolomics, bioinformaticians can develop detailed network models revealing AMP effects on host-pathogen dynamics by synthesizing genomic, proteomic, and metabolomics data. These holistic perspectives help in identifying synergistic effects between AMPs and other antimicrobials, ultimately leading to optimal combination therapies.

The rise of CRISPR-Cas and genomic editing technologies presents exciting new avenues for antimicrobial resistance research. Bioinformatics plays a pivotal role in designing CRISPR-Cas systems to manipulate microbial genomes for greater AMP production; similarly, genomic editing may also be used to modify host organisms by increasing the expression and secretion of endogenous antimicrobials as part of an innate immune response, offering new prophylactic and therapeutic strategies.

High-throughput screening and big data analytics: Recent advances in high-throughput screening technologies coupled with big data analytics are facilitating rapid evaluations of AMP libraries against multiple pathogens quickly and accurately. Bioinformatic pipelines process screening data to quickly identify promising AMP candidates, predict their spectrum of activity, and assess any potential toxicity concerns; their integration speeds up development from discovery through to preclinical trials.

Cloud computing and collaborative bioinformatics platforms have revolutionized AMP research globally by providing researchers with real-time access to shared data, tools, computational resources, and computational services in real time, encouraging an open and collaborative atmosphere across disciplines. Researchers worldwide can also contribute to and benefit from advances in AMP development as they emerge, driving innovation forward while hastening the translation of research findings into clinical applications.

5.3 Final thoughts on the integration of bioinformatics into multidisciplinary strategies for combating antibiotic resistance

Antibiotic resistance poses a global health threat that requires a concerted multidisciplinary response; bioinformatics is one of the primary strategies. By harnessing its computational and analytical power and capabilities alongside advances in microbiology, pharmacology, and clinical sciences, we may soon witness a new era in developing and deploying AMPs or other novel therapeutics.

Combating antibiotic resistance requires the coordination of multiple scientific disciplines. Bioinformatics provides an intermediary link, connecting molecular biology with clinical applications. Bioinformatics allows the identification of novel AMP candidates from genetic and proteomic data; the prediction and rational design of enhanced antimicrobial activity peptides; and the analysis of microbial genomes to understand resistance mechanisms. By integrating this insight with experimental pharmacology, it enables optimizing both delivery systems and their contents in terms of efficacy, safety, and reduced resistance development.

Bioinformatics and the personalization of antimicrobial therapy: Emerging trends in bioinformatics, such as machine learning and big data analytics, offer promising avenues for the personalization of antimicrobial therapy. By analyzing

patient-specific data, bioinformatic models can predict individual responses to antibiotics while simultaneously minimizing adverse effects. Such personalized approaches to therapy could transform antimicrobial treatment, making it more targeted, effective, and resistant.

Combating antibiotic resistance is not limited to individual laboratories or countries—it is a global challenge that demands global solutions. Bioinformatics allows researchers worldwide to share data, tools, findings, and results through collaborative platforms created using bioinformatics; these platforms enhance collective understanding of antibiotic resistance while encouraging innovative solution development as well as speedy translation into clinical practice of research discoveries. Furthermore, global initiatives using bioinformatics bring together scientific communities, policymakers, and healthcare providers in a coordinated effort against antibiotic resistance.

Looking ahead, education has an increasingly vital role in bioinformatics and antimicrobial research. Training the next generation of scientists in using bioinformatic tools and multidisciplinary approaches is critical to maintaining progress against antibiotic resistance; public education regarding the responsible use of antibiotics and the importance of supporting antibiotic stewardship programs is also essential to prevent resistance from spreading.

In summary, bioinformatics integration into multidisciplinary strategies represents a beacon of hope in our fight against antibiotic resistance. By harnessing computational analyses, encouraging collaboration across disciplines, and providing education both within the scientific community and at large, we can facilitate novel antimicrobial drug discovery while safeguarding existing therapies—thus making progress toward our ultimate goal more tangible and safeguarding global health more secure. The journey ahead may be difficult, yet with continued innovation and cooperation, we will overcome antibiotic resistance threats and ensure global wellbeing is maintained.

References

- Abraham, M. J., Murtola, T., Schulz, R., Páll, S., Smith, J. C., Hess, B., & Lindahl, E. (2015). Gromacs: High performance molecular simulations through multi-level parallelism from laptops to supercomputers. *SoftwareX*, 1-2, 19–25. Elsevier B.V., Sweden. 23527110. Available from: <http://www.journals.elsevier.com/softwarex/>. <https://doi.org/10.1016/j.softx.2015.06.001>.
- Adelusi, T. I., Oyedele, A. Q. K., Boyenle, I. D., Ogunlana, A. T., Adeyemi, R. O., Ukachi, C. D., Idris, M. O., Olaoba, O. T., Adedotun, I. O., Kolawole, O. E., Xiaoxing, Y., & Abdul-Hammed, M. (2022). Molecular modeling in drug discovery. *Informatics in Medicine Unlocked*, 29. Elsevier Ltd, Nigeria. 23529148. Available from: <http://www.journals.elsevier.com/informatics-in-medicine-unlocked>. <https://doi.org/10.1016/j.imu.2022.100880>.
- Agrawal, P., Bhalla, S., Usmani, S. S., Singh, S., Chaudhary, K., Raghava, G. P. S., & Gautam, A. (2016). CPPsite 2.0: A repository of experimentally validated cell-penetrating peptides. *Nucleic Acids Research*, 44(1). D1098, Oxford University Press, India. 13624962. Available from: <http://nar.oxfordjournals.org/>. <https://doi.org/10.1093/nar/gkv1266>.
- Alipanahi, B., Delong, A., Weirauch, M. T., & Frey, B. J. (2015). Predicting the sequence specificities of DNA- and RNA-binding proteins by deep learning. *Nature Biotechnology*, 33(8), 831–838. Nature Publishing Group, Canada. 15461696. Available from: <http://www.nature.com/nbt/index.html>. <https://doi.org/10.1038/nbt.3300>.
- Allen, T. M., & Cullis, P. R. (2013). Liposomal drug delivery systems: From concept to clinical applications. *Advanced Drug Delivery Reviews*, 65(1), 36–48. 18728294 <https://doi.org/10.1016/j.addr.2012.09.037>.
- Almeida, Z. L., & Brito, R. M. M. (2020). Structure and aggregation mechanisms in amyloids. *Molecules*, 25(5). MDPI AG, Portugal. 14203049. Available from: <https://www.mdpi.com/1420-3049/25/5/1195/pdf>. <https://doi.org/10.3390/molecules25051195>.
- Almeida, J. R., & Martins, M. A. P. (2019). Bioinformatics tools for the design of nanoparticle-based drug delivery systems. *Journal of Nanobiotechnology*, 17.
- Altschul, S. F., Madden, T. L., Schäffer, A. A., Zhang, J., Zhang, Z., Miller, W., & Lipman, D. J. (1997). Gapped BLAST and PSI-BLAST: A new generation of protein database search programs. *Nucleic Acids Research*, 25(17), 3389–3402. 03051048 <https://doi.org/10.1093/nar/25.17.3389>.
- Bailey, T. L., Boden, M., Buske, F. A., Frith, M., Grant, C. E., Clementi, L., Ren, J., Li, W. W., & Noble, W. S. (2009). MEME suite: Tools for motif discovery and searching. *Nucleic Acids Research*, 37(2), W202. 13624962 <https://doi.org/10.1093/nar/gkp335>.
- Bailey, T. L., & Elkan, C. (1994). Fitting a mixture model by expectation maximization to discover motifs in biopolymers. In *Proceedings of the 2nd international conference on intelligent systems for molecular biology*. ISMB 1994 9780929280684 28 36 AAAI Press United States. 1 1994/01.
- Bechinger, B., & Gorr, S. U. (2017). Antimicrobial peptides: Mechanisms of action and resistance. *Journal of Dental Research*, 96(3), 254–260. SAGE Publications Inc., France. 15440591. Available from: <http://jdr.sagepub.com/content/by/year>. <https://doi.org/10.1177/0022034516679973>.
- Bennett, M. J., Schlunegger, M. P., & Eisenberg, D. (1995). 3D domain swapping: A mechanism for oligomer assembly. *Protein Science*, 4(12), 2455–2468. 1469896X <https://doi.org/10.1002/pro.5560041202>.
- Brandenburg, L. O., Merres, J., Albrecht, L. J., Varoga, D., & Pufe, T. (2012). Antimicrobial peptides: Multifunctional drugs for different applications. *Polymers*, 4(1), 539–560. 20734360. Germany. Available from: <http://www.mdpi.com/2073-4360/4/1/539/pdf>. <https://doi.org/10.3390/polym4010539>.
- Brogden, K. A. (2005). Antimicrobial peptides: Pore formers or metabolic inhibitors in bacteria? *Nature Reviews Microbiology*, 3(3), 238–250. <https://doi.org/10.1038/nrmicro1098>.

- Brown, E. D., & Wright, G. D. (2016). Antibacterial drug discovery in the resistance era. *Nature*, 529(7586), 336–343. Nature Publishing Group, Canada. 14764687. Available from: <http://www.nature.com/nature/index.html>. <https://doi.org/10.1038/nature17042>.
- Bulet, P., Stocklin, R., & Menin, L. (2004). Anti-microbial peptides: From invertebrates to vertebrates. *Immunological Reviews*, 198(1), 169–184. 0105-2896 <https://doi.org/10.1111/j.0105-2896.2004.0124.x>.
- Cherkasov, A., Hilpert, K., Jenssen, H., Fjell, C. D., Waldbrook, M., Mullaly, S. C., Volkmer, R., & Hancock, R. E. W. (2009). Use of artificial intelligence in the design of small peptide antibiotics effective against a broad spectrum of highly antibiotic-resistant superbugs. *ACS Chemical Biology*, 4(1), 65–74. 15548929 <https://doi.org/10.1021/cb800240j>.
- Chiti, F., & Dobson, C. M. (2006). Protein misfolding, functional amyloid, and human disease. *Annual Review of Biochemistry*, 75, 333–366. 00664154 <https://doi.org/10.1146/annurev.biochem.75.101304.123901>.
- Cole, C., Barber, J. D., & Barton, G. J. (2008). The Jpred 3 secondary structure prediction server. *Nucleic Acids Research*, 36, W197. (Web Server). 0305-1048 <https://doi.org/10.1093/nar/gkn238>.
- Conchillo-Solé, O., de Groot, N. S., Avilés, F. X., Vendrell, J., Daura, X., & Ventura, S. (2007). AGGRESCAN: A server for the prediction and evaluation of hot spots of aggregation in polypeptides. *BMC Bioinformatics*, 8, 14712105. <https://doi.org/10.1186/1471-2105-8-65>.
- Conlon, J. M., Mechkarska, M., Lukic, M. L., & Platt, P. R. (2014). Potential therapeutic applications of multifunctional host-defense peptides from frog skin as anti-cancer, anti-viral, immunomodulatory, and anti-diabetic agents. *Peptides*, 57, 67–77. Elsevier Inc., United Arab Emirates. 18735169. Available from: <http://www.elsevier.com/locate/peptides>. <https://doi.org/10.1016/j.peptides.2014.04.019>.
- Craik, D. J., Fairlie, D. P., Liras, S., & Price, D. (2013). The future of peptide-based drugs. *Chemical Biology and Drug Design*, 81(1), 136–147. 17470285 <https://doi.org/10.1111/cbdd.12055>.
- Dathe, M., & Wieprecht, T. (1999). Structural features of helical antimicrobial peptides: Their potential to modulate activity on model membranes and biological cells. *Biochimica et Biophysica Acta - Biomembranes*, 1462(1-2), 71–87. 00052736 [https://doi.org/10.1016/S0005-2736\(99\)00201-1](https://doi.org/10.1016/S0005-2736(99)00201-1).
- Deslouches, B., & Di, Y. P. (2017). Antimicrobial peptides with selective antitumor mechanisms: Prospect for anticancer applications. *Oncotarget*, 8(28), 46635–46651. 1949-2553 [10.18632/oncotarget.16743](https://doi.org/10.18632/oncotarget.16743).
- Di, Y. P. (2015). Antimicrobial peptides: New hope in the war against multidrug resistance. *Zoological Research*, 41(6), 488–505.
- Dobson, C. M. (2003). Protein folding and misfolding. *Nature*, 426(6968), 884–890. <https://doi.org/10.1038/nature02261>.
- Drayton, M., Kizhakkedath, J. N., & Strau, S. K. (2020). Towards robust delivery of antimicrobial peptides to combat bacterial resistance. *Molecules*, 25(13). MDPI AG, Canada. 14203049. Available from: <https://www.mdpi.com/1420-3049/25/13/3048/pdf>. <https://doi.org/10.3390/molecules25133048>.
- Dror, O., Nussinov, R., & Wolfson, H. (2010). Predicting molecular interactions in silico: I. A guide to pharmacophore identification and its applications to drug design. *Drug Discovery Today*, 5(4), 165–173. [https://doi.org/10.1016/S1359-6446\(00\)01451-4](https://doi.org/10.1016/S1359-6446(00)01451-4).
- Dürr, U. H. N., Sudheendra, U. S., & Ramamoorthy, A. (2006). LL-37, the only human member of the cathelicidin family of antimicrobial peptides. *Biochimica et Biophysica Acta - Biomembranes*, 1758(9), 1408–1425. 00052736 <https://doi.org/10.1016/j.bbamem.2006.03.030>.
- Durrant, J. D., & McCammon, J. A. (2011). Molecular dynamics simulations and drug discovery. *BMC Biology*, 9, 17417007. United States. Available from: <http://www.biomedcentral.com/1741-7007/9/71>. <https://doi.org/10.1186/1741-7007-9-71>.
- Eddy, S. R., & Pearson, W. R. (2011). Accelerated profile HMM searches. *PLoS Computational Biology*, 7(10), e1002195. 1553-7358 <https://doi.org/10.1371/journal.pcbi.1002195>.
- Etheridge, M. L., Campbell, S. A., Erdman, A. G., Haynes, C. L., Wolf, S. M., & McCullough, J. (2013). The big picture on nanomedicine: The state of investigational and approved nanomedicine products. *Nanomedicine: Nanotechnology, Biology and Medicine*, 9(1), 1–14. 15499642 <https://doi.org/10.1016/j.nano.2012.05.013>.
- Fan, L., Sun, J., Zhou, M., Zhou, J., Lao, X., Zheng, H., & Xu, H. (2016). DRAMP: A comprehensive data repository of antimicrobial peptides. *Scientific Reports*, 6. Nature Publishing Group, China. 20452322. Available from: <http://www.nature.com/srep/index.html>. <https://doi.org/10.1038/srep24482>.
- Fernandez-Escamilla, A. M., Rousseau, F., Schymkowitz, J., & Serrano, L. (2004). Prediction of sequence-dependent and mutational effects on the aggregation of peptides and proteins. *Nature Biotechnology*, 22(10), 1302–1306. <https://doi.org/10.1038/nbt1012>.
- Finn, R. D., Clements, J., & Eddy, S. R. (2011). HMMER web server: Interactive sequence similarity searching. *Nucleic Acids Research*, 39(2), W29. 13624962 <https://doi.org/10.1093/nar/gkr367>.
- Fiser, A., & Šali, A. (2003). MODELLER: generation and refinement of homology-based protein structure models. *Methods in Enzymology*, 374, 461–491. 00766879 [https://doi.org/10.1016/S0076-6879\(03\)74020-8](https://doi.org/10.1016/S0076-6879(03)74020-8).
- Freire, E., Mayorga, O. L., & Straume, M. (1990). Isothermal titration calorimetry. *Analytical Chemistry*, 62(18), 950A. 0003-2700. [10.1021/ac00217a002](https://doi.org/10.1021/ac00217a002).
- Gabere, M. N., & Noble, W. S. (2017). Empirical comparison of web-based antimicrobial peptide prediction tools. *Bioinformatics*, 33(13), 1921–1929. Oxford University Press, Saudi Arabia. 14602059. Available from: <http://bioinformatics.oxfordjournals.org/>. <https://doi.org/10.1093/bioinformatics/btx081>.
- Ganz, T. (2003). Defensins: Antimicrobial peptides of innate immunity. *Nature Reviews Immunology*, 3(9), 710–720. <https://doi.org/10.1038/nri1180>.
- Gasteiger, E., Hoogland, C., Gattiker, A., Duvaud, S. 'e., Wilkins, M. R., Appel, R. D., & Bairoch, A. (2005). *Protein identification and analysis tools on the ExPASy server* (pp. 571–607). Springer Nature. <https://doi.org/10.1385/1-59259-890-0:571>.
- Gentilucci, L., de Marco, R., & Cerisoli, L. (2010). Chemical modifications designed to improve peptide stability: Incorporation of non-natural amino acids, pseudo-peptide bonds, and cyclization. *Current Pharmaceutical Design*, 16(28), 3185–3203. 13816128 <https://doi.org/10.2174/138161210793292555>.
- Georgescu, J., Munhoz, V. H., & Bechinger, B. (2020). The pH-dependent activity of antimicrobial peptides against bacterial pathogens. *Frontiers in Microbiology*, 11. <https://doi.org/10.3389/fmicb.2020.588231>.

- Gref, R., Lück, M., Quellec, P., Marchand, M., Dellacherie, E., Harnisch, S., Blunk, T., & Müller, R. H. (2000). 'Stealth' corona-core nanoparticles surface modified by polyethylene glycol (PEG): Influences of the corona (PEG chain length and surface density) and of the core composition on phagocytic uptake and plasma protein adsorption. *Colloids and Surfaces B: Biointerfaces*, 18(3-4), 301–313. 09277765 [https://doi.org/10.1016/S0927-7765\(99\)00156-3](https://doi.org/10.1016/S0927-7765(99)00156-3).
- Gupta, S., Kapoor, P., Chaudhary, K., Gautam, A., Kumar, R., & Raghava, G. P. S. (2013). In silico approach for predicting toxicity of peptides and proteins. *PLoS One*, 8(9), 19326203. India. Available from: <http://www.plosone.org/article/attachment.action?jsessionid=BFD4330D2451F927CB9068BBF3DEFC6B&uri=info%3Adoi%2F10.1371%2Fjournal.pone.0073957&representation=PDF>. <https://doi.org/10.1371/journal.pone.0073957>.
- Hafner, A., Lovrić, J., Lakš, G. P., & Pepić, I. (2014). Nanotherapeutics in the EU: An overview on current state and future directions. *International Journal of Nanomedicine*, 9(1), 1005–1023. 11782013. Croatia. Available from: <http://www.dovepress.com/getfile.php?fileID=19061>. <https://doi.org/10.2147/IJN.S55359>.
- Hamamoto, K., Kida, Y., Zhang, Y., Shimizu, T., & Kuwano, K. (2002). Antimicrobial activity and stability to proteolysis of small linear cationic peptides with D-amino acid substitutions. *Microbiology and Immunology*, 46(11), 741–749. Center for Academic Publications Japan, Japan. 03855600. Available from: [http://onlinelibrary.wiley.com/journal/10.1111/\(ISSN\)1348-0421](http://onlinelibrary.wiley.com/journal/10.1111/(ISSN)1348-0421). <https://doi.org/10.1111/j.1348-0421.2002.tb02759.x>.
- Hammami, R., Zouhir, A., Le Lay, C., Hamida, J. B., & Fliss, I. (2010). BACTIBASE second release: A database and tool platform for bacteriocin characterization. *BMC Microbiology*, 10(1), 1471–2180. <https://doi.org/10.1186/1471-2180-10-22>.
- Hancock, R. E. W., & Chapple, D. S. (1999). Peptide antibiotics. *Antimicrobial Agents and Chemotherapy*, 43(6), 1317–1323. American Society for Microbiology, Canada. 00664804. Available from: <http://aac.asm.org/>. 10.1128/aac.43.6.1317.
- Hancock, R. E. W., & Lehrer, R. (1998). Cationic peptides: A new source of antibiotics. *Trends in Biotechnology*, 16(2), 82–88. 01677799 [https://doi.org/10.1016/S0167-7799\(97\)01156-6](https://doi.org/10.1016/S0167-7799(97)01156-6).
- Hancock, R. E. W., & Sahl, H. G. (2006). Antimicrobial and host-defense peptides as new anti-infective therapeutic strategies. *Nature Biotechnology*, 24(12), 1551–1557. 15461696 <https://doi.org/10.1038/nbt1267>.
- Haney, E. F., Mansour, S. C., Hilchie, A. L., De La Fuente-Núñez, C., & Hancock, R. E. W. (2015). High throughput screening methods for assessing antibiofilm and immunomodulatory activities of synthetic peptides. *Peptides*, 71, 276–285. Elsevier Inc., Canada 18735169. Available from: <http://www.elsevier.com/locate/peptides>. <https://doi.org/10.1016/j.peptides.2015.03.015>.
- Hansch, C., & Fujita, T. (1964). ρ - σ - π Analysis. A method for the correlation of biological activity and chemical structure. *Journal of the American Chemical Society*, 86(8), 1616–1626. 15205126 <https://doi.org/10.1021/ja01062a035>.
- Harris, F., Dennison, S. R., & Phoenix, D. A. (2009). Anionic antimicrobial peptides from eukaryotic organisms. *Current Protein and Peptide Science*, 10(6), 585–606. 13892037. United Kingdom. Available from: http://docstore.ingenta.com/cgi-bin/ds_deliver/1/u/d/ISIS/54166077.1/ben/cpps/2009/00000010/00000006/art00006/E7787C4584BAFD881262176514529C66C0948E6F79.pdf?link=http://www.ingentaconnect.com/error/delivery&format=pdf. <https://doi.org/10.2174/138920309789630589>.
- Highley, C. B., Rodell, C. B., & Burdick, J. A. (2015). Direct 3D printing of shear-thinning hydrogels into self-healing hydrogels. *Advanced Materials*, 27(34), 5075–5079. Wiley-VCH Verlag, United States. 15214095. Available from: <http://www3.interscience.wiley.com/journal/119030556/issue>. <https://doi.org/10.1002/adma.201501234>.
- Hoffman, A. S. (2012). Hydrogels for biomedical applications. *Advanced Drug Delivery Reviews*, 64, 18–23. 18728294 <https://doi.org/10.1016/j.addr.2012.09.010>.
- Immordino, M. L., Dosio, F., & Cattel, L. (2006). Stealth liposomes: Review of the basic science, rationale, and clinical applications, existing and potential. *International Journal of Nanomedicine*, 1(3), 297–315. 11782013. Italy. Available from: <http://www.dovepress.com/getfile.php?fileID=2667>.
- Jenssen, H., Hamill, P., & Hancock, R. E. W. (2006). Peptide antimicrobial agents. *Clinical Microbiology Reviews*, 19(3), 491–511. 08938512 <https://doi.org/10.1128/CMR.00056-05>.
- Jones, D. T. (1999). Protein secondary structure prediction based on position-specific scoring matrices. *Journal of Molecular Biology*, 292(2), 195–202. Academic Press, United Kingdom. 00222836. Available from: <http://www.elsevier.com/inca/publications/store/6/2/2/8/9/0/index.htm>. <https://doi.org/10.1006/jmbi.1999.3091>.
- Jumper, J., Evans, R., Pritzel, A., Green, T., Figurnov, M., Ronneberger, O., Tunyasuvunakool, K., Bates, R., Žídek, A., Potapenko, A., Bridgland, A., Meyer, C., Kohl, S. A. A., Ballard, A. J., Cowie, A., Romera-Paredes, B., Nikolov, S., Jain, R., Adler, J., ... Hassabis, D. (2021). Highly accurate protein structure prediction with AlphaFold. *Nature*, 596(7873), 583–589. Nature Research, United Kingdom 14764687. Available from: <http://www.nature.com/nature/index.html>. <https://doi.org/10.1038/s41586-021-03819-2>.
- Kamerlin, S. C. L., & Warshel, A. (2010). At the dawn of the 21st century: Is dynamics the missing link for understanding enzyme catalysis. *Proteins: Structure, Function, and Bioinformatics*, 78(6), 1339–1375. 10970134 <https://doi.org/10.1002/prot.22654>.
- Kang, X., Dong, F., Shi, C., Liu, S., Sun, J., Chen, J., Li, H., Xu, H., Lao, X., & Zheng, H. (2019). DRAMP 2.0, an updated data repository of antimicrobial peptides. *Scientific Data*, 6(1). Nature Research, China. 20524463. Available from: <http://www.nature.com/sdata/>. <https://doi.org/10.1038/s41597-019-0154-y>.
- Katoh, K., & Standley, D. M. (2013). MAFFT multiple sequence alignment software version 7: Improvements in performance and usability. *Molecular Biology and Evolution*, 30(4), 772–780. 15371719 <https://doi.org/10.1093/molbev/mst010>.
- Kelly, J. W. (1998). The alternative conformations of amyloidogenic proteins and their multi-step assembly pathways. *Current Opinion in Structural Biology*, 8(1), 101–106. Elsevier Ltd, United States. 0959440X. Available from: <http://www.elsevier.com/locate/sbi>. [https://doi.org/10.1016/S0959-440X\(98\)80016-X](https://doi.org/10.1016/S0959-440X(98)80016-X).

- Kessler, H. (1982). Conformation and biological activity of cyclic peptides. *Angewandte Chemie International Edition in English*, 21(7), 512–523. 15213773 <https://doi.org/10.1002/anie.198205121>.
- Kola, I., & Landis, J. (2004). Can the pharmaceutical industry reduce attrition rates? *Nature Reviews Drug Discovery*, 3(8), 711–715. Nature Publishing Group, United States 14741776. Available from: <http://www.nature.com/nrd/index.html>. <https://doi.org/10.1038/nrd1470>.
- Koo, H. B., & Seo, J. (2019). Antimicrobial peptides under clinical investigation. *Peptide Science*, 111(5). John Wiley and Sons Inc., South Korea. 24758817. Available from: [http://onlinelibrary.wiley.com/journal/10.1002/\(ISSN\)1097-0282a](http://onlinelibrary.wiley.com/journal/10.1002/(ISSN)1097-0282a). <https://doi.org/10.1002/pep2.24122>.
- Kuhlman, B., & Baker, D. (2000). Native protein sequences are close to optimal for their structures. *Proceedings of the National Academy of Sciences*, 97(19), 10383–10388. 0027-8424 <https://doi.org/10.1073/pnas.97.19.10383>.
- Labouta, H. I., & Schneider, M. (2013). Interaction of inorganic nanoparticles with the skin barrier: Current status and critical review. *Nanomedicine: Nanotechnology, Biology and Medicine*, 9(1), 39–54. 15499642 <https://doi.org/10.1016/j.nano.2012.04.004>.
- Lai, Y., & Gallo, R. L. (2009). AMPed up immunity: How antimicrobial peptides have multiple roles in immune defense. *Trends in Immunology*, 30(3), 131–141. 14714906 <https://doi.org/10.1016/j.it.2008.12.003>.
- Lammers, T., Kiessling, F., Ashford, M., Hennink, W., Crommelin, D., & Storm, G. (2016). Cancer nanomedicine: Is targeting our target? *Nature Reviews Materials*, 1(9), 2058–8437. <https://doi.org/10.1038/natrevmats.2016.69>.
- Langer, R., & Tirrell, D. A. (2004). Designing materials for biology and medicine. *Nature*, 428(6982), 487–492. <https://doi.org/10.1038/nature02388>.
- Lazzaro, B. P., Zasloff, M., & Rolff, J. (2020). Antimicrobial peptides: Application informed by evolution. *Science*, 368(6490), eaau5480. <https://doi.org/10.1126/science.aau5480>.
- Lee, A. C. L., Harris, J. L., Khanna, K. K., & Hong, J. H. (2019). A comprehensive review on current advances in peptide drug development and design. *International Journal of Molecular Sciences*, 20(10). MDPI AG, Australia. 14220067. Available from: <https://www.mdpi.com/1422-0067/20/10/2383/pdf>. <https://doi.org/10.3390/ijms20102383>.
- Lee, K. Y., & Mooney, D. J. (2001). Hydrogels for tissue engineering. *Chemical Reviews*, 101(7), 1869–1879. 00092665 <https://doi.org/10.1021/cr000108x>.
- Lehrer, R. I., & Ganz, T. (2002). Defensins of vertebrate animals. *Current Opinion in Immunology*, 14(1), 96–102. Elsevier Ltd, United States. 09527915. Available from: <http://www.journals.elsevier.com/current-opinion-in-immunology/>. [https://doi.org/10.1016/S0952-7915\(01\)00303-X](https://doi.org/10.1016/S0952-7915(01)00303-X).
- Lewis, K. (2013). Platforms for antibiotic discovery. *Nature Reviews Drug Discovery*, 12(5), 371–387. 14741784 <https://doi.org/10.1038/nrd3975>.
- Lien, E. C., Ghislat, G., Nassif, H., Chan, R. B., Rousakis, A., Zhang, Y., & Glicksman, M. A. (2020). Bioavailability challenges of peptides and strategies for enhancement. *Life Sciences*, 260.
- Loperena, A. L., Qian, N., & Kolattukudy, P. E. (2001). Machine learning-based feature selection for prediction of the biological activity of short peptides. *Peptides*, 22(12), 540–548. [https://doi.org/10.1016/S0196-9781\(01](https://doi.org/10.1016/S0196-9781(01).
- Luheshi, L. M., & Dobson, C. M. (2009). Bridging the gap: From protein misfolding to protein misfolding diseases. *FEBS Letters*, 583(16), 2581–2586. 00145793 <https://doi.org/10.1016/j.febslet.2009.06.030>.
- Maccari, G., Di Luca, M., Nifosi, R., Cardarelli, F., Signore, G., Boccardi, C., Bifone, A., & Grubmüller, H. (2013). Antimicrobial peptides design by evolutionary multiobjective optimization. *PLoS Computational Biology*, 9(9), e1003212. 1553-7358 <https://doi.org/10.1371/journal.pcbi.1003212>.
- Madhavi Sastry, G., Adzhigirey, M., Day, T., Annabhimoju, R., & Sherman, W. (2013). Protein and ligand preparation: Parameters, protocols, and influence on virtual screening enrichments. *Journal of Computer-Aided Molecular Design*, 27(3), 221–234. Kluwer Academic Publishers, India. 15734951. Available from: <https://www.springer.com/journal/10822>. <https://doi.org/10.1007/s10822-013-9644-8>.
- Mahlpuu, M., Håkansson, J., Ringstad, L., & Björn, C. (2016). Antimicrobial peptides: An emerging category of therapeutic agents. *Frontiers in Cellular and Infection Microbiology*, 6.
- Maleš, M., & Zoranić, L. (2022). Simulation study of the effect of antimicrobial peptide associations on the mechanism of action with bacterial and eukaryotic membranes. *Membranes*, 12(9), 891. 2077-0375 <https://doi.org/10.3390/membranes12090891>.
- Mann, M., & Jensen, O. N. (2003). Proteomic analysis of post-translational modifications. *Nature Biotechnology*, 21(3), 255–261. <https://doi.org/10.1038/nbt0303-255>.
- Manning, M. C., Chou, D. K., Murphy, B. M., Payne, R. W., & Katayama, D. S. (2010). Stability of protein pharmaceuticals: An update. *Pharmaceutical Research*, 27(4), 544–575. 1573904X <https://doi.org/10.1007/s11095-009-0045-6>.
- Marr, A. K., Gooderham, W. J., & Hancock, R. E. (2006). Antibacterial peptides for therapeutic use: Obstacles and realistic outlook. *Current Opinion in Pharmacology*, 6(5), 468–472. 14714892 <https://doi.org/10.1016/j.coph.2006.04.006>.
- Marrink, S. J., Corradi, V., Souza, P. C. T., Ingólfsson, H. I., Tieleman, D. P., & Sansom, M. S. P. (2019). Computational modeling of realistic cell membranes. *Chemical Reviews*, 119(9), 6184–6226. American Chemical Society, Netherlands. 15206890. Available from: <http://pubs.acs.org/journal/creay>. <https://doi.org/10.1021/acs.chemrev.8b00460>.
- Marrink, S. J., & Mark, A. E. (2003). Molecular dynamics simulation of the formation, structure, and dynamics of small phospholipid vesicles. *Journal of the American Chemical Society*, 125(49), 15233–15242. 00027863 <https://doi.org/10.1021/ja0352092>.
- Marrink, S. J., Risselada, H. J., Yefimov, S., Tieleman, D. P., & De Vries, A. H. (2007). The MARTINI force field: Coarse grained model for biomolecular simulations. *Journal of Physical Chemistry B*, 111(27), 7812–7824. American Chemical Society, Netherlands. 15206106. Available from: <http://pubs.acs.org/journal/jpcbtk>. <https://doi.org/10.1021/jp071097f>.
- Marrink, S. J., & Tieleman, D. P. (2013). Perspective on the martini model. *Chemical Society Reviews*, 42(16), 6801–6822. 14604744 <https://doi.org/10.1039/c3cs60093a>.
- Marrink, S. J., & Vries, (2004). The molecular face of lipid rafts in model membranes. *National Academy of Sciences of the United States of America*, 101(4), 10826–10831. <https://doi.org/10.1073/pnas.0403517101>.

- Matsuzaki, K. (1999). Why and how are peptide-lipid interactions utilized for self-defense? Magainins and tachyplesins as archetypes. *Biochimica et Biophysica Acta - Biomembranes*, 1462(1-2), 1–10. 00052736 [https://doi.org/10.1016/S0005-2736\(99\)00197-2](https://doi.org/10.1016/S0005-2736(99)00197-2).
- Matsuzaki, K. (2009). Control of cell selectivity of antimicrobial peptides. *Biochimica et Biophysica Acta - Biomembranes*, 1788(8), 1687–1692. 00052736 <https://doi.org/10.1016/j.bbamem.2008.09.013>.
- Maurya, N. S., Kushwaha, S., & Mani, A. (2019). Recent advances and computational approaches in peptide drug discovery. *Current Pharmaceutical Design*, 25(31), 3358–3366. Bentham Science Publishers, India. 18734286. Available from: <http://www.eurekaselect.com/174817/article>. <https://doi.org/10.2174/1381612825666190911161106>.
- Meli, M., Morra, G., & Colombo, G. (2008). Investigating the mechanism of peptide aggregation: Insights from mixed Monte Carlo-molecular dynamics simulations. *Biophysical Journal*, 94(11), 4414–4426. Biophysical Society, Italy 15420086. Available from: <http://download.cell.com/biophysj/pdf/PIIS0006349508700961.pdf?intermediate=true>. <https://doi.org/10.1529/biophysj.107.121061>.
- Melo, M. N., Ferre, R., & Castanho, M. A. R. B. (2009). Antimicrobial peptides: Linking partition, activity and high membrane-bound concentrations. *Nature Reviews Microbiology*, 7(3), 245–250. 17401526 <https://doi.org/10.1038/nrmicro2095>.
- Metanis, N., Keinan, E., & Dawson, P. E. (2010). Traceless ligation of cysteine peptides using selective deselenization. *Angewandte Chemie, International Edition*, 49(39), 7049–7053. 15213773. Israel. Available from: <http://onlinelibrary.wiley.com/doi/10.1002/anie.201001900/pdf>. <https://doi.org/10.1002/anie.201001900>.
- Mitragotri, S., Anderson, D. G., Chen, X., Chow, E. K., Ho, D., Kabanov, A. V., Karp, J. M., Kataoka, K., Mirkin, C. A., Petrosko, S. H., Shi, J., Stevens, M. M., Sun, S., Teoh, S., Venkatraman, S. S., Xia, Y., Wang, S., Gu, Z., & Xu, C. (2015). Accelerating the translation of nanomaterials in biomedicine. *ACS Nano*, 9(7), 6644–6654. American Chemical Society, United States. 1936086X. Available from: <http://pubs.acs.org/journal/ancac3>. <https://doi.org/10.1021/acs.nano.5b03569>.
- Mooney, C., Haslam, N. J., Pollastri, G., & Shields, D. C. (2012). Towards the improved discovery and design of functional peptides: Common features of diverse classes permit generalized prediction of bioactivity. *PLoS One*, 7(10), 19326203. Ireland. Available from: <http://www.plosone.org/article/attachment.action?uri=info%3Adoi%2F10.1371%2Fjournal.pone.0045012&representation=PDF>. <https://doi.org/10.1371/journal.pone.0045012>.
- Müller, A. T., Hiss, J. A., & Schneider, G. (2018). Recurrent neural network model for constructive peptide design. *Journal of Chemical Information and Modeling*, 58(2), 472–479. American Chemical Society, Switzerland. 1549960X. Available from: <http://pubs.acs.org/journal/jcis8>. <https://doi.org/10.1021/acs.jcim.7b00414>.
- Nguyen, L. T., Chau, J. K., Perry, N. A., de Boer, L., Zaat, S. A. J., & Vogel, H. J. (2010). Serum stabilities of short tryptophan- and arginine-rich antimicrobial peptide analogs. *PLoS One*, 5(9), 1–8. 19326203. Canada. Available from: <http://www.plosone.org/article/attachment.action?uri=info%3Adoi%2F10.1371%2Fjournal.pone.0012684&representation=PDF>. <https://doi.org/10.1371/journal.pone.0012684>.
- Oliveira, C., Taube, P. S., Lima, A. H., & Junior, C. D. S. D. S. (2022). Biological membrane-penetrating peptides: Computational prediction and applications. *Frontiers in Cellular and Infection Microbiology*, 12.
- Pace, C. N., Fu, H., Fryar, K. L., Landua, J., Trevino, S. R., Schell, D., Thurlkill, R. L., Imura, S., Scholtz, J. M., Gajiwala, K., Sevcik, J., Urbanikova, L., Myers, J. K., Takano, K., Hebert, E. J., Shirley, B. A., & Grimsley, G. R. (2014). Contribution of hydrogen bonds to protein stability. *Protein Science*, 23(5), 652–661. Blackwell Publishing Ltd, United States. 1469896X. Available from: [http://onlinelibrary.wiley.com/journal/10.1002/\(ISSN\)1469-896X](http://onlinelibrary.wiley.com/journal/10.1002/(ISSN)1469-896X). <https://doi.org/10.1002/pro.2449>.
- Patel, K., Piagentini, M., Rascher, A., Tian, X., Buchanan, G., Regnier, F., & Skiles, G. L. (2001). Oxidation of methionine residues in polypeptide pharmaceuticals: Chemical, physical, and biological consequences. *Biological and Pharmaceutical Bulletin*, 24(6), 667–677. <https://doi.org/10.1248/bpb.24.667>.
- Payne, D. J., Gwynn, M. N., Holmes, D. J., & Pompliano, D. L. (2007). Drugs for bad bugs: Confronting the challenges of antibacterial discovery. *Nature Reviews Drug Discovery*, 6(1), 29–40. 14741784 <https://doi.org/10.1038/nrd2201>.
- Pearson, W. R. (2013). An introduction to sequence similarity (“homology”) searching. *Current Protocols in Bioinformatics*, 42, 1934340X. United States. Available from: <http://onlinelibrary.wiley.com/store/10.1002/0471250953.bi0301s42/asset/bi0301.pdf?v=1&t=hl30qnf&s=b7cbecc4e490370a549d91d7ddb9a8506b9fcb78>. <https://doi.org/10.1002/0471250953.bi0301s42>.
- Peppas, N. A., Hilt, J. Z., Khademhosseini, A., & Langer, R. (2006). Hydrogels in biology and medicine: From molecular principles to bionanotechnology. *Advanced Materials*, 18(11), 1345–1360. 09359648 <https://doi.org/10.1002/adma.200501612>.
- Periole, X., & Marrink, S. J. (2013). The martini coarse-grained force field. *Methods in Molecular Biology*, 924, 533–565. Humana Press Inc., undefined. 10643745. Available from: <http://www.springer.com/series/7651>. https://doi.org/10.1007/978-1-62703-17-5_20.
- Perron, G. G., Zasloff, M., & Bell, G. (2006). Experimental evolution of resistance to an antimicrobial peptide. *Proceedings of the Royal Society B: Biological Sciences*, 273(1583), 251–256. Royal Society, Canada. 14712970. Available from: <http://rspb.royalsocietypublishing.org/>. <https://doi.org/10.1098/rspb.2005.3301>.
- Phillips, J. C., Braun, R., Wang, W., Gumbart, J., Tajkhorshid, E., Villa, E., Chipot, C., Skeel, R. D., Kalé, L., & Schulten, K. (2005). Scalable molecular dynamics with NAMD. *Journal of Computational Chemistry*, 26(16), 1781–1802. John Wiley and Sons Inc., United States. 1096987X. Available from: [http://onlinelibrary.wiley.com/journal/10.1002/\(ISSN\)1096-987X](http://onlinelibrary.wiley.com/journal/10.1002/(ISSN)1096-987X). <https://doi.org/10.1002/jcc.20289>.
- Pires, D. E. V., Blundell, T. L., & Ascher, D. B. (2015). pkCSM: Predicting small-molecule pharmacokinetic and toxicity properties using graph-based signatures. *Journal of Medicinal Chemistry*, 58(9), 4066–4072. American Chemical Society, United Kingdom 15204804. Available from: <http://pubs.acs.org/jmc>. <https://doi.org/10.1021/acs.jmedchem.5b00104>.
- Pirtskhalava, M., Armstrong, A. A., Grigolava, M., Chubinidze, M., Alimbarashvili, E., Vishnepolsky, B., Gabrielian, A., Rosenthal, A., Hurt, D. E., & Tartakovsky, M. (2021). DBAASP v3: Database of antimicrobial/cytotoxic activity and structure of peptides as a resource for development of new

- therapeutics. *Nucleic Acids Research*, 49(1), D288, Oxford University Press, Georgia. 13624962. Available from: <https://academic.oup.com/nar/issue>. <https://doi.org/10.1093/nar/gkaa991>.
- Porto, W. F., Pires, Á. S., & Franco, O. L. (2018). Predicting antimicrobial peptides with improved specificity: Focus on machine learning. *Bioinformatics*, 34(8), 1333–1342.
- Powers, J. P. S., & Hancock, R. E. W. (2003). The relationship between peptide structure and antibacterial activity. *Peptides*, 24(11), 1681–1691. Elsevier Inc., Canada. 01969781. Available from: <http://www.elsevier.com/locate/peptides>. <https://doi.org/10.1016/j.peptides.2003.08.023>.
- Raies, A. B., & Bajic, V. B. (2016). In silico toxicology: computational methods for the prediction of chemical toxicity. *Wiley Interdisciplinary Reviews: Computational Molecular Science*, 147–172. Blackwell Publishing Inc., Saudi Arabia 17590884. Available from: [http://onlinelibrary.wiley.com/journal/10.1111/\(ISSN\)1759-0884](http://onlinelibrary.wiley.com/journal/10.1111/(ISSN)1759-0884). <https://doi.org/10.1002/wcms.1240>.
- Rawlings, N. D., Waller, M., Barrett, A. J., & Bateman, A. (2014). MEROPS: The database of proteolytic enzymes, their substrates and inhibitors. *Nucleic Acids Research*, 42(1), D503. 13624962 <https://doi.org/10.1093/nar/gkt953>.
- Rennie, J., Noyce, R. S., & Mossman, K. L. (2019). Opportunities and challenges of antiviral peptides as therapeutics. *Chemical Reviews*, 119(12), 7057–7107. <https://doi.org/10.1021/acs.chemrev.8b00536>.
- Richter, A., Sutherland, D., Ebrahimikondori, H., Babcock, A., Louie, N., Li, C., Coombe, L., Lin, D., Warren, R. L., Yanai, A., Kotkoff, M., Helbing, C. C., Hof, F., Hoang, L. M. N., & Birol, I. (2022). Associating biological activity and predicted structure of antimicrobial peptides from amphibians and insects. *Antibiotics*, 11(12), 1710. 2079-6382 <https://doi.org/10.3390/antibiotics11121710>.
- Robinson, N. E., & Robinson, A. B. (2004). Deamidation of human proteins. *National Academy of Sciences of the United States of America*, 101(21), 8234–8239. <https://doi.org/10.1073/pnas.0401336101>.
- Rodríguez-Cerdeira, C., Molares-Vila, A., Sánchez-Cárdenas, C. D., Velásquez-Bámaca, J. S., & Martínez-Herrera, E. (2023). Bioinformatics approaches applied to the discovery of antifungal peptides. *Antibiotics*, 12(3). MDPI, Spain. 20796382. Available from: <http://www.mdpi.com/journal/antibiotics>. <https://doi.org/10.3390/antibiotics12030566>.
- Róg, T., & Pasenkiewicz-Gierula, M. (2001). Cholesterol effects on the phosphatidylcholine bilayer nonpolar region: A molecular simulation study. *Biophysical Journal*, 81(4), 2190–2202. Biophysical Society, Poland. 00063495. Available from: <http://www.sciencedirect.com/science/journal/00063495>. [https://doi.org/10.1016/S0006-3495\(01\)75867-5](https://doi.org/10.1016/S0006-3495(01)75867-5).
- Rohl, C. A., Strauss, C. E. M., Misura, K. M. S., & Baker, D. (2004). Protein structure prediction using Rosetta. *Methods in Enzymology*, 383, 66–93. 00766879 [https://doi.org/10.1016/S0076-6879\(04\)83004-0](https://doi.org/10.1016/S0076-6879(04)83004-0).
- Rosenfeld, Y., Papo, N., & Shai, Y. (2006). Endotoxin (lipopolysaccharide) neutralization by innate immunity host-defense peptides: Peptide properties and plausible modes of action. *Journal of Biological Chemistry*, 281(3), 1636–1643. 1083351X. Israel. Available from: <http://www.jbc.org/cgi/reprint/281/3/1636>. <https://doi.org/10.1074/jbc.M504327200>.
- Rosengren, K. J., Clark, R. J., Daly, N. L., Göransson, U., Jones, A., & Craik, D. J. (2003). Microcin J25 has a threaded sidechain-to-backbone ring structure and not a head-to-tail cyclized backbone. *Journal of the American Chemical Society*, 125(41), 12464–12474. 00027863 <https://doi.org/10.1021/ja0367703>.
- Roy, K., Kar, S., & Das, R. N. (2015). *A primer on QSAR/QSPR modeling: Fundamental concepts Springer briefs in molecular science*. Springer International Publishing. <https://doi.org/10.1007/978-3-319-17281-1>.
- Ruiz Puentes, P., Henao, M. C., Cifuentes, J., Muñoz-Camargo, C., Reyes, L. H., Cruz, J. C., & Arbeláez, P. (2022). Rational discovery of antimicrobial peptides by means of artificial intelligence. *Membranes*, 12(7). MDPI, Colombia. 20770375. Available from: <http://www.mdpi.com/journal/membranes>. <https://doi.org/10.3390/membranes12070708>.
- Šali, A., & Blundell, T. L. (1993). Comparative protein modelling by satisfaction of spatial restraints. *Journal of Molecular Biology*, 234(3), 779–815. 00222836 <https://doi.org/10.1006/jmbi.1993.1626>.
- Saravanan, R., Joshi, M., Mohanram, H., Nair, D., & Banerjee, R. (2019). Membrane active peptides and their biophysical characterization. *Biomolecules*, 9(8).
- Sato, H., & Feix, J. B. (2006). Peptide-membrane interactions and mechanisms of membrane destruction by amphipathic α -helical antimicrobial peptides. *Biochimica et Biophysica Acta - Biomembranes*, 1758(9), 1245–1256. 00052736 <https://doi.org/10.1016/j.bbamem.2006.02.021>.
- Schmidtchen, A., Frick, I. M., & Björck, L. (2001). Dermatan sulfate is released by proteinases of common pathogenic bacteria and inactivates antibacterial alpha-defensin. *Journal of Biological Chemistry*, 276(21), 17795–17800. <https://doi.org/10.1074/jbc.M100464200>.
- Schneider, G., & Fechner, U. (2005). Computer-based de novo design of drug-like molecules. *Nature Reviews Drug Discovery*, 4(8), 649–663. <https://doi.org/10.1038/nrd1799>.
- Schneider, T., & Sahl, H. G. (2010). An oldie but a goodie—Cell wall biosynthesis as antibiotic target pathway. *International Journal of Medical Microbiology*, 300(2-3), 161–169. 16180607 <https://doi.org/10.1016/j.ijmm.2009.10.005>.
- Scott, R. W., DeGrado, W. F., & Tew, G. N. (2008). De novo designed synthetic mimics of antimicrobial peptides. *Current Opinion in Biotechnology*, 19(6), 620–627. 09581669 <https://doi.org/10.1016/j.copbio.2008.10.013>.
- Seebah, S., Suresh, A., Zhuo, S., Choong, Y. H., Chua, H., Chuon, D., Beuerman, R., & Verma, C. (2007). Defensins knowledgebase: A manually curated database and information source focused on the defensins family of antimicrobial peptides. *Nucleic Acids Research*, 35(1), D265. 13624962 <https://doi.org/10.1093/nar/gkl866>.
- Seliktar, D. (2012). Designing cell-compatible hydrogels for biomedical applications. *Science*, 336(6085), 1124–1128. American Association for the Advancement of Science, Israel. 10959203. Available from: <http://www.sciencemag.org/content/336/6085/1124.full.pdf>. <https://doi.org/10.1126/science.1214804>.
- Selkoe, D. J. (2003). Folding proteins in fatal ways. *Nature*, 426(6968), 900–904. <https://doi.org/10.1038/nature02264>.

- Senior, A. W., Evans, R., Jumper, J., Kirkpatrick, J., Sifre, L., Green, T., Qin, C., Žídek, A., Nelson, A. W. R., Bridgland, A., Penedones, H., Petersen, S., Simonyan, K., Crossan, S., Kohli, P., Jones, D. T., Silver, D., Kavukcuoglu, K., & Hassabis, D. (2020). Improved protein structure prediction using potentials from deep learning. *Nature*, 577(7792), 706–710. Nature Research, United Kingdom. 14764687. Available from: <http://www.nature.com/nature/index.html>. <https://doi.org/10.1038/s41586-019-1923-7>.
- Seo, M. D., Won, H. S., Kim, J. H., Mishig-Ochir, T., & Lee, B. J. (2012). Antimicrobial peptides for therapeutic applications: A review. *Molecules*, 17(10), 12276–12286. 14203049. South Korea. Available from: <http://www.mdpi.com/1420-3049/17/10/12276/pdf>. <https://doi.org/10.3390/molecules171012276>.
- Shai, Y. (2002). Mode of action of membrane active antimicrobial peptides. *Biopolymers*, 66(4), 236–248. <https://doi.org/10.1002/bip.10260>.
- Sieprawska-Lupa, M., Mydel, P., Krawczyk, K., Wójcik, K., Puklo, M., Lupa, B., Suder, P., Silberring, J., Reed, M., Pohl, J., Shafer, W., McAleese, F., Foster, T., Travis, J., & Potempa, J. (2004). Degradation of human antimicrobial peptide LL-37 by *Staphylococcus aureus*-derived proteinases. *Antimicrobial Agents and Chemotherapy*, 48(12), 4673–4679. <https://doi.org/10.1128/AAC.48.12.4673-4679.2004>.
- Sievers, F., Wilm, A., Dineen, D., Gibson, T. J., Karplus, K., Li, W., Lopez, R., McWilliam, H., Remmert, M., Söding, J., Thompson, J. D., & Higgins, D. G. (2011). Fast, scalable generation of high-quality protein multiple sequence alignments using Clustal Omega. *Molecular Systems Biology*, 7, 17444292. <https://doi.org/10.1038/msb.2011.75>.
- Simons, K. T., Kooperberg, C., Huang, E., & Baker, D. (1997). Assembly of protein tertiary structures from fragments with similar local sequences using simulated annealing and Bayesian scoring functions. *Journal of Molecular Biology*, 268(1), 209–225. Academic Press, United States. 00222836. Available from: <https://www.journals.elsevier.com/journal-of-molecular-biology>. <https://doi.org/10.1006/jmbi.1997.0959>.
- Smith, A. M., Jahn, T. R., Ashcroft, A. E., & Radford, S. E. (2006). Direct observation of oligomeric species formed in the early stages of amyloid fibril formation using electrospray ionisation mass spectrometry. *Journal of Molecular Biology*, 364(1), 9–19. Academic Press, United Kingdom. 00222836. Available from: <https://www.journals.elsevier.com/journal-of-molecular-biology>. <https://doi.org/10.1016/j.jmb.2006.08.081>.
- Smith, L., & Smith, J. (2020). Molecular dynamics simulations of antimicrobial peptide interactions with lipid membranes. *Biochimica et Biophysica Acta (BBA) - Biomembranes*, 1862(5).
- Song, J., Tan, H., Perry, A. J., Akutsu, T., Webb, G. I., Whisstock, J. C., & Pike, R. N. (2012). PROSPER: An integrated feature-based tool for predicting protease substrate cleavage sites. *PLoS One*, 7(11), 19326203. Australia. Available from: <http://www.plosone.org/article/attachment.action?uri=info%3Adoi%2F10.1371%2Fjournal.pone.0050300&representation=PDF>. <https://doi.org/10.1371/journal.pone.0050300>.
- Spellberg, B., & Gilbert, D. N. (2014). The future of antibiotics and resistance: A tribute to a career of leadership by John Bartlett. *Clinical Infectious Diseases*, 59, S71. Oxford University Press, United States. 15376591. Available from: <http://cid.oxfordjournals.org/content/by/year>. <https://doi.org/10.1093/cid/ciu392>.
- Spencer, M., Eickholt, J., & Cheng, J. (2015). A deep learning network approach to. *IEEE/ACM Transactions on Computational Biology and Bioinformatics*, 12(1), 103–112. Institute of Electrical and Electronics Engineers Inc., United States. 15455963. Available from: <http://ieeexplore.ieee.org/xpl/RecentIssue.jsp?punumber=8857>. <https://doi.org/10.1109/TCBB.2014.2343960>.
- Tam, J. P., & Lu, Y. A. (1998). Vaccine design using synthetic peptides. *Journal of Immunological Methods*, 221(1-2), 136–2. [https://doi.org/10.1016/S0022-1759\(98\)136-2](https://doi.org/10.1016/S0022-1759(98)136-2).
- Tartaglia, G. G., Pawar, A. P., Campioni, S., Dobson, C. M., Chiti, F., & Vendruscolo, M. (2008). Prediction of aggregation-prone regions in structured proteins. *Journal of Molecular Biology*, 380(2), 425–436. Academic Press, United Kingdom. 00222836. Available from: <https://www.journals.elsevier.com/journal-of-molecular-biology>. <https://doi.org/10.1016/j.jmb.2008.05.013>.
- Tartaglia, G. G., Pechmann, S., Dobson, C. M., & Vendruscolo, M. (2007). Life on the edge: A link between gene expression levels and aggregation rates of human proteins. *Trends in Biochemical Sciences*, 32(5), 204–206. 09680004 <https://doi.org/10.1016/j.tibs.2007.03.005>.
- Teixeira, V., Feio, M. J., & Bastos, M. (2012). Role of lipids in the interaction of antimicrobial peptides with membranes. *Progress in Lipid Research*, 51(2), 149–177. 18732194 <https://doi.org/10.1016/j.plipres.2011.12.005>.
- Thomas, S., Karnik, S., Barai, R. S., Jayaraman, V. K., & Idicula-Thomas, S. (2010). CAMP: a useful resource for research on antimicrobial peptides. *Nucleic Acids Research*, 38(suppl_1), D774. 0305-1048 <https://doi.org/10.1093/nar/gkp1021>.
- Thorpe, C., & Hooper, K. L. (1996). Biochemistry of disulfide bonds in proteins. *EXS*, 77, 255–270.
- Tieleman, D. P., & Marrink, S. J. (2006). Lipids out of equilibrium: Energetics of desorption and pore mediated flip-flop. *Journal of the American Chemical Society*, 128(38), 12462–12467. 00027863 <https://doi.org/10.1021/ja0624321>.
- Tinkle, S., Mcneil, S. E., Mühlebach, S., Bawa, R., Borchard, G., Barenholz, Y. C., Tamarkin, L., & Desai, N. (2014). Nanomedicines: Addressing the scientific and regulatory gap. *Annals of the New York Academy of Sciences*, 1313(1), 35–56. Blackwell Publishing Inc., United States 17496632. Available from: <http://www.blackwellpublishing.com/0077-8923>. <https://doi.org/10.1111/nyas.12403>.
- Tiwari, G., Tiwari, R., Bannerjee, S. K., Bhati, L., Pandey, S., Pandey, P., & Sriwastawa, B. (2012). Drug delivery systems: An updated review. *International Journal of Pharmaceutical Investigation*, 2(1), 2. 2230-973X <https://doi.org/10.4103/2230-973x.96920>.
- Torchilin, V. P. (2014). Multifunctional, stimuli-sensitive nanoparticulate systems for drug delivery. *Nature Reviews Drug Discovery*, 13(11), 813–827. Nature Publishing Group, United States. 14741784. Available from: <http://www.nature.com/nrd/index.html>. <https://doi.org/10.1038/nrd4333>.
- Torrent, M., Andreu, D., Nogués, V. M., & Boix, E. (2012). Connecting peptide physicochemical and antimicrobial properties by a rational prediction model. *PLoS One*, 7(2).
- Torrent, M., Andreu, D., Nogués, V. M., Boix, E., & Heimesaat, M. (2011). Connecting peptide physicochemical and antimicrobial properties by a rational prediction model. *PLoS One*, 6(2), e16968. 1932-6203 <https://doi.org/10.1371/journal.pone.0016968>.

- Torres-Vanegas, J. D., Cruz, J. C., & Reyes, L. H. (2021). Delivery systems for nucleic acids and proteins: Barriers, cell capture pathways and nanocarriers. *Pharmaceutics*, 13(3). MDPI AG, Colombia. 19994923. Available from: <https://www.mdpi.com/1999-4923/13/3/428/pdf>. <https://doi.org/10.3390/pharmaceutics13030428>.
- Tossi, A., Sandri, L., & Giangaspero, A. (2000). Amphipathic, α -helical antimicrobial peptides. *Biopolymers*, 55(1), 4–30. [https://doi.org/10.1002/1097-0282\(2000\)55:1<4::AID-BIP30>3.0.CO;2-M](https://doi.org/10.1002/1097-0282(2000)55:1<4::AID-BIP30>3.0.CO;2-M).
- Tropsha, A. (2010). Best practices for QSAR model development, validation, and exploitation. *Molecular Informatics*, 29(6-7), 476–488. Wiley-VCH Verlag, United States. 18681751. Available from: [http://onlinelibrary.wiley.com/journal/10.1002/\(ISSN\)1868-1751](http://onlinelibrary.wiley.com/journal/10.1002/(ISSN)1868-1751). <https://doi.org/10.1002/minf.201000061>.
- Vapnik, V. N., & Vapnik, V. (1998). *Statistical learning theory* (p. 1780).
- Veltri, D., Kamath, U., & Shehu, A. (2018). Deep learning improves antimicrobial peptide recognition. *Bioinformatics*, 34(16), 2740–2747. Oxford University Press, United States. 14602059. Available from: <http://bioinformatics.oxfordjournals.org/>. <https://doi.org/10.1093/bioinformatics/bty179>.
- Verma, J., Khedkar, V. M., & Coutinho, E. C. (2010). 3D-QSAR in drug design—A review. *Current Topics in Medicinal Chemistry*, 10(1), 95–115. 15680266. India. Available from: http://www.benthamdirect.org/pages/b_byvolumeissue.php. <https://doi.org/10.2174/156802610790232260>.
- Voss, J., Wu, J., Hubbell, W. L., Jacques, V., Meares, C. F., & Kaback, H. R. (2001). Helix packing in the lactose permease of *Escherichia coli*: Distances between site-directed nitroxides and a lanthanide. *Biochemistry*, 40(10), 3184–3188. 00062960 <https://doi.org/10.1021/bi002333e>.
- Waghu, F. H., Barai, R. S., Gurung, P., & Idicula-Thomas, S. (2016). CAMPR3: A database on sequences, structures and signatures of antimicrobial peptides. *Nucleic Acids Research*, 44(1), D1094. Oxford University Press, India. 13624962. Available from: <http://nar.oxfordjournals.org/>. <https://doi.org/10.1093/nar/gkv1051>.
- Wagner, V., Dullaart, A., Bock, A. K., & Zweck, A. (2006). The emerging nanomedicine landscape. *Nature Biotechnology*, 24(10), 1211–1217. 15461696 <https://doi.org/10.1038/nbt1006-1211>.
- Wang, G. (2010). *Antimicrobial peptides: Discovery, design and novel therapeutic strategies*. CABI. <https://doi.org/10.1079/9781845936570.0000>.
- Wang, G. (2014). Human antimicrobial peptides and proteins. *Pharmaceutics*, 7(5), 545–594. MDPI AG, United States. 14248247. Available from: <http://www.mdpi.com/1424-8247/7/5/545/pdf>. <https://doi.org/10.3390/ph7050545>.
- Wang, G. (2020). Bioinformatic analysis of 1000 amphibian antimicrobial peptides uncovers multiple length-dependent correlations for peptide design and prediction. *Antibiotics*, 9(8), 1–26. MDPI AG, United States. 20796382. Available from: <https://www.mdpi.com/2079-6382/9/8/491/pdf>. <https://doi.org/10.3390/antibiotics9080491>.
- Wang, G., Li, X., & Wang, Z. (2016). APD3: The antimicrobial peptide database as a tool for research and education. *Nucleic Acids Research*, 44(D1), D1087. 0305-1048 <https://doi.org/10.1093/nar/gkv1278>.
- Wetzel, R. (2006). Kinetics and thermodynamics of amyloid fibril assembly. *Accounts of Chemical Research*, 39(9), 671–679. 00014842 <https://doi.org/10.1021/ar050069h>.
- Wu, M., Maier, E., Benz, R., & Hancock, R. E. W. (1999). Mechanism of interaction of different classes of cationic antimicrobial peptides with planar bilayers and with the cytoplasmic membrane of *Escherichia coli*. *Biochemistry*, 38(22), 7235–7242. 00062960 <https://doi.org/10.1021/bi9826299>.
- Xie, Y., An, S. S. A., Yang, G., & Zhang, Y. (2021). Design strategies and application progress of therapeutic exosomes. *Theranostics*, 11(3), 1026–1045. <https://doi.org/10.7150/thno.46688>.
- Yap, C. W. (2011). PaDEL-descriptor: An open source software to calculate molecular descriptors and fingerprints. *Journal of Computational Chemistry*, 32(7), 1466–1474. 1096987X <https://doi.org/10.1002/jcc.21707>.
- Yeaman, M. R., & Yount, N. Y. (2003). Mechanisms of antimicrobial peptide action and resistance. *Pharmacological Reviews*, 55(1), 27–55. <https://doi.org/10.1124/pr.55.1.2>.
- Yoo, J., Park, C., Yi, G., Lee, D., & Koo, H. (2019). Active targeting strategies using biological ligands for nanoparticle drug delivery systems. *Cancers*, 11(5), 640. 2072-6694 <https://doi.org/10.3390/cancers11050640>.
- Young, L. M., Saunders, J. C., Mahood, R. A., Reville, C. H., Foster, R. J., Tu, L. H., Raleigh, D. P., Radford, S. E., & Ashcroft, A. E. (2015). Screening and classifying small-molecule inhibitors of amyloid formation using ion mobility spectrometry-mass spectrometry. *Nature Chemistry*, 7(1), 73–81. Nature Publishing Group, United Kingdom. 17554349. Available from: <http://www.nature.com/nchem/index.html>. <https://doi.org/10.1038/nchem.2129>.
- Zaslloff, M. (2002). Antimicrobial peptides of multicellular organisms. *Nature*, 415(6870), 389–395. <https://doi.org/10.1038/415389a>.
- Zhang, L., Pornpattananankul, D., Hu, C.-M., & Huang, C.-M. (2010). Development of nanoparticles for antimicrobial drug delivery. *Current Medicinal Chemistry*, 17(6), 585–594. 09298673 <https://doi.org/10.2174/092986710790416290>.
- Zhou, H. X., & Pang, X. (2018). Electrostatic interactions in protein structure, folding, binding, and condensation. *Chemical Reviews*, 118(4), 1691–1741. American Chemical Society, United States. 15206890. Available from: <http://pubs.acs.org/journal/chcreay>. <https://doi.org/10.1021/acs.chemrev.7b00305>.

ANTIMICROBIAL PEPTIDES

A Roadmap for Accelerating Discovery and Development

Edited by

Luis H. Reyes, Department of Chemical and Food Engineering, Universidad de los Andes, Bogotá, Colombia

Juan C. Cruz, Department of Biomedical Engineering, Universidad de los Andes, Bogotá, Colombia

Gregory R. Wiedman, Department of Chemistry and Biochemistry Seton Hall University, South Orange, NJ, United States

Contains a comprehensive description of computational and experimental approaches for the discovery, manufacture, and clinical translation of antimicrobial peptides.

Antimicrobial Peptides: A Roadmap for Accelerating Discovery and Development covers the most important efforts of scientists and engineers worldwide to accelerate the process of discovery, production, and eventual market penetration of more potent antimicrobial peptides. These efforts have been fueled by emerging technologies such as artificial intelligence and data science, molecular and CFD simulations, easy-to-use process simulation packages, microfluidics, and 3D printing, among many others. Such technologies can now be implemented and scaled up quickly and at relatively low cost in low-budget production facilities, critical to moving to sustainable and marketable products worldwide.

Discovering novel antimicrobial peptides rationally and cost-effectively has emerged as one of the significant challenges of modern biotechnology. Thus far, this process has been tedious and costly, resulting in molecules with activities far below those needed to address the current challenge of microbial resistance to antibiotics that takes the lives of thousands of people around the world every year. Due to these issues, large biopharmaceutical companies have decided not to invest in discovering novel antimicrobials, which is worrisome in the long run due to the possibility of a new pandemic.

This book also delineates how multidisciplinary teams have assembled to address the challenges of manufacturing, biological testing, and clinical trials to finally reach complete translation. It is an ideal resource for scientists, researchers, engineers, and students in the fields of biotechnology, microbiology, biochemistry, and pharmaceuticals. Finally, anyone interested in the emerging technologies that are enabling the discovery and development of new antimicrobial peptides may find this book interesting and informative.

Key Features

- Covers computational tools (including emerging artificial intelligence algorithms) and microfluidic systems for discovering and high-throughput screening of AMPs
- Discusses the application of bioprocess engineering scale-up approaches for AMPs production and purification with the aid of process simulation tools and rapid prototyping
- Highlights user-centered design and formulation of products with AMPs
- Describes the whole pipeline for AMPs production



ELSEVIER

elsevier.com/books-and-journals

ISBN 978-0-443-15393-8



9 780443 153938