

SNGULAR

A financial fraud predictive AI
model integrated with Spring Boot.


Predictive Model for Financial Industry

Contents:

- What is Machine Learning
- Key Concepts
- Supervised Learning Process
- Introduction to Anomaly Detection
- Anomaly Detection Use Cases
- Example:
 - Dataset Description
 - Data Preparation
 - How Logistic Regression Works
 - Logistic Regression Implementation
 - How Support Vector Machine Works
 - SVM Implementation


Fraud in Bank Industry in 2024

More than half banks reported an increase in business fraud.




Increase of frauds

Check fraud losses in the Americas reached nearly \$21 billion, and 70% of U.S. financial institutions reported check fraud.



Check Fraud

Over half report increasing investment in third-party fraud prevention.




Increase of Investment

- Thompson Reuters, Deloitte, and the Federal Trade Commission (FTC) <https://www.alloy.com/state-of-fraud-benchmark-report-2024#component-marketo-embed>
- SEC. (n.d.). <https://www.sec.gov/files/fy24-oiad-sar-objectives-report.pdf>

Preview Results


Predictive model classifies 60% of frauds over 24 million bank transactions



Detection of
Frauds

What is the best approach?

# step	Δ type	# amount	# isFraud
430	TRANSFER	2828068.73	1
430	CASH_OUT	2828068.73	1
431	PAYMENT	4506.4	0
431	PAYMENT	20711.86	0
431	PAYMENT	14014.89	0
431	PAYMENT	3501.32	0
431	PAYMENT	13936.67	0
431	PAYMENT	1366.84	0
431	PAYMENT	5959.65	0



# step	Δ type	# amount
431	PAYMENT	7536.7

What is the best approach?



What is the best approach?




Machine learning

What Machine Learning(ML) is


It's a sub-topic of Artificial Intelligence field, which is focused on predicting data, through information patterns.

It learns from data to enhance automation of decision making.

ML doesn't implement hard-coded rules. Instead, it predicts data from unseen information.



Classification



Regression

Data

01



The more data, the better.

02


Data format can be numbers, text, images, sounds.

03

It is divided into training (used to teach the model) and test (used to evaluate the model).



Train




Test

Model

- 01** Mathematical representation that learns from data.
- 02** Models capture data patterns and relationships to make predictions and decisions.


03 Typical models are:

- Logistic Regression
- Support Vector Machine
- Neural Networks, etc.




Training & Prediction


- 01** Training is teaching mathematical model to recognize patterns in data.
- 02** Data can be labeled(supervised learning) or unlabeled(unsupervised learning).



Supervised Learning Process




Anomaly Detection



Machine learning model used to detect outliers in extreme unbalanced datasets, usually big enough to consider high-demand computational processing.

Count of each isFraud of transaction



Unbalanced dataset over 24 million


Anomaly Detection Use Cases



01

Financial Fraud:

Identifying unusual spending patterns on credit cards to detect fraudulent transactions.



02

Healthcare Monitoring:

Identifying unusual vital signs in patient data that could indicate a medical emergency.



03

Retail Sales Analysis:

Identifying sudden spikes or drops in sales for specific products that could indicate issues with pricing or demand.

Data Description

“PaySim is a financial simulator that simulates mobile money transactions based on an original dataset.”

The dataset has 24 million financial records.

E. A. Lopez-Rojas, A. Elmir, and S. Axelsson. "PaySim: A financial mobile money simulator for fraud detection". In: The 28th European Modeling and Simulation Symposium-EMSS, Larnaca, Cyprus. 2016

Dataset Fields

- **step:** Represents a unit of time in the real world, with 1 step equating to 1 hour.
- **type:** Transaction types include CASH-IN, CASH-OUT, DEBIT, PAYMENT, and TRANSFER.
- **amount:** The transaction amount in the local currency.
- **nameOrig:** The customer initiating the transaction.
- **oldbalanceOrig:** The initial balance before the transaction.
- **newbalanceOrig:** The new balance after the transaction.
- **nameDest:** Transaction's recipient customer.
- **oldbalanceDest:** The initial recipient's balance before the transaction.
- **newbalanceDest:** The new recipient's balance after the transaction.
- **isFraud:** Identifies transactions conducted by fraudulent agents aiming to deplete customer accounts through transfers and cash-outs.

Dimensional Reduction

Feature Selection:

Shapiro-Wilk test to determine null hypothesis - > not normal distribution. > 0.05 confidence level:

$$W = \frac{\left(\sum_{i=1}^n a_i x_{(i)}\right)^2}{\sum_{i=1}^n (x_i - \bar{x})^2},$$

$$(a_1, \dots, a_n) = \frac{m^T V^{-1}}{\|V^{-1} m\|} = (m^T V^{-1} V^{-1} m)^{1/2}$$

V: Variance Covariance Matrix
m: x

Dimensional Reduction

Feature Selection:

Pearson Correlation: Correlation between two normal distributed variables.

Coefficient correlation: -1 to 1

$$\rho_{X,Y} = \frac{\text{cov}(X, Y)}{\sigma_X \sigma_Y}$$

Theta : Standard Deviation

Cov : Variance Covariance Matrix

Dimensional Reduction

Feature Selection:

Spearman Correlation: Correlation between two non-normal distributed variables.

Coefficient correlation: -1 to 1


$$r_s = \rho [R[X], R[Y]] = \frac{\text{cov} [R[X], R[Y]]}{\sigma_{R[X]} \sigma_{R[Y]}},$$

$\text{cov} [R[X], R[Y]]$: Covariance of ranked variables

$\sigma_{R[X]} \sigma_{R[Y]}$: Standard Deviation

Dimensional Reduction

Pearson
Correlation
Matrix



Spearman
Correlation
Matrix

Dimensional Reduction

Test Hypothesis

Logistic Regression: Relationship between two variables. Only applicable when dependent variable (y) is categorical, and independent variable (x) is continuous.

p-Value: 0 - 0.05 (confidence threshold)

$$p(x) = \frac{1}{1 + e^{-(\beta_0 - \beta_1 x)}}$$

Beta: Weight optimization parameter

Dimensional Reduction

Test Hypothesis

Chi-Square: Relationship between two variables. Only applicable when dependent variable (y) is categorical, and independent variable (x) is also categorical.

p-Value: 0 - 0.05 (confidence threshold)



$$\chi^2 = \sum_{i=1}^n \frac{O_i^2}{E_i} - N.$$

O_i : Number of observations of variable i

N : Total number of observations

E_i : Expected number of type i

Logistic Regression





Sigmoid Function

Logistic Regression

Cost Optimization Function

$$\text{Cost}(h_{\theta}(x), y) = -y \log \frac{1}{1 + e^{-\theta^T x}} - (1 - y) \log \left(1 - \frac{1}{1 + e^{-\theta^T x}}\right)$$




Logistic Regression

Cost Optimization Function

Repeat until convergence {


$$\theta_j \leftarrow \theta_j - \alpha \frac{\partial}{\partial \theta_j} J(\theta)$$

}




Support Vector Machine

Classification Function Hyperplane Clasificator



Support Vector Machine

Optimization Function



$$w^* = \arg \max_w \left[\min_n d_{\mathcal{H}}(\phi(x_n)) \right]$$



Optimization function: Max distance of the hyperplane of the nearest point from the hyperplane

$$d_{\mathcal{H}}(\phi(x_0)) = \frac{|w^T \phi(x_0) + b|}{\|w\|_2}$$

Distance of points from hyperplane


Support Vector Machine

Kernel



Support Vector Machine

Kernel





Support Vector Machine

Kernel

Lagrange Multipliers

$$\begin{pmatrix} x_1 \\ x_2 \\ x_3 \end{pmatrix} \cdot \begin{pmatrix} y_1 \\ y_2 \\ y_3 \end{pmatrix} = x_1 y_1 + x_2 y_2 + x_3 y_3 .$$




Hilbert Space

Implementation

- 01** Inferential Analysis.
- 02** Data Preparation.
- 03** Implementation of Logistic Regression.
- 04** Implementation of Support Vector Machine.
- 05** Spring Boot Integration.




Bonus




Modelo Neuronal - Santiago Ramon y Cajal (1906)

Bonus


Logistic Regression Function



Neuron Model



Bonus



Bibliography

- Lopez-Rojas, E., Elmir, A., & Axelsson, S. (2016). PaySim: A financial mobile money simulator for fraud detection. In *28th European Modeling and Simulation Symposium, EMSS, Larnaca* (pp. 249-255). Dime University of Genoa.
- Mahesh, B. (2020). Machine learning algorithms-a review. *International Journal of Science and Research (IJSR)*. [Internet], 9(1), 381-386.
- Hilal, W., Gadsden, S. A., & Yawney, J. (2022). Financial fraud: a review of anomaly detection techniques and recent advances. *Expert systems With applications*, 193, 116429.
- Virtanen, P., Gommers, R., Oliphant, T. E., Haberland, M., Reddy, T., Cournapeau, D., Burovski, E., et al. (2020). SciPy 1.0: Fundamental Algorithms for Scientific Computing in Python. *Nature Methods*, 17, 261-272. doi:10.1038/s41592-019-0686-2
- Kramer, O., & Kramer, O. (2016). Scikit-learn. *Machine learning for evolution strategies*, 45-53.
- Komer, B., Bergstra, J., & Eliasmith, C. (2019). Hyperopt-sklearn. *Automated Machine Learning: Methods, Systems, Challenges*, 97-111.
- Sarkar, T. (2022). GPU-Based Data Science for High Productivity. In *Productive and Efficient Data Science with Python: With Modularizing, Memory profiles, and Parallel/GPU Processing* (pp. 299-326). Berkeley, CA: Apress
- SEC. (n.d.). <https://www.sec.gov/files/fy24-oiad-sar-objectives-report.pdf>

Questions

Thanks for your attention!!!