UIL Computer Science Written Test

2023 Invitational A

January/February 2023

General Directions (Please read carefully!)

1. DO NOT OPEN THE EXAM UNTIL TOLD TO DO SO.
2. There are 40 questions on this contest exam. You will have 45 minutes to complete this contest.
3. All answers must be legibly written on the answer sheet provided. Indicate your answers in the appropriate blanks provided on the answer sheet. Clean erasures are necessary for accurate grading.
4. You may write on the test packet or any additional scratch paper provided by the contest director, but NOT on the answer sheet, which is reserved for answers only.
5. All questions have ONE and only ONE correct answer. There is a 2-point penalty for all incorrect answers.
6. Tests may not be turned in until 45 minutes have elapsed. If you finish the test before the end of the allotted time, remain at your seat and retain your test until told to do otherwise. You may use this time to check your answers.
7. If you are in the process of actually writing an answer when the signal to stop is given, you may finish writing that answer.
8. All provided code segments are intended to be syntactically correct, unless otherwise stated. You may also assume that any undefined variables are defined as used.
9. A reference to many commonly used Java classes is provided with the test, and you may use this reference sheet during the contest. AFTER THE CONTEST BEGINS, you may detach the reference sheet from the test booklet if you wish.
10. Assume that any necessary import statements for standard Java SE packages and classes (e.g., `java.util`, `System`, etc.) are included in any programs or code segments that refer to methods from these classes and packages.
11. NO CALCULATORS of any kind may be used during this contest.

Scoring

1. Correct answers will receive **6 points**.
2. Incorrect answers will lose **2 points**.
3. Unanswered questions will neither receive nor lose any points.
4. In the event of a tie, the student with the highest percentage of attempted questions correct shall win the tie.

Standard Classes and Interfaces – Supplemental Reference

package java.lang

```
class Object
  boolean equals(Object anotherObject)
  String toString()
  int hashCode()

interface Comparable<T>
  int compareTo(T anotherObject)
```
Returns a value < 0 if this is less than anotherObject.
Returns a value = 0 if this is equal to anotherObject.
Returns a value > 0 if this is greater than anotherObject.

```
class Integer implements Comparable<Integer>
  Integer(int value)
  int intValue()
  boolean equals(Object anotherObject)
  String toString()
  String toString(int i, int radix)
  int compareTo(Integer anotherInteger)
  static int parseInt(String s)

class Double implements Comparable<Double>
  Double(double value)
  double doubleValue()
  boolean equals(Object anotherObject)
  String toString()
  int compareTo(Double anotherDouble)
  static double parseDouble(String s)

class String implements Comparable<String>
  int compareTo(String anotherString)
  boolean equals(Object anotherObject)
  int length()
  String substring(int begin)
```
Returns substring(begin, length()).
```
  String substring(int begin, int end)
```
Returns the substring from index begin through index (end - 1).
```
  int indexOf(String str)
```
Returns the index within this string of the first occurrence of str. Returns -1 if str is not found.
```
  int indexOf(String str, int fromIndex)
```
Returns the index within this string of the first occurrence of str, starting the search at fromIndex. Returns -1 if str is not found.
```
  int indexOf(int ch)
  int indexOf(int ch, int fromIndex)
  char charAt(int index)
  String toLowerCase()
  String toUpperCase()
  String[] split(String regex)
  boolean matches(String regex)
  String replaceAll(String regex, String str)

class Character
  static boolean isDigit(char ch)
  static boolean isLetter(char ch)
  static boolean isLetterOrDigit(char ch)
  static boolean isLowerCase(char ch)
  static boolean isUpperCase(char ch)
  static char toUpperCase(char ch)
  static char toLowerCase(char ch)

class Math
  static int abs(int a)
  static double abs(double a)
  static double pow(double base, double exponent)
  static double sqrt(double a)
  static double ceil(double a)
  static double floor(double a)
  static double min(double a, double b)
  static double max(double a, double b)
  static int min(int a, int b)
  static int max(int a, int b)
  static long round(double a)
  static double random()
```
Returns a double greater than or equal to 0.0 and less than 1.0.

package java.util

```
interface List<E>
class ArrayList<E> implements List<E>
  boolean add(E item)
  int size()
  Iterator<E> iterator()
  ListIterator<E> listIterator()
  E get(int index)
  E set(int index, E item)
  void add(int index, E item)
  E remove(int index)

class LinkedList<E> implements List<E>, Queue<E>
  void addFirst(E item)
  void addLast(E item)
  E getFirst()
  E getLast()
  E removeFirst()
  E removeLast()

class Stack<E>
  boolean isEmpty()
  E peek()
  E pop()
  E push(E item)

interface Queue<E>
class PriorityQueue<E>
  boolean add(E item)
  boolean isEmpty()
  E peek()
  E remove()

interface Set<E>
class HashSet<E> implements Set<E>
class TreeSet<E> implements Set<E>
  boolean add(E item)
  boolean contains(Object item)
  boolean remove(Object item)
  int size()
  Iterator<E> iterator()
  boolean addAll(Collection<? extends E> c)
  boolean removeAll(Collection<?> c)
  boolean retainAll(Collection<?> c)

interface Map<K,V>
class HashMap<K,V> implements Map<K,V>
class TreeMap<K,V> implements Map<K,V>
  Object put(K key, V value)
  V get(Object key)
  boolean containsKey(Object key)
  int size()
  Set<K> keySet()
  Set<Map.Entry<K, V>> entrySet()

interface Iterator<E>
  boolean hasNext()
  E next()
  void remove()

interface ListIterator<E> extends Iterator<E>
  void add(E item)
  void set(E item)

class Scanner
  Scanner(InputStream source)
  Scanner(String str)
  boolean hasNext()
  boolean hasNextInt()
  boolean hasNextDouble()
  String next()
  int nextInt()
  double nextDouble()
  String nextLine()
  Scanner useDelimiter(String regex)
```

Package java.util.function

```
Interface BiConsumer<T,U>
  void accept(T t, U u)

Interface BiFunction<T,U,R>
  R apply(T t, U u)

Interface BiPredicate<T,U>
  boolean test(T t, U u)

Interface Consumer<T>
  void accept(T t)

Interface Function<T,R>
  R apply(T t)

Interface Predicate<T>
  boolean test(T t)

Interface Supplier<T>
  T get()
```

UIL Computer Science Written Test – 2023 Invitational A

Note: Correct responses are based on **Java SE Development Kit 17 (JDK 17)** from Oracle, Inc. All provided code segments are intended to be syntactically correct, unless otherwise stated (e.g., "error" is an answer choice) and any necessary Java SE 17 Standard Packages have been imported. Ignore any typographical errors and assume any undefined variables are defined as used. **For all output statements, assume that the System class has been statically imported using:** `import static java.lang.System.*;`

Question 1

Which of the following decimal numbers has the largest base 10 value?

A) 100101_2 **B)** 56_8 **C)** 26_{16} **D)** 46_7 **E)** $1A_{12}$

Question 2

What is the output of the code segment to the right?

A) 1 **B)** 4 **C)** 6 **D)** 17 **E)** 17.25

```
out.print(15 + 5 / 4 + 1);
```

Question 3

What is the output of the code segment to the right?

A)
```
OneTwo
ThreeFour
Five
```

B)
```
One
TwoThree
FourFive
```

C)
```
One
TwoThreeFour
Five
```

D)
```
OneTwo
ThreeFourFive
```

E)
```
OneTwo
Three
FourFive
```

```
out.print("One");
out.println("Two");
out.print("Three");
out.println("Four");
out.print("Five");
```

Question 4

What is the output of the code segment to the right?

A) niv **B)** i **C)** iv **D)** ive **E)** v

```
String str = "University";
out.print(str.substring(2,3));
```

Question 5

What is the output of the code segment to the right?

A) true

B) false

```
boolean M = true;
boolean N = false;
out.print(M || true && N);
```

Question 6

What is the output of the code segment to the right?

A) 4.0 **B)** 6 **C)** 5.0 **D)** 5 **E)** 6

```
out.print((int)Math.floor(5.85));
```

Question 7

What is the output of the code segment to the right?

A) 78 **B)** 67.5 **C)** 67 **D)** 92 **E)** 70

```
int x = 7;
int y = 8;
double a = 2.0;
out.print(x / a + y * y);
```

Question 8

What is the output of the code segment to the right?

A) MRVVRM

B) VRM

C) RVRM

D) VVRM

E) V

```
int R = 7;
int V = 9;
int W = V - R;

if(R > V)
  out.print("M");
if(2 + R < V)
  out.print("R");
else
  out.print("V");
if(W + R == V)
  out.print("VRM");
```

Question 9

What is the output of the code segment to the right?

A) 1 2 3 4 5 6 7 8 9

B) 1 3 5 7 9

C) 1 4 9 16 25 36 49 64 81

D) 1 4 9

E) 1 9 25 49 81

```
for(int x = 1; x < 10; x=x+2)
  out.print(x*x + " ");
```

Question 10

What is the output of the code segment to the right?

A) 26 **B)** 4 **C)** 221 **D)** 33 **E)** 85

```
int[] stuff = {2,17,3,13,5,11,7};
out.print(stuff[1]*stuff[4]);
```

Question 11

What is output by the code segment to the right?

A) MICH

B) MII

C) MICHI

D) CHGAN

E) MICHIGAN

```
Scanner t = new Scanner("MI CH I GAN");
t.next();
String st = t.next();
t.next();
st += t.next();
out.print(st);
```

Question 12

What is the output of the code segment to the right?

A) 100 **B)** 400 **C)** 210 **D)** 110 **E)** 81

```
int h = 0;
for(int i = 1; i <= 20; i = i + 2)
    h += i;
out.print(h);
```

Question 13

What is the output of the code segment to the right?

A) 40 **B)** 46 **C)** 20 **D)** 10 **E)** 80

```
int a = 10, b = 4, c = 4;
out.print(a << 2 + b >> 1 + ++c);
```

Question 14

What is the output of the code segment shown on the right?

A) 8 **B)** 16 **C)** 32 **D)** 4 **E)** 64

```
out.println(Integer.SIZE);
```

Question 15

What is output by the code segment to the right?

A) [11, 22, 33, 44, 55, 66]

B) [44, 55, 66]

C) [11, 55, 66]

D) [22, 55, 66]

E) [22, 44, 66]

```
ArrayList<Integer> list;
list = new ArrayList<Integer>();
list.add(11);
list.add(22);
list.remove(1);
list.add(33);
list.add(44);
list.remove(1);
list.add(55);
list.add(66);
list.remove(1);
out.println(list);
```

Question 16

What is the output of the code segment shown on the right?

A) F **B)** G **C)** H **D)** I **E)** J

```
String car = "FGHIJKLMNOPQRST";
int L = car.indexOf("KL");
out.println(car.charAt(L-1));
```

Question 17

In the code segment to the right, which of the following numbers could NOT be printed?

A) 22 **B)** 24 **C)** 26 **D)** 28 **E)** 30

```
int T = (int)(Math.random()*7) + 22;
System.out.print(T);
```

Question 18

What is the output of the code segment shown on the right?

A) 15 **B)** 12 **C)** 4 **D)** 20 **E)** 7

```
out.print(12 & 7 + 8 ^ 11);
```

Question 19

What is the output of the code segment shown on the right?

A) 1 **B)** 8 **C)** 7 **D)** 5 **E)** 0

```
int[][] w = {{5,1,2},{8,0,6},{7,1,3}};
out.print(w[2][1]);
```

Question 20

In the code segment to the right, in line #1, if **<???>** was replaced by 2, what would the output be?

A) 8 **B)** 7 **C)** 5 **D)** 3 **E)** 9

Question 21

In the code segment to the right, in line #1, if **<???>** was replaced by 6, what would the output be?

A) 8 **B)** 7 **C)** 5 **D)** 3 **E)** 9

Question 22

In the code segment to the right, in line #1, if **<???>** was replaced by L-1, what would the code do to the list?

A) It would set all values of the list to 8

B) It would set all values of the list to 9

C) It would sort the list

D) It would delete all odd numbers from the list

E) It would reverse the order of the numbers

```
int[]jenny = {8,6,7,5,3,0,9};
int box;
int L = jenny.length;
int N = <???>;    // line #1

for(int x=1; x<=N; x++)
  for(int y=0; y<=L-2; y++)
    if (jenny[y] > jenny[y+1])
      {
        box = jenny[y];
        jenny[y] = jenny[y+1];
        jenny[y+1] = box;
      }
out.print(jenny[2]);
```

Question 23

What is the output of the code segment shown on the right?

A) 2 **B)** B **C)** 10 **D)** D **E)** 34

```
int x = 2 << 5;
x++;
++x;
System.out.print((char) x);
```

Question 24

What is the output of the code segment shown on the right?

A) -33

B) -15

C) 16

D) 17

E) -16

```
int A = 5;
 for(int x = 0; x < 10; x++)
   switch(x)
   {
      case 0: A++;  break;
      case 1: A += 11;
      case 2: A = -A; break;
      case 3: A++; A++;  break;
      case 4: A/=2;
      case 5: A*=2; break;
      case 6: A = -A; break;
      case 7: A++;
      case 8: A++; break;
    }
  out.print(A);
```

Question 25

What is returned by the method call `Go(2)`

A) 1 **B)** 2 **C)** 3 **D)** 4 **E)** 5

Question 26

What is returned by the method call `Go(3)`

A) 9 **B)** 12 **C)** 30 **D)** 15 **E)** 18

Question 27

What is returned by the method call `Go(33)`

A) 165 **B)** 163 **C)** 161 **D)** 159 **E)** 157

```
public static int Go(int x)
{
  if (x==0)
    return 10;
  if (x < 3)
    return x * 2;
  else
    return Go(x-1) + 5;
}
```

Question 28

In the code to the right, what is output on line #1?

A) 12 **B)** 24 **C)** 36 **D)** 48 **E)** null

Question 29

In the code to the right, what is output on line #2?

A) [12, 24, 48, 72]

B) [12, 24, 72]

C) [12, 24]

D) [12, 36]

E) [12, 36, 60]

Question 30

IIn the code to the right, what is output on line #3?

A) [36, 60, 72]

B) [36, 72]

C) [36]

D) [36, 48, 60]

E) [12, 36, 60, 72]

```
Stack<Integer> tall;
tall = new Stack<Integer>();
Stack<Integer> shorter;
shorter = new Stack<Integer>();

tall.push(12);
tall.push(24);
shorter.push(36);
tall.push(48);
out.println(shorter.peek());//line 1

tall.push(60);
shorter.push(tall.pop());
tall.push(72);
shorter.push(tall.peek());
tall.pop();
tall.pop();
out.println(tall);          // line 2
out.println(shorter);       // line 3
```

Question 31

What is the output of the code segment shown on the right?

A) 8 **B)** 9 **C)** 10 **D)** 11 **E)** 12

```
int x = 8;
for(x = 15; x>=12; x++)
  x = x - 3;
out.print(x);
```

Question 32

In the code to the right, how many class variables does the Dog class contain?

A) 2 **B)** 3 **C)** 4 **D)** 1 **E)** 0

Question 33

In the code to the right, what is the resulting output caused by line #1?

A) 12

B) 22

C) 34

D) 46

E) 80

Question 34

In the code to the right, what is the resulting output caused by line #2?

A) 9

B) 11

C) 13

D) 15

E) 17

```
public class Dog
{
  private int A;
  private int B;

  public Dog()
   {
     A = 11;
     B = A * 2;
   }

  public Dog(int C)
   {
     B = C;
     A = B - 4;;
   }

  public void display()
   {
     A++;
     B +=A;
     out.println(A + B);
   }

 }

//client code
Dog R = new Dog();
R.display();          // line 1
Dog S = new Dog(7);
S.display();          // line 2
```

Question 35

What is the output of the code segment shown on the right?

A) 770 **B)** 78 **C)** 66 **D)** 846 **E)** 902

```
int T = 0;
for(char x = 'A'; x <= 'L'; x++)
  T += x;
out.print(T);
```

Question 36

If the letters to the right were inserted into an initially empty binary search tree in the order shown, how many leaves would the resulting tree contain?

A) 9 **B)** 10 **C)** 12 **D)** 1 **E)** 19

```
A B C D E F G H I J J I H G F E D C B A
```

Question 37

What is the output of the code segment shown on the right?

A) 120 **B)** 24 **C)** 72 **D)** 504 **E)** 3024

```
int N = 123456789;
int C = 1;
do
{
   C *= N % 10;
   N /= 10;
}
while (N > 1000000);
out.println(C);
```

Question 38

What is the output of the code segment shown on the right?

A) 5 **B)** 7 **C)** 9 **D)** 0 **E)** 1021

```
int A = 5;
int B = 7;
int C = 9;
int D = 0;
for (int x = 1; x <= 1000; x++)
{
  D = A;
  A = B;
  B = C;
  C = D;
}
out.print(A);
```

Question 39

After the code to the right is completed, what letter will be at the front of the queue?

```
add A
add B
add C
remove
remove
add D
add E
remove
add F
remove
add G
add H
add I
remove
remove
add J
```

Question 40

Of the 8 possible ordered triplets (example 000), how many will make the expression at the right true?

$$\overline{A * B} * (A + C)$$