

Riccardo BONAFEDE

Università di Padova

Matteo Golinelli

File Disclosure and Server-Side Request Forgery




<https://cybersecnatlab.it>

License & Disclaimer

2

License Information

This presentation is licensed under the
Creative Commons BY-NC License



To view a copy of the license, visit:

<http://creativecommons.org/licenses/by-nc/3.0/legalcode>

Disclaimer

- We disclaim any warranties or representations as to the accuracy or completeness of this material.
- Materials are provided “as is” without warranty of any kind, either express or implied, including without limitation, warranties of merchantability, fitness for a particular purpose, and non-infringement.
- Under no circumstances shall we be liable for any loss, damage, liability or expense incurred or suffered which is claimed to have resulted from use of this material.

Goal

3

- Present common file disclosure vulnerabilities and their possible mitigations
- Learn how to perform a Server-Side Request Forgery attack

Prerequisites

4

□ Lecture:

□ *WS_1.1 - HTTP Protocol and Web Security Overview*

Outline

5

- File Disclosure
 - Impact and Overview
 - Paths 101
 - Path traversal attacks
 - Fixes
- Server-Side Request Forgery

Outline

6

- File Disclosure
 - Impact and Overview
 - Paths 101
 - Path traversal attacks
 - Fixes
- Server-Side Request Forgery

File Disclosure

7

- A file disclosure is the **impact of certain vulnerabilities**
- As the name suggests, it consists of the ability to **disclose/leak important files from a server**
- Because it is an impact, there are **multiple classes of vulnerabilities that lead to file disclosure**
 - For example, remote code execution is another type of vulnerability that could results in a file disclosure

File Disclosure

8

- Files inside a server are critical information:
 - In many applications, users-uploaded files are the sensitive information that the application is protecting
 - The disclosure of such files can be a violation of the site policy

File Disclosure

9

- ❑ It is also possible to **steal configuration files** from the webserver **which might contain critical information items**
 - ▢ *Database configuration files* often contain the credentials to access the database
 - ▢ Files like the *tomcat-users.xml* contain the credentials to access the tomcat manager
 - ▢ Files like *flask configuration* or *web.config* in a .net application contain the secret used to sign the session

File Disclosure

10

- Finally, it is possible to **steal the source code** of the web application
 - For some business, the source code of the web application is their **product/asset**
 - An attacker in possession the source code is more effective
 - It is easier for the attacker to find other vulnerabilities, especially if the application was developed according to a *security by obscurity* model

File Disclosure

11

- How can a web app disclose internal files?
 - Basically, **everything that works with files can lead to a file disclosure vulnerability**
 - There are standard sinks, and some of them are a trivial
 - If a user-controlled input manages to go inside these sinks, the web app is at risk

File Disclosure

12

- ❑ Some sinks are trivial...
 - ❑ Every function in every programming language that manages files
 - ❑ Every flavor of **open/fopen** in every language
 - ❑ Flask **send_file**
 - ❑ ...
- ❑ As said before, it is also possible to leak files if the web app suffers from **code execution**

File Disclosure

13

□ Some sin

□ Every fu
manage

□ Every f

□ Flask s

□ ...

□ As said b
web app

```

fopen
tmpfile
bzopen
gzopen
SplFileObject->__construct
// write to filesystem (partially in combination with rea
chgrp
chmod
chown
copy
file_put_contents
lchgrp
lchown
link
mkdir
move_uploaded_file
rename
rmdir

```

language that

ge

leak files if the
n

File Disclosure

14

- Some single

- Every function manages

- Every file

- Flask server

- ...

- As said before, web applications

```
readfile
readlink
realpath
stat
gzfile
readgzfile
getimagesize
imagecreatefromgif
imagecreatefromjpeg
imagecreatefrompng
imagecreatefromwbmp
imagecreatefromxbm
imagecreatefromxpm
ftp_put
ftp_nb_put
exif_read_data
read_exif_data
exif_thumbnail
exif_imagetype
```

language that


age

leak files if the
on

File Disclosure

15

- Other sinks are less trivial
 - **cURL** is used as a http client, but it can also be used to open files



```
$fd = curl_init('file:///etc/passwd');  
echo curl_exec($a);
```

File Disclosure

16

- It's sometimes possible to leak important files just because they are publicly accessible
 - ▢ *.git* directory exposed
 - If you make your git directory open to the internet, everyone will be able to dump all files inside it
 - ▢ Web-server misrouting
 - It's sometimes possible to trick a web server to return a *.php* file as an image...

Outline

17

- File Disclosure
 - Impact and Overview
 - Paths 101
 - Path traversal attacks
 - Fixes
- Server-Side Request Forgery

Paths 101

18

- Let us focus on what happens if a user-controlled input finds a way to an open-like function
- We first need to understand few things about how paths work

Paths 101

19


- An **absolute path** is a path that describes the location of a file regardless of the working directory
`/etc/passwd`
- A **relative path** is a path that describes the location of a file starting from the working directory
`foo/bar`

Paths 101

20

- Paths are composed by a **dirname** and a **basename**
 - The **dirname** is the portion of the path up to the last /
 - The **basename** is the portion of the path after the last /

`/usr/bin/firefox`



Dirname Basename

Paths 101

21

- Every directory has two special subdirectories:
 - The **current directory**, whose name is `.`

`/foobar./` ➡ `/foobar/`

- And the **parent directory**, whose name is `..`

`/foobar../baz` ➡ `/baz`

- The parent directory is useful for file disclosure because it permits to access deeper directories inside the file system

Paths 101

22

- A path in its **shortest form** is called **normalized**
- For example:
 - `/foo/bar` is normalized, there is no way to make it shorter
 - `//foo/bar` is not normalized, `/foo/bar` is shorter
 - `/foo./bar` is not normalized, `/foo/bar` is shorter
- What about `/foo/test/../bar`?

Paths 101

23

- What about `/foo/test/../bar`?
- Its shortest form would be `/foo/bar`, but what happens if `/foo/test/` does not exist?
 - If the path is normalized before opened, then everything is fine: we can access `/foo/bar` without any problem
 - If the path is not normalized, then the open would fail because `/foo/test/` does not exist, and so ..

Outline

24

- File Disclosure
 - Impact and Overview
 - Paths 101
 - Path traversal attacks
 - Fixes
- Server-Side Request Forgery

Path Traversal

25

- ❑ **Path traversal** is a vulnerability that leads to a file disclosure
- ❑ It happens when a user-controlled input finds its way into an *open()* or an equivalent function
- ❑ If there are no security checks or security sanitizations, an attacker could inject paths that are not meant to be opened

Path Traversal

26

- ❑ Path traversal is a technique to access files and directories outside the web root directory
- ❑ It happens when the application does not properly sanitize its input
- ❑ If the application does not properly sanitize its input, an attacker could inject paths that are not meant to be opened

```
<nowiki>
<?php
$template = 'blue.php';
if ( isset( $_COOKIE['TEMPLATE'] ) )
    $template = $_COOKIE['TEMPLATE'];
include ( "/home/users/web/templates/" . $template );
?>
</nowiki>
```

Path Traversal

27

- Path traversal is a technique used to access files and directories outside the web root directory.
- It happens when an application does not properly sanitize user input before using it to construct file paths.
- If the application does not perform proper sanitizations, an attacker could inject paths that are not meant to be opened.

```
<nowiki>
<?php
$template = 'blue.php';
if ( isset( $_COOKIE['TEMPLATE'] ) )
    $template = $_COOKIE['TEMPLATE'];
include ( "/home/users/web/templates/" . $template );
?>
</nowiki>
```

Entry point

Path Traversal

28

- ❑ Path traversal is a technique to access files and directories outside the web root directory.
- ❑ It happens when the application does not properly sanitize its input.
- ❑ If the application does not perform proper sanitizations, an attacker could inject paths that are not meant to be opened

```

<nowiki>
<?php
$template = 'blue.php';
if ( isset( $_COOKIE['TEMPLATE'] ) )
    $template = $_COOKIE['TEMPLATE'];
include ( "/home/users/web/templates/" . $template );
?>
</nowiki>

```

Sink

Path Traversal

29

□ Few cases might happen:

□ **Plain** injection

```
open($input)
```

□ **Prepended** injection

```
open($input + '/foobar')
```

□ **Appended** injection

```
open('/foobar' + $input)
```

□ **Appended and prepended**

```
open('/foo'+$input+'/bar')
```

Full Plain Path Traversal

30

- ❑ *open(\$input)*
- ❑ Without security checks, it is possible to leak every file on the filesystem
- ❑ Other problems:
 - ❑ Protocols like HTTP / gopher / ssh could be used, making it a Server-Side Request Forgery
 - ❑ For some functions, it is possible to execute arbitrary code. (For example if the injection is inside Perl's `open`¹)

¹: <https://perldoc.perl.org/functions/open>

Full Plain Path Traversal

31

- ❑ The exploit for this kind of injection is trivial
 - ❑ Just put the path of the file to disclose
- ❑ A useful test file on Unix systems is **/etc/passwd**
- ❑ Why?
 - ❑ It always exists and is accessible by every user of the system
 - ❑ Is a good target to properly check if there is an actual injection inside an open-like function

Appended Path Traversal

32

- ❑ `open('/somedir/' . $input)`
- ❑ It is the most common one
- ❑ It is a plain injection without the possibility to use other protocols
- ❑ If there is no protection, it is possible to leak every file in the filesystem

Appended Path Traversal

33

- ❑ To exploit this, append some ../ in order to get to the root directory
- ❑ In this way, it is possible to access every file of the filesystem
- ❑ For example, try to inject:

`../../../../../../etc/passwd`

Appended Path Traversal

34

```
https://[redacted]/html/js/editor/editor.jsp?editorImpl=../../../../WEB-INF/web.xml?
```

```
HTTP/1.1 200 OK
```

```
Content-Type: text/html
```

```
Server: Microsoft-IIS/8.5
```

```
X-Powered-By: ASP.NET
```

```
Date: Thu, 30 Mar 2017 20:24:43 GMT
```

```
Connection: close
```

```
Content-Length: 54193
```

```
<?xml version="1.0"?>
```

```
<web-app xmlns="http://java.sun.com/xml/ns/j2ee" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" version="2.4"
```

```
  <context-param>
```

```
    <param-name>contextClass</param-name>
```

```
    <param-value>com.liferay.portal.spring.context.PortalApplicationContext</param-value>
```

```
  </context-param>
```

Appended Path Traversal

35

```
https://[redacted]/html/js/editor/editor.jsp?editorImpl=../../WEB-INF/web.xml?
```

```
HTTP/1.1 200 OK
Content-Type: text/html
Server: Microsoft-IIS/8.5
X-Powered-By: ASP.NET
Date: Thu, 30 Mar 2017 20:24:43 GMT
Connection: close
Content-Length: 54193
```

```
<?xml version="1.0"?>

<web-app xmlns="http://java.sun.com/xml/ns/j2ee" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" version="2.4"
  <context-param>
    <param-name>contextClass</param-name>
    <param-value>com.liferay.portal.spring.context.PortalApplicationContext</param-value>
  </context-param>
```

Prepended Path Traversal

36

- ▣ `open($input . 'someotherdata')`
- ▣ A little bit trickier than the previous one, normally in two forms:
 - ▣ With an appended extension
 - ▣ `file_get_content($input . '.txt')`
 - ▣ Or with an appended filename/directory
 - ▣ `file_get_contents($input . '/somefile.txt')`

Prepended Path Traversal

37

- Allows the disclosure of files whose path finish with a hardcoded suffix
- There are some tricks
 - e.g., including a null byte

Prepended Path Traversal

38

- Some languages support the file:// scheme.
- Particularly interesting because it is parsed as a URL
 - `file://localhost/path/to/file?someotherdata == /path/to/file`

```
ubuntu@ip-172-31-24-48:~$ curl file://localhost/etc/passwd\?someotherdata
root:x:0:0:root:/root:/bin/bash
daemon:x:1:1:daemon:/usr/sbin:/usr/sbin/nologin
bin:x:2:2:bin:/bin:/usr/sbin/nologin
sys:x:3:3:sys:/dev:/usr/sbin/nologin
sync:x:4:65534:sync:/bin:/bin/sync
games:x:5:60:games:/usr/games:/usr/sbin/nologin
man:x:6:12:man:/var/cache/man:/usr/sbin/nologin
lp:x:7:7:lp:/var/spool/lpd:/usr/sbin/nologin
mail:x:8:8:mail:/var/mail:/usr/sbin/nologin
news:x:9:9:news:/var/spool/news:/usr/sbin/nologin
uucp:x:10:10:uucp:/var/spool/uucp:/usr/sbin/nologin
proxy:x:13:13:proxy:/bin:/usr/sbin/nologin
www-data:x:33:33:www-data:/var/www:/usr/sbin/nologin
backup:x:34:34:backup:/var/backups:/usr/sbin/nologin
```

Prepended Path Traversal

39

- Some scripting languages internally use the C function *open*
- Because of how C handles strings, open will **ignore everything after a NULL character (`\x00`)**

```
http://foo.bar/?file=../../etc/passwd%00
```

- This trick worked very well for older versions of PHP, but now is patched

Path Traversal

40

- A **denylist** is a common mitigation against these types of vulnerabilities
- A denylist is used to look for "dangerous" words inside a user-supplied input
- If a dangerous word is found, the system rejects the input or sanitizes it, thus removing the dangerous word

Path Traversal

41

- ❑ Denylists **are insecure**, because they are error prone
 - ❑ You will never be able to insert all the edge cases!
- ❑ For example, does a denylist that contains the word '*proc*' prevent access to the '*/proc/*' directory?
 - ❑ No, */dev/fd/* is a link to */proc/self/fd*, so you can access every file of */proc/* with the directory */dev/fd/../../*

Path Traversal

42

- ❑ What if we denylist single dangerous characters like “.” or “/” ?
 - ❑ The problem here is congruence. Some languages, javascript in particular, don't handle malformed unicode characters.
 - ❑ e.g., the unicode character `\u012e (Ĳ)`, when converted to ascii, is incorrectly transformed to the byte `\x2e (.)`
 - ❑ You can see that if the denylist is using *unicode* but the open function is using the *ASCII* encoding then there is a problem

Outline

43

- File Disclosure
 - Impact and Overview
 - Paths 101
 - Path traversal attacks
 - Fixes
- Server-Side Request Forgery

Fixes

44

- ❑ **Normalize paths**
- ❑ In this way there are no "nasty points" inside paths, and it is possible to **enforce a dirname**
 - Pay attention that the function used for normalization parses paths the same way of the open function
 - ❑ In this way, you will be able to avoid problems caused by incongruences

Fixes

45

- ❑ Another good mitigation is a **chroot**
- ❑ Chroots are "jails" enforced by the OS or by some programming languages
- ❑ If a path is set as a chroot, then every access outside this path would be denied by the OS/interpreter
- ❑ If an attacker manages to bypass all security checks, they will be stopped by the chroot

Fixes

46

- In summary
 - **Denylists are insecure**, as they can be bypassed in different ways
 - **Allowlists work better**, but defeat the purpose of passing user input inside an open function
 - **Avoid incongruence**, check paths in the same way you open them

Outline


47

- File Disclosure
 - Impact and Overview
 - Paths 101
 - Path traversal attacks
 - Fixes
- Server-Side Request Forgery

Server-Side Request Forgery

48

□ **A Server-Side Request Forgery** is a vulnerability that allows an attacker to send a network request from the remote application



Server-Side Request Forgery

49

- The impact varies a lot, depending on the control the attacker has on the forged request:
 - Control over the whole **TCP packet**
 - Control over some parts of an **HTTP request**
 - Control only over the **host/port** to which the request is made
 - ...

Server-Side Request Forgery

50

- ❑ SSRFs are dangerous because they allow bypassing the firewall
- ❑ If the internal network is not properly designed, it is possible to **access to sensible hosts**, like internal web applications and control panels

Server-Side Request Forgery

51

- If the vulnerable web application is hosted on a **cloud instance**, things become more interesting
- Some instances have access to specials *URLs* that often contain **critical data**

Server-Side Request Forgery

52

- For example, AWS instances can access the **metadata API**, at the URL <http://169.254.169.254/>
- This host contains sensitive information such as the **IAM security credentials** and general information about the vulnerable instance¹

1: <https://blog.appsecco.com/an-ssrf-privileged-aws-keys-and-the-capital-one-breach-4c3c2cded3af>

Server-Side Request Forgery

53

- If there is no output, the SSRF is called **blind SSRF**
- It is less dangerous than a normal SSRFs
- With a blind SSRF it is possible to
 - Map the internal network
 - **Trigger actions** on hosts behind the firewall¹

1: A nice collection of payloads to use:
<https://blog.assetnote.io/2021/01/13/blind-ssrf-chains/>

Server-Side Request Forgery

54

- It is possible to map the internal network by trying *URLs/ports*, and by looking at the response time
 - This can be done if the response time of the vulnerable endpoint **depends** on the response time of the SSRF request

Server-Side Request Forgery

55

- ❑ To find an SSRF, you should:
 - ❑ Find suspicious endpoints: If you see a URL inside a parameter try putting a URL controlled by you (e.g., an ngrok)
 - ❑ If you have a pingback at your host, then probably you have an SSRF.
 - ❑ You can try to insert internal hostnames, like "localhost" or common internal IPs (192.168.1.1, 10.0.0.1, and so on..)
 - ❑ Examine the response time!

Server-Side Request Forgery

56



alyssa_herrera submitted a report to **U.S. Dept Of Defense**.

Mar 15th (2 years ago)

Summary:

An end point on [REDACTED] allows an internal access to the network thus revealing sensitive data and allowing internal tunneling


Description:

OAuth Plugin allows you to provide a url that gives a snap shot of the web page. We can pass internal URLs and conduct SSRF.

Impact


Critical

Step-by-step Reproduction Instructions

[https://\[REDACTED\]/plugins/servlet/oauth/users/icon-uri?consumerUri=http://169.254.169.254/latest/meta-data/hostname](https://[REDACTED]/plugins/servlet/oauth/users/icon-uri?consumerUri=http://169.254.169.254/latest/meta-data/hostname) 

We can see the follow data

ip-172-31-12-254.[REDACTED].compute.internal

[https://\[REDACTED\]/plugins/servlet/oauth/users/icon-uri?consumerUri=http://169.254.169.254/latest/meta-data/public-ipv4](https://[REDACTED]/plugins/servlet/oauth/users/icon-uri?consumerUri=http://169.254.169.254/latest/meta-data/public-ipv4) 

[REDACTED]

Server-Side Request Forgery

57



alyssa_herrera submitted a report to U.S. Dept Of Defense.

Mar 15th (2 years ago)

Summary:

An end point on [REDACTED] allows an internal access to the network thus revealing sensitive data and allowing internal tunneling

Description:

OAuth Plugin allows you to provide a url that gives a snap shot of the web page. We can pass internal URLs and conduct SSRF.

Impact

Critical

Step-by-step Reproduction Instructions

`https://[REDACTED]/plugins/servlet/oauth/users/icon-uri?consumerUri=http://169.254.169.254/latest/meta-data/hostname`

We can see the follow data

`ip-172-31-12-254.[REDACTED].compute.internal`

`https://[REDACTED]/plugins/servlet/oauth/users/icon-uri?consumerUri=http://169.254.169.254/latest/meta-data/public-ipv4`

Server-Side Request Forgery

58

- Every piece of code that can issue a connection can lead to this vulnerability
- Common functions/libraries are:
 - PHP open-like functions
 - CURL
 - Python's urllib
 - ...

Server-Side Request Forgery

59

```
def send_email(request):  
    try:  
        recipients = request.GET['to'].split(',')  
        url = request.GET['url']  
        proto, server, path, query, frag = urlsplit(url)  
        if query: path += '?' + query  
        conn = HTTPConnection(server)  
        conn.request('GET', path)  
        resp = conn.getresponse()
```

Snippet of code from
Graphite

Server-Side Request Forgery

60

- Generally speaking, SSRFs are really difficult to avoid
- The most effective way is to check the user-supplied host against an **allowlist**
- Another good mitigation is to make requests from a host that is **isolated from sensitive internal hosts**

Riccardo BONAFEDE
Università di Padova

Matteo Golinelli - 02/03/2023

File Disclosure and Server-Side Request Forgery

