Summary Post

My first post introduces Multi-Agent Systems (MAS) Architecture as a flexible, distributed alternative to traditional centralized manufacturing control systems, highlighting its benefits and challenges.

In Ahmed's response, he supported the use of large language models (LLMs) in MAS while acknowledging risks such as hallucinations. This prompted me to examine the safety implications of integrating LLMs into manufacturing processes. In industrial settings, hallucinations can lead LLMs to generate plausible but incorrect outputs, such as references to non-existent equipment or physically impossible actions (Ji *et al.*, 2023). These errors may have serious operational and safety consequences (Rebedea *et al.*, 2023). To mitigate such risks, the Autonomous Action Execution (AAE) framework incorporates LLM reasoning within a layered MAS architecture, where the LLM serves only in a monitoring role, and all safety-critical decisions are verified and executed by deterministic agents (Schall, 2026). This approach ensures that LLM-generated recommendations are validated against engineering constraints before implementation.

In Panagiotis' response, he argued that a hybrid approach combining local agent autonomy with centralized human oversight is the most effective strategy for manufacturing. This prompted me to explore how humans can remain in the loop of agentic workflows without sacrificing the efficiency gains that make autonomous agents valuable. Unlike traditional oversight, which relies on fixed approval checkpoints, the Dynamic Intervention Framework treats human attention as a dynamically allocated resource. As described by Kumar and Singh (2026), a Supervisor Agent continuously evaluates Worker Agent decisions using confidence scores. High-confidence decisions execute autonomously, medium-confidence decisions proceed with post-hoc review, and low-confidence decisions are halted and escalated to a human operator. This adaptive approach enables effective oversight while maintaining the efficiency required for high-throughput manufacturing environments.

In summary, this discussion broadened my understanding of MAS in manufacturing by highlighting the opportunities and challenges of technologies such as LLMs. It also revealed the importance of balancing autonomy with safety through mechanisms like LLM verification and dynamic human oversight. As a result, I gained a more realistic perspective on the practical challenges of deploying agentic AI in manufacturing environments.

REFERENCES

Ji, Z. *et al*. (2023) 'Survey of Hallucination in Natural Language Generation', *ACM Computing Surveys*, 55(12), p. 248:1-248:38. Available at: https://doi.org/10.1145/3571730.

Kumar, M. and Singh, D. (2026) 'Balancing autonomy and oversight in reliable agentic artificial intelligence through adaptive human interaction architectures', *Discover Artificial Intelligence*, 6(1), p. 709. Available at: https://doi.org/10.1007/s44163-026-01373-2.

Rebedea, T. *et al*. (2023) 'NeMo Guardrails: A Toolkit for Controllable and Safe LLM Applications with Programmable Rails', in Y. Feng and E. Lefever (eds) *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing: System Demonstrations*. Singapore: Association for Computational Linguistics, pp. 431–445. Available at: https://doi.org/10.18653/v1/2023.emnlp-demo.40.

Schall, D. (2026) 'Safe integration of Large Language Models into industrial process control: a multi-agent architecture with P&ID-grounded validation', *Autonomous Intelligent Systems*, 6(1), p. 14. Available at: https://doi.org/10.1007/s43684-026-00136-1.