MX525 Digital Projector











Features

- High brightness 3,200 ANSI Lumens
- Up to 10,000 hours Long lamp life
- SmartEco Power Saving technology
- Blu-ray Full HD 3D support
- HDMI digital input

Box Contents

- Remote Control w/ Battery *I
- Power Cord (by region) *I
- UM Download Instruction and Regulatory Statements *I
- Quick Start Guide *I
- VGA(D-sub 15pin) Cable *I

Dimension






Optional Accessories

•	Spare Lamp Kit 5J.J9R05.001
•	Ceilling Mount
•	3D Glasses
•	Carry bag



Input and Output Terminals



- 1 AC power jack
- Audio input jack Audio output jack
- 3 S-Video input jack Video input jack
- 4 HDMI-input port
- RGB (PC)/Component Video (YPbPr/YCbCr) signal input jacks
- 6 RGB signal output jack
- **7** USB port
- 8 RS232 control port
- Kensington anti-theft lock slot
- Ceiling mount holes

Product Specifications

Projection System	DLP	
Native Resolution	XGA (1024 x 768)	
Brightness	3200AL	
Contrast Ratio	13000:1	
Display Color	1.07 Billion Colors	
ens	F=2.56-2.8, f=21-23.1 mm	
Aspect Ratio	Native 4:3 (5 aspect ratio selectable)	
hrow Ratio	I.86-2.04 (53"@2m)	
mage Size (Diagonal)	36"~300"	
Coom Ratio	LI:I	
атр Туре	190W	
amp Mode (Normal/Eco/SmartEco/LampSave)*	4500/6000/6500/10000 hours	
Keystone Adjustment	ID, Vertical +/- 40 degrees	
Projection Offset	120% ±5%	
Resolution Support	VGA(640 x 480) to UXGA(1600 x 1200)	
Horizontal Frequency	15~102KHz	
Vertical Scan Rate	23~120Hz	
Compatibility	HDTV Compatibility Video Compatibility 3D Compatibility (Please refer to User's Manual for detailed support timing.)	480i, 480p, 576i, 576p, 720p, 1080i, 1080p NTSC, PAL, SECAM Frame Sequential: Up to 720p Frame Packing: Up to 1080p Side by Side: Up to 1080i/p Top Bottom: Up to 1080i
nterface	Computer in (D-sub 15pin) Monitor out (D-sub 15pin) Composite Video in (RCA) S-Video in (Mini DIN 4pin) HDMI Audio in (Mini Jack) Audio out (Mini Jack) Speaker USB (Type mini B) RS232 (DB-9pin) IR Receiver	x 2 (Shared with component) x x x x x x x x x x
Dimensions	$\label{eq:definition} Dimensions(W \times H \times D)$ $\label{eq:definition} Weight$	$283 \times 95 \times 222$ mm (with feet) $283 \times 88.7 \times 222$ mm (without feet) 1.9kg
ower	Power Supply Power Consumption	AC 100 to 240 V, 50 to 60 Hz Normal 270W, Eco 220W, Standby<0.5W
Audible Noise	33/28 dBA (Normal/Economic mode)	
On-Screen Display Languages	Arabic/Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hindi/ Hungarian/ Italian/ Indonesian/ Japanese/ Korean/ Norwegian/ Polish/ Portuguese/ Romanian/ Russian/ Simplified Chinese/Spanish/ Swedish/ Turkish/ Thai/ Traditional	

^{*} Lamp life results will vary depending on environmental conditions and usage. Actual product's features and specifications are subject to change without notice.

Logistics information

Product Code	9H.JCG77.13E	
EAN Code	471 8755 05332 0	
Dimensions Single Carton (cm)	35.1 × 14.50 × 29.50	
Carton Weight (kg)	2,9	
Pallet Oty	120	

Chinese (28 Languages)





Meerenakkerweg 1-17 5652 AR Eindhoven The Netherlands Tel: +31 88 8889200 Fax: +31 88 8889299

