

1 console.log(0.1 * 3 === 0.3);

2 console.log(9007199254740992);

false

9007199254740992



main.py × +



```
1 p = "maçã"
2 print(len(p), len(p.encode()))
3
```

Console

I/O

AI Agent

126 ms ✓

4 6



main.go

```
1 package main
2 import "fmt"
3
4 func main() {
5     var b byte = 255
6     b++
7     fmt.Println(b)
8
9 }
```

Console

I/O

AI Agent

264 ms



0

OneCompiler

Upgrade

AI

Java

Run

Save

Login

Main.java

1import java.util.*;

2

3public class Main {

4 public static void main(String[] args) {

5 int[] v = new int[3];

6 System.out.println(v[0]);

7 System.out.println(v[2]);

8 }

9 }

Console

I/O

AI Agent

831 ms

Ready

Terminal

Light

Wiki

Internet

HelloWorld.rs x

```
1 fn main() {  
2     let s = String::from("oi");  
3     let t = s;  
4     println!("{}", s, t);  
5 }  
6 }
```

Console

I/O

AI Agent

Exit 1

```
error[E0382]: borrow of moved value: `s`  
  --> HelloWorld.rs:4:23  
2 |     let s = String::from("oi");  
  |         - move occurs because `s` has type `String`, which  
  |         does not implement the `Copy` trait  
3 |     let t = s;  
  |         - value moved here  
4 |     println!("{}", s, t);  
  |                   ^ value borrowed here after move  
  
help: consider cloning the value if the performance cost is  
acceptable  
3 |     let t = s.clone();  
  |               +++++++  
  
error: aborting due to 1 previous error  
  
For more information about this error, try `rustc --explain  
E0382`.  
  
Debug this error
```

C Main.c x +

Console

I/O

AI Agent

189 ms ✓

```
1 #include <stdio.h>
2 int main()
3 {
4     union { int i; float f; } u;
5     u.f = 1.0f;
6     printf("%d\n", u.i);
7
8 }
```

1065353216