```
19 if (typeof Logger == 'undefined') {
18   globalThis.Logger = { log: (...args) => console.log(...args) };
17 }
16
15 const AGE = 23;
14 const NAME = 'Jane';
13
12 function isAdult() {
11   const response = "We don't know yet";
10   if (AGE < 18) {
 9     const response = NAME + ' is not an adult';
 8     Logger.log(response)
 7   } else {
 6     const response = NAME + ' is an adult';
 5     Logger.log(response);
 4   }
 3   Logger.log(response);
 2 }
 1
20 isAdult()
~
~
~
~
~
~
~
~
~
~
```

```
:!node code.js
Jane is an adult
We don't know yet

Press ENTER or type command to continue
```

uni_ 1:nvim 00:15

```
11 if (typeof Logger == 'undefined') {
10   globalThis.Logger = { log: (...args) => console.log(...args) };
 9 }
 8
 7
 6 function printUserName() {
 5   const user = 'Jane';
 4   Logger.log("The user's name is " + user)
 3 }
 2
 1 function greetUser() {
12   Logger.log('Hello ' + user + ', how are you today?');
```

```
:!node code.js
The user's name is Jane
/home/styx/uni/ms_google/code.js:12
  Logger.log('Hello ' + user + ', how are you today?');
                        ^

ReferenceError: user is not defined
    at greetUser (/home/styx/uni/ms_google/code.js:12:25)
    at Object.<anonymous> (/home/styx/uni/ms_google/code.js:16:1)
    at Module._compile (node:internal/modules/cjs/loader:1760:14)
    at Object..js (node:internal/modules/cjs/loader:1892:10)
    at Module.load (node:internal/modules/cjs/loader:1480:32)
    at Module._load (node:internal/modules/cjs/loader:1299:12)
    at TracingChannel.traceSync (node:diagnostics_channel:328:14)
    at wrapModuleLoad (node:internal/modules/cjs/loader:245:24)
    at Module.executeUserEntryPoint [as runMain] (node:internal/modules/run_main:154:5)
    at node:internal/main/run_main_module:33:47

Node.js v25.1.0

shell returned 1

Press ENTER or type command to continue
```

```
15 if (typeof Logger == 'undefined') {
14   globalThis.Logger = { log: (...args) => console.log(...args) };
13 }
12
11 const USER = 'Jane';
10
 9 function printUserName() {
 8   Logger.log("The user's name is " + USER)
 7 }
 6
 5 function greetUser() {
 4   Logger.log('Hello ' + USER + ', how are you today?');
 3 }
 2
 1 printUserName()
16 greetUser()
~
~
~
~
~
~
~
~
~
~
~
~
~
~
~
:!node code.js
The user's name is Jane
Hello Jane, how are you today?

Press ENTER or type command to continue
uni_  1:nvim                                                    00:06
```

```
if (typeof Logger == 'undefined') {
  globalThis.Logger = { log: (...args) => console.log(...args) };
}

function arrayOfObjects() {
  const ar = [
    {
      firstName: 'John',
      lastName: 'Doe',
    },
    {
      firstName: 'Jane',
      lastName: 'Doe',
    },
    {
      firstName: 'Peter',
      lastName: 'Parker',
    },
    {
      firstName: 'Bruce',
      lastName: 'Wayne',
    },
  ];

  Logger.log(ar[3].firstName);
}

arrayOfObjects();
~
~
~
```

```
:!node code.js
Bruce

Press ENTER or type command to continue
```

uni_ 1:nvim 00:02

```
20 if (typeof Logger == 'undefined') {
19   globalThis.Logger = { log: (...args) => console.log(...args) };
18 }
17
16 function myFunction() {
15   const employee = {
14     firstName: 'John',
13     lastname: 'Doe',
12     sayHello() {
11       Logger.log('Hi there, my name is ' + this.firstName);
10     },
 9     hobbies: ['skiing', 'chess', 'cooking'],
 8     address: {
 7       street: '123 main street',
 6       city: 'Anytown',
 5       state: 'CA',
 4       zipCode: '91234',
 3       countr: 'USA',
 2     }
 1   }
21   Logger.log(employee.firstName + ' lives in ' + employee.address.countr)
 1 }
 2
 3 myFunction();
~
~
~
~
~
~
~
```

```
:!node code.js
John lives in USA

Press ENTER or type command to continue
```

uni_ 1:nvim 23:58

```
if (typeof Logger == 'undefined') {
  globalThis.Logger = { log: (...args) => console.log(...args) };
}

function myFunction() {
  const spreadsheetData = [
    ['First name', 'Last Name', 'Age'],
    ['John', 'Doe', 24],
    ['Jane', 'Doe', 19]
  ];

  for (let i = 0; i < spreadsheetData.length; i++) {
    for (let j = 0; j < spreadsheetData[i].length; j++) {
      Logger.log(spreadsheetData[i][j]);
    }
  }
}

myFunction();
~
~
~
~
```

```
:!node code.js
First name
Last Name
Age
John
Doe
24
Jane
Doe
19

Press ENTER or type command to continue
```

uni_ 1:nvim 23:48

```
if (typeof Logger == 'undefined') {
  globalThis.Logger = { log: (...args) => console.log(...args) };
}

function myFunction() {
  const spreadsheetData = [
    ['First name', 'Last Name', 'Age'],
    ['John', 'Doe', 24],
    ['Jane', 'Doe', 19]
  ];

  Logger.log(spreadsheetData[0][0]);
  Logger.log(spreadsheetData[1][2]);
}

myFunction();
~
~
~
```

```
10 if (typeof Logger == 'undefined') {
 9   globalThis.Logger = { log: (...args) => console.log(...args) };
 8 }
 7
 6 function loopThroughArray() {
 5   const names = ['Alice', 'Bob', 'Carol', 'Dave', 'Eve'];
 4   names.unshift('Luka')
 3   Logger.log(names)
 2 }
 1
11 loopThroughArray();
~
~
~
```

```
if (typeof Logger == 'undefined') {
  globalThis.Logger = { log: (...args) => console.log(...args) };
}

function loopThroughArray() {
  const names = ['Alice', 'Bob', 'Carol', 'Dave', 'Eve'];
  names.shift()
  Logger.log(names)
}

loopThroughArray();
```

```
:!node code.js
[ 'Bob', 'Carol', 'Dave', 'Eve' ]
```

```
if (typeof Logger == 'undefined') {
  globalThis.Logger = { log: (...args) => console.log(...args) };
}

function loopThroughArray() {
  const names = ['Alice', 'Bob', 'Carol', 'Dave', 'Eve'];
  names.push('Luka');
  Logger.log(names)
  names.pop()
  Logger.log(names)
}

loopThroughArray();
```

```
:!node code.js
[ 'Alice', 'Bob', 'Carol', 'Dave', 'Eve', 'Luka' ]
[ 'Alice', 'Bob', 'Carol', 'Dave', 'Eve' ]
```

```
8 if (typeof Logger == 'undefined') {
7   globalThis.Logger = { log: (...args) => console.log(...args) };
6 }
5
4 function loopThroughArray() {
3   const names = ['Alice', 'Bob', 'Carol', 'Dave', 'Eve'];
2   names.push('Luka');
1   Logger.log(names)
9 }
1
2 loopThroughArray();
~
~
~
```

```
if (typeof Logger == 'undefined') {
  globalThis.Logger = { log: (...args) => console.log(...args) };
}

function loopThroughArray() {
  const names = ['Alice', 'Bob', 'Carol', 'Dave', 'Eve'];
  for (let i = 0; i < names.length; i++) {
    Logger.log(names[i]);
  }
}

loopThroughArray();
~
~
~
```