

Tall enclosure height. about 4.1 m in front projection, at least +/-25% uncertainty. 6.000 m clear. Deliberate brief override to achieve exact 2:1.

Prominent front frame rhythm. five lines / four bays. seven transverse frames / six depth bays. Synthesis with expressive repeated roof; not a photographic replica.

Low aperture. no reliable absolute scale. 0.900 x 2.100 m clear. Programme assumption for a usable entrance.

Raised floor and exterior stair. present in reference. floor 0.096 m above grade; no stair. Single room brief does not require raised tower access; simple low threshold.

Experiment 16 design notes — GPT-6

2026-09-14 — v01 concept: two envelopes

The five images share a useful distinction: a calm enclosure can sit within a much more active external assembly. Adopt a flat red square room and put changing depth in exterior column trusses and roof trusses. Rejected a wavy inner wall/ceiling because the brief expressly asks for the inside to remain simple. Rejected separate decorative fins because the exterior must read as a series of trusses with actual web triangles and identifiable load paths.

2026-09-14 — v01 concept: scale and photo calibration

The front-photo stair supplies a weak scale anchor: about10 assumed170mm risers across280 pixels gives about165px/m at the stair plane. That suggests roughly2.8m facade width; it does not measure a clear room or cancel perspective. Initial3.6m width would have added about29% to that estimate. After scope review, adopted3.0m width (+7%, within the stated uncertainty) and exactly6.0m clear height. Rejected a claim of surveyed dimensions. The height is a deliberate brief-led increase over the approximate4.1m projected photo enclosure. The user ratio is the controlling dimension.

The reference's low opening is not credible as a normal-door calibration. A0.9x2.1m opening provides one usable entrance. Raised floor and exterior staircase from the red tower are not copied: a0.096m slat-mat floor keeps the requested single room direct and compact. No second entrance, movable door leaf, stair or gallery has been added.

2026-09-14 — v01 concept: thin slats and load paths

The repeated catalogue is24x90mm boarding and36x90mm structural slats. Paired chords bracket a single web layer; deep truss action comes from separated chords, not a solid thick beam. Roof reactions go to the paired side-column heads, down triangulated inner/outer chords to sole runners and a crossed slat mat. Longitudinal braces tie frame stations to ground; explicit floor/roof diagonals collect lateral action. Rejected conventional glulam posts, plywood gussets and steel brackets as modeled elements because they would undermine the entirely-thin-timber brief. Concealed fasteners and anchors are acknowledged as unresolved construction necessities.

The manuals establish only analogies: CMHC19mm boards at600mm support spacing and FRIM35x72mm truss members over5.77m. Our24mm boards at500mm spacing and36x90 paired chords are mine, not manual-certified. The6m braced columns, connections, base anchors and soil interface have no matching prescriptive design. No structural adequacy claim is made.

2026-09-14 — v01 concept: fixed faceted expression

Seven frames at500mm spacing carry an additive roof height field: a low curved profile sampled across x plus a changing vertical offset along y. Each interval remains a planar facet, so straight short slats can close the roof and bear at their ends. The outer side-column nodes also vary in depth while their inner chords stay vertical. Rejected an arbitrary double-curved skin that would force twisted long boards; rejected a simple pitched roof repeated unchanged because the two expressive references ask for stronger articulation.

All characteristic profiles and paired chord layer offsets are fixed in concept.md before geometry. A Builder may fit and clip joints within those profiles; changing the room, number of ribs, exterior expression or member catalogue is a design question.

2026-09-14 — v01 concept: enclosure and daylight scope

Opaque lower walls concentrate light at0.75m-high clerestory bands immediately under the6m ceiling on both side walls. End walls remain full-height red boards, as in the interior photo. The roof is fully covered by slats and ceiling is a level slat plane. No glass or membrane is modeled. CraftBot confirmed the open-air pavilion reading on2026-09-14: this is a geometric architectural proposal with no demonstrated rain-tightness or conditioned-building performance. Rejected adding glazing merely to make the model appear weatherproof.

Deviation ledger at concept release

Category: Decision. Reason / rejected alternative.

Source deviation. 3.0x3.0x6.0m clear volume. Photo width estimate retained approximately; exact user2:1 ratio overrides projected photo height.

Source deviation. Seven transverse frames rather than copying five prominent front lines. Series synthesizes roof references; red photos guide scale and assembly, not a literal replica.

Source deviation. Usable0.9x2.1m entrance; floor close to grade. No requirement for low aperture or raised tower stair.

Source deviation. All-slat paired nodes instead of FRIM plywood gussets and steel base shoes. User material palette; connection capacity not inferred from substituted detail.

Considered, kept. Red vertical enclosure, natural chords, triangulated webs, high side light. Features agree across the red-building and expressive references.

Considered, kept. Level inner ceiling despite varying roof trusses. Expressive exterior must not disturb simple interior.

Not verified. Strength, buckling, fasteners, uplift/overturning, soil bearing, moisture, fire, weatherproofing. Outside source coverage and geometric checks; no construction certification.

Phase-2 comparison and structural review

Performed on v02 on 2026-09-15. The comparison and structural-review records below supersede the concept-stage placeholder. The original concept decisions and v01 clarification remain as the design history.

2026-09-14 — v01 build clarification: sole-runner datum

Accepted the Builder's integrated upper-layer sole runner assembly. Continuous longitudinal S runners occupy z=−0.060..−0.024, and upper transverse sleeper segments stop at their faces. Column feet remain at z=−0.024. Lower longitudinal sleepers sit directly beneath the runners and every foot footprint, carrying the load from foot to runner to lower sleeper to grade without a thin-slat cantilever. Floor support spacing remains ≤=0.500 m; fitted butt contacts replace intersecting volumes, with concealed connection design still unverified. This clarifies R-16 and the SOLE_RUNNERS row without changing stock or clear room dimensions.

Rejected placing a third 36 mm sole layer above the mat because it would raise feet to z=+0.012 and contradict the released COLUMN_Z datum. Rejected omitting the runner because a continuous bearing and tying line is part of the stated base assembly. The accepted arrangement retains that line within the existing 96 mm

ground-to-floor stack; the crossing mat is continuous through the lower layer where upper transverse pieces are interrupted.

2026-09-15 — v02 independent structural review

This review concerns the built evidence in version notes.md v01/v02, inspection_v01.md, inspection_v02.md and inspection_v02_room.md. The Designer did not read the geometry scripts or renders, and did not infer compliance merely from the concept. The Builder supplies numerical and fitted-plane evidence; the room Inspector supplies the separate visual channel. The reference images were set aside for this pass.

Element family / condition. Built load-path argument and evidence. Finding / action.

Roof slats. Version notes report short boards spanning adjacent 0.500 m frame stations with undersides on the actual beveled upper-chord planes and fitted facet boundaries. Inspector views 11/16 show complete coverage and support lines. Gravity goes through those contacts to the upper chords. Retain R-15. No reported unsupported board or visible gap. Every contact area is not independently measurable in renders; no roof-board capacity or fastening claim.

Roof trusses. Notes identify upper/lower chords, web nodes, column-head seats and complementary joints; views 08/11/12 confirm web triangles and supported heels. Reactions pass through the web/chord assembly to the paired inner and outer column heads. Retain R-08/R-17/R-22. The 90 mm seats are Builder evidence, visually consistent at view 12. Connection forces and the adequacy of segmented chord splices remain unassigned.

Ceiling. Notes explicitly put ceiling top at z = 6.024 against the lower-chord underside. Its gravity load goes through concealed face fixings into the lower chords, then to column heads. View 19 confirms a level unobstructed plane. Retain R-23. This is a proposed fixing-dependent load path, not bearing from above. Fixing number, withdrawal resistance and fire performance are unverified.

Side and end-wall boards / rails. Notes report rails at no more than 0.750 m, supported staggered board joints, ripped side attachment battens and end rails terminating at inner-chord faces. Boards transfer gravity and out-of-plane loads through their fixings and rails to exterior chords; lower board ends also meet the floor edge where detailed. Views 06/07/10/19 confirm the enclosure and upper openings. Retain R-05/R-21. Exact rail spacing and every concealed attachment depend on Builder evidence; no wall shear capacity is assigned to the boarding.

Entrance discontinuity. Notes name a header with 90 mm seats, doubled jamb plies, a ripped edge slat supporting both plies, and removed infill/rails inside the passage. The header carries infill above into the jambs, then into the supported mat edge. The transverse roof frames avoid using this opening as their principal roof support. View 15 confirms the header/jamb grammar and clear passage. Retain R-02/R-18. No uncarried end or obstructing member is reported. Header, jamb and connection capacities remain uncalculated.

Truss-column feet and soles. v02 actual-mesh assertion checks all 56 horizontal foot faces against both sole and lower sleeper, including support top levels and full 90.000 mm seat width. The sole is at z = −0.060..−0.024, the aligned lower sleeper at z = −0.096..−0.060, then grade. View 14 shows seated feet. R-16 is resolved geometrically. The former maximum 0.753 mm unsupported edge per side was removed by fitted foot-end bevels, not hidden by a relaxed tolerance. No further strips or larger stock justified.

Floor and ground mat. Notes report floor boards spanning the 0.500 m stations, upper transverse sleeper pieces fitted against continuous longitudinal sole runners, and lower sleepers directly below column-foot lines. Floor gravity passes to upper sleepers/runners, then the lower layer, then grade. Views 09/18 show continuous support and no isolated floor strip. Retain R-14/R-16. No modeled retaining wall, slope or suspended undercroft requires another foundation detail. Soil pressure, settlement and long-term timber-to-grade exposure are unverified.

Transverse x direction. Each x-z roof/column frame contains actual triangles. Roof-plane braces collect lateral action over the room width to the exterior truss-column lines; the frame chord/web forces reach their separated feet and the mat. Frame view 08 and roof-bracing view 17 confirm the relevant members. Retain R-08/R-20. This is a braced truss proposal, not a moment frame. Global resistance still depends on designed node connections and ground hold-downs; contact alone cannot carry tension or overturning.

Longitudinal y direction. Built notes identify longitudinal ties at column nodes and diagonal end bays connecting the seven frames. The nominal 3.0 m frame array has 0.500 m bays. Roof/ground-plan diagonals collect shear into these braced side lines, whose braces continue to the mat. Views 07/08/17/18 confirm the members. Retain R-19/R-20. Fitted tie/brace ends were segmented to avoid intersections in v01; their force continuity requires concealed fasteners, which are named but not designed. Skin is not claimed as the diaphragm.

Member slenderness and restraint. The reported system remains 36 x 90 mm structural slats, paired for chords, with roughly 1.5 m column panels and 0.500 m frame repetition. A single 36 mm ply has a weak-axis radius of gyration of 36/sqrt(12) = 10.4 mm; if a 1.5 m panel were an effective buckling length, L/r would be about 144. This is the Designer's dimensional indicator, not a stability calculation; paired-ply composite action and effective restraint are not established. Keep the explicit unsupported-engineering finding in R-26/R-28. The slender column system needs member, restraint and connection design before construction. No evidence supports an arbitrary larger post or a change to the thin-slat brief during this geometric review.

Sliding, uplift, moisture and drainage. Notes do not model a ground anchor, moisture break or weatherproof membrane. The roof is faceted and fully covered with slats; upper clerestories are intentionally open. A seated foot transmits compression but does not establish a tensile ground connection. Roof seams/falls have no demonstrated waterproof drainage detail. Record as unverified under R-28, not as proven stability or weather protection. No glazed enclosure, steel shoe, concrete foundation or membrane is silently added. This remains the accepted conceptual pavilion scope.

The two reported geometric checks are 0 penetrating pairs above 1 mm and 0 floating members at a 2 mm contact tolerance, with no exclusions. They neither prove global connectivity to ground nor adequate bearing by themselves. The separate v02 full-foot assertion uses actual horizontal mesh faces and a 1 micrometre precision tolerance; it supplies the specific bearing evidence missing from v01. Roof and doorway seats use Builder dimension/assembly evidence with visual consistency, not an equally comprehensive independent mesh-bearing audit.

No new geometric defect is established by this review. The explicit lateral members, full-foot correction and documented opening/support paths meet the geometric requirements without another version. This conclusion is limited to the supplied built records and Inspector findings. It does not certify that the pavilion is stable, anchored, weatherproof or ready to construct. R-14/R-15/R-21/R-22/R-23 retain their stated partial-visibility limits; those limitations are not waived visible defects.

Rejected unnecessary changes: added base strips would duplicate the resolved foot bearing; a third sole layer would change the accepted datum; oversized posts or plywood gussets would replace the user's thin-slat system without an engineering design; glazing or a membrane would expand the accepted pavilion scope. None is introduced as a speculative fix.

2026-09-15 — v02 source-versus-model comparison and final design disposition

The mechanical comparison Inspector opened all five original input photographs, the six concept-cited manual snippets, and v02 views 01–04, 06–08 and 10–19. Its complete row-by-row record is inspection_v02_comparison.md. The following Designer table accepts or acts on those actual-image findings; it is not a comparison inferred from the concept text. No additional source search was

undertaken.

Reference image / figure. In the reference. In v02, from comparison Inspector. Change or retained with reason.

01-soane-front.jpg. Tall compact red volume in thin framing; five prominent front lines, raised floor and exterior stair. Views 03/06 show the red volume, pale/red frame and centered entry; the seven-frame rhythm is along depth. Retain. A 3.0 m room width is close to the approximate 2.8 m photograph estimate. The 6.0 m height deliberately overrides the approximate 4.1 m photo height to meet the user's exact 2:1 ratio. Seven depth frames and a low threshold are recorded synthesis choices.

02-soane-outside.jpg. Paired slender timber, diagonal braces, open gaps and small projections around red boarding. Views 01–04/07/08 show paired pale members, red webs, repeated projections and open structural depth. Retain. This is the strongest direct construction-character transfer. Projections are not literal survey dimensions; no heavy post substitute appears.

03-soaneinterior-1.jpg. Tall red vertical boards, high side light, simple floor and unusually low aperture. Views 06/10/19 show the tall clear room, level ceiling and upper side openings with the normal entrance. Retain. Usable 0.9 x 2.1 m entry and a flat ceiling preserve the programme. View 19 hides end boards to expose construction, so the enclosure comparison also uses view 10 and front view 06; it is not a photometric daylight test.

Erne_Dachbau_778.webp. Repeated segmented trusses with genuine triangles and changing depth. Views 01–04/08/11/16 show a compact series of triangulated roof ribs, changing profile and slat cover. Retain. The truss system is adapted to the pavilion's scale. Its industrial dimensions and joint capacities are not transferred.

Tchumi-02.jpg. Repeated straight members describe a rising/falling projected outer profile; glass behind a dense timber screen. Views 01–04/07/08 show a side wave from straight slats with layered depth and shadow. Retain. The outer articulation is transferred; glass, dense screening, vegetation and optical performance are outside the adopted brief.

FRIM Sheet 9 truss elevation / heel. Slender triangular truss with heel supports and center rise. Views 08/11/12 show changing-depth roof triangles and lower-chord seats on paired column heads. Retain topology and supported heel. Faceting, span and paired nodes are project-specific rather than a scaled structural design.

FRIM Sheet 9 roof-bracing plan. Roof-plane diagonals restrain and tie the truss series. Views 08/17 show longitudinal ties and crossed diagonal pairs connecting the seven frames. Retain. Apparent crossings in projected images are not an identified solid penetration; the separate geometry report remains zero pairs. Brace joint capacity is unverified.

FRIM Sheet 9 gussets / nailing. Plywood gussets and specified nail patterns transfer node forces. Views 12/13 show layered timber contacts and straps without gussets or hardware. Retain as the explicit all-slat deviation. This does not establish that the substituted node can develop the source truss forces; fastening must be designed.

CMHC Fig. 68 wall opening. Lintel and jamb framing carry interrupted wall infill. Views 06/15/19 show the supported entrance header and jambs with infill above. Retain opening grammar. The Builder reports 90 mm seats; the render cannot independently measure all bearing areas or verify connections.

CMHC Fig. 86 rafter heel. Roof members seat over aligned supports. Views 11/12/16 show roof lower-chord seats at the side-column heads and the level ceiling below. Retain aligned bearing logic. The proposed truss does not adopt rafter/collar-tie prescriptions. Ceiling gravity still requires the named face fixings.

CMHC Fig. 47 sleeper on slab. Supported timber sleeper with separate ground/moisture layers. Views 14/18 show the crossed slat mat and continuous sole runners. Retain geometric bearing arrangement, with no claim that the omitted slab, moisture break or anchorage is supplied by wood-to-ground contact.

Disposition: all five primary photo rows and all six cited manual-figure rows are retained or intentionally synthesized with the reasons above. No concrete missing member, unintended envelope gap, obstructed opening, wrong profile or other geometric/photo defect was identified. R-13 is checked, bringing requirements to 28 of 28 without waivers. Phase 2 accepts v02 unchanged; another geometry version would have no review finding to resolve.

Incidental specification correction: the existing roof formula samples seven ribs at three repeated vertical offset levels through one rise and fall. The earlier phrase "seven distinct rib heights" overstated what that formula says. The phrase is corrected in concept.md; the formula, dimensions and built geometry are unchanged.

Review cost evidence: one gpt-5.6-luna comparison Inspector, five primary photos, six manual snippets and seventeen v02 render views. This Designer reviewed built notes and reports without opening scripts or renders. No additional renders, manual research, geometry files or shared-tool changes were made during this phase. Token and monetary totals are not exposed and are not estimated.

Experiment 16 version notes — GPT-6

v01 — phase 1, 2026-09-14

Implemented the released 3.000 × 3.000 × 6.000 m clear room with one 0.900 × 2.100 m entrance, two open high clerestories, flat red vertical boarding and a level timber ceiling. Seven transverse frames carry paired pale timber chords, red web triangles, varying outer-column profiles and a fully boarded faceted roof. The geometry starts from tools/experiment_template.py and uses craftbot lib, geometry2d, planes and framing; no shared toolkit was changed.

The crossed ground mat includes the Designer-approved continuous sole runners within its upper layer, z=−0.060..−0.024. Transverse sleepers butt to those runners, with lower longitudinal sleepers directly below their centerlines. A ripped edge slat carries both entrance-jamb plies. The doorway header has 90 mm seats. Side-wall rails are ripped to the specified 31 mm attachment gap; end rails terminate against the inner-chord faces. Wall butt joints stagger on rail heights and individual wall boards are at most 3.000 m long.

Column-chord turns use complementary mitres. Roof chords are split at web nodes; their upper faces bevel to the additive roof facets. Short B roof boards span adjacent 0.500 m frame stations and meet on complementary vertical facet boundaries. Ceiling boards are face-fixed to the lower chords; concealed fixings carry their gravity load; the boards do not bear on the tops of members above them.

Longitudinal ties and end-bay diagonals connect the transverse frames. Roof-plan crossed braces occupy separate 36 mm layers between the lower-chord faces. Ground-plan diagonals fit between the crossed sleeper network in its two thickness layers. These members name the lateral load path; boarding alone is not called a diaphragm, and the concealed connections remain undesigned.

Verification

- Final rendered model: **2,101 members, 0 penetrating pairs >1 mm, 0 floating members at 2 mm contact tolerance, 0 overlap families.**
- No ignored contact families and no changed check tolerances.
- Initial unrendered preflight: 2,031 members, 86 pairs, 0 floating. Its two causes were longitudinal ties crossing column runs (70 pairs) and longitudinal diagonals crossing transverse column webs (16 pairs). Fitting these members to the web faces removed both causes; the segmented ties add 70 members. Both preflights occurred before the first render, so there is only one rendered v01.
- Script assertions check clear room and entrance volumes against every member's bounds, exact room ratio, frame spacing/count, clerestory limit, roof-facet count, declared catalogue/material, floor support spacing, sole/support centerline alignment, header seats and rail spacing.
- The full renderer ran successfully in Blender 4.3.2; all views **01–19** were rendered. Views include four orbits, top/front/east elevations, frame-only, from below, room section, roof/profile, heel, layered column node, base, entrance, roof boarding, roof-plan bracing, mat

underside and interior front.

- Saved model: experiment_16_gpt6_v01_blender.blend; pair report: experiment_16_gpt6_v01_blender_pairs.txt. The version is immutable after these renders.
- Closeout's textual view-schema check initially missed the valid frame-only view because it recognizes only a double-quoted inline hide list or a variable named COVER. View 08's identical hide values were inlined using double quotes; camera, visibility and rendered view identity did not change. No render was necessary.

Bearing audit beyond the contact check

R-16 remains open. A horizontal cut through each sloping outer-column foot produces a horizontal width of **90.008–91.505 mm**, against the 90.000 mm sole/support width. The maximum unsupported edge is **0.753 mm on each side**. The contact check correctly reports contact but cannot prove full footprint bearing. The next version must add adjacent ripped S sole/lower-support strips with fitted transverse-mat cuts, or fit a local foot-end bevel within the S stock. Preserve the released column profile, mat datums and clear-room dimensions.

Inspection and requirements

The fresh single-room Inspector reviewed all 19 views and reported no clear major missing geometry, unintended envelope void, misplaced member or floating member. The room, entrance, upper light, seven frames, layered chords and expressive roof are visually confirmed. Detailed observations are in inspection_v01_room.md; the merged result and Builder dispositions are in inspection_v01.md.

R-14, R-15, R-21, R-22 and R-23 contain details that cannot be measured or seen fully in these renders. Their generation rules, dimension chains, fitted-plane construction and named ceiling face fixing supply the Builder evidence; there is no contrary visual finding. The requirement checkboxes now record **26 of 28 satisfied**: R-13 awaits phase-2 reference comparison, and R-16 remains open. Thus **phase 1 is not converged**. No other visual correction was requested for v02.

Scope and evidence limits

CMHC board-thickness examples and the FRIM slender-truss drawing are precedents, not capacity evidence for this assembly. The 6 m slat columns are outside the cited prescriptive stud cases; FRIM plywood gussets do not validate the modeled paired-slat joints. No plywood, metal shoes, glazing, concrete or invented heavy beams are modeled. The low threshold replaces the reference stair, the usable doorway replaces its unusually low aperture, and the exact 2:1 clear height follows the user's brief.

This is a pavilion with open high clerestories. Structural adequacy, fastener and connection design, uplift/overturning anchorage, weatherproofing, durability, fire, soil bearing and moisture separation are not verified. Sections are plausible visual propositions, not calculated. These limitations do not waive geometric bearing or inspection findings.

Next version and Designer questions

- Correct the quantified R-16 foot-seat deficit with an in-catalogue local assembly detail; the two alternatives above preserve the design. No scope change is requested.
 - No additional visual defects were identified. Recheck the base close-up, full numeric model and required full phase-ending views in a fresh v02; do not overwrite v01.
- No open design-authority question at this stage. Usage/context statistics are not exposed to this Builder and are not estimated.

v02 — phase 1 foot-bearing correction, 2026-09-14

Copied the immutable v01 script and corrected R-16 with fitted foot-end bevels. Each sloping first chord segment has two additional cut planes: they run from the edges of the 90 mm horizontal seat to the original stock edges 90 mm above that seat. Above this short end detail the original chord profile remains. The cuts remove material from the S36x90 blank, keep every solid convex, and retain the fixed column centerlines, room dimensions, sole runners and ground-mat datums. No support strips or other members were added. The alternative of adjacent ripped supports would require new mat cuts and more pieces; the fitted bevel resolves the local deficit directly.

Verification

- 2,101 members; 0 penetrating pairs >1 mm; 0 floating members at 2 mm contact tolerance; 0 overlap families.** No ignored members or changed harness tolerances.
- A new assertion selects the four actual mesh vertices of each horizontal chord foot and checks that its full rectangle lies within both the sole-runner and lower-sleeper footprint. It also checks the support top levels and requires a full 90 mm seat. The 1 micrometre assertion tolerance accommodates Blender mesh precision; it is distinct from the overlap/contact tolerances.
- Test-first evidence: before the bevel was added, that assertion failed on ColumnOuter -1 00 -1 00 against SoleRunner_00. After the correction, all **56 foot faces** passed, with measured widths **90.000–90.000 mm**. The previous maximum 0.753 mm unsupported edge is removed.
- Full Blender 4.3.2 render completed with exit code 0; every stable view **01–19** was rendered. No view definition changed. The base is shown by views 14 and 18, with frame and underside context in 08 and 09.
- Artifacts: experiment_16_gpt6_v02.py, experiment_16_gpt6_v02_blender.blend, experiment_16_gpt6_v02_blender_pairs.txt, and 19 experiment_16_gpt6_v02_blender_view_XX.png renders. No changes to v01 geometry or shared tools were made by this Builder. Runner owns viewer export and close-out.

Inspection and requirements

The fresh single-room Inspector completed all 19 views and found no missing member, unintended envelope gap, clearly floating member or new absence. Base view 14 shows seated feet without a visible gap; the small bevel itself is below reliable visual measurement, so the full-foot assertion supplies the exact support evidence. Frame, underside, heel, node, roof-board and bracing views show no regressions. Its saved report inspection_v02_room.md was complete before the final-message usage interruption; the continuation on 2026-09-15 merged it into inspection_v02.md without repeating renders or inspection.

R-16 is now checked. **27 of 28 requirements are satisfied, and phase 1 is converged**: 0 pairs, 0 floating, no open visual defect, and every phase-one requirement satisfied. R-13 alone remains pending for phase-2 reference comparison. Runner's closeout_v02.md records **8 passed, 0 failed**, including exported model, layers, all 19 renders and viewer screenshots.

Scope and Designer questions

The named load path remains chord foot → continuous upper sole → directly aligned lower sleeper → grade. Full geometric bearing is verified; fastener forces, buckling, capacity, anchorage, soil/moisture design and weatherproofing remain unverified. The open clerestory pavilion and all v01 scope interpretations remain in force. Sections are a visual proposition, not calculated.

No open design-authority question. No shared helper promotion is proposed. Usage/context statistics are not exposed to this Builder and are not estimated.

Credits

The project author is Luka Piškorec, previously a lecturer at Aalto University and researcher at ETH Zürich, co-founder of TEN Studio (Zürich and Belgrade) and {protocell:labs} (Helsinki), practices that work at an intersection of architecture, design, digital art and research. CraftBot is part of the art-ai-fact initiative funded by Aalto University in 2025-2026.