

WX1000



FEATURES

Profile: - European.

- Certified to EN:1303:2015, meeting and exceeding this standard.

Body: - Made of extruded brass.

- Nickel matt or brass finishes available.

Security systems: - Triple anti-bumping protection. Innovative double pin and

double spring system.

- Reinforced anti-snap bar, made of stainless steel and fixed

to the cylinder's body with 4 stainless steel bolts.

- Maximum antidrill protection with pins fitted inside the front of the body

and additional anti-drill steel pins inside.

- Antipick protection.

Internal elements: - 16 active pins, all of them able for master keying, with millions of differs.

Cam: - Available in Standard DIN cam (15 mm) and short cam (13 mm).

Range: - Standard cylinders, half cylinders, cylinders with adjustable axis,

thumb turn cylinders, cylinders with adjustable tab for doors with

panic bars and cylinders with adjustable cam angle.

Keys: - Security dimple keys. Key profile patented by IFAM (no. 2.061.242).

- Silver nickel keys with bow over-moulded with high strength ABS resin

for a comfortable use. - Supplied with 5 keys.

- Supllied with property card with the CCS (Control Code System)

security system. This guarantees a maximum security level, control and


traceability of key-duplications.


Packaging: - Boxed.



WX1000

DIMENSIONS







Ref.	Cod.	CI.	Α	A	В	Uni.				
STANDARD DIN CAM 15mm. Pack.										
1000WX3030L	060201		60	30	30	6				
1000WX3030N	060211		60	30	30	6				
1000WX3040L	060401		70	30	40	6				
1000WX3040N	060411		70	30	40	6				
1000WX3535L	061001		70	35	35	6				
1000WX3535N	061011		70	35	35	6				
1000WX4040L	061401		80	40	40	6				
1000WX4040N	061411		80	40	40	6				
SHORT CAM 13mm. Pack.										
1000WX3030LC	060251		60	30	30	6				
1000WX3030NC	060261		60	30	30	6				
1000WX3040LC	060451		70	30	40	6				
1000WX3040NC	060461		70	30	40	6				
1000WX3535LC	061051		70	35	35	6				
1000WX3535NC	061061		70	35	35	6				
1000WX4040LC	061451		80	40	40	6				
1000WX4040NC	061461		80	40	40	6				
THUMB TURN. STANDARD DIN CAM 15mm.										
	Pack.	Α								
1000WXP3030L	060202		60	30	30	6				
1000WXP3040L	060402	_	70	30	40	6				
1000WXP3040N	060412		70	30	40	6				
1000WXP3535L	061002	_	70	35	35	6				
1000WXP3535N	061012		70	35	35	6				
1000WXP4040L	061402		80	40	40	6				
1000WXP4040N	061412		80	40	40	6				
THUMB TURN. SHORT CAM 13mm. Pack.										
1000WXP3030LC	060252		60	30	30	6				
1000WXP3030NC	060262		60	30	30	6				
1000WXP3040LC	060452		70	30	40	6				
1000WXP3040NC	060462		70	30	40	6				
1000WXP3535LC	061052		70	35	35	6				
1000WXP3535NC	061062		70	35	35	6				
1000WXP4040LC	061452		80	40	40	6				
1000WXP4040NC	061462		80	40	40	6				



Ref.	Cod.	CI.	L	Α	В	Uni.				
STANDARD DIN CAM 15mm. Pack.										
1000WXE3030L	060206		60	30	30	1				
1000WXE3030N	060216		60	30	30	1				
1000WXE3035N	060316		65	30	35	1				
1000WXE3040L	060406		70	30	40	1				
1000WXE3040N	060416		70	30	40	1				
1000WXE3045L	060506		75	30	45	1				
1000WXE3045N	060516		75	30	45	1				
1000WXE3050N	060616		80	30	50	1				
1000WXE3060N	060716		90	30	60	1				
1000WXE3070N	060816		100	30	70	1				



CYLINDER WITH

