

Seminar Algorithms for Big Data

Fast Random Integer Generation in an Interval

Based on a paper of the same title by Daniel Lemire

Lukas Geis

Supervised by Dr. Manuel Penschuck

29th February 2024 · Algorithm Engineering (Prof. Dr. Ulrich Meyer)

What is the problem?

0



What is the problem?

1



What is the problem?


0



uniform random bit




What is the problem?



What is the problem?


0 1 1 0 1 0 1 0



What is the problem?

1 1 0 1 0 0 0 1

$W = 8$ independent uniform bits



What is the problem?

1 1 0 1 0 0 0 1

$W = 8$ independent uniform bits

Goal:

Generate a uniform integer between 100 and 200

What is the problem?

1 1 0 1 0 0 0 1

interpret as unsigned 8-bit integer

Goal:

Generate a uniform integer between 100 and 200

What is the problem?



1 1 0 1 0 0 0 1

2^0
↓

interpret as unsigned 8-bit integer

Goal:

Generate a uniform integer between 100 and 200

What is the problem?

1 1 0 1 0 0 0 1

2^1 2^0

↓ ↓

interpret as unsigned 8-bit integer

Goal:

Generate a uniform integer between 100 and 200

What is the problem?


					2^2	2^1	2^0
					↓	↓	↓
1	1	0	1	0	0	0	1

interpret as unsigned 8-bit integer

Goal:

Generate a uniform integer between 100 and 200

What is the problem?



2^7	2^6	2^5	2^4	2^3	2^2	2^1	2^0
↓	↓	↓	↓	↓	↓	↓	↓
1	1	0	1	0	0	0	1

interpret as unsigned 8-bit integer

Goal:

Generate a uniform integer between 100 and 200

What is the problem?

209 in binary

2^7	2^6	2^5	2^4	2^3	2^2	2^1	2^0
↓	↓	↓	↓	↓	↓	↓	↓
1	1	0	1	0	0	0	1

interpret as unsigned 8-bit integer

Goal:

Generate a uniform integer between 100 and 200

What is the problem?

209 in binary

2^7	2^6	2^5	2^4	2^3	2^2	2^1	2^0
↓	↓	↓	↓	↓	↓	↓	↓
1	1	0	1	0	0	0	1

interpret as uniform 8-bit integer in $[0, 2^8)$

Goal:

Generate a uniform integer between 100 and 200

Table of Contents

1 Preliminaries

- Formal Definition
- Operations
- The Naive Approach

2 Unbiased Algorithms

- The OpenBSD Algorithm
- The Java Algorithm
- The Bitmask Algorithm

3 Lemire's Algorithm

- Multiply-And-Shift
- The Algorithm

4 Summary

1

Preliminaries





Formal Definition

Input:



Formal Definition

Input:

- source of uniform random integers in $[0, 2^W)$: `rand()`



Formal Definition

Input:

- source of uniform random integers in $[0, 2^W)$: `rand()`
- upper bound of interval $n \in \mathbb{N}$




Formal Definition

Input:

- source of uniform random integers in $[0, 2^W)$: `rand()`
- upper bound of interval $n \in \mathbb{N}$

Output:

- uniform random integer in interval $[0, n)$



Formal Definition

Input:

- source of uniform random integers in $[0, 2^W)$: `rand()`
- upper bound of interval $n \in \mathbb{N}$

Output:

- uniform random integer in interval $[0, n)$



Formal Definition

Input:

- source of uniform random integers in $[0, 2^W)$: `rand()`
- upper bound of interval $n \in \mathbb{N}$

Output:

- uniform random integer in interval $[0, n)$



Formal Definition

Input:

- source of uniform random integers in $[0, 2^W)$: `rand()`
- upper bound of interval $n \in \mathbb{N}$

Output:

- uniform random integer in interval $[0, n)$




Formal Definition

Input:

- source of uniform random integers in $[0, 2^W)$: `rand()`
- upper bound of interval $n \in \mathbb{N}$

Output:

- uniform random integer in interval $[0, n)$





Definition (Common Operations)



Definition (Common Operations)

■ Integer-Division: $x \div y \quad := \lfloor x/y \rfloor$



Definition (Common Operations)

- Integer-Division: $x \div y \quad := \lfloor x/y \rfloor$
- Remainder-Operation: $x \bmod y \quad := x - (x \div y)y$

Definition (Common Operations)

- Integer-Division: $x \div y \quad := \lfloor x/y \rfloor$
- Remainder-Operation: $x \bmod y \quad := x - (x \div y)y$
- Bit-RIGHTSHIFT: $x \gg W \quad := x \div 2^W$

Definition (Common Operations)

- Integer-Division: $x \div y := \lfloor x/y \rfloor$
- Remainder-Operation: $x \bmod y := x - (x \div y)y$
- Bit-RIGHTSHIFT: $x \gg W := x \div 2^W$
- Bit-LEFTSHIFT: $x \ll W := x \cdot 2^W$

Definition (Common Operations)

- Integer-Division: $x \div y \quad := \lfloor x/y \rfloor$
- Remainder-Operation: $x \bmod y \quad := x - (x \div y)y$
- Bit-RIGHTSHIFT: $x \gg W \quad := x \div 2^W$
- Bit-LEFTSHIFT: $x \ll W \quad := x \cdot 2^W$
- Bitwise-AND: $x \& y$

Definition (Common Operations)

- Integer-Division: $x \div y \quad := \lfloor x/y \rfloor$
- Remainder-Operation: $x \bmod y \quad := x - (x \div y)y$
- Bit-RIGHTSHIFT: $x \gg W \quad := x \div 2^W$
- Bit-LEFTSHIFT: $x \ll W \quad := x \cdot 2^W$
- Bitwise-AND: $x \& y \rightarrow x \bmod 2^W \quad := x \& (2^W - 1)$

Definition (Common Operations)

- Integer-Division: $x \div y := \lfloor x/y \rfloor$
- Remainder-Operation: $x \bmod y := x - (x \div y)y$
- Bit-RIGHTSHIFT: $x \gg W := x \div 2^W$
- Bit-LEFTSHIFT: $x \ll W := x \cdot 2^W$
- Bitwise-AND: $x \& y \rightarrow x \bmod 2^W := x \& (2^W - 1)$

Definition (Power Remainder)

For $W, n \in \mathbb{N}$, we write \mathcal{R} for $2^W \bmod n$.

The Naive Approach



The Naive Approach

$\text{rand}() \bmod n$



The Naive Approach

$\text{rand}() \bmod n$

Does this work?



The Naive Approach

$\text{rand}() \bmod n$

Does this work?

- Yes, the generated number is in $[0, n)$.



The Naive Approach

$\text{rand}() \bmod n$

Does this work?

- Yes, the generated number is in $[0, n)$.

Is this efficient?



The Naive Approach


$\text{rand}() \bmod n$

Does this work?

- Yes, the generated number is in $[0, n)$.

Is this efficient?

- No, we require one expensive integer division operation.



The Naive Approach

$\text{rand}() \bmod n$


Does this work?

- Yes, the generated number is in $[0, n)$.

Is this efficient?

- No, we require one expensive integer division operation.

Is the generated number uniform in $[0, n)$?



The Naive Approach - Bias



The Naive Approach - Bias

In general, applying $x \bmod n$ to $[0, 2^W)$ yields



The Naive Approach - Bias

In general, applying $x \bmod n$ to $[0, 2^W)$ yields

$$\begin{array}{c}
 \overbrace{0, 1, \dots, n-1, 0, 1, \dots, n-1, \dots, 0, 1, \dots, n-1, 0, 1, \dots, \mathcal{R}-1}^{2^W \text{ values}} \\
 \underbrace{0, 1, \dots, n-1, 0, 1, \dots, n-1, \dots, 0, 1, \dots, n-1}_{(2^W \div n) \cdot n \text{ values}} \quad \underbrace{0, 1, \dots, \mathcal{R}-1}_{\mathcal{R} \text{ values}}
 \end{array}$$

The Naive Approach - Bias

In general, applying $x \bmod n$ to $[0, 2^W)$ yields

$$\underbrace{\overbrace{0, 1, \dots, n-1}^{n \text{ values}}, \overbrace{0, 1, \dots, n-1}^{n \text{ values}}, \dots, \overbrace{0, 1, \dots, n-1}^{n \text{ values}}, \underbrace{0, 1, \dots, \mathcal{R}-1}_{\mathcal{R} \text{ values}}}_{(2^W \div n) \cdot n \text{ values}}^{2^W \text{ values}}$$

We have a **leftover** interval that introduces bias.

The Naive Approach - Bias

In general, applying $x \bmod n$ to $[0, 2^W)$ yields

$$\overbrace{\underbrace{0, 1, \dots, n-1}_{n \text{ values}}, \underbrace{0, 1, \dots, n-1}_{n \text{ values}}, \dots, \underbrace{0, 1, \dots, n-1}_{n \text{ values}}, \underbrace{0, 1, \dots, \mathcal{R}-1}_{\mathcal{R} \text{ values}}}_{(2^W \div n) \cdot n \text{ values}}^{2^W \text{ values}}$$

We have a **leftover** interval that introduces bias.

Deterministic Mappings

The Naive Approach - Bias

In general, applying $x \bmod n$ to $[0, 2^W)$ yields

$$\overbrace{\underbrace{0, 1, \dots, n-1}_{n \text{ values}}, \underbrace{0, 1, \dots, n-1}_{n \text{ values}}, \dots, \underbrace{0, 1, \dots, n-1}_{n \text{ values}}, \underbrace{0, 1, \dots, \mathcal{R}-1}_{\mathcal{R} \text{ values}}}_{(2^W \div n) \cdot n \text{ values}}^{2^W \text{ values}}$$


We have a **leftover** interval that introduces bias.

Deterministic Mappings

Every deterministic mapping $f: [0, 2^W) \rightarrow [0, n)$

The Naive Approach - Bias

In general, applying $x \bmod n$ to $[0, 2^W)$ yields



We have a **leftover** interval that introduces bias.

Deterministic Mappings

Every deterministic mapping $f: [0, 2^W) \rightarrow [0, n)$ does **not** generate **uniform** random integers in one step

The Naive Approach - Bias

In general, applying $x \bmod n$ to $[0, 2^W)$ yields

$$\underbrace{\overbrace{0, 1, \dots, n-1}^{n \text{ values}}, \overbrace{0, 1, \dots, n-1}^{n \text{ values}}, \dots, \overbrace{0, 1, \dots, n-1}^{n \text{ values}}, \underbrace{0, 1, \dots, \mathcal{R}-1}_{\mathcal{R} \text{ values}}}_{(2^W \div n) \cdot n \text{ values}}^{2^W \text{ values}}$$

We have a **leftover** interval that introduces bias.

Deterministic Mappings

Every deterministic mapping $f: [0, 2^W) \rightarrow [0, n)$ does **not** generate **uniform** random integers in one step whenever n does not divide 2^W .

2

Unbiased Algorithms



The OpenBSD Algorithm




The OpenBSD Algorithm

- Shift the **rejection interval** to the left:




The OpenBSD Algorithm

- Shift the rejection interval to the left:



The OpenBSD Algorithm


- Shift the rejection interval to the left:



- Algorithm:

The OpenBSD Algorithm

- Shift the rejection interval to the left:




- Algorithm:

- Generate a uniform random number $x \in [0, 2^W)$ until $x \geq \mathcal{R}$

The OpenBSD Algorithm

- Shift the **rejection interval** to the left:



- Algorithm:
 - Generate a uniform random number $x \in [0, 2^W)$ until $x \geq \mathcal{R}$
 - Return $x \bmod n$

The OpenBSD Algorithm - Efficiency

Algorithm:

- Generate a uniform random number $x \in [0, 2^W)$ until $x \geq \mathcal{R}$
- Return $x \bmod n$



The OpenBSD Algorithm - Efficiency

Algorithm:

- Generate a uniform random number $x \in [0, 2^W)$ until $x \geq \mathcal{R}$
- Return $x \bmod n$

Efficiency

The OpenBSD Algorithm - Efficiency

Algorithm:

- Generate a uniform random number $x \in [0, 2^W)$ until $x \geq \mathcal{R}$
- Return $x \bmod n$

Efficiency

We require 2 integer division operations:

The OpenBSD Algorithm - Efficiency

Algorithm:

- Generate a uniform random number $x \in [0, 2^W)$ until $x \geq \mathcal{R}$
- Return $x \bmod n$

Efficiency

We require 2 integer division operations:

- one for computing \mathcal{R}

The OpenBSD Algorithm - Efficiency

Algorithm:

- Generate a uniform random number $x \in [0, 2^W)$ until $x \geq \mathcal{R}$
- Return $x \bmod n$

Efficiency

We require 2 integer division operations:

- one for computing \mathcal{R}
- and one for computing $x \bmod n$.

The Java Algorithm



The Java Algorithm


- Consider $x - (x \bmod n)$ for $x \in [0, 2^W)$:



The Java Algorithm

- Consider $x - (x \bmod n)$ for $x \in [0, 2^W)$:


$$\begin{array}{c}
 \overbrace{\hspace{15em}}^{(2^W \div n) \cdot n \text{ values}} \\
 \underbrace{0, 1, \dots, n-1}_{n \text{ values}}, \underbrace{0, 1, \dots, n-1}_{n \text{ values}}, \dots, \underbrace{0, 1, \dots, n-1}_{n \text{ values}}, \underbrace{0, 1, \dots, \mathcal{R}-1}_{\mathcal{R} \text{ values}}
 \end{array}$$



The Java Algorithm

- Consider $x - (x \bmod n)$ for $x \in [0, 2^W)$:

$$\begin{array}{c}
 \overbrace{\hspace{15em}}^{(2^W \div n) \cdot n \text{ values}} \\
 \underbrace{0, 1, \dots, n-1}_{\text{mapped to 0}}, \underbrace{0, 1, \dots, n-1}_{n \text{ values}}, \dots, \underbrace{0, 1, \dots, n-1}_{n \text{ values}}, \underbrace{0, 1, \dots, \mathcal{R}-1}_{\mathcal{R} \text{ values}}
 \end{array}$$




The Java Algorithm

- Consider $x - (x \bmod n)$ for $x \in [0, 2^W)$:

$$\begin{array}{c}
 \overbrace{\hspace{15em}}^{(2^W \div n) \cdot n \text{ values}} \\
 \underbrace{0, 1, \dots, n-1}_{\text{mapped to 0}}, \underbrace{0, 1, \dots, n-1}_{\text{mapped to } n}, \dots, \underbrace{0, 1, \dots, n-1}_{n \text{ values}}, \underbrace{0, 1, \dots, \mathcal{R}-1}_{\mathcal{R} \text{ values}}
 \end{array}$$


The Java Algorithm

- Consider $x - (x \bmod n)$ for $x \in [0, 2^W)$:




The Java Algorithm

- Consider $x - (x \bmod n)$ for $x \in [0, 2^W)$:



The Java Algorithm


- Consider $x - (x \bmod n)$ for $x \in [0, 2^W)$:



- Map every number to the next-smallest multiple of n

The Java Algorithm


- Consider $x - (x \bmod n)$ for $x \in [0, 2^W)$:



- Map every number to the next-smallest multiple of n
- Only numbers in **leftover** interval mapped to $2^W - \mathcal{R} > 2^W - n$

The Java Algorithm


- Consider $x - (x \bmod n)$ for $x \in [0, 2^W)$:



- Map every number to the next-smallest multiple of n
- Only numbers in **leftover** interval mapped to $2^W - \mathcal{R} > 2^W - n$
- Algorithm:

The Java Algorithm


- Consider $x - (x \bmod n)$ for $x \in [0, 2^W)$:



- Map every number to the next-smallest multiple of n
- Only numbers in **leftover** interval mapped to $2^W - \mathcal{R} > 2^W - n$
- Algorithm:
 - (1) Draw $x \in [0, 2^W)$ and compute $r = x \bmod n$

The Java Algorithm

- Consider $x - (x \bmod n)$ for $x \in [0, 2^W)$:



- Map every number to the next-smallest multiple of n
- Only numbers in **leftover** interval mapped to $2^W - R > 2^W - n$
- Algorithm:
 - (1) Draw $x \in [0, 2^W)$ and compute $r = x \bmod n$
 - (2) Return r if $x - r \leq 2^W - n$ else goto (1)

The Java Algorithm - Efficiency

Algorithm:

- (1) Draw $x \in [0, 2^W)$ and compute $r = x \bmod n$
- (2) Return r if $x - r \leq 2^W - n$ else goto (1)



The Java Algorithm - Efficiency

Algorithm:

- (1) Draw $x \in [0, 2^W)$ and compute $r = x \bmod n$
- (2) Return r if $x - r \leq 2^W - n$ else goto (1)

Efficiency

The Java Algorithm - Efficiency

Algorithm:

- (1) Draw $x \in [0, 2^W)$ and compute $r = x \bmod n$
- (2) Return r if $x - r \leq 2^W - n$ else goto (1)

Efficiency

- At least one integer division operation

The Java Algorithm - Efficiency

Algorithm:

- (1) Draw $x \in [0, 2^W)$ and compute $r = x \bmod n$
- (2) Return r if $x - r \leq 2^W - n$ else goto (1)

Efficiency

- At least one integer division operation
- Number of integer divisions operations equal to number of rounds

The Java Algorithm - Efficiency

Algorithm:

- (1) Draw $x \in [0, 2^W)$ and compute $r = x \bmod n$
- (2) Return r if $x - r \leq 2^W - n$ else goto (1)

Efficiency

- At least one integer division operation
- Number of integer divisions operations equal to number of rounds
- Return number in round if $x < 2^W - \mathcal{R}$

The Java Algorithm - Efficiency

Algorithm:

- (1) Draw $x \in [0, 2^W)$ and compute $r = x \bmod n$
- (2) Return r if $x - r \leq 2^W - n$ else goto (1)

Efficiency

- At least one integer division operation
- Number of integer divisions operations equal to number of rounds
- Return number in round if $x < 2^W - \mathcal{R}$
- Happens with probability $\frac{2^W - \mathcal{R}}{2^W} > \frac{1}{2}$

The Java Algorithm - Efficiency

Algorithm:

- (1) Draw $x \in [0, 2^W)$ and compute $r = x \bmod n$
- (2) Return r if $x - r \leq 2^W - n$ else goto (1)

Efficiency

- At least one integer division operation
- Number of integer divisions operations equal to number of rounds
- Return number in round if $x < 2^W - \mathcal{R}$
- Happens with probability $\frac{2^W - \mathcal{R}}{2^W} > \frac{1}{2}$
- Expected number of integer division operations is $\frac{2^W}{2^W - \mathcal{R}} < 2$

The Bitmask Algorithm - Representation



The Bitmask Algorithm - Representation

- Consider the **binary** representation of n :



The Bitmask Algorithm - Representation

- Consider the **binary** representation of n :

$$\begin{array}{ccccccc}
 & & 2^{W-1} & & 2^{\lfloor \log_2 n \rfloor} & & 2^1 2^0 \\
 & & \downarrow & & \downarrow & & \downarrow \downarrow \\
 n & \xrightarrow{\text{binary}} & \underbrace{0, \dots, 0}_{\text{only 0's}} & , & \textcolor{red}{1} & , & \underbrace{1, \dots, 0, 1}_{\text{series of 0's and 1's}}
 \end{array}$$



The Bitmask Algorithm - Representation

- Consider the binary representation of n :

$$\begin{array}{ccccccc}
 & & 2^{W-1} & & 2^{\lfloor \log_2 n \rfloor} & & 2^1 2^0 \\
 & & \downarrow & & \downarrow & & \downarrow \downarrow \\
 n & \xrightarrow{\text{binary}} & \underbrace{0, \dots, 0}_{\text{only 0's}} & , & \textcolor{red}{1} & , & \underbrace{1, \dots, 0, 1}_{\text{series of 0's and 1's}}
 \end{array}$$

- Every number $x \leq n$ only needs the last $\lfloor \log_2 n \rfloor + 1$ bits

The Bitmask Algorithm - Representation

- Consider the binary representation of n :

$$\begin{array}{ccccc}
 & 2^{W-1} & 2^{\lfloor \log_2 n \rfloor} & 2^1 & 2^0 \\
 & \downarrow & \downarrow & \downarrow & \downarrow \\
 n & \xrightarrow{\text{binary}} & \underbrace{0, \dots, 0}_{\text{only 0's}} & 1, & \underbrace{1, \dots, 0, 1}_{\text{series of 0's and 1's}}
 \end{array}$$

- Every number $x \leq n$ only needs the last $\lfloor \log_2 n \rfloor + 1$ bits
- Get these bits with a bitwise-AND with

$$\begin{array}{ccccc}
 & 2^{W-1} & 2^{\lfloor \log_2 n \rfloor} & 2^1 & 2^0 \\
 & \downarrow & \downarrow & \downarrow & \downarrow \\
 2^{\lfloor \log_2 n \rfloor + 1} - 1 & \xrightarrow{\text{binary}} & \underbrace{0, \dots, 0}_{\text{only 0's}} & 1, & \underbrace{1, \dots, 1, 1}_{\text{only 1's}}
 \end{array}$$

The Bitmask Algorithm - Mask



The Bitmask Algorithm - Mask

- How can we compute $2^{\lfloor \log_2 n \rfloor + 1}$?




The Bitmask Algorithm - Mask

- How can we compute $2^{\lfloor \log_2 n \rfloor + 1}$?
- Count the number ℓ of leading 0's in $n!$




The Bitmask Algorithm - Mask

- How can we compute $2^{\lfloor \log_2 n \rfloor + 1}$?
- Count the number ℓ of leading 0's in n !



The Bitmask Algorithm - Mask


- How can we compute $2^{\lfloor \log_2 n \rfloor + 1}$?
- Count the number ℓ of leading 0's in n !



- $\lfloor \log_2 n \rfloor = W - \ell - 1$

The Bitmask Algorithm - Mask


- How can we compute $2^{\lfloor \log_2 n \rfloor + 1}$?
- Count the number ℓ of leading 0's in n !



$$\lfloor \log_2 n \rfloor = W - \ell - 1 \quad \longrightarrow \quad 2^{\lfloor \log_2 n \rfloor + 1} = 1 \ll (W - \ell)$$

The Bitmask Algorithm - Mask


- How can we compute $2^{\lfloor \log_2 n \rfloor + 1}$?
- Count the number ℓ of leading 0's in n !



- $\lfloor \log_2 n \rfloor = W - \ell - 1 \quad \longrightarrow \quad 2^{\lfloor \log_2 n \rfloor + 1} = 1 \ll (W - \ell)$
- Algorithm:

The Bitmask Algorithm - Mask


- How can we compute $2^{\lfloor \log_2 n \rfloor + 1}$?
- Count the number ℓ of leading 0's in n !



- $\lfloor \log_2 n \rfloor = W - \ell - 1 \quad \longrightarrow \quad 2^{\lfloor \log_2 n \rfloor + 1} = 1 \ll (W - \ell)$
- Algorithm:
 - (1) Compute ℓ and $\mathcal{M} = 2^{\lfloor \log_2 n \rfloor + 1} - 1$

The Bitmask Algorithm - Mask

- How can we compute $2^{\lfloor \log_2 n \rfloor + 1}$?
- Count the number ℓ of leading 0's in n !




- $\lfloor \log_2 n \rfloor = W - \ell - 1 \quad \longrightarrow \quad 2^{\lfloor \log_2 n \rfloor + 1} = 1 \ll (W - \ell)$

- Algorithm:

- (1) Compute ℓ and $\mathcal{M} = 2^{\lfloor \log_2 n \rfloor + 1} - 1$
- (2) Draw $x \in [0, 2^W)$ and compute $b = x \ \& \ \mathcal{M}$

The Bitmask Algorithm - Mask

- How can we compute $2^{\lfloor \log_2 n \rfloor + 1}$?
- Count the number ℓ of leading 0's in n !



- $\lfloor \log_2 n \rfloor = W - \ell - 1 \quad \longrightarrow \quad 2^{\lfloor \log_2 n \rfloor + 1} = 1 \ll (W - \ell)$

- Algorithm:

- (1) Compute ℓ and $\mathcal{M} = 2^{\lfloor \log_2 n \rfloor + 1} - 1$
- (2) Draw $x \in [0, 2^W)$ and compute $b = x \ \& \ \mathcal{M}$
- (3) Return b if $b < n$ else goto (2)

The Bitmask Algorithm - Efficiency

Algorithm:

- (1) Compute ℓ and $\mathcal{M} = 2^{\lfloor \log_2 n \rfloor + 1} - 1$
- (2) Draw $x \in [0, 2^W)$ and compute $b = x \ \& \ \mathcal{M}$
- (3) Return b if $b < n$ else goto (2)



The Bitmask Algorithm - Efficiency

Algorithm:

- (1) Compute ℓ and $\mathcal{M} = 2^{\lceil \log_2 n \rceil + 1} - 1$
- (2) Draw $x \in [0, 2^W)$ and compute $b = x \ \& \ \mathcal{M}$
- (3) Return b if $b < n$ else goto (2)

Efficiency

The Bitmask Algorithm - Efficiency

Algorithm:

- (1) Compute ℓ and $\mathcal{M} = 2^{\lfloor \log_2 n \rfloor + 1} - 1$
- (2) Draw $x \in [0, 2^W)$ and compute $b = x \ \& \ \mathcal{M}$
- (3) Return b if $b < n$ else goto (2)

Efficiency

- b at most $\mathcal{M} = 2^{\lfloor \log_2 n \rfloor + 1} - 1 < 2n$

The Bitmask Algorithm - Efficiency

Algorithm:

- (1) Compute ℓ and $\mathcal{M} = 2^{\lfloor \log_2 n \rfloor + 1} - 1$
- (2) Draw $x \in [0, 2^W)$ and compute $b = x \ \& \ \mathcal{M}$
- (3) Return b if $b < n$ else goto (2)

Efficiency

■ b at most $\mathcal{M} = 2^{\lfloor \log_2 n \rfloor + 1} - 1 < 2n \quad \longrightarrow \quad$ success probability at least $\approx \frac{1}{2}$

The Bitmask Algorithm - Efficiency

Algorithm:

- (1) Compute ℓ and $\mathcal{M} = 2^{\lfloor \log_2 n \rfloor + 1} - 1$
- (2) Draw $x \in [0, 2^W)$ and compute $b = x \ \& \ \mathcal{M}$
- (3) Return b if $b < n$ else goto (2)

Efficiency

- b at most $\mathcal{M} = 2^{\lfloor \log_2 n \rfloor + 1} - 1 < 2n \quad \longrightarrow \quad$ success probability at least $\approx \frac{1}{2}$
- At most ≈ 2 rounds in expectation

The Bitmask Algorithm - Efficiency

Algorithm:

- (1) Compute ℓ and $\mathcal{M} = 2^{\lfloor \log_2 n \rfloor + 1} - 1$
- (2) Draw $x \in [0, 2^W)$ and compute $b = x \ \& \ \mathcal{M}$
- (3) Return b if $b < n$ else goto (2)

Efficiency

- b at most $\mathcal{M} = 2^{\lfloor \log_2 n \rfloor + 1} - 1 < 2n \quad \longrightarrow \quad$ success probability at least $\approx \frac{1}{2}$
- At most ≈ 2 rounds in expectation
- No integer division at all

The Bitmask Algorithm - Efficiency

Algorithm:

- (1) Compute ℓ and $\mathcal{M} = 2^{\lfloor \log_2 n \rfloor + 1} - 1$
- (2) Draw $x \in [0, 2^W)$ and compute $b = x \ \& \ \mathcal{M}$
- (3) Return b if $b < n$ else goto (2)

Efficiency

- b at most $\mathcal{M} = 2^{\lfloor \log_2 n \rfloor + 1} - 1 < 2n \rightarrow$ success probability at least $\approx \frac{1}{2}$
- At most ≈ 2 rounds in expectation
- No integer division at all
- Computation of leading 0's requires `clz` instruction/algorithm

The Bitmask Algorithm - Efficiency

Algorithm:

- (1) Compute ℓ and $\mathcal{M} = 2^{\lfloor \log_2 n \rfloor + 1} - 1$
- (2) Draw $x \in [0, 2^W)$ and compute $b = x \ \& \ \mathcal{M}$
- (3) Return b if $b < n$ else goto (2)

Efficiency

- b at most $\mathcal{M} = 2^{\lfloor \log_2 n \rfloor + 1} - 1 < 2n \rightarrow$ success probability at least $\approx \frac{1}{2}$
- At most ≈ 2 rounds in expectation
- No integer division at all
- Computation of leading 0's requires `clz` instruction/algorithm
- Roughly as expensive as a `div` instruction

Lemire's Algorithm



Multiply-And-Shift



Multiply-And-Shift

- Map `rand()` to $[0, n)$ divisionless with $(\text{rand}() \cdot n) \gg W$:



Multiply-And-Shift

- Map `rand()` to $[0, n)$ divisionless with $(\text{rand}() \cdot n) \gg W$:

$$(\text{rand}() \cdot n) \gg W$$



Multiply-And-Shift

- Map `rand()` to $[0, n)$ divisionless with $(\text{rand}() \cdot n) \gg W$:

$$(\text{rand}() \cdot n) \div 2^W$$



Multiply-And-Shift

- Map `rand()` to $[0, n)$ divisionless with $(\text{rand}() \cdot n) \gg W$:

$$\underbrace{(\text{rand}() \cdot n)}_{\in [0, 2^W)} \div 2^W$$



Multiply-And-Shift

- Map `rand()` to $[0, n)$ divisionless with $(\text{rand}() \cdot n) \gg W$:

$$\underbrace{(\text{rand}() \cdot n)}_{\in [0, n \cdot 2^W)} \div 2^W$$




Multiply-And-Shift

- Map `rand()` to $[0, n)$ divisionless with $(\text{rand}() \cdot n) \gg W$:

$$\underbrace{(\text{rand}() \cdot n)}_{\in [0, n \cdot 2^W)} \div 2^W$$

- $n < 2^W \implies n \cdot 2^W < 2^W \cdot 2^W = 2^{2W}$




Multiply-And-Shift

- Map `rand()` to $[0, n)$ divisionless with $(\text{rand}() \cdot n) \gg W$:

$$\underbrace{(\text{rand}() \cdot n)}_{\in [0, n \cdot 2^W)} \div 2^W$$

- $n < 2^W \implies n \cdot 2^W < 2^W \cdot 2^W = 2^{2W}$
- $2W$ bits enough to represent $\text{rand}() \cdot n$




Multiply-And-Shift

- Map `rand()` to $[0, n)$ divisionless with $(\text{rand}() \cdot n) \gg W$:

$$\underbrace{(\text{rand}() \cdot n) \div 2^W}_{\in [0, n)}$$

- $n < 2^W \implies n \cdot 2^W < 2^W \cdot 2^W = 2^{2W}$
- $2W$ bits enough to represent `rand()` · n



Multiply-And-Shift

- Map `rand()` to $[0, n)$ divisionless with $(\text{rand}() \cdot n) \gg W$:

$$\underbrace{(\text{rand}() \cdot n) \div 2^W}_{\in [0, n)}$$

- $n < 2^W \implies n \cdot 2^W < 2^W \cdot 2^W = 2^{2W}$
- $2W$ bits enough to represent $\text{rand}() \cdot n$

Is this uniform?

Multiply-And-Shift

- Map `rand()` to $[0, n)$ divisionless with $(\text{rand}() \cdot n) \gg W$:

$$\underbrace{(\text{rand}() \cdot n) \div 2^W}_{\in [0, n)}$$

- $n < 2^W \implies n \cdot 2^W < 2^W \cdot 2^W = 2^{2W}$
- $2W$ bits enough to represent $\text{rand}() \cdot n$

Is this uniform?

- Mapping is deterministic!

Multiply-And-Shift

- Map `rand()` to $[0, n)$ divisionless with $(\text{rand}() \cdot n) \gg W$:

$$\underbrace{(\text{rand}() \cdot n) \div 2^W}_{\in [0, n)}$$

- $n < 2^W \implies n \cdot 2^W < 2^W \cdot 2^W = 2^{2W}$
- $2W$ bits enough to represent `rand()` · n

Is this uniform?

- Mapping is deterministic!
- Mapping can **not** be uniform for all n !

The Algorithm - Intervals



The Algorithm - Intervals

- Split $[0, n \cdot 2^W)$ into intervals $[i \cdot 2^W, (i + 1) \cdot 2^W)$ for $i < n$



The Algorithm - Intervals

- Split $[0, n \cdot 2^W)$ into intervals $[i \cdot 2^W, (i + 1) \cdot 2^W)$ for $i < n$

$$\overbrace{0, \dots, 2^W - 1, \dots, i \cdot 2^W, \dots, (i + 1) \cdot 2^W - 1, \dots, (n - 1) \cdot 2^W, \dots, n \cdot 2^W - 1}^{n \cdot 2^W \text{ values}}$$

0^{th} interval
 mapped to 0 by $\gg W$

i^{th} interval
 mapped to i by $\gg W$

$(n - 1)^{\text{th}}$ interval
 mapped to $n - 1$ by $\gg W$

The Algorithm - Intervals

- Split $[0, n \cdot 2^W)$ into intervals $[i \cdot 2^W, (i + 1) \cdot 2^W)$ for $i < n$

$$\overbrace{0, \dots, 2^W - 1, \dots, i \cdot 2^W, \dots, (i + 1) \cdot 2^W - 1, \dots, (n - 1) \cdot 2^W, \dots, n \cdot 2^W - 1}^{n \cdot 2^W \text{ values}}$$

0^{th} interval
 mapped to 0 by $\gg W$

i^{th} interval
 mapped to i by $\gg W$

$(n - 1)^{\text{th}}$ interval
 mapped to $n - 1$ by $\gg W$

- Define the restricted i^{th} interval as $[i \cdot 2^W + \mathcal{R}, (i + 1) \cdot 2^W)$

The Algorithm - Intervals

- Split $[0, n \cdot 2^W)$ into intervals $[i \cdot 2^W, (i + 1) \cdot 2^W)$ for $i < n$

$$\overbrace{0, \dots, 2^W - 1, \dots, i \cdot 2^W, \dots, (i + 1) \cdot 2^W - 1, \dots, (n - 1) \cdot 2^W, \dots, n \cdot 2^W - 1}^{n \cdot 2^W \text{ values}}$$

$\underbrace{0, \dots, 2^W - 1}_{0^{\text{th}} \text{ interval}}$
 mapped to 0 by $\gg W$

$\underbrace{i \cdot 2^W, \dots, (i + 1) \cdot 2^W - 1}_{i^{\text{th}} \text{ interval}}$
 mapped to i by $\gg W$

$\underbrace{(n - 1) \cdot 2^W, \dots, n \cdot 2^W - 1}_{(n - 1)^{\text{th}} \text{ interval}}$
 mapped to $n - 1$ by $\gg W$

- Define the restricted i^{th} interval as $[i \cdot 2^W + \mathcal{R}, (i + 1) \cdot 2^W)$
- This interval has size

$$(i + 1) \cdot 2^W - (i \cdot 2^W + \mathcal{R}) = 2^W - \mathcal{R}$$

The Algorithm - Intervals

- Split $[0, n \cdot 2^W)$ into intervals $[i \cdot 2^W, (i + 1) \cdot 2^W)$ for $i < n$

$$\underbrace{0, \dots, 2^W - 1}_{\substack{0^{\text{th}} \text{ interval} \\ \text{mapped to } 0 \text{ by } \gg W}}, \dots, \underbrace{i \cdot 2^W, \dots, (i + 1) \cdot 2^W - 1}_{\substack{i^{\text{th}} \text{ interval} \\ \text{mapped to } i \text{ by } \gg W}}, \dots, \underbrace{(n - 1) \cdot 2^W, \dots, n \cdot 2^W - 1}_{\substack{(n - 1)^{\text{th}} \text{ interval} \\ \text{mapped to } n - 1 \text{ by } \gg W}}$$

$n \cdot 2^W$ values

- Define the restricted i^{th} interval as $[i \cdot 2^W + \mathcal{R}, (i + 1) \cdot 2^W)$
- This interval has size

$$(i + 1) \cdot 2^W - (i \cdot 2^W + \mathcal{R}) = 2^W - \mathcal{R}$$

which is divisible by n

The Algorithm - Intervals

- Split $[0, n \cdot 2^W)$ into intervals $[i \cdot 2^W, (i + 1) \cdot 2^W)$ for $i < n$

$$\overbrace{0, \dots, 2^W - 1, \dots, i \cdot 2^W, \dots, (i + 1) \cdot 2^W - 1, \dots, (n - 1) \cdot 2^W, \dots, n \cdot 2^W - 1}^{n \cdot 2^W \text{ values}}$$

0^{th} interval
 mapped to 0 by $\gg W$

i^{th} interval
 mapped to i by $\gg W$

$(n - 1)^{\text{th}}$ interval
 mapped to $n - 1$ by $\gg W$

- Define the restricted i^{th} interval as $[i \cdot 2^W + \mathcal{R}, (i + 1) \cdot 2^W)$
- This interval has size


$$(i + 1) \cdot 2^W - (i \cdot 2^W + \mathcal{R}) = 2^W - \mathcal{R}$$

which is divisible by n

- Every restricted i^{th} interval has $\frac{2^W - \mathcal{R}}{n} = \lfloor \frac{2^W}{n} \rfloor$ multiples of n

The Algorithm - Intervals

- Split $[0, n \cdot 2^W)$ into intervals $[i \cdot 2^W, (i + 1) \cdot 2^W)$ for $i < n$



- Define the **restricted** i^{th} interval as $[i \cdot 2^W + \mathcal{R}, (i + 1) \cdot 2^W)$
- This interval has size

$$(i + 1) \cdot 2^W - (i \cdot 2^W + \mathcal{R}) = 2^W - \mathcal{R}$$

which is divisible by n

- Every **restricted** i^{th} interval has $\frac{2^W - \mathcal{R}}{n} = \lfloor \frac{2^W}{n} \rfloor$ multiples of n
- We can make **Multiply-And-Shift** uniform by only accepting multiples of n in **restricted** intervals

The Algorithm - Rejection



The Algorithm - Rejection

When do we reject $x := \text{rand}() \cdot n$?

The Algorithm - Rejection

When do we reject $x := \text{rand}() \cdot n$?

- $x \in [i \cdot 2^W, i \cdot 2^W + \mathcal{R})$ for some $i < n$

The Algorithm - Rejection

When do we reject $x := \text{rand}() \cdot n$?

- $x \in [i \cdot 2^W, i \cdot 2^W + \mathcal{R})$ for some $i < n$
- Applying $x \bmod 2^W$ to any i^{th} interval yields

The Algorithm - Rejection

When do we reject $x := \text{rand}() \cdot n$?

- $x \in [i \cdot 2^W, i \cdot 2^W + \mathcal{R})$ for some $i < n$
- Applying $x \bmod 2^W$ to any i^{th} interval yields

$$\overbrace{0, 1, \dots, \mathcal{R} - 1, \mathcal{R}, \dots, n, \dots, 2^W - 1}^{2^W \text{ values}}$$

rejected part restricted i^{th} interval

The Algorithm - Rejection

When do we reject $x := \text{rand}() \cdot n$?

- $x \in [i \cdot 2^W, i \cdot 2^W + \mathcal{R})$ for some $i < n$
- Applying $x \bmod 2^W$ to any i^{th} interval yields

$$\overbrace{0, 1, \dots, \mathcal{R} - 1, \mathcal{R}, \dots, n, \dots, 2^W - 1}^{2^W \text{ values}}$$

$\underbrace{0, 1, \dots, \mathcal{R} - 1}_{\text{rejected part}}$

$\underbrace{\mathcal{R}, \dots, n, \dots, 2^W - 1}_{\text{restricted } i^{\text{th}} \text{ interval}}$

- We **reject** x if $x \bmod 2^W < \mathcal{R}$

The Algorithm - Sketch



The Algorithm - Sketch

```
1  $\mathcal{R} \leftarrow 2^W \bmod n$                                 /* Compute rejection threshold */
```



The Algorithm - Sketch

```
1  $\mathcal{R} \leftarrow 2^W \bmod n$                                 /* Compute rejection threshold */  
2 while true do
```



The Algorithm - Sketch

```
1  $\mathcal{R} \leftarrow 2^W \bmod n$                                 /* Compute rejection threshold */  
2 while true do  
3    $x \leftarrow \text{rand}()$ 
```

The Algorithm - Sketch

```
1  $\mathcal{R} \leftarrow 2^W \bmod n$                                 /* Compute rejection threshold */
2 while true do
3    $x \leftarrow \text{rand}()$ 
4    $m \leftarrow x \cdot n$                                 /* Use  $2W$  bits for representation */
```

The Algorithm - Sketch

```
1  $\mathcal{R} \leftarrow 2^W \bmod n$                                 /* Compute rejection threshold */
2 while true do
3    $x \leftarrow \text{rand}()$ 
4    $m \leftarrow x \cdot n$                                 /* Use  $2W$  bits for representation */
5    $l \leftarrow m \ \& \ (2^W - 1)$                         /*  $m \bmod 2^W$  */
```

The Algorithm - Sketch

```
1  $\mathcal{R} \leftarrow 2^W \bmod n$                                 /* Compute rejection threshold */
2 while true do
3    $x \leftarrow \text{rand}()$ 
4    $m \leftarrow x \cdot n$                                 /* Use  $2W$  bits for representation */
5    $l \leftarrow m \ \& \ (2^W - 1)$                         /*  $m \bmod 2^W$  */
6   if  $l \geq \mathcal{R}$  then                                     /* Apply rejection rule */
     |
     |
```

The Algorithm - Sketch

```
1  $\mathcal{R} \leftarrow 2^W \bmod n$                                 /* Compute rejection threshold */
2 while true do
3    $x \leftarrow \text{rand}()$ 
4    $m \leftarrow x \cdot n$                                 /* Use  $2W$  bits for representation */
5    $l \leftarrow m \ \& \ (2^W - 1)$                         /*  $m \bmod 2^W$  */
6   if  $l \geq \mathcal{R}$  then                                     /* Apply rejection rule */
7     return  $m \gg W$ 
```

The Algorithm - Avoiding Division



The Algorithm - Avoiding Division

Consider the **first** iteration of the loop:



The Algorithm - Avoiding Division

Consider the **first** iteration of the loop:

- We **reject** x if $l < \mathcal{R}$



The Algorithm - Avoiding Division

Consider the **first** iteration of the loop:

- We **reject** x if $l < \mathcal{R}$ \longrightarrow we need to compute \mathcal{R} beforehand



The Algorithm - Avoiding Division

Consider the **first** iteration of the loop:

- We **reject** x if $l < \mathcal{R} \quad \longrightarrow \quad$ we need to compute \mathcal{R} beforehand
- But we know $\mathcal{R} < n$



The Algorithm - Avoiding Division

Consider the **first** iteration of the loop:

- We **reject** x if $l < \mathcal{R}$ \longrightarrow we need to compute \mathcal{R} beforehand
- But we know $\mathcal{R} < n$ \longrightarrow if $l \geq n$ we do **not** need to know \mathcal{R}



The Algorithm - Avoiding Division

Consider the **first** iteration of the loop:

- We **reject** x if $l < \mathcal{R}$ \longrightarrow we need to compute \mathcal{R} beforehand
- But we know $\mathcal{R} < n$ \longrightarrow if $l \geq n$ we do **not** need to know \mathcal{R}

We can **alter** the **first** iteration of the loop:




The Algorithm - Avoiding Division

Consider the **first** iteration of the loop:

- We **reject** x if $l < \mathcal{R}$ \longrightarrow we need to compute \mathcal{R} beforehand
- But we know $\mathcal{R} < n$ \longrightarrow if $l \geq n$ we do **not** need to know \mathcal{R}

We can **alter** the **first** iteration of the loop:

- We do **not** compute \mathcal{R} beforehand



The Algorithm - Avoiding Division

Consider the **first** iteration of the loop:

- We **reject** x if $l < \mathcal{R}$ \longrightarrow we need to compute \mathcal{R} beforehand
- But we know $\mathcal{R} < n$ \longrightarrow if $l \geq n$ we do **not** need to know \mathcal{R}

We can **alter** the **first** iteration of the loop:

- We do **not** compute \mathcal{R} beforehand
- If $l \geq n$, we accept x without computing \mathcal{R}

The Algorithm - Avoiding Division

Consider the **first** iteration of the loop:

- We **reject** x if $l < \mathcal{R}$ \longrightarrow we need to compute \mathcal{R} beforehand
- But we know $\mathcal{R} < n$ \longrightarrow if $l \geq n$ we do **not** need to know \mathcal{R}

We can **alter** the **first** iteration of the loop:

- We do **not** compute \mathcal{R} beforehand
- If $l \geq n$, we accept x without computing \mathcal{R}
- If not, we compute \mathcal{R} and proceed as before

The Algorithm - Avoiding Division

Consider the **first** iteration of the loop:

- We **reject** x if $l < \mathcal{R}$ \longrightarrow we need to compute \mathcal{R} beforehand
- But we know $\mathcal{R} < n$ \longrightarrow if $l \geq n$ we do **not** need to know \mathcal{R}

We can **alter** the **first** iteration of the loop:

- We do **not** compute \mathcal{R} beforehand
- If $l \geq n$, we accept x without computing \mathcal{R}
- If not, we compute \mathcal{R} and proceed as before

With what probability do we need to compute \mathcal{R} :

The Algorithm - Avoiding Division

Consider the **first** iteration of the loop:

- We **reject** x if $l < \mathcal{R}$ \longrightarrow we need to compute \mathcal{R} beforehand
- But we know $\mathcal{R} < n$ \longrightarrow if $l \geq n$ we do **not** need to know \mathcal{R}

We can **alter** the **first** iteration of the loop:

- We do **not** compute \mathcal{R} beforehand
- If $l \geq n$, we accept x without computing \mathcal{R}
- If not, we compute \mathcal{R} and proceed as before

With what probability do we need to compute \mathcal{R} :

- We assume x to be uniform in $[0, 2^W)$

The Algorithm - Avoiding Division

Consider the **first** iteration of the loop:

- We **reject** x if $l < \mathcal{R}$ \longrightarrow we need to compute \mathcal{R} beforehand
- But we know $\mathcal{R} < n$ \longrightarrow if $l \geq n$ we do **not** need to know \mathcal{R}

We can **alter** the **first** iteration of the loop:

- We do **not** compute \mathcal{R} beforehand
- If $l \geq n$, we accept x without computing \mathcal{R}
- If not, we compute \mathcal{R} and proceed as before

With what probability do we need to compute \mathcal{R} :

- We assume x to be uniform in $[0, 2^W)$ \longrightarrow l is also uniform in $[0, 2^W)$

The Algorithm - Avoiding Division

Consider the **first** iteration of the loop:

- We **reject** x if $l < \mathcal{R}$ \longrightarrow we need to compute \mathcal{R} beforehand
- But we know $\mathcal{R} < n$ \longrightarrow if $l \geq n$ we do **not** need to know \mathcal{R}

We can **alter** the **first** iteration of the loop:

- We do **not** compute \mathcal{R} beforehand
- If $l \geq n$, we accept x without computing \mathcal{R}
- If not, we compute \mathcal{R} and proceed as before

With what probability do we need to compute \mathcal{R} :

- We assume x to be uniform in $[0, 2^W)$ \longrightarrow l is also uniform in $[0, 2^W)$
- We compute \mathcal{R} if $l < n$

The Algorithm - Avoiding Division

Consider the **first** iteration of the loop:

- We **reject** x if $l < \mathcal{R}$ \longrightarrow we need to compute \mathcal{R} beforehand
- But we know $\mathcal{R} < n$ \longrightarrow if $l \geq n$ we do **not** need to know \mathcal{R}

We can **alter** the **first** iteration of the loop:

- We do **not** compute \mathcal{R} beforehand
- If $l \geq n$, we accept x without computing \mathcal{R}
- If not, we compute \mathcal{R} and proceed as before

With what probability do we need to compute \mathcal{R} :


- We assume x to be uniform in $[0, 2^W)$ \longrightarrow l is also uniform in $[0, 2^W)$
- We compute \mathcal{R} if $l < n$ \longrightarrow happens with probability $\frac{n}{2^W}$

The Algorithm - Pseudocode




The Algorithm - Pseudocode

1 $x \leftarrow \text{rand}()$



The Algorithm - Pseudocode

```
1  $x \leftarrow \text{rand}()$   
2  $m \leftarrow x \cdot n$            /* Use  $2W$  bits for representation */
```



The Algorithm - Pseudocode

```
1  $x \leftarrow \text{rand}()$   
2  $m \leftarrow x \cdot n$                                 /* Use  $2W$  bits for representation */  
3  $l \leftarrow m \ \& \ (2^W - 1)$                   /*  $m \bmod 2^W$  */
```

The Algorithm - Pseudocode

```
1  $x \leftarrow \text{rand}()$   
2  $m \leftarrow x \cdot n$                                 /* Use  $2W$  bits for representation */  
3  $l \leftarrow m \ \& \ (2^W - 1)$                     /*  $m \bmod 2^W$  */  
4 if  $l < n$  then                                    /* Possibly skip division */
```

The Algorithm - Pseudocode

```
1  $x \leftarrow \text{rand}()$ 
2  $m \leftarrow x \cdot n$ 
3  $l \leftarrow m \ \& \ (2^W - 1)$ 
4 if  $l < n$  then
    |
    |
    |
10 return  $m \gg W$ 
```

/* Use $2W$ bits for representation */
/* $m \bmod 2^W$ */
/* Possibly skip division */

The Algorithm - Pseudocode

```
1  $x \leftarrow \text{rand}()$ 
2  $m \leftarrow x \cdot n$ 
3  $l \leftarrow m \ \& \ (2^W - 1)$ 
4 if  $l < n$  then
5      $\mathcal{R} \leftarrow 2^W \bmod n$ 
     $\text{/* Use } 2W \text{ bits for representation */}$ 
     $\text{/* } m \bmod 2^W \text{ */}$ 
     $\text{/* Possibly skip division */}$ 
     $\text{/* Compute rejection threshold */}$ 
10 return  $m \gg W$ 
```

The Algorithm - Pseudocode

```
1  $x \leftarrow \text{rand}()$ 
2  $m \leftarrow x \cdot n$ 
3  $l \leftarrow m \ \& \ (2^W - 1)$ 
4 if  $l < n$  then
5      $\mathcal{R} \leftarrow 2^W \bmod n$ 
6     while  $l < \mathcal{R}$  do
7          $l \leftarrow m \ \& \ (2^W - 1)$ 
8          $\mathcal{R} \leftarrow 2^W \bmod n$ 
9          $m \leftarrow x \cdot n$ 
10 return  $m \gg W$ 
```

/* Use $2W$ bits for representation */
/* $m \bmod 2^W$ */
/* Possibly skip division */
/* Compute rejection threshold */
/* Apply rejection rule */

The Algorithm - Pseudocode

```
1  $x \leftarrow \text{rand}()$ 
2  $m \leftarrow x \cdot n$ 
3  $l \leftarrow m \ \& \ (2^W - 1)$ 
4 if  $l < n$  then
5      $\mathcal{R} \leftarrow 2^W \bmod n$ 
6     while  $l < \mathcal{R}$  do
7          $x \leftarrow \text{rand}()$ 
8          $m \leftarrow x \cdot n$ 
9          $l \leftarrow m \ \& \ (2^W - 1)$ 
10 return  $m \gg W$ 
```

/* Use $2W$ bits for representation */
/* $m \bmod 2^W$ */
/* Possibly skip division */
/* Compute rejection threshold */
/* Apply rejection rule */

4 Summary



Summary

Summary



	expected number of integer division operations	maximum number of integer division operations	Unbiased?
--	--	---	-----------



	expected number of integer division operations	maximum number of integer division operations	Unbiased?
Modulo Reduction	1	1	X



	expected number of integer division operations	maximum number of integer division operations	Unbiased?
Modulo Reduction	1	1	X
Multiply-and-Shift	0	0	X

	expected number of integer division operations	maximum number of integer division operations	Unbiased?
Modulo Reduction	1	1	X
Multiply-and-Shift	0	0	X
OpenBSD	2	2	✓

	expected number of integer division operations	maximum number of integer division operations	Unbiased?
Modulo Reduction	1	1	✗
Multiply-and-Shift	0	0	✗
OpenBSD	2	2	✓
Java	$\frac{2^W}{2^W - \mathcal{R}}$	∞	✓

	expected number of integer division operations	maximum number of integer division operations	Unbiased?
Modulo Reduction	1	1	✗
Multiply-and-Shift	0	0	✗
OpenBSD	2	2	✓
Java	$\frac{2^W}{2^W - \mathcal{R}}$	∞	✓
Bitmask	0	0	✓

	expected number of integer division operations	maximum number of integer division operations	Unbiased?
Modulo Reduction	1	1	✗
Multiply-and-Shift	0	0	✗
OpenBSD	2	2	✓
Java	$\frac{2^W}{2^W - \mathcal{R}}$	∞	✓
Bitmask	0	0	✓
Lemire	$\frac{n}{2^W}$	1	✓

End of Talk

