Exercise 15_ThingSpeak

s214417 Lukas Schou

s214413 Christian Cederhorn

```
1   #include <ESP8266WiFi.h>
2   #include <ThingSpeak.h>
3
4   const char* ssid = "Lukas telefon";
5   const char* pass = "11111111";
6
7   WiFiClient client;
8
9   unsigned long channelID = 2397414;        //your TS channal
10  const char* APIKey = "7AK685PVDZJP7CLW";  //your TS API
11  const char* server = "api.thingspeak.com";
12  const int postDelay = 1 * 1000;  //post data every 20 seconds
13
14  void setup() {
15    Serial.begin(115200);
16    pinMode(D2, OUTPUT);
17    pinMode(D3, INPUT);
18    WiFi.begin(ssid, pass);
19  }
20
21  float data;  //measured data
22
23  void loop() {
24    digitalWrite(D2, LOW);
25    if (digitalRead(D2) == 1) {
26      data = 1;
27    }
28    else {
29      data = 0;
30    }
31
32    long rssi = WiFi.RSSI();
33
34    ThingSpeak.begin(client);
35    client.connect(server, 80);  //connect(URL, Port)
36
37    ThingSpeak.setField(1, data);            //set data on the X graph
38    ThingSpeak.setField(2, rssi);            //set data on the X graph
39    ThingSpeak.writeFields(channelID, APIKey);  //post everything to TS
40
41    //ThingSpeak.setField(2, data, rssi);          //set data on the X graph
42    //ThingSpeak.writeFields(channelID, APIKey);  //post everything to TS
43
44    client.stop();
45    delay(postDelay);  //wait and then post again
46  }
```