

Lab7

November 21, 2025

1 Lab 7

1.1 NN with Defined Distances

```
[1]: import numpy as np
      from sklearn.model_selection import train_test_split
      X = np.genfromtxt("ionosphere.txt", delimiter=",",
                        usecols=np.arange(34))
      y = np.genfromtxt("ionosphere.txt", delimiter=",",
                        usecols=34, dtype='int')
      X_train, X_test, y_train, y_test = train_test_split(X, y,
                                                          random_state=42)
```

```
[2]: from sklearn.neighbors import KNeighborsClassifier
      knn = KNeighborsClassifier(n_neighbors=1)
      knn.fit(X_train, y_train)
      KNeighborsClassifier(algorithm='auto', leaf_size=30,
                          metric='minkowski', metric_params=None, n_jobs=1,
                          n_neighbors=1, p=2, weights='uniform')
```

```
[2]: KNeighborsClassifier(n_jobs=1, n_neighbors=1)
```

```
[3]: np.mean(knn.predict(X_test) == y_test)
```

```
[3]: 0.8522727272727273
```

```
[4]: knn = KNeighborsClassifier(n_neighbors=1, p=1)
      knn.fit(X_train, y_train)
      np.mean(knn.predict(X_test)==y_test)
```

```
[4]: 0.9090909090909091
```

1.2 Kernel Methods

```
[5]: def poly_kernel(x, y, d):
      return (1+np.dot(x,y))**d

      d = 2
```

```
def poly_dist(x, y):
    return poly_kernel(x,x,d) + poly_kernel(y,y,d) - 2 * poly_kernel(x,y,d)

knn = KNeighborsClassifier(n_neighbors=1, metric=poly_dist)
knn.fit(X_train, y_train)
np.mean(knn.predict(X_test)==y_test)
```

[5]: 0.8522727272727273

```
[6]: def rbf_kernel(x, y, gamma):
    return np.exp(-gamma*np.sum((x-y)**2))

gamma = 1

def rbf_dist(x, y):
    return rbf_kernel(x,x,gamma) + rbf_kernel(y,y,gamma) - 2 *
    ↪rbf_kernel(x,y,gamma)

knn = KNeighborsClassifier(n_neighbors=1, metric=rbf_dist)
knn.fit(X_train, y_train)
np.mean(knn.predict(X_test)==y_test)
```

[6]: 0.8522727272727273

```
[7]: from sklearn.model_selection import cross_val_score
best_score = 0
for gamma in [0.01, 0.1, 1, 10, 100]:

    def rbf_dist(x, y):
        return rbf_kernel(x,x,gamma) + rbf_kernel(y,y,gamma) -
        ↪2*rbf_kernel(x,y,gamma)
    knn = KNeighborsClassifier(n_neighbors=1, metric=rbf_dist)

    scores = cross_val_score(knn, X_train, y_train, cv=5)
    score = np.mean(scores)

    if score > best_score:
        best_score = score
        best_gamma = gamma

def rbf_dist(x, y):
    return rbf_kernel(x,x,best_gamma) + rbf_kernel(y,y,best_gamma) -
    ↪2*rbf_kernel(x,y,best_gamma)

knn = KNeighborsClassifier(n_neighbors=1, metric=rbf_dist)
knn.fit(X_train, y_train)
test_score = knn.score(X_test, y_test)
```

```

print("Best CV score:", best_score)
print("Best parameter gamma:", best_gamma)
print("Test set score with best parameters:", test_score)

```

Best CV score: 0.9317851959361393

Best parameter gamma: 10

Test set score with best parameters: 0.9431818181818182

1.3 Custom Estimator

```

[8]: class My_Classifier(KNeighborsClassifier):
      """My first example of a classifier"""
      def __init__(self, n_neighbors=1):
          KNeighborsClassifier.__init__(self, n_neighbors=n_neighbors)
      def fit(self, X, y):
          KNeighborsClassifier.fit(self, X, y)
          return self
      def predict(self, X, y=None):
          return KNeighborsClassifier.predict(self, X)
      def score(self, X, y):
          return KNeighborsClassifier.score(self, X, y)

```

```

[9]: knn = My_Classifier()
      knn.fit(X_train, y_train)
      knn.score(X_test, y_test)

```

[9]: 0.8522727272727273

```

[10]: class rbfClassifier(KNeighborsClassifier):
       """Kernel K-nearest neighbours classifier"""
       def __init__(self, n_neighbors=1, gamma=1):
           def rbf_dist(x, y): # squared distance
               return rbf_kernel(x,x,gamma) + rbf_kernel(y,y,gamma) -
↪ 2*rbf_kernel(x,y,gamma)
           KNeighborsClassifier.__init__(self, n_neighbors=n_neighbors,
               metric=rbf_dist)
           self.gamma = gamma
           self.n_neighbors=n_neighbors
       def fit(self, X, y):
           KNeighborsClassifier.fit(self, X, y)
           return self
       def predict(self, X, y=None):
           return KNeighborsClassifier.predict(self, X)
       def score(self, X, y):
           return KNeighborsClassifier.score(self, X, y)

```

```
[11]: knn = rbfClassifier()
      knn.fit(X_train, y_train)
      knn.score(X_test, y_test)
```

```
[11]: 0.8522727272727273
```

```
[12]: from sklearn.datasets import load_iris

      iris = load_iris()
      X_train, X_test, y_train, y_test = train_test_split(iris.data,
      iris.target, random_state=42)
      knn = KNeighborsClassifier()
      knn.fit(X_train, y_train)
      knn.predict(X_test)
```

```
[12]: array([[1, 0, 2, 1, 1, 0, 1, 2, 1, 1, 2, 0, 0, 0, 0, 1, 2, 1, 1, 2, 0, 2,
      0, 2, 2, 2, 2, 2, 0, 0, 0, 0, 1, 0, 0, 2, 1, 0]])
```

```
[13]: knn.predict_proba(X_test)
```

```
[13]: array([[0. , 1. , 0. ],
      [1. , 0. , 0. ],
      [0. , 0. , 1. ],
      [0. , 1. , 0. ],
      [0. , 1. , 0. ],
      [1. , 0. , 0. ],
      [0. , 1. , 0. ],
      [0. , 0. , 1. ],
      [0. , 0.6, 0.4],
      [0. , 1. , 0. ],
      [0. , 0.2, 0.8],
      [1. , 0. , 0. ],
      [1. , 0. , 0. ],
      [1. , 0. , 0. ],
      [1. , 0. , 0. ],
      [0. , 0.8, 0.2],
      [0. , 0. , 1. ],
      [0. , 1. , 0. ],
      [0. , 1. , 0. ],
      [0. , 0. , 1. ],
      [1. , 0. , 0. ],
      [0. , 0.2, 0.8],
      [1. , 0. , 0. ],
      [0. , 0. , 1. ],
      [0. , 0. , 1. ],
      [0. , 0. , 1. ],
      [0. , 0. , 1. ]])
```

```
[0. , 0. , 1. ],  
[1. , 0. , 0. ],  
[1. , 0. , 0. ],  
[1. , 0. , 0. ],  
[1. , 0. , 0. ],  
[0. , 1. , 0. ],  
[1. , 0. , 0. ],  
[1. , 0. , 0. ],  
[0. , 0.4, 0.6],  
[0. , 1. , 0. ],  
[1. , 0. , 0. ]])
```