# Reliable Transport (Lab 2) Report

Luke Dickinson

2/22/2017

## 1   Introduction

TCP is one of the core protocols that make the Internet possible. Even through the TCP layer sits on top an unreliable layer, the IP layer, TCP can create a reliable connection between nodes on the Internet.Using Bene and TCP implemented, we are able to run these simulations. We simulate different situations using TCP to see how TCP will function in these cases. We will test networks which drop packets at different rates. We will examine the effects of fast retransmit in TCP. We will also simulate different window sizes to measure the effect it has on throughput and queueing delay.

## 2   Basic Tests

This section includes a network that consisting of 2 nodes. We set the bandwidth between the nodes to 10 Mbps, and set the propagation delay between the nodes to 10 ms. We use the TCP protocol to send a file.

### 2.1   First simulation of a two node network

For the first simulation, we use the network described above and set the window size to 3,000. We set out mss to 1,000. We send a file called "test.txt" of size 10,000 bytes from one node to the other. We test the following loss rates: 0%, 10%, 20%, 50%.

#### 2.1.1   First simulation of a two node network: 0%

This can be run with the following command: python lab2-basic-1.py -f test.txt -l 0.0

The last 10 lines output of this simulation is the following: 0.0532 application got 1000 bytes 0.0532 n2 (2) sending TCP ACK to 1 for 8000 0.054 n2 (2) received TCP segment from 1 for 8000 0.054 application got 1000 bytes 0.054 n2 (2) sending TCP ACK to 1 for 9000 0.0624 n1 (1) sending TCP segment to 2 for 9000 0.0732 n2 (2) received TCP segment from 1 for 9000 0.0732 application got 1000 bytes 0.0732 n2 (2) sending TCP ACK to 1 for 10000 Success! both files match

When we used a loss rate of 0%, test.txt was sent in 0.0732 seconds.

#### 2.1.2   First simulation of a two node network: 10%

This can be run with the following command: python lab2-basic-1.py -f test.txt -l 0.10

The last 10 lines output of this simulation is the following: 0.0532 application got 1000 bytes 0.0532 n2 (2) sending TCP ACK to 1 for 8000 0.054 n2 (2) received TCP segment from 1 for 8000 0.054 application got 1000 bytes 0.054 n2 (2) sending TCP ACK to 1 for 9000 0.0624 n1 (1) sending TCP segment to 2 for 9000 0.0732 n2 (2) received TCP segment from 1 for 9000 0.0732 application got 1000 bytes 0.0732 n2 (2) sending TCP ACK to 1 for 10000 Success! both files match

When we used a loss rate of 10%, test.txt was sent in also 0.0732 seconds. In this case, we didn't lose any packets, even though we had a 10% chance to lose each packet.

### 2.1.3 First simulation of a two node network: 20%

This can be run with the following command: python lab2-basic-1.py -f test.txt -l 0.20

The last 10 lines output of this simulation is the following: 4.094 n2 (2) sending TCP ACK to 1 for 9000 4.0948 n2 (2) received TCP segment from 1 for 9000 4.0948 application got 1000 bytes 4.0948 n2 (2) sending TCP ACK to 1 for 10000 5.0832 n1 (1) sending TCP segment to 2 for 9000 5.0832 n1 (1) retransmission timer fired 5.094 n2 (2) received TCP segment from 1 for 9000 5.094 application got 0 bytes 5.094 n2 (2) sending TCP ACK to 1 for 10000 Success! both files match

When we used a loss rate of 20%, test.txt was sent in 5.094 seconds. We can see multiple packets lost in a row (the ACK for 10,000 and then the packet 9,000) sometimes result in a timeout. These drasticly increase the time needed to send the entire file.

### 2.1.4 First simulation of a two node network: 50%

This can be run with the following command: python lab2-basic-1.py -f test.txt -l 0.50

The last 10 lines output of this simulation is the following: 21.0732 n2 (2) received TCP segment from 1 for 7000 21.0732 application got 0 bytes 21.0732 n2 (2) sending TCP ACK to 1 for 9000 21.0832 n1 (1) sending TCP segment to 2 for 9000 22.0832 n1 (1) sending TCP segment to 2 for 9000 22.0832 n1 (1) retransmission timer fired 22.094 n2 (2) received TCP segment from 1 for 9000 22.094 application got 1000 bytes 22.094 n2 (2) sending TCP ACK to 1 for 10000 Success! both files match

When we used a loss rate of 50%, test.txt was sent in 22.094 seconds. Similar to the simulation with 20% loss rate, this simulation has enough loss to result in a timeout. In addition, we can see that packet with sequence 7000 gets through, but the application gains 0 bytes. This is because packet with sequence 7000 had already gone through, but the ACK had been lost.

## 2.2 Second simulation of a two node network

For the second simulation, we use the network described above and set the window size to 10,000. We set out mss to 1,000. We send a file called "internet-architecture.pdf" of size 514,520 bytes from one node to the other. We test the following loss rates: 0%, 50%.

### 2.2.1 Second simulation of a two node network: 0%

This can be run with the following command: python lab2-basic-2.py -f internet-architecture.pdf -l 0.0

The last 10 lines output of this simulation is the following: 1.0732 n2 (2) received TCP segment from 1 for 512000 1.0732 application got 1000 bytes 1.0732 n2 (2) sending TCP ACK to 1 for 513000 1.074 n2 (2) received TCP segment from 1 for 513000 1.074 application got 1000 bytes 1.074 n2 (2) sending TCP ACK to 1 for 514000 1.074416 n2 (2) received TCP segment from 1 for 514000 1.074416 application got 520 bytes 1.074416 n2 (2) sending TCP ACK to 1 for 514520 Success! both files match

When we used a loss rate of 0%, internet-architecture.pdf was sent in 1.074416 seconds.

### 2.2.2 Second simulation of a two node network: 50%

This can be run with the following command: python lab2-basic-2.py -f internet-architecture.pdf -l 0.50

The last 10 lines output of this simulation is the following: 398.1016 n1 (1) sending TCP segment to 2 for 514000 398.112016 n2 (2) received TCP segment from 1 for 514000 398.112016 application got 520 bytes 398.112016 n2 (2) sending TCP ACK to 1 for 514520 399.1016 n1 (1) sending TCP segment to 2 for 514000 399.1016 n1 (1) retransmission timer fired 399.112016 n2 (2) received TCP segment from 1 for 514000 399.112016 application got 0 bytes 399.112016 n2 (2) sending TCP ACK to 1 for 514520 Success! both files match

When we used a loss rate of 50%, internet-architecture.pdf was sent in 399.1120 seconds. This is almost 400 times longer than with a 0% loss rate!

# 3 Fast Retransmit

In this section, we want to see the effect TCP's fast retransmit has on total transfer time. We will run a simulation once with fast transmit off, and once with fast transmit on.

We will use the same network as in the basic test section. We use a network that consists of 2 nodes. We set the bandwidth between the nodes to 10 Mbps, and set the propagation delay between the nodes to 10 ms. We set out mss to 1,000. We use the TCP protocol to send the "internet-architecture.pdf" file. We set the loss rate to 20%.

## 3.1 Fast Retransmit Simulation: off

This can be run with the following command: python lab2-fast-1.py -f internet-architecture.pdf -l 0.2

With fast transmit off, we run the simulation. The last 10 lines output of this simulation is the following:

68.978 n2 (2) received TCP segment from 1 for 511000 68.978 application got 2000 bytes 68.978 n2 (2) sending TCP ACK to 1 for 513000 68.9788 n2 (2) received TCP segment from 1 for 513000 68.9788 application got 1000 bytes 68.9788 n2 (2) sending TCP ACK to 1 for 514000 68.979216 n2 (2) received TCP segment from 1 for 514000 68.979216 application got 520 bytes 68.979216 n2 (2) sending TCP ACK to 1 for 514520 Success! both files match

With a loss rate of 20%, and when we did not use fast retransmit. internet-architecture.pdf was sent in 68.979216 seconds.

## 3.2 Fast Retransmit Simulation: on

This can be run with the following command: python lab2-fast-1.py -f internet-architecture.pdf -l 0.2 -r

With fast transmit on, we run the simulation. The last 10 lines output of this simulation is the following:

34.4084 n2 (2) sending TCP ACK to 1 for 512000 34.408816 n2 (2) received TCP segment from 1 for 514000 34.408816 application got 0 bytes 34.408816 n2 (2) sending TCP ACK to 1 for 512000 35.3976 n1 (1) sending TCP segment to 2 for 512000 35.3976 n1 (1) retransmission timer fired 35.4084 n2 (2) received TCP segment from 1 for 512000 35.4084 application got 2520 bytes 35.4084 n2 (2) sending TCP ACK to 1 for 514520 Success! both files match

With a loss rate of 20%, and when we did use fast retransmit. internet-architecture.pdf was sent in 35.4084 seconds. This is almost twice as fast than the simulation that did not use fast retransmit.

# 4 Experiments

In this section, we explore the effect the size of TCP's window size has on throughput and average queueing delay on our file transfer.

We will use the a similar network as in the previous sections. We use a network that consists of 2 nodes. We set the bandwidth between the nodes to 10 Mbps, and set the propagation delay between the nodes to 10 ms. We set out mss to 1,000. We also set the queue size to 100 packets. We use the TCP protocol to send the "internet-architecture.pdf" file. We set the loss rate to 0%.

To measure throughput, we take the file size and divide it by the time it takes for the file to completely transfer. We measure the average queueing delay by aggregating the total queueing delay experienced from every packet sent and dividing it by the total number of packets sent.

We will run our simulation 6 times, with the following windows sizes: 1,000, 2,000, 5,000, 10,000, 15,000, 20,000. It may be helpful to point out that because our mss is 1,000, a window size of 1,000 is a window size of 1 packet. This may be useful in understanding why there is no queueing delay.

In the graphs below, we graphed our experimental data.