

Nuclear Disarmament Verification

Aldridge, Barritt, Christodoulou, Lu,
Moors, Rajroop, Theodorou, Xiao,

Department of Physics and Astronomy,
University College London,
London WC1E 6BT,
United Kingdom

2012 March 06th

Executive summary

The Context

Why do we Verify? We verify to assure confidence. We have a declaration, our verification methods, and our confidence. If we are too intrusive with our verification methods there is the threat of the spread of proliferation information which could in turn lead to a breakdown of the declaration agreements alongside an increased risk of mass devastation. If the verification methods employed are too feeble, the uncertainty in the confidence will be high and inspectors may fail to detect anomalous behaviour in the hosts disarmament activities. This balance is known as the information barrier and it is spawn from the consideration of ratified treaties, the capabilities of the equipment and the feasibility of the procedure. The treaties outline what information should and shouldnt be shared with the inspectors; the equipment and procedure are the technological or economic constraints. *A chart of time, treaty and declaration information or disarmament rates, there should be an inflection at 2002 * Summers treaty review Nicks information barrier in the context of treaty Lukes weapon introduction Jacks confidence in verification

The Process

What do we verify? Lukes weapon introduction Nicks brief overview Ralphs dismantling process Valentinos chain of custody / Containment and surveillance of dismantlement Lukes Blending down

The Methods

How do we verify? Jenelles Passive detection; Gamma signature, Neutron signature Kaijians detection methods; Induced Gamma and Neutron signature Nicks Pit stuffing Lukes blending down

The Technology

What do we use to verify and how does it work? Valentinos Containment and surveillance / Ralphs review of tags and seals tech Kaijians detection methods Jenelles Passive detection Valentinos Muon Tomography

The Conclusion

(What are the Strengths weaknesses opportunities and threats?)

Final Summary

Contents

1	Introduction	3
2	Political Background	3
2.1	Treaties	3
2.2	Nick's Stuff	3
2.2.1	Information barrier	4
2.2.2	Design Elements	4
2.2.3	Ideas for conclusion	7
3	Overall Process	9
3.1	Dismantlement	9
3.1.1	Storage of Fissile materials/nuclear weapons	11
3.1.2	MPC+A, Material Protection Control and Accounting	11
3.2	Chain of Custody	11
3.2.1	Seals and Tags	12
3.2.2	Vulnerability of seals	13
3.2.3	Surveillance technologies	13
3.2.4	Vulnerability in chain of custody	14
4	Detection Schemes	15
4.1	Passive Detection	15
4.1.1	Gamma Ray Detection	16
4.1.2	Neutron Detection	17
4.1.3	Existing Detection Equipment	18
4.2	Active Detection	18
4.3	Muon Tomography	18
4.3.1	Cosmic Rays	18
4.3.2	Muons	19
4.3.3	Limitations of X-rays	20
4.3.4	Muon tomography concept	20
4.3.5	Simulations of muon tomography	21
4.3.6	Experimental results of muon tomography	24
4.3.7	Applications of muon tomography	27

1 Introduction


2 Political Background

2.1 Treaties

2.2 Nick's Stuff

The Verification process seeks to ensure consistency with declaration, and that disarmament has been achieved with a degree of irreversibility. The challenge facing proponents of Nuclear disarmament is to ensure that measures have been taken to safeguard against a Nuclear Weapon State attempting to cheat against the international agreements that have been put in place. The foundations for confidence are essentially built upon two key principles: Declaration and Verification. The interplay between the two is what establishes the iterative development towards Nuclear disarmament; because a more complete declaration can lead to greater confidence in the verification, and successful verification can lead to a decision to release a more complete declaration. However there is a third consideration that mediates between the two and also governs what should be done with the sensitive information that may emerge from the verification measurements – the “information barrier”; the foundations of which shall be discussed in section ??.

What do we verify? – Nicks brief overview Nuclear warhead dismantlement starts with the removal from warheads from the deployment areas to the storage areas. The warheads are then transported to the dismantlement facilities where the “Physics package” is removed and then stored to await further dismantlement. Lastly plutonium and Highly Enriched Uranium re-emerge in an unclassified form ready for final disposition.



[dismantlement process.png] [Fig ?? : accompanying text] [Global Fissile Material Report 2009: A Path to Nuclear Disarmament, IPFM Annual report, Acton et al., p67] Verification may take place at any point along this chain. A Nuclear Weapon State may declare numbers and types of weapons in storage sites for example, and it is the job of the inspector to confirm or refute this information. However inspectors do not enjoy the unrestricted right to freely examine the weapons; they must do so behind the veil of an information barrier because the act of inspection incurs the risk of spreading weapon information.

2.2.1 Information barrier

In support of several ratified and pending nuclear material control agreements, technical representatives from the US and Russia have recognised the necessity for assurances against the release of sensitive information to be put in place. The majority of these agreements involve storing nuclear materials and components from stockpile weapons within specially designed containers.

Strategies for monitoring the agreements include measuring the neutron and gamma radiation signature to verify declared attributes of the plutonium or HEU. If these measurements are accurate enough to serve for this verification purpose, then they are accurate enough to contain information about the design of the component being monitored. Subsequently safeguards have been designed to prevent the disclosure of that information. Hardware, software and procedural measures containing the sensitive data will only present the relevant results required for verification.


[Progress in Gamma Ray Measurement Information Barriers for Nuclear Material Transparency Monitoring”, Wolford and White, Lawrence Livermore National Laboratory Library, 2000] In the interest of transparent monitoring, inspectors may witness or perform restricted measurements on controlled items. The information barrier is designed to mitigate the intrusiveness of taking these measurements, and the proliferation knowledge it would pass on to the inspector. Wolford and White (2000) highlight three objectives that hardware, software, and human procedures should fulfill in order to be an effective information barrier: “Prevent the unintended release of sensitive information during an inspection; Display a simple but reliable and useful result to the inspector; Allow checks on the integrity of the internal operations not visible during an inspection.” However in applying the barrier, the person monitoring may lose the assurance that the internal operations proceeded as intended. Fortunately it can be shown that thoughtful design elements can help recover some of that lost assurance for the human operator.

2.2.2 Design Elements

An actual information barrier must be adapted to the measurement instrument it accompanies. However there are certain design elements that must be implemented no matter what type of measurement is being performed. The DOE-DOD information Barrier Working Group has provided guidance for 10 design bases which, when grouped into functional categories, fall into 3 top-level elements: “(1) A barrier to conceal the sensitive information gathered in a measurement, and from which the physical attributes of an inspected item are derived. This consists of some combination of hardware, software, and human procedures, and must work in both directions, shielding unintended signals originating both outside and inside the measurement system. (2) A simplified display that indicates clearly the selected results of the measurements as defined in the agreement, and nothing more. Accordingly, the display should be no more complex than is necessary to convey the result to the inspector. (3) Enough autonomy to compensate for the lack of a human operator, both in monitoring the measurement and in safeguarding the data. The instrument must assure the reliability of its own measurements as well as protect the data resident during an inspection. In the event of failure or signs of tampering, this mechanisms

should erase all traces of sensitive data from the instrument and halt the inspection.” [THE JOINT U.S. DOD-DOE INFORMATION BARRIER WORKING GROUP, Functional Requirements for Information Barriers, PNNL-13285, Pacific Northwest National Laboratory, Richland, WA, May 1999.]

How do we verify? – Nicks Pit stuffing ‘Pit-stuffing’ was developed at Los Alamos National Laboratory to ensure that warheads that had been internally evaluated to be unsafe would not accidentally go off. Pit-Stuffing makes it possible to disable thousands of nuclear warheads, quickly, cheaply, and irreversibly; in a verifiable manner.



[Pits.png Fig??] Figure 5.3. Storage arrangements for U.S. plutonium warhead “pits” at the Pantex warhead dismantlement facility in Amarillo, Texas.²¹⁷ [Global Fissile Material Report 2009: A Path to Nuclear Disarmament, IPFM Annual report, Acton et al., p71] Modern implosion-type nuclear weapons have a “pit” which is a hollow sphere of plutonium or highly-enriched uranium, with a tiny tube through which the tritium is passed into the hollow sphere. If an appropriate material is fed in through this small tube until the inside of the pit is stuffed, and the plutonium can no longer be compressed enough to reach the critical mass to sustain a nuclear chain reaction as it would encounter the fill on the way.

At Los Alamos there had been discussions as to what would be the most suitable material. Aluminium powder and epoxy were suggested, however powder could be made to fall back out the tube, and organic material within the vicinity of plutonium could trigger chemical radiations and thus threaten the safety.

The best considered option is to use bits of metal wire that are shaped so that they cannot be removed via the fill tube. If this were achieved the only way to make the weapon functional again would be to dismantle it, remove the pit and cut it open to take the wire out; then remanufacture the pit and reassemble the weapon. This would be an expensive process, especially compared to the minimal time it takes to fill the pit. The physical act of stuffing the pit would about a minute; therefore a single inspection visit could be very productive, even if additional time is spent carrying out necessary safety procedures. Verifying

that the pit had indeed been filled could be confirmed by incorporating micro-curie quantities of cobalt-60 in the stuffing wire. One set of gamma-ray counters aligned to view the pit from one side would give a few simultaneous counts with another gamma-ray detector orientated in a perpendicular direction. This is because cobalt-60 gives two simultaneous high-energy gamma rays. Such measurements could not be mimicked by gamma-ray sources that are not in the interior of the pit. [R. Garwin, Technologies and procedures for verifying warhead status and dismantlement, Transparency in Nuclear Warheads and Materials: The Political and Technical Dimensions edited by Nicholas Zarimpas, 2001] However further measures may have to be taken against the host merely inserting minimal amounts of cobalt-60 without inserting the wire, or semi-inserting the wire with a view to remove it after the inspection. Also because pit-stuffing depends on certain details of warhead design and fabrication, it might not be an approach that can be administered entirely blindly.

The practicalities of this approach are encouraging for the cause of verified dismantlement because of the speed and minimal cost. The intrusiveness in principle could be low, if there was assurance that the wire had been inserted and could not be removed. The host could then be free to complete the dismantlement in privacy, removing the need for foreign verification during transportation which is currently a considerable expense.

After the dismantlement, the inspectors would return and be shown the canisters containing the stuffed pits. Again a gamma-ray spectrum could confirm that the containers enclosed hollow spheres of plutonium stuffed with wire. The inspector could be very confident that these were the same pits observed before the dismantlement as it would be very expensive and cumbersome to manufacture thousands of hollow plutonium spheres stuffed with wire.

[‘Pit-Stuffing’: How to Disable Thousands of Warheads and Easily Verify Their Dismantlement, Bunn, Federation of American Scientists Public Interest Report, volume 51, issue 2, pages 3-5, 1998] This method would work for US warheads, but needs to be evaluated for Russian warheads that may have a different design. [R. Garwin, Technologies and procedures for verifying warhead status and dismantlement, Transparency in Nuclear Warheads and Materials: The Political and Technical Dimensions edited by Nicholas Zarimpas, 2001] However pit-stuffing as a verification technique might not get its opportunity to be utilised because of the asymmetry between the sensitivity of classified items between Russia and the US. The years 2000-2002 saw dramatic global change, including the changing of American and Russian leaders. This meant that the enthusiasm for implementing Initiatives negotiated in the late 1990s was not sustained. The Russian Federation decided that it would melt its pits into 2-kilogram balls and pack two plutonium balls into each specialized AT-400R container before submitting the material for U.S. or IAEA verification. The US and Japan provided AT-400Rs are the standard containers designed for Russia’s Mayak Fissile Material Storage facility. Russia maintained that the isotopic composition of its weapon plutonium in the 2-kg balls was classified. [Global Fissile Material Report 2008, p. 70]

Although political decisions on declarations might stand in the way of pit-stuffing as a universal verification technique, further work* could be done to address some of the technical issues discussed as it could prove to be a useful tool to verify the US.

*(perhaps similar to the UK Norway Initiative Workshop on Nuclear Dis-

armament Verification 7-9 December 2011) Example: Information Barrier for Gamma Ray Measurements Gamma ray measurements can infer a lot of information about the object being measured including, constituents abundances, a lower bound for the masses, and the amount of intervening material. Also in a neutron-emitting source such as plutonium, the presence of other elements can be inferred from the evidence of activation products. Clearly much of this information lies outside that demanded of transparency agreements and fortunately a full spectrum is not required to derive the most useful attributes.

Programmers have an opportunity to protect most of the information. At LLNL software was created that used plutonium lines between 630 KeV and 670 KeV to compute a ratio of ^{240}Pu to ^{239}Pu which distinguishes weapon-grade plutonium from non-weapon grade. The tool, called Pu600, was adapted and enhanced for the requirements of the Trilateral Initiative and the FMTT program. Programmers at LLNL developed similar methods called Pu300 for determining the time since separation, and Pu900 for determining the amount of oxide present in a sample.

[Progress in Gamma Ray Measurement Information Barriers for Nuclear Material Transparency Monitoring”, Wolford and White, Lawrence Livermore National Laboratory Library, 2000] [Fig??: The gamma ray spectrum for a non-sensitive sample of plutonium containing several isotopes and decay products. The three narrow intervals of spectral lines are what is used in the attribute calculations Pu 300, Pu600 and Pu900.]

2.2.3 Ideas for conclusion

The United States has stated the need to protect the host’s warhead design information overrules the need to provide confidence to the inspecting party regarding the accuracy and reproducibility of the measurements; in case an inspection is carried out in the absence of any agreement to share classified nuclear weapon design.

We could recommend that this shouldn’t be the case for Non-Nuclear weapons states like Iran, where their proliferation information is obviously less developed than that of the US or Russia. Talking about info barrier.. The greatest potential for improvement in the transition from generic laboratory instrumentation to more special purpose inspection equipment, and the greatest challenge is to move away from stored programs and microprocessors towards pure hardware solutions. The technology of information barriers is primitive compared to the technology of radiation detection and data reduction. Nevertheless, relatively simple systems such as those described above and in the references have provided sufficient assurance to sustain negotiations. The specific implementation of an information barrier system will depend on the requirements of the inspection regime. Nevertheless the three elements introduced here will always form its basis. More specific design influences include decisions about equipment origin and custody and the number and type of physical attributes to be collected. [Progress in Gamma Ray Measurement Information Barriers for Nuclear Material Transparency Monitoring”, Wolford and White, Lawrence Livermore National Laboratory Library, 2000]

The treaty should challenge the Host facility to demonstrate compliance: Change the emphasis of the verification procedure. Consider that a Nuclear Weapon State intends to cheat the disarmament agreements that are in place.





Figure 2. Plot of the gamma ray spectrum from a non-sensitive sample. The details illustrate the relatively weak spectral lines used in the attribute calculations known as Pu300, (courtesy of Thomas B. Gosnell, LLNL.)

“Winning” if they manage to fool the inspector. However if the onus were on host, it would be their duty to convince the inspector they are abiding by the agreements; for the cheat winning would be managing to convince the inspector. This approach addresses the underlying psychology between inspector and host facility more positively.

3 Overall Process

3.1 Dismantlement

Joint exercise between UK and Norway describes a possible dismantlement and verification process, conducted near Oslo in 2009. Cobalt 60 sample used to mimic physics package. A single nuclear weapon was moved into a dismantlement facility, where screwdrivers are used to open a side panel and remove the physics package. It is placed in a separate container. Everyone entering or leaving the dismantlement room is checked for radioactive material. Inspectors then confirm that radioactive material is present in the container. It is stored overnight in a sealed room with cctv. Seals used on items are low tech. The doors on the overnight storage room had a purple adhesive down the hinge which would change colour if disturbed. The adhesive strip itself is identifiable with a cluster of glitter suspended in transparent glue. On application and removal of the adhesive strip, this glue tag is photographed to check it has not been replaced, the exact configuration of suspended pieces of glitter would be near impossible to replicate. A simple technology like this seems to provide a reliable way of detecting tampering with a door or package seal. The following day the physics package would be moved to the “hot cell” where it would be dismantled. Using an “information barrier” device, the amount of material in the package can be measured without revealing the quantity to the inspectors. It gives a green light if the result was the same as the last measurement. Both countries independently developed and built their own detector. Using this method the package can be inspected at multiply points to insure no material has been siphoned off. Once the weapon has been dismantled the nuclear material is taken away for storage.[1]



The magazine transparency system is a proposed method of storage to monitor and maintain the inventory of a “magazine”, a storage area containing nuclear warheads or nuclear fissile materials during dismantlement verification

operations.




Figure 1: A schematic of the Magazine Transparency System (MTS) showing the primary components.

A system like this has been demonstrated at the Pantex dismantlement facility in Texas. The weapon itself has only passive tags and seals placed upon it to eliminate problems associated with battery life. The MagTag blanket is simply a tarp containing permanent magnets in random orientations, so as to make it unique. The system has a high resolution magnetometer to detect changes in the position or characteristics of the blanket. The bar-code reader records the bar-code on the seal of each container when the magazine is emptied or filled. this data is stored on an integrated notebook computer which can transmit to a central monitoring station. The RF receiver transmits the unique RF tag number on each weapon/storage vessel to the notebook. Low light video cameras also send video straight to the notebook for processing. With all of this information, Gauss readings, video, RF tag etc... the notebook computer sends

an “all ok” signal once every second assuming no anomalous activity is detected from any of the sensors. The notebook computer records no Non Proliferation treaty sensitive information. In the event of anomalous activity in an MTS during disarmament verification operations, the notebook is immediately given to the inspectors who can determine what kind of activity took place. [2]

Many weapons are dismantled without foreign verification by nuclear weapon states. This is done to reduce the size of the stockpile or to dispose of older outdated weapons. In the US, the national nuclear security administration (NNSA) is “responsible for the management and security of the nations nuclear weapons, nuclear nonproliferation, and naval reactor programs” [2] Part of this management is weapon dismantlement. design laboratory’s work with production facilities to identify and mitigate any risks associated with dismantling a particular design of weapon. A plan is formulated to safely dismantle the weapon and it is taken to the Pantex Plant in Texas. The time required to dismantle a warhead ranges from “a few days to a few weeks” depending on the complexity of the design.[3] With the weapon dismantled, the high explosives and other non-nuclear materials are processed on site at Pantex and a few other facilities. The special nuclear materials are then dismantled at the Y-12 National Security Complex. [4] Here nuclear materials are down blended to reduce the enrichment and render the uranium useless for military application. Down blended uranium is then used to fuel nuclear power plants. According to the department of energy 10% of the electricity used in the United States is produced using former Russian nuclear weapons.[5] Uranium “pits” that are not down blended can be stored in a “sealed insert” system. Leak-tight stainless steel vessels are placed into steel storage over pack drums.

3.1.1 Storage of Fissile materials/nuclear weapons

Assuming confidence in the dismantlement of a warhead, for real progress to made storage is equally important. Nuclear weapon fissile materials need to be stored under international or bilateral monitoring, to prevent the construction of new weapons and also safeguard against theft.

3.1.2 MPC+A, Material Protection Control and Accounting

This program is an example of bilateral efforts to safely and securely store nuclear materials. Funded initially by the DOD and then by the DOE, its goal was to improve security on hundreds of buildings at 40 sites in Russia to prevent theft or loss of nuclear materials. 600 tons of material was found to be at “risk”. in 2001, a report detailed that so far 81 buildings housing 81 tons of fissile material had received upgraded security systems. In 1998 the program was predicted to finish upgrading the storage facility’s by 2020. [6]

3.2 Chain of Custody

Chain of custody refers to the system of routines used to provide a high confidence level that a nuclear warhead will be delivered from its field deployment or storage location to the dismantlement facility and that the recovered nuclear material will be monitored until its disposition to make sure that it will not be reused [1]. Chain of custody includes the use of photography (X-ray or

gamma ray images, optical pictures), seals and tags, visual surveillance or video, warhead authentication (detection and confirmation of nuclear or non-nuclear warhead) and information processing (data transmission and relay, data compression, encryption and decryption etc.). There are two categories of chain of custody: limited chain of custody of a specific dismantlement facility and full range chain of custody with continuous knowledge of the disarmament process and the total number of nuclear warheads. [2]

3.2.1 Seals and Tags

A tag is a unique characteristic ('fingerprint') of an object or container that is used to unambiguously identify it. A seal or tamper-indicating device is a device or material that records unauthorised access and leaves inerasable evidence behind. There are two categories of modern seals: passive and active. Passive seals do not need electrical power to work and they are inexpensive but they can only be used once. Active or dynamic seals require electrical power to work, either internally or externally. They are more expensive than passive seals but they are typically reusable. [3]

Seals used in verification of nuclear disarmament need some unique attributes such as transparency and negotiability. If the inspected facility provides and controls the seals, then the inspectors will be suspicious and think that the seals have been tampered with. If the inspectors provide and control the seals, then the inspected facility will worry about espionage devices such as microphones being embedded in the seals. High tech electronic seals could be less comfortable to both parties due to tampering, safety and espionage concerns. Also some weapon containers cannot accommodate extra seals so the seals for nuclear disarmament will have to coexist with seals for safeguards and internal security. [3]

Current technologies and technologies under development: [1] Reflective Particle Tags (RPT): Reflective particles are mixed into glue that is applied to the object being tagged. If the tag is illuminated by a point light source, particle reflections form a unique pattern to that tag and incident angle. A tag reader records the pattern of individual pictures using a camera and forms a set of fingerprints unique to that tag. The object can be uniquely identified by reading its tag. [4] Ultrasonic Intrinsic Tags (UIT): A sample is scanned ultrasonically and a hand-held scanner collects sub-surface structure data. A computer performs the alignment and correlation functions. These tags are resistant to surface changes and counterfeit. Surface feature tags: A unique fingerprint of an item by examining its surface using scanning electron microscopy, holographic interferometry and micro-videography. Shrink-wrap seals: They consist of a plastic film that shrinks tightly around the safeguarded object. A unique pattern is produced by multiple layers of geometrically patterned film and its photographed for verification. VACOSS fibre optic seal: The first IEAE electronic seal which consists of a loop of fibre optic cable that is actively checked for integrity by the seals electronic system. Remote reading of the seal is also possible. They are no longer supported by the manufacturer and are being replaced by the EOSS seal which is more secure. [5] Electronic Optical Sealing System (EOSS): It is intended for long duration surveillance with high reliability. It uses a seal for enhanced authentication, smart power management system, tamper indication and encryption. A tamper indicating enclosure protects the electronics and a

microwave foil protects the complete housing against drilling. It can be coupled with surveillance systems and can be remotely interrogated. [5] Cobra seals: Consist of a loop of fibre optic cable and a polycarbonate sealing body. A unique light pattern is created when a blade cuts the cable. The Cobra seal reader photographically records this unique pattern and uses it for future comparison. E-type cup wire loop seals: Consist of two metal cups which snap together and cover the crimped ends of a wire loop. The inside of the cups is covered with melted solder and is scratched to create a unique pattern that is recorded for future comparisons. E-tag mechanical seals: Similar to E-type cup wire loop seals but also contain an electronic chip that contains a unique identification number that can be verified without opening the seal. Pressure-sensitive adhesive seals: Use pressure-sensitive adhesives to attach fragile labels to an object. Unique reflective patterns are created by microscopic glass beads. T-1 radio-frequency seals and tags: Consist of a fibre optic seal, case tamper switches, motion detector and low and high temperature indicators. Acoustic tags: Based on the unique resonant properties of an object when scanned using sound waves of a specific frequency. Radio-frequency (RF) tags: Emit a unique identification number and can be scanned using a radio-frequency device. VNI-IEF smart bolts: A small reader is used to read the unique electrical properties and the digital identification of the seal. The electrical properties of the bolt change if its unscrewed and that indicates tampering.

3.2.2 Vulnerability of seals

All seals appear to be vulnerable to simple, rapid, low tech attacks. Attacking a seal means to trying to gain access to whatever the seal is protecting without being detected. Defeating a seal means opening the seal without being detected or leaving evidence of entry, or repairing any damage and erasing evidence of entry, or replacing the entire seal or parts of it with counterfeits. The most comprehensive seal vulnerability study has been undertaken by the Vulnerability Assessment Team (VAT) at the Los Alamos National Laboratory. They analysed 94 different seals and defeated them for a total of 132 defeats. All of the defeats were implemented using low tech attacks with tools and supplies that in some cases can be easily carried in a persons pockets. The time taken for successful attacks varied from 3 seconds for several seals to 125 min for the most difficult seals. The mean time taken to complete the 132 defeats was 4.3 min and the mean cost of the defeats was \$56. [6]

3.2.3 Surveillance technologies

Surveillance is another important element in the chain of custody and comprehensive surveillance can also increase the security status of the monitored nuclear warheads. Comprehensive surveillance provides a high confidence in the dismantlement process and establishes mutual trust between the involved countries. Comprehensive surveillance combined with seals and tags can constitute an in depth inspection system. Several technologies can be used for comprehensive surveillance such as video monitoring, sensor monitoring, photograph comparing, intrusion detection and satellite imaging. [2]

Video monitoring is widely used in international safeguards and domestic security and it plays an important role in preventing illegal activities and prov-

ing treaty compliant activities. It is one of the most widely used containment and surveillance techniques by the IAEA. [2] Modern digital imaging used by the IAEA includes single camera digital surveillance units such as the All-in-one System (ALIS), All-in-one Portable System (ALIP), Digital Single Camera Optical Surveillance System (DSOS) and multi-camera digital surveillance systems such as the Server Digital Image Surveillance System (SDIS) and the Digital Multi-camera Optical Surveillance System (DMOS). These systems were developed to replace aging videotape based systems and the SDIS can be used for remote and unattended operation. The General Advanced Review Station Software (GARS) was developed to review all digital image surveillance records of the IAEA using a desktop computer. [7] The newest system is the Next Generation of Surveillance System (NGSS) and it will be used in 2012. It is scalable to any number of cameras, has solid state storage media, low power consumption, advanced security features and is highly reliable under harsh environmental conditions. It can be configured as a single all in one camera system or as a scalable multi-camera system. It supports various trigger signals from electronic seals and sensors, high resolution and coloured images, remote monitoring and picture taking rates of one image per second. Four different fields of view can be recorded simultaneously by a single NGSS camera. [5]

Sensor monitoring is another effective method used to track and authenticate nuclear warheads. Various sensors such as motion/acceleration, weight, acoustic, radioactive, magnetic, thermal, temperature/humidity, impact force sensitive and vibration sensors can be combined to monitor nuclear warhead reduction and provide a high confidence. Most of these sensors are commercially available and can be used in an integrated monitoring system which is easy to understand, technically transparent and applicable by all parties. [2]

Photograph comparing is used to carefully examine recorded images of the objects being monitored and detect tamper activities. Drawing random marks or images near the monitored object and then photograph it from all angles can enhance the photograph comparing method. It can easily raise disputes because it requires specific interpretation, either algorithmic or artificial, and the picture taking process can be also affected by environmental elements so it is never used on its own. It is often embedded into tamper-indicating monitoring methods and used as a complimentary technique in nuclear disarmament. [2]

Intrusion detection is used in guarding nuclear warheads and uses microwave, capacity sensitive, weight detection, infrared beam and motion/acceleration sensors to detect unauthorised access. The technologies and intrusion detection methods are being continuously developed to increase the efficiency and reliability of intrusion detection. [2]

Satellite imaging is used to detect change of large facilities or objects and requires advanced space and electronic sensor technologies. It can integrate visual, multi-spectra, synthesized aperture radar (SAR), thermal/infrared and other photographic technologies into a comprehensive system to provide a meaning full picture of a specific area or object. [2]

3.2.4 Vulnerability in chain of custody

The Vulnerability Assessment Team (VAT) at the Los Alamos National Laboratory has extensively researched issues associated with nuclear safeguards in the areas of transport security, intrusion detection and vulnerability assessments.



Figure 2: Picture of the Next Generation of Surveillance System (NGSS) with 24 cameras [5].

4 Detection Schemes

4.1 Passive Detection

Nuclear warhead detectability is reliant upon 4 factors. These factors are: the warhead design, the technique used for detection, the sensitivity of the detectors, and any material between the warhead and detector that functions as a shield for the radiation. [1]

In order for detectors to accurately identify special nuclear material (SNM), they need to be able to accurately isolate the true signal (for example, the gamma ray spectrum) from noise (background radiation). That is, the detector needs to have a high signal-to-noise ratio. A detectors ability to obtain a true signal depends on its efficiency and spectral resolution.[2]

The efficiency of a detector is a measure of its ability to detect radiation and the rate at which the detector is able to record data. [2][3]. SNM emits radiation in all directions; however its intensity decreases with distance. Therefore, to improve efficiency, the detector should be large or close to the SNM. It should

also record data as fast as possible so as to reduce the time spent waiting for the scan to take place. [2]

Spectral resolution describes the sharpness of peaks in a gamma ray spectrum. Since a radioactive isotope releases radiation at certain energies, an ideal detector would record the spectrum as vertical lines corresponding to those energies. However, detectors are not ideal, thus the energy is recorded as a bell shaped curve. The closer the curve is to a vertical line, the more beneficial the data is. [2]

The features of materials which allow them to be detected or identified are:

1. Atomic Number and Density: The atomic number (Z) is the number of protons in the nucleus of the atom; it is unique to every element. Density is described as mass per unit volume. Plutonium has an atomic number which is slightly higher than uranium but its density varies from slightly more to slightly less than uranium [2].
2. Radioactivity: Atoms which are radioactive are unstable and give off different types of radiation in order to become stable. The types of radiation used in nuclear detection are gamma rays and neutrons [2]. Gamma ray spectra are unique to each isotope, thus, it is fairly easy to determine the radiation that is emitted from an isotope.
3. Photon Opacity: The impenetrability of a material to a photon beam depends on three things: the amount of material presented to the path of the beam, the energy of the photons and the atomic number and density of the material. Gamma rays are able to travel through low Z materials without any problems, however, high Z materials absorb and deflect them. On the other hand, neutrons are able to pass easily through high Z materials but are absorbed and scattered by low Z materials.

4.1.1 Gamma Ray Detection

Gamma rays are produced from within the nuclei of radioactive atoms. [3] To detect gamma rays, a scintillation detector is used. A scintillation detector consists of a scintillator and photomultiplier tube (PMT). A scintillator is a material which converts the energy deposited by the gamma ray into optical photons (pulses of visible light). The optical photons are picked up by the PMT which has two functions: conversion of the optical photons into an electrical signal and amplification of the signal so that it can be measured. The PMT consists of a photocathode, dynodes and an anode. The photocathode emits electrons when struck by the optical photons. The electrons are attracted to the first dynode which amplifies the electrons into more electrons that are then accelerated to the second dynode which produces even more electrons, and the process continues until the electrons reach the anode. This is done so that a measurable current pulse can be detected. The voltage of the current pulse is proportional to the number of low energy photons which in turn is proportional to the energy of the gamma ray. Each pulse height produced from the PMT is analysed by a device called a Multi-Channel Analyser (MCA). When the MCA receives a voltage pulse, it sorts it into a bin depending on the energy and increases the counts in that particular bin by one. A histogram representing the gamma ray spectrum of an isotope is then drawn based on the information in the different bins. [2][3]

(FIGURE 1: PICTURE OF A SCINTILLATION DETECTOR)

An alternative detector which can be used to measure gamma rays is a semi-

conductor detector. A voltage is placed between two terminals on opposite sides of the semiconductor crystal. [3] When a gamma ray strikes the crystal, its energy is given to the electron which is then able to escape from the crystal. The electron is then attracted to the positive electrode. When enough electrons are able to escape from the crystal, a current will flow. The electric current has a voltage proportional to the energy of the gamma ray. The voltage is then sorted into a bin in the same way as the scintillation detector. [2][3]

(FIGURE 2: PICTURE OF A NEUTRON DETECTOR)

4.1.2 Neutron Detection

Neutrons are uncharged particles. To detect neutrons, helium-3, an isotope of helium is a good material to use. A tube consisting of helium-3 gas linked to a power supply is a conventional neutron detector. The tube contains charged plated or wires that are positive and negative. When a low energy neutron strikes the detector, it is absorbed by a helium-3 atom. Energetic charged particles are then produced which lose their energy by knocking off other helium-3 atoms. Positively charged particles are attracted to the negative plate and the electrons are attracted to the positive plate. This movement causes a small electric current to be generated which is then recorded. Neutron detection cannot be used to identify isotopes because they do not have characteristic lines that correspond to discrete energies and they lose energy as they interact with a low Z-material, thus their spectra is blurred. [3]

There are two techniques used for detection. These are passive and active detection. The simplest detection method is passive detection which involves detecting any and all radiation (gamma rays and neutrons) that are spontaneously emitted by the warhead. [1] The advantages of passive detectors are they require less electrical output, they are not very expensive, they are easy to build and do not add any additional health risks to workers. However, they are not without their disadvantages. The major disadvantage is that the signal emitted from a nuclear warhead needs to be greater than the background signal in order for it to be recognised. As a result, there is a very good chance that passive detection systems can easily be fooled if the radioactive material is shielded to prevent measureable amounts of radiation from reaching the detector [4]

The passive methods that are used to detect the presence of plutonium depend on the emission of both neutrons and gamma rays from its isotopes. The gamma rays emitted from the plutonium isotope are of relatively low energy and attenuate greatly as they travel through the warhead, thus gamma ray detection is not a reliable method to use. The best technique to use is to look for neutrons emitted by the plutonium-240 (Pu-240) isotope. The fissile isotope of plutonium is plutonium-239 (Pu-239); however, Pu-240 is active also [5]. This isotope spontaneously fissions and typically emits about 106 neutrons per second with a characteristic energy of 1 MeV [5]. In spite of the attenuation that these neutrons undergo as they travel through the warhead, approximately 10% emerge from the weapon and can be detected. It has been estimated that a warhead containing 4kg of Pu-239 contaminated by 6% of Pu-240 could reliably be detected with a detector 1m from the warhead in only 1 second [5]. The most important advantage of using this method is that a well-defined image of the warhead is not observed because the neutrons are scattered repeatedly as they travel through the weapon to the outside, thus only the grainiest geomet-

rical information is revealed. [5][6]. A drawback of using this method is that the emerging neutrons can be shielded without any difficulty. These factors suggest that this neutron detection technique is best used in examinations in which nuclear material is expected to be present, for example, to verify that the warheads earmarked to be dismantled are indeed nuclear.

The passive detection of uranium can be carried out by measuring the high energy gamma rays that are emitted from the uranium-238 (U-238) isotope. U-238 emits about 1MeV hard gamma rays at the rate of about 7.5 per gram per second with 1MeV energy [5]. Depleted uranium (almost all U-238) also emits gamma rays at this rate but HEU emits gammas at a rate of 0.5 gammas per gram-second with 1MeV energy. The amount of depleted uranium and HEU determines the amount of gamma rays escaping from the warhead. When a simple model of a nuclear warhead is used to estimate this flux, the result is about 100 gamma rays per second which is easily detectable [5]. The primary advantages of this technique are that the counting rate (the number of gamma rays detected in a particular time) is generally high. One disadvantage of this technique is that the radiation signature of HEU is relatively small; hence it quickly attenuates [7]. A second disadvantage is that U-238 is used for other applications in which a high Z material is essential, therefore there could be a lot of false positives (from U-238 used in something that is not a nuclear weapon) if the method was used at questionable sites.

4.1.3 Existing Detection Equipment

The existing detection technologies available are: 1. Radiation Pagers: These are able to detect radiation at close distances. They are lightweight and inexpensive, but are unable to ascertain the source emitting the radiation. [2] 2. Radioactive isotope identification devices: These devices are able to identify radioisotopes based on their gamma ray spectrum. These devices are mainly handheld but heavy and delicate. They need to be cooled with liquid nitrogen or by mechanical means, thus their usability in the field is limited. They have a relatively short range for detecting radiation sources with low radioactivity, notably shielded HEU, making them unsuitable as the primary method of screening cargo containers. [2] 3. Radiation Portal Monitors: Many of these devices use large sheets of plastic scintillator material, such as polyvinyl toluene (PVT), to detect radiation coming from a vehicle. However, PVT cannot identify the source of radiation. However, there are lots of items in everyday trade that contain radioactive material. As a result, some produce many false alarms, which may require considerable effort to resolve, delaying the flow of commerce. Newer versions have some isotope identification capability. [2] They are primarily used for security purposes at checkpoints and borders. [7]

4.2 Active Detection

4.3 Muon Tomography

4.3.1 Cosmic Rays

Cosmic rays are a flux of high energy particles that bombard the earth's atmosphere. They are produced in other parts of the universe and approximately 98% of these particles are protons or heavier nuclei and 2% are electrons. These

cosmic rays collide with air molecules and produce a shower of particles that include protons, neutrons, electrons, positrons, photons, kaons and pions (both neutral and charged). These particles interact by the nuclear and electromagnetic forces to produce additional particles in a cascade process. Pions will interact with air molecules via the strong force but some will spontaneously decay via the weak force into a muon plus a muon neutrino or an anti-muon neutrino. [1]

$$\pi^+ \rightarrow \mu^+ + \bar{\nu}_\mu \quad (1)$$

$$\pi^- \rightarrow \mu^- + \nu_\mu \quad (2)$$




Figure 3: Cosmic ray cascade induced by a cosmic ray proton striking an air molecule nucleus. [1]

4.3.2 Muons

Muons are the most abundant charged particles at sea level. They are produced high in the atmosphere, typically 15 km and lose about 2 GeV before reaching the ground due to ionization. The mean energy of muons at the ground is 4 GeV [2]. They interact with matter via the weak and electromagnetic forces but not with the strong force. They decay via the weak force into an electron plus an electron neutrino or an anti-electron neutrino.

$$\mu^- \rightarrow e^- + \bar{\nu}_e + \nu_\mu \quad (3)$$

$$\mu^+ \rightarrow e^+ + \nu_e + \bar{\nu}_\mu \quad (4)$$

The muon flux at sea level is about $1 \text{ muon cm}^{-2} \text{ min}^{-1}$ [3] or $10000 \text{ muons m}^{-2} \text{ min}^{-1}$. They are highly penetrating charged radiation. A typical cosmic ray muon of

energy 3 GeV can penetrate more than 1000 g cm^{-2} (eg. 10 m of water). As muons pass through matter they either scatter if they have high energy or are absorbed if they have low energy. The angle at which they scatter depends on the atomic number Z (number of protons) of the material. As the atomic number of the material increases, the scattering angle increases. In a layer 10 cm thick, a 3 GeV muon will scatter with an angle of 2.3 mrad in water, 11 mrad in iron and 20 mrad in lead. [4]

4.3.3 Limitations of X-rays

X-ray radiography is successful in many areas but has limitations. X-rays are unable to penetrate dense objects that have a high atomic number. Multiple projections are needed in order to resolve a three-dimensional structure using X-rays and they also pose health risks from radiation. In X-ray radiography, absorption and scattering cause attenuation of the incident beam which determines the intensity of an image pixel. The maximum mean free path of photons is about 25 g cm^{-2} for all materials which corresponds to 2 cm of lead [4]. Even the most penetrating gamma rays are attenuated by an e-folding in 2 cm of lead. A very large incident dose of radiation is needed to penetrate thicker objects and that is harmful for living organisms [5]. A different type of radiography must be used for thicker objects and it must be based on the interaction of charged particles with matter by multiple Coulomb scattering [4].

4.3.4 Muon tomography concept

Muon tomography is based on the multiple Coulomb scattering of muons as they pass through a material. Radiographs of objects of any thickness can be produced by using multiple scattering. Cosmic ray muons are passive and harmless radiation and allow radiograph of dense objects with no artificial dose of radiation such as X-rays or gamma rays. The scattering of muons differs significantly in three different groups of materials: low Z (water, plastic, concrete), medium Z (iron, copper) and high Z (lead, tungsten, uranium) [6]. Each muon carries information about the objects it has penetrated and the properties of these objects can be determined by measuring the scattering of multiple muons. High Z objects can be detected amongst typical low Z and medium Z objects. [3]

The muon tomography concept is illustrated above in Figure 4. The position and angle of incoming muon tracks are provided by a set of two or more planes of muon detectors above and below the object. These detectors only detect vertically oriented muons. Side detectors could be used to detect horizontally oriented muons. The detectors above the object measure the position of incident muons in two orthogonal coordinates. The scattering of the muons that pass through the material depends on the type of the object. The detectors below the object measure the positions and angles of the scattered muons. The scattering angle of each muon is calculated from the corresponding incident and scattered measurements. The momentum is calculated from the slight scattering of muons in the detectors themselves. [3]




Figure 4: Muon tomography concept. The grey tracks are the muons going through air and the black tracks are the muons that penetrate a dense object. [3]

4.3.5 Simulations of muon tomography

Simulations of muon tomography are very promising and results can be obtained within a very short exposure time of approximately 1 min. The GEANT4 Monte Carlo package is used for the simulations because it implements a complete, accurate and validated model for multiple scattering. A detailed GEANT4 simulation of a passenger van has been produced and reconstruction was achieved using two different methods: mean and median. [3]

The mean method of reconstruction shown on Figure 6 contains red spots scattered over the image. The median method shown on Figure 7 does not contain these effects. The denser components of the van (engine, battery, drive train) are shown as green (low Z) or blue (medium) but the high Z threat object stands out as red. The median method is clearly better. [3]

A ray crossing algorithm has been developed that highlights locations where strongly scattered muons cross paths. The basis of the ray crossing algorithm is the fact that a high Z object produces many highly scattered rays which intersect in a small volume. A large depth of medium Z material can also produce highly scattered rays but these rays will spread over a larger volume. The algorithm was applied to a simulated scene of a $6 \times 2.4 \times 2.4 \text{ m}^3$ cargo container filled with 12 tons of iron and three $9 \times 9 \times 12 \text{ cm}^3$ uranium bricks were buried within the iron. A cosmic ray exposure of 1 min was simulated and the tracks were processed using the ray crossing algorithm. The results are




Figure 5: Illustration of major objects in a simulated passenger van using GEANT4. The red block in the centre represents a $10 \times 10 \times 10 \text{ cm}^3$ solid piece of tungsten which is a high Z threat object. [3]




Figure 6: Reconstruction of 1 min of simulation muon exposure of the passenger van using the mean method. [3]

shown below on Figure 8. [6]

All three uranium bricks are clearly identified on Figure 8a. The image without the uranium bricks is empty of any signal as shown on Figure 8b. The ray crossing algorithm shows great promise in eliminating the scattering




Figure 7: Reconstruction of 1 min of simulation muon exposure of the passenger van using the median method. [3]




Figure 8: Ray crossing algorithm reconstructions of 1 min of simulated muon radiography of a $6 \times 2.4 \times 2.4 \text{ m}^3$ cargo container filled with 12 tons of iron and three $9 \times 9 \times 12 \text{ cm}^3$ uranium bricks (a) and without the uranium bricks (b). [6]

background. [6]

Other simulations were also produced using a Monte Carlo simulation code and the results are shown below on Figure 9.




Figure 9: Muon radiograph of a complex target in a volume of $9 \times 3 \times 5.5 \text{ m}^3$. The first object (a) is a large complex lead sculpture. The reconstructed image (b) shows much of the detail of the object and its based on 1 min of exposure. The second object (c) consists of a $4 \times 2.4 \times 2.4 \text{ m}^3$ container with walls of thickness equivalent to 3 mm of steel. There are 69 sheep made of water (shown in blue) inside the container with a body size of $60 \times 30 \times 40 \text{ cm}^3$ and three uranium bricks of size $9 \times 9 \times 12 \text{ cm}^3$ (shown in black). The reconstructed image (d), based on 1 min of exposure, shows that the 3 uranium bricks stand out. The colour intensity in the two reconstructed images corresponds to the significance of the signal. [5]

4.3.6 Experimental results of muon tomography

There are a few prototype experimental muon tomography detectors that show excellent results which are consistent with the simulations. A small scale experimental detector system was developed in 2003 at the Los Alamos National Laboratory, Los Alamos, New Mexico [5]. A picture of the detector is shown below Figure 10.

Eight X and eight Y locations were measured for each muon by four ionizing radiation detectors contained in the detector stack. The two detectors on top measure the incoming muon track while the two detectors at the bottom measure the scattered track. Each delay line drift chamber detector had an active area of $60 \times 60 \text{ cm}^2$. The detector was calibrated with no test object to determine the




Figure 10: Picture of experimental apparatus at the Los Alamos National Laboratory in 2003. There are four muon detectors labelled D1-D4 with a vertical spacing of 27 cm. The detectors determine the positions and angles of the muons in two orthogonal coordinates (X and Y). The test object (W) was a tungsten cylinder of radius 5.5 cm and height 5.7 cm. A thick Lexan (L) plate of dimensions $35 \times 60 \times 1 \text{ cm}^3$ and steel support beams (B) were used to support the test object. [5]

precision of the position measurement. A Windows based acquisition program was used to collect the data. The reconstruction was approximated using the following simple technique. Multiple scattered tracks were approximated to have only a single scattering event and the point of scatter was located by extrapolating the incident and scattered rays. A maximum likelihood technique was used to assign voxels (3D pixels) to each scattered muon. The reconstructed 3D image of the tungsten test object is shown below on Figure 11. [5]

The data for the above image were collected over several hours because the detector was not fully optimised. An optimised detector with 100% tracking efficiency and large solid angle could acquire the same data in approximately 30 min. The test object and the test support beams can be clearly resolved using this long run. Considerably shorter runs could be used for a simple yes/no detection. [5]

Another sub-scale prototype was built at the Los Alamos National Laboratory in 2006 called the Large Muon Tracker (LMT) which is 20' tall. The design of this detector is very similar to the previous detector. It consists of 6 top and 6 bottom planes of drift tube detectors for each X and Y dimensions (24 planes in total) on a flexible frame. The top and bottom sections are separated by 1.5 m to allow a large sampling region. X and Y tracks are fitted separately to




Figure 11: Test object reconstruction using 100 000 muons. A volumetric image of $1 \times 1 \times 1 \text{ cm}^3$ voxels was reconstructed. The eight planes are horizontal slices near the middle of the volume, moving from top to bottom. Both the tungsten cylinder and the steel support beams are clearly visible. [5]

find the slope and intercept of each dimension and combining them yields the 3D trajectory of the muon. A picture of LMT is shown below on Figure 12. [7]

The prototype of LMT was completed and tested in 2008. A simple reconstruction technique was used to process the data. The sample volume of $1.5 \times 1.5 \times 1.0 \text{ m}^3$ was segmented into $2 \times 2 \times 2 \text{ cm}^3$ voxels. The median scattering angle was calculated for all muons whose trajectories intersected a voxel with an adjustable distance. The prototype was tested using a $10 \times 10 \times 10 \text{ cm}^3$ lead cube that represented the threat object and it was placed in the LMT along with a car engine and transmission. A photograph of the engine in the LMT is shown below on Figure 13. [8]

Data were collected for approximately 160 min and have been analysed to reconstruct the images shown below on Figure 14. The mean scattering angle is plotted for all trajectories that pass through each voxel. [8]

Another muon tomography prototype is located at the INFN National Laboratories of Legnaro, Padova, Italy. A volume of 11 m^3 can be inspected using the prototype which is ideal for cargo inspection. A picture of the prototype is shown below on Figure 15. [9]

Two Muon Barrel drift chambers of dimensions $300 \times 250 \times 29 \text{ cm}^3$, built for the CMS experiment at CERN, were used for the experiment, separated by 160 cm. A concrete and iron structure is supporting the chambers. There are two additional drift chambers underneath the bottom detector that will be used in the future as a momentum filter. The reconstruction procedure uses a List Mode Iterative Algorithm (LMIA) that process events one at a time instead of grouping similar events together. [9]

The experiment was repeated using two lead blocks of dimensions $10 \times 10 \times 20 \text{ cm}^3$



Figure 12: The Large Muon Tracker (LMT) prototype at the Los Alamos National Laboratory in 2006. The precise positions of muon tracks above and below the sampling region are determined by the overlapping X and Y detector planes. The new redundant detector planes will be used improve the tracking efficiency and quality. [7]

and two iron blocks of dimensions $10 \times 20 \times 20 \text{ cm}^3$ placed on a support structure 65 cm in the vertical direction. The 3D reconstruction of this layout is shown below on Figure 17.

The position of the blocks is reproduced correctly but there is finite spatial resolution in the reconstruction especially in the vertical direction. The reconstructed scattering density of the lead blocks is greater than that of the iron blocks. Its straightforward to discriminate low Z or medium Z materials from high Z materials using this method. The problem with this method is that discrimination between high Z materials denser than iron is more difficult because of the non- linearity in the reconstructed scattering density. This means that the muon momentum has to be measured as well to allow a better material recognition and increase the statistical precision of the density measurement. [9]

4.3.7 Applications of muon tomography

Muon tomography could be used to protect the rail network from terrorism. The idea is to equip train stations with large muon detectors above and below. Density images can be produced very fast in a time scale of minutes. High



Figure 13: Photograph of a car engine in the LMT at the Los Alamos National Laboratory in 2008. [8]

density objects such as nail bombs and fissile materials will be easily identified. [10]

It could also be used as a detection method of nuclear devices or material in vehicles and containers. An automobile sized counting station could be used to scan vehicles at border crossing. This would allow examination of every vehicle and shipping container crossing a border. It will require enough detectors to handle the traffic at the borders. The total traffic crossing the US – Mexico and the US – Canada borders in 2008 was 1.3×10^8 vehicles. Assuming a single muon tomography detector could analyse a vehicle within 1 min and operates for 12 hours per day, then 500 detectors would be needed to handle the entire border crossing traffic. This would cost a total of 1.5 to 2 billion dollars but its negligible compared to the consequences of the detonation of a nuclear bomb. A picture of how it could be implemented at a border crossing is shown below on Figure 18. [8]




Figure 14: Mean scattering angle for a slice through the scene 50 cm above the base plate. The left image shows the car engine, the middle image shows the engine with the lead cube and the right image shows the difference of the other two images. The lead block stands out dramatically. [8]

Both methods could be used for nuclear dismantlement verification. The vehicle transporting the bomb for disarmament could be scanned at several stations during its journey to the dismantlement facilities. A single muon tomography detector at the dismantlement facility could be used to verify a small quantity of nuclear bombs. If there is a large number of bombs queued for verification then the idea of the train stations could be used. A room with muon detectors on the floor and the ceiling could be used to scan all of them at the same time.




Figure 15: Muon tomography system prototype located at the INFN National Laboratories of Legnaro. [9]




Figure 16: Test of the imaging capability of the prototype. The picture on the left shows the layout of iron bricks forming the word INFN and the picture on the right shows the result of the data analysis using the LMIA. The reconstructed image is very clear. [9]





Figure 17: The left image is a sketch of the layout with the two lead and the two iron blocks. The darker blocks are the lead blocks. The right image shows the 3D view of the reconstructed image using the LMIA. [9]




Figure 18: Schematic view of how a counting station might look. Vehicles would have to stop for approximately 20 seconds for the scan. [8]