


## Mutual exclusion



## Example use I – mutual exclusion [access granted in order]

Goal: a solution for granting a resource to a process which satisfies the following three conditions:

- [mutual exclusion] A process which has been granted the resource must release it before the resource can be granted to another process.
- [termination/progress] If every process which is granted the resource eventually releases it, then every request is eventually granted.
- [ordering] Requests must be granted in the order in which they are made.



# <u>Distributed</u> Mutual Exclusion Is Different

Regular mutual exclusion solved using shared state

E.g., atomic test-and-set of shared variable

Only tool for distributed mutual exclusion:

# Assumptions

- Communication channels
  - reliable: messages do arrive at destination
  - in-order: messages are delivered in the order in which they are sent
  - asynchronous (messages may take long time)
- Participants do not fail.

## Q: Potential Designs?



## Distributed Mutual Exclusion


### **Protocols**

- Key ideas:
- Before entering critical section, processor must get permission (from other processors, or from arbitrator)
- When exiting critical section, processor must let the others know that he's finished
- For fairness, processors allow other processors who have asked for permission <u>earlier</u> than them to proceed


## Solution 1: Centralized Lock Server


- To enter critical section:
  - send REQUEST to central server
  - wait for permission from server
- To leave critical section:
  - send RELEASE to central server
- Server:
  - Has an internal queue of all REQUESTs it's received
  - but to which it hasn't yet sent OK
  - Delays sending OK back to process until process is at head of queue
  - Removes process from the queue after it get
    RELEASE
















P<sub>2</sub>


P<sub>3</sub>






































## Lamport's algorithm -

 Each process (locally) maintains Qi a local copy of a shared priority queue

- To enter critical section, P
  - must have replies from all other processes AND
  - be at the front of Qi

- Rationale: When P has all replies:
  - #1: All other processes are aware of P's request
  - #2: P is aware of any earlier requests for the mutex (if any)



## Advantages:

- Simple (we like simple!)
- Only 3 messages required per sync session (enter&exit)

## Disadvantages:

- Single point of failure
- Single performance bottleneck
- With an asynchronous network, doesn't achieve in-order fairness (even for logical time order)
- Must select (or elect) a central server

## Solution 2: A ring-based algorithm

#### Pass a token around a ring

- Participant enters critical section only if it holds the token

#### **Problems:**

- Not in-order
- Long synchronization delay
  Need to wait for up to N-1 messages, for N processors
- Very unreliable
  Any process failure breaks the ring

Does not guarantee ordering (but this can be fixed). How?

- 1. To request the resource: process Pi sends
  - the message request\_resource (T<sup>m</sup>:P<sup>i</sup>) to every process, and
  - puts that message on its own request queue

[T<sup>m</sup> is the timestamp of resource request: i.e. logical clock when req. is sent]

- 2. When P<sup>j</sup> receives request\_resource (T<sup>m</sup>:P<sup>j</sup>),
  - it places it on its request queue
  - sends a (timestamped) acknowledgment message to Pi
- 4. To release the resource, Pi
  - removes any request\_resource(T<sup>m</sup>:P<sup>i</sup>) message from its request queue
  - sends a (timestamped) release\_resource (Pi) to every other process.
- When process P<sup>j</sup> receives a P<sup>i</sup> releases resource message,
  - it removes any request\_resource (T<sup>m</sup>:P<sup>i</sup>) message from its queue.
  - Process Pi is granted the resource when
    - there is a *requests resource* (T<sup>m</sup>:P<sup>i</sup>) message at the top of its own request queue (ordered by logical timestamp in T<sup>m</sup>) AND
    - P<sup>i</sup> has received a message from every other process timestamped later than T<sup>m</sup>

# Lamport Algorithm

#### Rule 1

- To request a resource, process i
  - sends a request message  $T_m$ : i to every other process,
    - $T_m$  is the timestamp of the message.
  - then stores a copy of the message in its request queue.

## Lampo

### Lamport Example


Total ordering: C < D < E</p>

$$RQ_C = \{ \}$$


$$RQ_{D} = \{ \}$$

$$\mathsf{RQ}_\mathsf{E} = \{\ \}$$


 D requests the resource by sending request messages to C and E




D then stores its own request



 C requests the resource by sending request messages to D and E




C then stores its own request




## Lamport Algorithm

#### Rule 2


- When process j receives a request message  $T_m$ : i,
  - it places it in its request queue, and
  - sends a timestamped acknowledgment back to process i.




 E places D's request in its queue and sends an acknowledgment back



 D places C's request in its queue and sends an acknowledgment back




 C places D's request in its queue and sends an acknowledgment back




## Lamport Algorithm

#### Rule 5


- Process i is granted the resource when the following conditions are satisfied:
  - There is a request  $T_m$ : i in its request queue that is ordered before any other request (by the total order)
  - Process i has received a message from every other process with a timestamp later than  $T_m$




• D isn't granted the resource since 1:C  $\Rightarrow$  1:D



 C isn't granted the resource since it has not received a message from E




 E places C's request in its queue and sends an acknowledgment back




# Lamp

# Lamport Example

• D isn't granted the resource since 1:C  $\Rightarrow$  1:D



 C is granted the resource since 1:C ⇒ 1:D and it has received later (i.e., timestamp > 1) messages from D and E






## Rule 3

- To release a resource,
  - process i removes any  $T_m$ : i requests from its queue, and
  - sends a timestamped release message to every other process.


C is finished with resource




# Lan

# Lamport Example

C removes its request from its own queue




 C releases the resource by sending release messages to D and E




# Lamport Algorithm

## Rule 4


- When process j receives a release message from process i,
  - it removes any  $T_m$ : *i* requests from its request queue.




E removes C's request



D removes C's request



 D is granted the resource since it has received more later messages (timestamp > 1) from C and E





# • Why is this cool?

- Fair, short synchronization delay
- Condition to enter critical section tested locally
- Each process independently follows these rules,
  - there is no one coordinating process or central storage.

# Disadvantages:

Unreliable: any process failure halts progress

# Other algorithms

- Ricart & Agrawal: optimizes Lamport to reduce the number of messages
  - Same drawbacks
- Voting based: more reliable deals with failures / slow servers
  - But unfair (no ordering)

# A voting-based protocol

- Goal: Higher availability deal with (temporary/ & full-stop) server failures, slow servers
- **Principle:** <u>Voting</u>. The server protecting the resource is replicated *n* times, we'll call each server replica a coordinator
  - Client access requires a majority vote from m > n/2 coordinators.
  - A coordinator always responds immediately to a request.
    - (without contacting other coordinators)
  - Client behavior if not enough votes: sends back votes and retries.
- **Failure model:** If a coordinator crashes, it will (eventually) recover, but will have forgotten about the past (permissions it had granted).
- **Availability?** Much better (load level dependednt?)
- **Correctness?** Probabilistic! **Issue:** How robust is this system? What is the probability to make an incorrect 'grant acces' decision?



# A voting-based protocol (cont)

## **Operating mode:** Assume *n* coordinators (servers)

- A coordinator always responds immediately to a request.
- Access requires a majority vote from m > n/2 coordinators.
- If a coordinator fails, it restarts immediately but looses state

### **Issue:** How robust is this system?

- When may the system malfunction?
- How many servers have to 'flip'
- What's the chance?



Initial state: decision made for A: M votes for A,

N-M votes for B



B B B

Some F nodes fail





B B B

And reset their state





Requests for B arrived later are effectively similar with a vote switch

Violation if (N-M) + F > M



**Operating mode:** Assume *n* coordinators (servers)

- A coordinator always responds immediately to a request.
- Access requires a majority vote from m > n/2 coordinators.
- If a coordinator fails, it restarts immediately but looses state

**Issue:** How robust is this system?

## What's the probability of malfunctioning

(violate mutual exclusion requirement and allow two clients in the critical region)?

- p the probability that a coordinator resets in the next  $\Delta t$  (crashes and recovers immediately)
  - $p = \Delta t / T$ , where T is the an average server lifetime
- The probability that k out m coordinators reset during  $\Delta t$   $P[k]=C(k,m)p^k(1-p)^{m-k}$ :
- Violation when at least 2m-n coordinators reset

$$\sum_{k=2m-n}^{m} \left(\frac{m}{k}\right) p^k (1-p)^{m-k}$$

[conservative bound]







Figure 2. Probability to break exclusivity.

# Issues

- Any possible issues with the design?
  - Deadlock?




### **Recap:** Assume *n* coordinators

- Access requires a majority vote from m > n/2 coordinators.
- A coordinator always responds immediately to a request.
- A client that does not gain a voting `round` sends back its votes.

How are we doing on various success criteria? fairness, avoid starvation, robustness (ability to deal with failures), low overhead, timeliness?

## Performance issue – starvation

Goodput with naïve solution






### Performance issue – starvation

### The fix:


- Exponential backoff +
- Informed by estimated place in the race



# Algorithm Comparison

Algorithm	Messages per entry/exit	Synchronization delay (in RTTs)	Liveness
Central server	3	1 RTT	Bad: coordinator crash prevents progress
Token ring	N	<= sum(RTTs)/2	Horrible: any process' failure prevents progress
Lamport	3*(N-1)	max(RTT) across processes	Horrible: any process' failure prevents progress
Ricart & Agrawal	2*(N-1)	max(RTT) across processes	Horrible: any process' failure prevents progress
Voting	>= 2*(N-1) (might have vote recalls, too)	max(RTT) between the fastest N/2+1 processes	Great: can tolerate up to N/2-1 failures

You want the lock; no one else has it; how long till you get it?



## So, Who Wins?

Well, none of the algorithms we've looked at thus far

But the closest one to industrial standards is...

- The centralized model (e.g., Google's Chubby, Yahoo's ZooKeeper)
- But replicate it for fault-tolerance across a few machines
  - Replicas coordinate via mechanisms similar to the ones we've shown for the distributed algorithms (e.g., voting) – we'll talk later about generalized voting alg.
  - For manageable load, app writers must avoid using the centralized lock service as much as humanly possible!

# Take-Aways

- Lamport algorithm
  - demonstrates how distributed processes can maintain consistent replicas of a data structure (the priority queue)
  - demonstrate utility of logical clocks
- Cost of a distributed system may be high.



\big\_detour{end}