



When Concurrency Matters: Behaviour-Oriented Concurrency

LUKE CHEESEMAN, Imperial College London, UK

MATTHEW J. PARKINSON, Microsoft Azure Research, UK

SYLVAN CLEBSCH, Microsoft Azure Research, UK

MARIOS KOGIAS, Imperial College London, UK Microsoft Research, UK

SOPHIA DROSSOPOULOU, Imperial College London, UK

DAVID CHISNALL, Microsoft, UK

TOBIAS WRIGSTAD, Uppsala University, Sweden

PAUL LIÉTAR, Imperial College London, UK

The state of BoC today



$$\text{STEP} \frac{E, h \hookrightarrow E', h'}{R \uplus (\bar{\kappa}, E), P, h \rightsquigarrow R \uplus (\bar{\kappa}, E'), P, h'}$$

$$\text{SPAWN} \frac{E \hookrightarrow_{\text{when } (\bar{\kappa}') \{E''\}} E'}{R \uplus (\bar{\kappa}, E), P, h \rightsquigarrow R \uplus (\bar{\kappa}, E'), P : (\bar{\kappa}', E''), h}$$

$$\text{RUN} \frac{(\cup_{(\bar{\kappa}', _) \in (P' \cup R)} \bar{\kappa}') \cap \bar{\kappa} = \emptyset}{R, P' : (\bar{\kappa}, E) : P'', h \rightsquigarrow R \uplus (\bar{\kappa}, E), P' : P'', h}$$

$$\text{END} \frac{\text{finished}(E)}{R \uplus (\bar{\kappa}, E), P, h \rightsquigarrow R, P, h}$$



Behavior-Oriented Concurrency in Python

Lock-less, Deadlock-free, Ownership-based

<https://microsoft.github.io/bocpy/>











OPSLA 2023

operational semantics

The state of BoC today

OOPSLA 2023

When Concurrency Matters: Behaviour-Oriented Concurrency

LUKE CHEESEMAN, Imperial College London, UK
MATTHEW J. PARKINSON, Microsoft Azure Research, UK
SYLVAN CLEBSCH, Microsoft Azure Research, UK
MARIOS KOGIAS, Imperial College London, UK Microsoft Research, UK
SOPHIA DROSSOPOULOU, Imperial College London, UK
DAVID CHISNALL, Microsoft, UK
TOBIAS WRIGSTAD, Uppsala University, Sweden
PAUL LIÉTAR, Imperial College London, UK

Operational Semantics

$$\begin{array}{l} \text{STEP} \frac{E, h \mapsto E', h'}{R \uplus (\bar{\kappa}, E), P, h \rightsquigarrow R \uplus (\bar{\kappa}, E'), P, h'} \quad \text{SPAWN} \frac{E \hookrightarrow_{\text{when } (\bar{\kappa}') \{E''\}} E'}{R \uplus (\bar{\kappa}, E), P, h \rightsquigarrow R \uplus (\bar{\kappa}, E'), P : (\bar{\kappa}', E''), h} \\ \\ \text{RUN} \frac{(\bigcup_{(\bar{\kappa}', _) \in (P' \cup R)} \bar{\kappa}') \cap \bar{\kappa} = \emptyset}{R, P' : (\bar{\kappa}, E) : P'', h \rightsquigarrow R \uplus (\bar{\kappa}, E), P' : P'', h} \quad \text{END} \frac{\text{finished}(E)}{R \uplus (\bar{\kappa}, E), P, h \rightsquigarrow R, P, h} \end{array}$$

<https://microsoft.github.io/bocpy/>



Behavior-Oriented Concurrency in Python

Lock-less, Deadlock-free, Ownership-based

But, ...

We specified *how*, and not *what*

How a program runs?

Operational semantics and implementations