


DWG's show 4'
Please confirm if 3' is acceptable.

3' WIDE GATE IS ACCEPTABLE PER DISCUSSION WITH ELBERT CO.
-WOLD A&E

~~Panic Bar with Keyed lever handle on entry side~~

PER DISCUSSION WITH OWNER, PANIC DEVICE AND LEVER LOCKSET IS NOT REQUIRED. PROVIDE PADLOCK CLASP (ACCESIBLE FROM BOTH SIDES)
-WOLD A&E

FABRIC: 72" 9 GA. GALVANIZED (2" Mesh) KK CHAIN LINK FABRIC.

BRACING: Terminal posts braced and trussed to the nearest line post with 1 5/8" O.D. DQ-40 PIPE and 3/8" TRUSS ROD & TRUSS ROD TIGHTENER.

GATES: SINGLE SWING GATE: Framework of 1 5/8" DQ-40 PIPE, 1.83 lbs. per foot.

Gates braced and trussed as necessary. Same fabric as fence.

GATE POST: SINGLE SWING GATE: 2 7/8" O.D. FULL WEIGHT PIPE, 5.79 lbs. per foot. Concrete footing: 12" diameter, 36" depth.

FITTINGS: REGULAR BRACE BAND & CARRIAGE BOLT, PRESSED STEEL RAIL-END, PRESSED STEEL EYE-TOP, PRESSED STEEL CAP, 3/16" X 5/8" TENSION BAR, REGULAR TENSION BAND & CARRIAGE BOLT.

TIE WIRE: 8 1/4" 12 GA. STEEL TIE WIRE & 7 1/2" 12 GA. STEEL TIE WIRE spaced 15" on center for line posts & 24" on center for rails.

POST FOOTING: HAND MIXED CONCRETE.

SPLIT RAIL FENCE
EXCEPTIONAL WORK—EVERY TIME

SPLIT RAIL FENCE COMPANY
8065 Brandon Dr
LITTLETON, COLORADO 80125
303-791-1997

3' SINGLE GATE, 1 5/8" DQ-40 PIPE FRAME

Drawn: 06/01/2022
File: