

Extending the Iris Proof Mode with Inductive Predicates using Elpi

Luko van der Maas

Computing Science
Radboud University

Program verification

- Verify programs by specifying pre and post conditions

Program verification

- Verify programs by specifying pre and post conditions
- Specification happens in separation logic

Program verification

- Verify programs by specifying pre and post conditions
- Specification happens in separation logic
- We make use of embeddings of separation logic in Coq

Program verification

- Verify programs by specifying pre and post conditions
- Specification happens in separation logic
- We make use of embeddings of separation logic in Coq
- Iris 2015 (Jung, Krebbers, et. al.)


Separation logic with Hoare triples

$$[\text{isD } d \ y] \text{ op } d \times [\text{isD } d \ (f \times y)]$$

Separation logic with Hoare triples

$$[\text{isD } d \ y] \text{ op } d \times [\text{isD } d \ (f \ x \ y)]$$

Imperative
program



Separation logic with Hoare triples

$$[\text{isD } d \ y] \text{ op } d \times [\text{isD } d \ (f \times y)]$$

Imperative
program

Functional
program


Separation logic with Hoare triples

Representation predicate

$[isD\ d\ y]\ op\ d\ x\ [isD\ d\ (f\ x\ y)]$

Imperative
program

Functional
program




Separation logic with Hoare triples

Representation predicate

$[isD\ d\ y]\ op\ d\ x\ [isD\ d\ (f\ x\ y)]$

Imperative
program

Functional
program



Separation logic with Hoare triples

Representation predicate

$[isD\ d\ y]\ op\ d\ x\ [isD\ d\ (f\ x\ y)]$


Imperative
program

Functional
program

$[isList\ hd\ \vec{v}]\ delete\ hd\ i\ [isList\ hd\ (remove\ i\ \vec{v})]$


Representation predicates

Representation predicates



Harris (2001)


Representation predicates



Harris (2001)

$$\begin{aligned}
 \text{isMLL } hd \vec{v} = & (hd = \mathbf{none} * \vec{v} = []) \vee \\
 & (\exists \ell, v', tl. hd = \mathbf{some} \ell * \ell \mapsto (v', \mathbf{true}, tl) * \text{isMLL } tl \vec{v}) \vee \\
 & \left(\begin{array}{l} \exists \ell, v', \vec{v}'', tl. hd = \mathbf{some} \ell * \ell \mapsto (v', \mathbf{false}, tl) * \\ \vec{v} = v' :: \vec{v}'' * \text{isMLL } tl \vec{v}'' \end{array} \right)
 \end{aligned}$$

Representation predicates




Harris (2001)

$$\text{isMLL } hd \vec{v} = (hd = \text{none} * \vec{v} = []) \vee$$

$$(\exists \ell, v', tl. hd = \text{some } \ell * \ell \mapsto (v', \text{true}, tl) * \text{isMLL } tl \vec{v}) \vee$$

$$\left(\begin{array}{l} \exists \ell, v', \vec{v}'', tl. hd = \text{some } \ell * \ell \mapsto (v', \text{false}, tl) * \\ \vec{v} = v' :: \vec{v}'' * \text{isMLL } tl \vec{v}'' \end{array} \right)$$

Representation predicates




Harris (2001)

$$\text{isMLL } hd \vec{v} = (hd = \mathbf{none} * \vec{v} = []) \vee$$

$$(\exists \ell, v', tl. hd = \mathbf{some} \ell * \ell \mapsto (v', \mathbf{true}, tl) * \text{isMLL } tl \vec{v}) \vee$$

$$\left(\begin{array}{l} \exists \ell, v', \vec{v}'', tl. hd = \mathbf{some} \ell * \ell \mapsto (v', \mathbf{false}, tl) * \\ \vec{v} = v' :: \vec{v}'' * \text{isMLL } tl \vec{v}'' \end{array} \right)$$

Representation predicates



Harris (2001)


$$\text{isMLL } hd \vec{v} = (hd = \mathbf{none} * \vec{v} = []) \vee$$

$$(\exists \ell, v', tl. hd = \mathbf{some} \ell * \ell \mapsto (v', \mathbf{true}, tl) * \text{isMLL } tl \vec{v}) \vee$$

$$\left(\exists \ell, v', \vec{v}'', tl. hd = \mathbf{some} \ell * \ell \mapsto (v', \mathbf{false}, tl) * \right.$$

$$\left. \vec{v} = v' :: \vec{v}'' * \text{isMLL } tl \vec{v}'' \right)$$


Representation predicates



Harris (2001)

$$\begin{aligned}
 \text{isMLL } hd \vec{v} = & (hd = \mathbf{none} * \vec{v} = []) \vee \\
 & (\exists \ell, v', tl. hd = \mathbf{some} \ell * \ell \mapsto (v', \mathbf{true}, tl) * \text{isMLL } tl \vec{v}) \vee \\
 & \left(\begin{array}{l} \exists \ell, v', \vec{v}'', tl. hd = \mathbf{some} \ell * \ell \mapsto (v', \mathbf{false}, tl) * \\ \vec{v} = v' :: \vec{v}'' * \text{isMLL } tl \vec{v}'' \end{array} \right)
 \end{aligned}$$

Representation predicates



Harris (2001)

$$\text{isMLL } hd \vec{v} = (hd = \mathbf{none} * \vec{v} = []) \vee$$

$$(\exists \ell, v', tl. hd = \mathbf{some} \ell * \ell \mapsto (v', \mathbf{true}, tl) * \text{isMLL } tl \vec{v}) \vee$$

$$\left(\exists \ell, v', \vec{v}'', tl. hd = \mathbf{some} \ell * \ell \mapsto (v', \mathbf{false}, tl) * \right.$$

$$\left. \vec{v} = v' :: \vec{v}'' * \text{isMLL } tl \vec{v}'' \right)$$

Outline of our solution

```
1  eiInd                                                                    Coq
2  Inductive is_MLL : val → list val → iProp :=
3      | empty_is_MLL : is_MLL NONEV []
4      | mark_is_MLL v vs l tl :
5          l ↦ (v, #true, tl) -* is_MLL tl vs -*
6          is_MLL (SOMEV #l) vs
7      | cons_is_MLL v vs tl l :
8          l ↦ (v, #false, tl) -* is_MLL tl vs -*
9          is_MLL (SOMEV #l) (v :: vs).
```

Outline of our solution

- Definition of `is_MLL`

```
1  eiInd                                                                    Coq
2  Inductive is_MLL : val → list val → iProp :=
3      | empty_is_MLL : is_MLL NONEV []
4      | mark_is_MLL v vs l tl :
5          l ↦ (v, #true, tl) -* is_MLL tl vs -*
6          is_MLL (SOMEV #l) vs
7      | cons_is_MLL v vs tl l :
8          l ↦ (v, #false, tl) -* is_MLL tl vs -*
9          is_MLL (SOMEV #l) (v :: vs).
```

Outline of our solution

```
1  eiInd                                                                    Coq
2  Inductive is_MLL : val → list val → iProp :=
3    | empty_is_MLL : is_MLL NONEV []
4    | mark_is_MLL v vs l tl :
5      l ↦ (v, #true, tl) -* is_MLL tl vs -*
6      is_MLL (SOMEV #l) vs
7    | cons_is_MLL v vs tl l :
8      l ↦ (v, #false, tl) -* is_MLL tl vs -*
9      is_MLL (SOMEV #l) (v :: vs).
```

- Definition of `is_MLL`
- Proof of constructors, `empty_is_MLL`, `mark_is_MLL`, `cons_is_MLL`

Outline of our solution

```
1  eiInd                                                                    Coq
2  Inductive is_MLL : val → list val → iProp :=
3    | empty_is_MLL : is_MLL NONEV []
4    | mark_is_MLL v vs l tl :
5      l ↦ (v, #true, tl) -* is_MLL tl vs -*
6      is_MLL (SOMEV #l) vs
7    | cons_is_MLL v vs tl l :
8      l ↦ (v, #false, tl) -* is_MLL tl vs -*
9      is_MLL (SOMEV #l) (v :: vs).
```

- Definition of `is_MLL`
- Proof of constructors, `empty_is_MLL`, `mark_is_MLL`, `cons_is_MLL`
- Proof of induction principle

Outline of our solution

```
1  eiInd                                                                    Coq
2  Inductive is_MLL : val → list val → iProp :=
3    | empty_is_MLL : is_MLL NONEV []
4    | mark_is_MLL v vs l tl :
5      l ↦ (v, #true, tl) -* is_MLL tl vs -*
6      is_MLL (SOMEV #l) vs
7    | cons_is_MLL v vs tl l :
8      l ↦ (v, #false, tl) -* is_MLL tl vs -*
9      is_MLL (SOMEV #l) (v :: vs).
```

- Definition of `is_MLL`
- Proof of constructors, `empty_is_MLL`, `mark_is_MLL`, `cons_is_MLL`
- Proof of induction principle
- Integration with IPM tactics

Approach

Theory

Challenges in practice

Approach

Theory

- Define the pre fixpoint function

Challenges in practice

Approach

Theory

- Define the pre fixpoint function
- Prove monotonicity

Challenges in practice

Approach

Theory

- Define the pre fixpoint function
- Prove monotonicity
- Apply least fixpoint theorem

Challenges in practice

Approach

Theory

- Define the pre fixpoint function
- Prove monotonicity
- Apply least fixpoint theorem

Challenges in practice

- Deal with n -ary predicates

Approach

Theory

- Define the pre fixpoint function
- Prove monotonicity
- Apply least fixpoint theorem

Challenges in practice

- Deal with n -ary predicates
- Proof search for monotonicity

Approach

Theory

- Define the pre fixpoint function
- Prove monotonicity
- Apply least fixpoint theorem

Challenges in practice

- Deal with n -ary predicates
- Proof search for monotonicity
- Integrating resulting definitions and lemmas into the Iris tactics language

Monotone pre fixpoint function

$$\begin{aligned} \text{isMLL } hd \, \vec{v} = & (hd = \mathbf{none} * \vec{v} = []) \vee \\ & (\exists \ell, v', tl. hd = \mathbf{some } l * l \mapsto (v', \mathbf{true}, tl) * \text{isMLL } tl \, \vec{v}) \vee \\ & \left(\begin{array}{l} \exists \ell, v', \vec{v}'', tl. hd = \mathbf{some } l * l \mapsto (v', \mathbf{false}, tl) * \\ \vec{v} = v' :: \vec{v}'' * \text{isMLL } tl \, \vec{v}'' \end{array} \right) \end{aligned}$$

Monotone pre fixpoint function

$$\begin{aligned} \text{isMLL}_F \Phi \text{hd } \vec{v} = & (\text{hd} = \mathbf{none} * \vec{v} = []) \vee \\ & (\exists \ell, \check{v}, tl. \text{hd} = \mathbf{some} \ell * \ell \mapsto (\check{v}, \mathbf{true}, tl) * \Phi \text{tl } \vec{v}) \vee \\ & \left(\begin{array}{l} \exists \ell, \check{v}, \vec{v}'', tl. \text{hd} = \mathbf{some} \ell * \ell \mapsto (\check{v}, \mathbf{false}, tl) * \\ \vec{v} = \check{v} :: \vec{v}'' * \Phi \text{tl } \vec{v}'' \end{array} \right) \end{aligned}$$

Monotone pre fixpoint function

$$\text{isMLL}_F \Phi \text{hd } \vec{v} = (hd = \mathbf{none} * \vec{v} = []) \vee \\ (\exists \ell, \check{v}, tl. hd = \mathbf{some} \ell * \ell \mapsto (\check{v}, \mathbf{true}, tl) * \Phi \text{tl } \vec{v}) \vee \\ \left(\begin{array}{l} \exists \ell, \check{v}, \vec{v}'', tl. hd = \mathbf{some} \ell * \ell \mapsto (\check{v}, \mathbf{false}, tl) * \\ \vec{v} = \check{v} :: \vec{v}'' * \Phi \text{tl } \vec{v}'' \end{array} \right)$$

Definition (Monotonicity)

Function $F: (A \rightarrow B \rightarrow iProp) \rightarrow A \rightarrow B \rightarrow iProp$ is *monotone* when, for any $\Phi, \Psi: A \rightarrow B \rightarrow iProp$, it holds that

$$\Box(\forall x, y. \Phi \text{ } x \text{ } y \multimap \Psi \text{ } x \text{ } y) \vdash \forall x, y. F \Phi \text{ } x \text{ } y \multimap F \Psi \text{ } x \text{ } y$$

Monotone signatures

Definition (Respectful relation)

$$R \Longrightarrow R' \triangleq \lambda f, g. \forall x, y. R x y \multimap R' (f x) (g y)$$

Definition (Pointwise relation)

$$\triangleright R \triangleq \lambda f, g. \forall x. R (f x) (g x)$$

(Sozeau 2009)

Connective	Type	Signature
*	$iProp \rightarrow iProp \rightarrow iProp$	$(\multimap) \Longrightarrow (\multimap) \Longrightarrow (\multimap)$

Monotone signatures

Definition (Respectful relation)

$$R \Longrightarrow R' \triangleq \lambda f, g. \forall x, y. R x y \multimap R' (f x) (g y)$$

Definition (Pointwise relation)

$$\triangleright R \triangleq \lambda f, g. \forall x. R (f x) (g x)$$

(Sozeau 2009)

Connective	Type	Signature
*	$iProp \rightarrow iProp \rightarrow iProp$	$(\multimap) \Longrightarrow (\multimap) \Longrightarrow (\multimap)$
\vee	$iProp \rightarrow iProp \rightarrow iProp$	$(\multimap) \Longrightarrow (\multimap) \Longrightarrow (\multimap)$

Monotone signatures

Definition (Respectful relation)

$$R \Longrightarrow R' \triangleq \lambda f, g. \forall x, y. R x y \multimap R' (f x) (g y)$$

Definition (Pointwise relation)

$$\triangleright R \triangleq \lambda f, g. \forall x. R (f x) (g x)$$

(Sozeau 2009)

Connective	Type	Signature
*	$iProp \rightarrow iProp \rightarrow iProp$	$(\multimap) \Longrightarrow (\multimap) \Longrightarrow (\multimap)$
\vee	$iProp \rightarrow iProp \rightarrow iProp$	$(\multimap) \Longrightarrow (\multimap) \Longrightarrow (\multimap)$
\exists	$(A \rightarrow iProp) \rightarrow iProp$	$\triangleright (\multimap) \Longrightarrow (\multimap)$

Monotone signatures

Definition (Respectful relation)

$$R \Longrightarrow R' \triangleq \lambda f, g. \forall x, y. R x y \multimap R' (f x) (g y)$$

Definition (Pointwise relation)

$$\triangleright R \triangleq \lambda f, g. \forall x. R (f x) (g x)$$

(Sozeau 2009)

Connective	Type	Signature
*	$iProp \rightarrow iProp \rightarrow iProp$	$(\multimap) \Longrightarrow (\multimap) \Longrightarrow (\multimap)$
\vee	$iProp \rightarrow iProp \rightarrow iProp$	$(\multimap) \Longrightarrow (\multimap) \Longrightarrow (\multimap)$
\exists	$(A \rightarrow iProp) \rightarrow iProp$	$\triangleright (\multimap) \Longrightarrow (\multimap)$

Definition (Proper element of a relation)

Given a relation $R: iRel\ A$ and an element $x \in A$, x is a proper element of R if $R x x$.

$$((\multimap) \Longrightarrow (\multimap) \Longrightarrow (\multimap))(\multimap)(\multimap) =$$

$$\forall P, P'. (P \multimap P') \multimap \forall Q, Q'. (Q \multimap Q') \multimap (P * Q) \multimap (P' * Q')$$

Proof search

$$\square (\forall hd \vec{v}. \Phi \, hd \, \vec{v} \multimap \Psi \, hd \, \vec{v}) \multimap$$
$$\left(\begin{array}{l} \forall hd \, \vec{v}. \text{isMLL}_F \, \Phi \, hd \, \vec{v} \multimap \\ \text{isMLL}_F \, \Psi \, hd \, \vec{v} \end{array} \right)$$

Normalization

- Introduce quantifiers and modalities
→ Application step

Application

- Apply reflexivity
- Apply assumption
- Apply signature → Normalization step

Proof search

$$\begin{aligned}
 & (hd = \mathbf{none} * \vec{v} = []) \vee \\
 & \left(\begin{array}{l} \exists \ell, \check{v}, tl. hd = \mathbf{some} \ell * \\ \quad l \mapsto (\check{v}, \mathbf{true}, tl) * \\ \quad \Phi \text{ } tl \vec{v} \end{array} \right) \vee \\
 & \left(\begin{array}{l} \exists \ell, \check{v}, \vec{v}'', tl. hd = \mathbf{some} \ell * \\ \quad l \mapsto (\check{v}, \mathbf{false}, tl) * \\ \quad \vec{v} = \check{v} :: \vec{v}'' * \Phi \text{ } tl \vec{v}'' \end{array} \right)
 \end{aligned}$$

→*

$$\begin{aligned}
 & (hd = \mathbf{none} * \vec{v} = []) \vee \\
 & \left(\begin{array}{l} \exists \ell, \check{v}, tl. hd = \mathbf{some} \ell * \\ \quad l \mapsto (\check{v}, \mathbf{true}, tl) * \\ \quad \Psi \text{ } tl \vec{v} \end{array} \right) \vee \\
 & \left(\begin{array}{l} \exists \ell, \check{v}, \vec{v}'', tl. hd = \mathbf{some} \ell * \\ \quad l \mapsto (\check{v}, \mathbf{false}, tl) * \\ \quad \vec{v} = \check{v} :: \vec{v}'' * \Psi \text{ } tl \vec{v}'' \end{array} \right)
 \end{aligned}$$

Normalization

- Introduce quantifiers and modalities
→ Application step

Application

- Apply reflexivity
- Apply assumption
- Apply signature → Normalization step

Proof search

$$\begin{aligned}
 & (hd = \mathbf{none} * \vec{v} = []) \vee \\
 & \left(\begin{array}{l} \exists \ell, \check{v}, tl. hd = \mathbf{some} \ell * \\ l \mapsto (\check{v}, \mathbf{true}, tl) * \\ \Phi \text{ } tl \vec{v} \end{array} \right) \vee \\
 & \left(\begin{array}{l} \exists \ell, \check{v}, \vec{v}'', tl. hd = \mathbf{some} \ell * \\ l \mapsto (\check{v}, \mathbf{false}, tl) * \\ \vec{v} = \check{v} :: \vec{v}'' * \Phi \text{ } tl \vec{v}'' \end{array} \right)
 \end{aligned}$$

→*

$$\begin{aligned}
 & (hd = \mathbf{none} * \vec{v} = []) \vee \\
 & \left(\begin{array}{l} \exists \ell, \check{v}, tl. hd = \mathbf{some} \ell * \\ l \mapsto (\check{v}, \mathbf{true}, tl) * \\ \Psi \text{ } tl \vec{v} \end{array} \right) \vee \\
 & \left(\begin{array}{l} \exists \ell, \check{v}, \vec{v}'', tl. hd = \mathbf{some} \ell * \\ l \mapsto (\check{v}, \mathbf{false}, tl) * \\ \vec{v} = \check{v} :: \vec{v}'' * \Psi \text{ } tl \vec{v}'' \end{array} \right)
 \end{aligned}$$

Normalization

- Introduce quantifiers and modalities
→ Application step

Application

- Apply reflexivity
- Apply assumption
- Apply signature → Normalization step

$$(-*) \implies (-*) \implies (-*)$$

Proof search

$$(hd = \mathbf{none} * \vec{v} = [])$$
$$\rightarrow *$$
$$(hd = \mathbf{none} * \vec{v} = [])$$

Normalization

- Introduce quantifiers and modalities
→ Application step

Application

- Apply reflexivity
- Apply assumption
- Apply signature → Normalization step

Proof search

$$(hd = \mathbf{none} * \vec{v} = [])$$
$$\rightarrow *$$
$$(hd = \mathbf{none} * \vec{v} = [])$$

Normalization

- Introduce quantifiers and modalities
→ Application step

Application

- Apply reflexivity
- Apply assumption
- Apply signature → Normalization step

Proof search

$$\left(\begin{array}{l} \exists \ell, \checkmark, tl. hd = \mathbf{some} \, l * \\ l \mapsto (\checkmark, \mathbf{true}, tl) * \\ \Phi \, tl \, \vec{v} \end{array} \right) \vee$$

$$\left(\begin{array}{l} \exists \ell, \checkmark, \vec{v}'', tl. hd = \mathbf{some} \, l * \\ l \mapsto (\checkmark, \mathbf{false}, tl) * \\ \vec{v} = \checkmark :: \vec{v}'' * \Phi \, tl \, \vec{v}'' \end{array} \right)$$

→*

$$\left(\begin{array}{l} \exists \ell, \checkmark, tl. hd = \mathbf{some} \, l * \\ l \mapsto (\checkmark, \mathbf{true}, tl) * \\ \Psi \, tl \, \vec{v} \end{array} \right) \vee$$

$$\left(\begin{array}{l} \exists \ell, \checkmark, \vec{v}'', tl. hd = \mathbf{some} \, l * \\ l \mapsto (\checkmark, \mathbf{false}, tl) * \\ \vec{v} = \checkmark :: \vec{v}'' * \Psi \, tl \, \vec{v}'' \end{array} \right)$$

Normalization

- Introduce quantifiers and modalities
→ Application step

Application

- Apply reflexivity
- Apply assumption
- Apply signature → Normalization step

Proof search

$$\left(\begin{array}{l} \exists \ell, \check{v}, tl.hd = \mathbf{some} \, l * \\ l \mapsto (\check{v}, \mathbf{true}, tl) * \\ \Phi \, tl \, \vec{v} \end{array} \right) \vee$$

$$\left(\begin{array}{l} \exists \ell, \check{v}, \vec{v}'', tl.hd = \mathbf{some} \, l * \\ l \mapsto (\check{v}, \mathbf{false}, tl) * \\ \vec{v} = \check{v} :: \vec{v}'' * \Phi \, tl \, \vec{v}'' \end{array} \right)$$

→*

$$\left(\begin{array}{l} \exists \ell, \check{v}, tl.hd = \mathbf{some} \, l * \\ l \mapsto (\check{v}, \mathbf{true}, tl) * \\ \Psi \, tl \, \vec{v} \end{array} \right) \vee$$

$$\left(\begin{array}{l} \exists \ell, \check{v}, \vec{v}'', tl.hd = \mathbf{some} \, l * \\ l \mapsto (\check{v}, \mathbf{false}, tl) * \\ \vec{v} = \check{v} :: \vec{v}'' * \Psi \, tl \, \vec{v}'' \end{array} \right)$$

Normalization

- Introduce quantifiers and modalities
→ Application step

Application

- Apply reflexivity
- Apply assumption
- Apply signature → Normalization step
 $(-*) \implies (-*) \implies (-*)$

Proof search

$$\begin{aligned} &\Box (\forall hd \vec{v}. \Phi \text{ } hd \vec{v} \multimap \Psi \text{ } hd \vec{v}) \\ &\vdash \Phi \text{ } t / \vec{v} \multimap \Psi \text{ } t / \vec{v} \end{aligned}$$

Normalization

- Introduce quantifiers and modalities
→ Application step

Application

- Apply reflexivity
- Apply assumption
- Apply signature → Normalization step

Proof search

$$\square (\forall hd \vec{v}. \Phi hd \vec{v} \multimap \Psi hd \vec{v})$$
$$\vdash \Phi t / \vec{v} \multimap \Psi t / \vec{v}$$

Normalization

- Introduce quantifiers and modalities
→ Application step

Application

- Apply reflexivity
- Apply assumption
- Apply signature → Normalization step

Least fixpoint

Theorem (Least fixpoint)

Given a monotone function $F: (A \rightarrow iProp) \rightarrow A \rightarrow iProp$, called the *pre fixpoint function*, there exists the *least fixpoint*

$$\mu F: A \rightarrow iProp \triangleq \lambda F x. \forall \Phi. \Box(\forall y. F \Phi y \multimap \Phi y) \multimap \Phi x$$

such that

- 1 The fixpoint equality holds

$$\mu F x \dashv\vdash F(\mu F) x$$

- 2 The iteration property holds

$$\Box(\forall y. F \Phi y \multimap \Phi y) \vdash \forall x. \mu F x \multimap \Phi x$$

Elpi

- λ Prolog dialect (Dunchev, Guidi, Coen, and Tassi 2015)


Elpi

- λ Prolog dialect (Dunchev, Guidi, Coen, and Tassi 2015)
- Coq meta-programming language (Tassi 2018)


Elpi

- λ Prolog dialect (Dunchev, Guidi, Coen, and Tassi 2015)
- Coq meta-programming language (Tassi 2018)
- Derive (Tassi 2019)
- Hierarchy Builder (Cohen, Sakaguchi, and Tassi 2020)
- Trocq (Cohen, Crance, and Mahboubi 2024)

Outline of implementation



Outline of implementation



Coq-Elpi HOAS

1

```
val → list val → iProp
```

Coq

Coq-Elpi HOAS

1 `val → list val → iProp`

Coq

1 `∀ _:val. ∀ _:list val. iProp`

Coq

Coq-Elpi HOAS

```
1 val → list val → iProp
```

Coq

```
1 ∀ _:val. ∀ _:list val. iProp
```

Coq

```
1 prod `_` (global (indt «val»))
2   c0 \
3     prod `_` (app [global (indt «list»),
4                   global (indt «val»)]
5     c1 \
6       app [global (indt «uPred»),
7            app [global (const «iResUR»),
8                global (const «Σ»)]])
```

Elpi

Generating terms

```
1  ∀ _:val. ∀ _:list val. iProp      Coq
```

$$\Box(\triangleright \triangleright (-*)) \implies \triangleright \triangleright (-*)$$

```
1  pred type->signature i:term, i:term, o:term.
2  type->signature PreFixF Type Proper :-
3      type->signature.aux Type P,
4      coq.elaborate-skeleton
5          {{ IProp (□▷ lp:P ==> lp:P) lp:PreFixF }}
6          {{ Prop }} Proper ok.
7
8  pred type->signature.aux i:term, o:term.
9  type->signature (prod N T F) {{ .> lp:P }} :-
10     pi x\ type->signature.aux (F x) P.
11  type->signature {{ iProp }} {{ bi_wand }}.
```

Elpi

Generating terms

1 $\forall _:\text{val}. \forall _:\text{list val}. \text{iProp}$ Coq $\square(\triangleright \triangleright (-*)) \implies \triangleright \triangleright (-*)$

1 **pred** type->signature **i:term**, **i:term**, **o:term**. Elpi
 2 type->signature PreFixF Type Proper :-
 3 type->signature.aux Type P,
 4 coq.elaborate-skeleton
 5 {{ IProp (□▷ **lp:P** ==> **lp:P**) **lp:PreFixF** }}
 6 {{ Prop }} Proper ok.
 7
 8 **pred** type->signature.aux **i:term**, **o:term**.
 9 type->signature (prod N T F) {{ .> **lp:P** }} :-
 10 **pi** x\ type->signature.aux (F x) P.
 11 type->signature {{ iProp }} {{ bi_wand }}.

Generating terms

```
1  ∀ _:val. ∀ _:list val. iProp      Coq
```

$$\Box(\triangleright \triangleright (-*)) \implies \triangleright \triangleright (-*)$$

```
1  pred type->signature i:term, i:term, o:term.      Elpi
2  type->signature PreFixF Type Proper :-
3  type->signature.aux Type P,
4  coq.elaborate-skeleton
5  {{ IProp (□▷ lp:P ==> lp:P) lp:PreFixF }}
6  {{ Prop }} Proper ok.
7
8  pred type->signature.aux i:term, o:term.
9  type->signature (prod N T F) {{ .> lp:P }} :-
10     pi x\ type->signature.aux (F x) P.
11 type->signature {{ iProp }} {{ bi_wand }}.
```

Generating terms

```
1  ∀ _:val. ∀ _:list val. iProp      Coq
```

$$\Box(\triangleright \triangleright (-*)) \implies \triangleright \triangleright (-*)$$

```
1  pred type->signature i:term, i:term, o:term.
2  type->signature PreFixF Type Proper :-
3      type->signature.aux Type P,
4      coq.elaborate-skeleton
5          {{ IProp (□▷ lp:P ==> lp:P) lp:PreFixF }}
6          {{ Prop }} Proper ok.
7
8  pred type->signature.aux i:term, o:term.
9  type->signature (prod N T F) {{ .> lp:P }} :-
10     pi x\ type->signature.aux (F x) P.
11 type->signature {{ iProp }} {{ bi_wand }}.
```

Elpi

Generating terms

```
1  ∀ _:val. ∀ _:list val. iProp      Coq
```

$$\Box(\triangleright \triangleright (*)) \implies \triangleright \triangleright (*)$$

```
1  pred type->signature i:term, i:term, o:term.
2  type->signature PreFixF Type Proper :-
3      type->signature.aux Type P,
4      coq.elaborate-skeleton
5          {{ IProp (□▷ lp:P ==> lp:P) lp:PreFixF }}
6          {{ Prop }} Proper ok.
7
8  pred type->signature.aux i:term, o:term.
9  type->signature (prod N T F) {{ .> lp:P }} :-
10     pi x\ type->signature.aux (F x) P.
11 type->signature {{ iProp }} {{ bi_wand }}.
```

Elpi

Generating terms

```
1  ∀ _:val. ∀ _:list val. iProp      Coq
```

$$\Box(\triangleright \triangleright (-*)) \implies \triangleright \triangleright (-*)$$

```
1  pred type->signature i:term, i:term, o:term.
2  type->signature PreFixF Type Proper :-
3      type->signature.aux Type P,
4      coq.elaborate-skeleton
5          {{ IProp (□▷ lp:P ==> lp:P) lp:PreFixF }}
6          {{ Prop }} Proper ok.
7
8  pred type->signature.aux i:term, o:term.
9  type->signature (prod N T F) {{ .> lp:P }} :-
10     pi x\ type->signature.aux (F x) P.
11  type->signature {{ iProp }} {{ bi_wand }}.
```

Elpi

Generating terms

```
1  ∀ _:val. ∀ _:list val. iProp      Coq
```

$$\Box(\triangleright \triangleright (-*)) \implies \triangleright \triangleright (-*)$$

```
1  pred type->signature i:term, i:term, o:term.      Elpi
2  type->signature PreFixF Type Proper :-
3    type->signature.aux Type P,
4    coq.elaborate-skeleton
5      {{ IProper (□> lp:P ==> lp:P) lp:PreFixF }}
6      {{ Prop }} Proper ok.
7
8  pred type->signature.aux i:term, o:term.
9  type->signature (prod N T F) {{ .> lp:P }} :-
10    pi x\ type->signature.aux (F x) P.
11  type->signature {{ iProp }} {{ bi_wand }}.
```

Generating proofs

- Proofs are also just terms

Generating proofs

- Proofs are also just terms
- Other Elpi projects just generate proof terms using roughly the previous method

Generating proofs

- Proofs are also just terms
- Other Elpi projects just generate proof terms using roughly the previous method
- We reuse the IPM lemmas written for its tactics

Generating proofs

- Proofs are also just terms
- Other Elpi projects just generate proof terms using roughly the previous method
- We reuse the IPM lemmas written for its tactics
- We develop a strategy for modular proof term generators which employ the Coq API

Generating proofs

- Proofs are also just terms
- Other Elpi projects just generate proof terms using roughly the previous method
- We reuse the IPM lemmas written for its tactics
- We develop a strategy for modular proof term generators which employ the Coq API
- These modular proof term generators are also repackaged into a new set of IPM tactics, e.g. `eIIntros` (Elpi Iris Intros).

Composing proof generators

```
1  hd : val
2  vs : list val
3  -----
4  is_MLL_pre is_MLL hd vs  $\dashv$  is_MLL hd vs
```

Coq

```
1  pred mk-unfold.proof i:int, i:term, i:term, i:hole.
2  mk-unfold.proof Ps Unfold1 Unfold2 H :-
3    do-iStartProof H (ihole N H'), !,
4    do-iAndSplit H' H1 H2,
5    std.map {std.iota Ps} (x\r\ r = {{ _ }}) Holes1, !,
6    do-iApplyLem (app [Unfold1 | Holes1]) (ihole N H1) [] [], !,
7    std.map {std.iota Ps} (x\r\ r = {{ _ }}) Holes2, !,
8    do-iApplyLem (app [Unfold2 | Holes2]) (ihole N H2) [] [].
```

Elpi

Demo

Conclusion

- Created a system for defining and using inductive predicates in the IPM

Conclusion

- Created a system for defining and using inductive predicates in the IPM
- Posed a strategy for defining modular tactics in Elpi

Conclusion

- Created a system for defining and using inductive predicates in the IPM
- Posed a strategy for defining modular tactics in Elpi
- Posed a syntactic proof search algorithm for finding a monotonicity proof of a pre fixpoint function

Conclusion

- Created a system for defining and using inductive predicates in the IPM
- Posed a strategy for defining modular tactics in Elpi
- Posed a syntactic proof search algorithm for finding a monotonicity proof of a prefixpoint function
- Evaluated Elpi as a meta-programming language for the IPM

Questions

Future work

- Non-expansive predicates
- Other fixpoint predicates
- Nested inductive predicates
- Mutual inductive predicates

Holes in proofs

Elpi

```

1  kind hole type.
2  type hole term -> term -> hole.
3
4  pred do-iAndSplit i:hole, o:hole, o:hole.
5  do-iAndSplit (hole Type Proof) (hole LType LProof)
6              (hole RType RProof) :-
7      @no-tc! => coq.elaborate-skeleton
8              {{ tac_and_split _ _ _ _ _ _ }}
9              Type Proof ok,
10     Proof = {{ tac_and_split _ _ _
11                  lp:FromAnd lp:LProof lp:RProof }},
12     coq.ltac.collect-goals FromAnd [G1] _,
13     open tc_solve G1 [],
14     coq.typecheck LProof LType ok,
15     coq.typecheck RProof RType ok.

```

Monotonicity as a signature

Definition (Proper element of a relation (Sozeau 2009))

Given a relation $R: iRel\ A$ and an element $x \in A$, x is a proper element of R if $R\ x\ x$.

Monotonicity as a signature

Definition (Proper element of a relation (Sozeau 2009))

Given a relation $R: iRel\ A$ and an element $x \in A$, x is a proper element of R if $R\ x\ x$.

Definition (Respectful relation)

$$R \Longrightarrow R' \triangleq \lambda f, g. \forall x, y. R\ x\ y \multimap R'\ (f\ x)\ (g\ y)$$

Definition (Pointwise relation)

$$\triangleright R \triangleq \lambda f, g. \forall x. R\ (f\ x)\ (g\ x)$$

Definition (Persistent relation)

$$\Box R \triangleq \lambda x, y. \Box (R\ x\ y)$$

Monotonicity as a signature

Definition (Proper element of a relation (Sozeau 2009))

Given a relation $R: iRel\ A$ and an element $x \in A$, x is a proper element of R if $R\ x\ x$.

Definition (Respectful relation)

$$R \Longrightarrow R' \triangleq \lambda f, g. \forall x, y. R\ x\ y \multimap R'\ (f\ x)\ (g\ y)$$

Definition (Pointwise relation)

$$\triangleright R \triangleq \lambda f, g. \forall x. R\ (f\ x)\ (g\ x)$$

Definition (Persistent relation)

$$\Box R \triangleq \lambda x, y. \Box(R\ x\ y)$$

$$\text{isMLL}_F: (Val \rightarrow List\ Val \rightarrow iProp) \rightarrow \\ Val \rightarrow List\ Val \rightarrow iProp$$

$$\Box (\forall hd\ \vec{v}. \Phi\ hd\ \vec{v} \multimap \Psi\ hd\ \vec{v}) \multimap \\ \left(\forall hd\ \vec{v}. \begin{array}{l} \text{isMLL}_F\ \Phi\ hd\ \vec{v} \multimap \\ \text{isMLL}_F\ \Psi\ hd\ \vec{v} \end{array} \right)$$

Monotonicity as a signature

Definition (Proper element of a relation (Sozeau 2009))

Given a relation $R: iRel\ A$ and an element $x \in A$, x is a proper element of R if $R\ x\ x$.

Definition (Respectful relation)

$$R \Longrightarrow R' \triangleq \lambda f, g. \forall x, y. R\ x\ y \multimap R' (fx) (gy)$$

Definition (Pointwise relation)

$$\triangleright R \triangleq \lambda f, g. \forall x. R (fx) (gx)$$

Definition (Persistent relation)

$$\Box R \triangleq \lambda x, y. \Box (R\ x\ y)$$

$$\text{isMLL}_F: (Val \rightarrow List\ Val \rightarrow iProp) \rightarrow \\ Val \rightarrow List\ Val \rightarrow iProp$$

$$\Box (\forall hd\ \vec{v}. \Phi\ hd\ \vec{v} \multimap \Psi\ hd\ \vec{v}) \multimap \\ \left(\begin{array}{c} \forall hd\ \vec{v}. \text{isMLL}_F\ \Phi\ hd\ \vec{v} \multimap \\ \text{isMLL}_F\ \Psi\ hd\ \vec{v} \end{array} \right)$$

$$\Box (\triangleright \triangleright (-*)) \Longrightarrow \triangleright \triangleright (-*)$$