

PART A

30 May 2016.

Q1.

```
SELECT u.user_id,  
       u.user_name,  
       s.subscription_id,  
       s.start_date
```

```
FROM users u
```

```
INNER JOIN subscriptions s
```

```
ON u.user_id = s.user_id;
```

Q2

```
SELECT v.session_id,  
       v.user_id,  
       sh.show_title,  
       sh.genre,  
       v.watch_minutes
```

```
FROM viewing_session v
```

```
INNER JOIN shows sh
```

```
ON v.show_id = sh.show_id;
```

Q4

```
SELECT u.user_name,  
       u.country,  
       v.session_id,  
       v.show_id,  
       v.show_minutes
```

```
FROM users u
```

```
INNER JOIN viewing_sessions v
```

```
ON u.user_id = v.user_id;
```

Q.5

```
SELECT u.user_name,  
       u.country,  
       p.plan_name,  
       p.monthly_price,  
       s.start_date
```

FROM users u

INNER JOIN Subscriptions s

ON u.user_id = s.user_id

INNER JOIN plans p

ON s.plan_id = p.plan_id;

PART B, Left JOIN

Q6

```
SELECT u.user_id,  
       u.user_name,  
       s.subscription_id,  
       s.start_date
```

FROM users u

LEFT JOIN Subscriptions s

ON u.user_id = s.user_id;

Q7

```
SELECT p.plan_id,  
       p.plan_name,  
       s.subscription_id,  
       s.user_id
```

FROM plans p

LEFT JOIN Subscriptions s

ON p.plan_id = s.plan_id;

Q8.

```
SELECT sh.show_id,  
       sh.session_id,  
       v.watch_minutes
```

FROM show sh

LEFT JOIN viewing-session v

ON sh.show_id = v.show_id;

Q.9

```
SELECT v.session_id,  
       v.show_id,  
       v.watch_minutes,  
       u.user_id,  
       u.user_name
```

FROM viewing-sessions v

LEFT JOIN users u

ON v.users_id = u.user_id;

Q.10

```
SELECT u.user_name,  
       u.country,  
       p.plan_name,  
       p.monthly_price
```

FROM users u

LEFT JOIN subscriptions

ON u.users_id = s.users_id

LEFT JOIN plan p

ON s.plan_id = p.plan_id;

Q.11

```

SELECT u.user_id,
       u.user_name,
       s.subscription_id,
       s.start_date

```

```

FROM users u
FULL OUTER JOIN subscriptions s
ON u.user_id = s.user_id;

```

Q.12

```

SELECT p.plan_id,
       p.plan_name,
       s.subscription_id,
       s.user_id

```

```

FROM plans p
FULL OUTER JOIN subscriptions s
ON p.plan_id = s.plan_id;

```

Q. Pivot table.

- day class column.
- month_name rows.
- values given as user_id.

Insert.

Graph.

Blank.

Q.13

```

SELECT sh.show_id,
       sh.show_title,
       v.session_id,
       v.watch_minutes

```

```

FROM shows sh
FULL OUTER JOIN viewing_session v
ON sh.show_id = v.show_id;

```

Q.14

```

SELECT u.user_id,
       u.user_name,
       v.session_id,
       v.show_id,
       v.watch_minutes

```

```

FROM users u
FULL OUTER JOIN viewing_session v
ON u.user_id = v.user_id;

```