


COMP-248

Object Oriented Programming I



Lecture 05:

Arithmetic and Assignment Operators

Emad Shihab, PhD

Parts of the slides are taken from Prof. L. Kosseim

In this chapter, we will see...

1. Comments
2. Identifiers
3. Indentation
4. Primitive Types
5. Variables
6. Output & Input
7. Assignment
8. **(more)** Arithmetic Expressions
9. **(now)** More Assignment Operators
10. **(now)** Assignment Compatibility
11. Strings

8- Arithmetic Expressions

- An *expression* is a combination of one or more operands and their operators
- *Arithmetic operators*:

Addition	+
Subtraction	-
Multiplication	*
Division	/
Remainder	%

Operator Precedence (p 24)

- Operators can be combined into complex expressions

```
result = total + count / max - offset;
```

- precedence determines the order of evaluation
 - 1st: expressions in parenthesis
 - 2nd: unary + and -
 - 3rd: multiplication, division, and remainder
 - 4th: addition, subtraction, and string concatenation
 - 5th: assignment operator

Operator Associativity

- Unary operators of equal precedence are grouped right-to-left

`+-+rate` is evaluated as `+(-(+rate))`

- Binary operators of equal precedence are grouped left-to-right

`base + rate + hours` is evaluated as
`(base + rate) + hours`

- **Exception:** A string of assignment operators is grouped right-to-left

`n1 = n2 = n3;` is evaluated as `n1 = (n2 = n3);`

Example

- What is the order of evaluation in the following expressions?

$a + b + c + d + e$

$a + b * c - d / e$

$(a + (b * c)) - (d / e)$

$a / (b + c) - d \% e$

$(a / (b + c)) - (d \% e)$


$a / (b * (c + (d - e)))$

$a / (b * (c + (d - e)))$

Assignment Revisited

- The assignment operator has a lower precedence than the arithmetic operators

First the expression on the RHS is evaluated



Then the result is stored in the variable on the LHS

Just checking...

- What is stored in the integer variable `num1` after this statement?

```
num1 = 2 + 3 * 5 - 5 * 2 / 5 + 10 ;
```

- A. 0
- B. 18
- C. 25
- D. 10

In this chapter, we will see...

1. Comments
2. Identifiers
3. Indentation
4. Primitive Types
5. Variables
6. Output & Input
7. Assignment
8. (more) Arithmetic Expressions
9. (now) **More Assignment Operators**
10. (now) Assignment Compatibility
11. Strings

9- More assignment operators

- in addition to =, often we perform an operation on a variable, and then store the result back into that variable
- Java has shortcut assignment operators:

`variable = variable operator expression;`
`variable operator = expression;`

<u>Operator</u>	<u>Example</u>	<u>Equivalent To</u>
<code>+=</code>	<code>x += y</code>	<code>x = x + y</code>
<code>-=</code>	<code>x -= y</code>	<code>x = x - y</code>
<code>*=</code>	<code>x *= y</code>	<code>x = x * y</code>
<code>/=</code>	<code>x /= y</code>	<code>x = x / y</code>
<code>%=</code>	<code>x %= y</code>	<code>x = x % y</code>

Shorthand Assignment Statements

Example:	Equivalent To:
<code>sum -= discount;</code>	<code>sum = sum - discount;</code>
<code>time /= rushFactor;</code>	<code>time = time / rushFactor;</code>
<code>amount *= count1 + count2;</code>	<code>amount = amount * (count1 + count2);</code>

Assignment operators

- The behavior of some assignment operators depends on the types of the operands
- ex: the +=
 - If the operands are strings, += performs string concatenation
 - The behavior of += is consistent with the behavior of the "regular" +

Example

```
int amount = 10;  
amount += 5;  
System.out.println(amount);
```

```
double temp = 10.0;  
temp *= 10;  
System.out.println(temp);
```

```
String word = "hello ";  
word += "bye";  
System.out.println(word);  
word *= "bye"; // ???
```

```
15  
100.0  
hellobye
```

Output

Increment and Decrement

- In Java, we often add-one or subtract-one to a variable...
- 2 shortcut operators:
 - The *increment operator* (`++`) adds one to its operand
 - The *decrement operator* (`--`) subtracts one from its operand
- The statement: `count++;`
is functionally equivalent to: `count = count+1;`
- The statement: `count--;`
is functionally equivalent to: `count = count-1;`

Increment and Decrement

- The increment and decrement operators can be used in expressions in two forms:
 1. **in prefix form: ++count;**
 1. the variable is incremented/decremented by 1
 2. the value of the entire expression is the **new** value of the variable (**after** the incrementation/decrementation)
 2. **in postfix form: count++;**
 1. the variable is incremented/decremented by 1
 2. the value of the entire expression is the **old** value of the variable (**before** the incrementation/decrementation)

Example

```
int nb = 50;  
++nb;
```

51
value of nb

```
int nb = 50;  
nb++;
```

51
value of nb

```
int nb = 50;  
int x;  
x = ++nb;
```

nb = 51
x = 51
value of nb & x

```
int nb = 50;  
int x;  
x = nb++;
```

nb = 51
x = 50
value of nb & x

```
int nb = 50;  
int x;  
x = nb++ + 10;
```

nb = 51
x = 60
value of nb & x

Just checking...

What is stored in the integer variables `num1`, `num2` and `num3` after the following statements?

```
num1 = 1;  
num2 = 0;  
num3 = 2 * num1++ + --num2 * 5;
```

- A. `num1 = 1, num2 = 0, num3 = 2`
- B. `num1 = 1, num2 = 0, num3 = -1`
- C. `num1 = 2, num2 = -1, num3 = 2`
- D. `num1 = 2, num2 = -1, num3 = -1`
- E. `num1 = 2, num2 = -1, num3 = -3`

Summary of ++ and --

<u>Expression</u>	<u>Operation</u>	<u>Value Used in Expression</u>
<code>count++</code>	add 1	old value
<code>++count</code>	add 1	new value
<code>count--</code>	subtract 1	old value
<code>--count</code>	subtract 1	new value

In this chapter, we will see...

1. Comments
2. Identifiers
3. Indentation
4. Primitive Types
5. Variables
6. Output & Input
7. Assignment
8. (more) Arithmetic Expressions
9. (now) More Assignment Operators
10. (now) **Assignment Compatibility**
11. Strings

10 - Assignment Compatibility

- In general, the value of one type cannot be stored in a variable of another type

```
int intValue = 2.99; //Illegal
```

- However, there are exceptions to this

```
double doubleVariable = 2;
```

- For example, an `int` value can be stored in a `double` type

Assignment Compatibility

- an expression has a value and a type

2	/	4	(value = 0, type = int)
2	/	4.0	(value = 0.5, type = double)

- the type of the expression depends on the type of its operands
- In Java, type conversions can occur in 3 ways:
 - arithmetic promotion
 - assignment conversion
 - casting


Arithmetic promotion

- happens automatically, if the operands of an expression are of different types

```
aLong + anInt * aDouble
```

- operands are promoted so that they have the same type
- promotion rules:
 - if 1 operand is of type... the others are promoted to...

double	double
float	float
long	long
 - short, byte and char are always converted to int



Examples

- value and type of these expressions?

2 / 4		
int / int		2/4
int		0

2 / 4 * 1.0		
int/int * double		0*1.0
double		0.0

1.0 * 2 / 4		
double * int/int		2.0/4
double		0.5

Assignment conversions

- occurs when an expression of one type is assigned to a variable of another type

```
var = expression;
```

- *widening* conversion
 - if the variable has a wider type than the expression
 - then, the expression is widened automatically

```
long aVar;  
aVar = 5+5;
```

```
byte aByte;  
int anInt;  
anInt = aByte;
```

```
double aDouble;  
int anInt = 10;  
aDouble = anInt;
```

- int & floating point types are compatible
- **boolean** are not compatible with any type

Assignment conversions


- *narrowing* conversion
 - if the variable has a smaller type than the expression
 - then, compilation error, because possible loss of information

```
int aVar;  
aVar = 3.7; ok?
```

```
int aVar;  
aVar = 10/4; ok?
```

```
int aVar;  
aVar = 10.0/4; ok?
```

Casting



- the programmer can explicitly force a type conversion
- syntax: `(desired_type) expression_to_convert`

```
int aVar;  
aVar = (int)3.7;  
(aVar is 3... not 4!)
```

```
byte aByte;  
int anInt = 75;  
aByte = anInt; // ok?  
aByte = (byte)anInt; // ok?
```

```
double d;  
d = 2/4; // d is 0  
d = (double)2/4; // d is 0.5 (2.0 / 4)  
d = (double)(2/4); // d is 0.0
```

Casting can be dangerous! you better know what you're doing...

```
byte aByte;  
int anInt = 75000;  
aByte = (byte)anInt; // ok  
System.out.print(aByte); // -8!
```

Question

In this chapter, we have seen...

- ✓ Comments
- ✓ Identifiers
- ✓ Indentation
- ✓ Primitive Types
- ✓ Variables
- ✓ Output
- ✓ Assignment
- ✓ Arithmetic Expressions
- ✓ More Assignment Operators
- ✓ Assignment Compatibility
- ✓ Strings

