ECC100

Cam5MP Dome IP67

Cloud Managed AI Outdoor Dome with 256GB Storage

Overview

The EnGenius Cloud Camera Cam5MP Dome (ECC100) is a cloud-managed outdoor surveillance solution for SMBs seeking scalable security. It enables seamless remote monitoring via the cloud dashboard and mobile app. This camera includes 256GB of built-in storage for reliable HD video recording, reducing reliance on traditional NVRs. Enhanced with a 5MP Sony Starvis sensor with HDR, a 132° viewing angle, and a 20m IR range, it delivers clear imaging in all lighting conditions. IP67 and IK10-rated, it is built to withstand harsh environments. Advanced AI technology detects unusual people and vehicles in real time, triggering instant alerts and enabling AI-powered searches to reduce footage review time from hours to minutes.

- Cloud Dashboard Management and Mobile App monitoring anywhere
- 5MP Sony Starvis sensor with HDR of crystal-clear image quality day and night
- Wide view angles of 132° and long IR distance of 20m fit a complicated environment
- Camera durable 256GB storage for event and continuous recording 24x7
- IP67 and IK10 for tough weather and vandal-resistant
- AI NPU of people and vehicle detection for instant alert, search, and statistics

Technical Specifications

Optics

Sensor
1/2.8 " Sony Starvis 5MP CMOS

Lens
Fixed 3.16mm

View Angle
H: 102°, V: 71.6°, D: 132°

Night Vision
Built-in IR LED illumination and IR cut filter

IR Distance
>20m / 66ft

Lens Adjustment Range
Manual, Pan: 0° ~ 350°, Tilt: 0° ~ 90°, Roll: 0° ~ 350°

Video

Resolution
5MP 2592 x 1944 (4:3)

Frame Rate
20 FPS

Video Compression
H.265, H.264

Streaming Bitrate
768Kbps ~ 2.5Mbps (Optional)

Video Processing
AE, AWB, AGC, BLC, HLC, WDR, HDR, 3DNR, Privacy Mask, OSD, Video Orientation

Audio

Audio Format
AAC, G.711

Microphone
Built-in, 5m / 15ft distance

Speaker
Not supported

Advanced AI Analytics

AI NPU
Built-in

People Detection and Tracking
History search, People counting

Vehicle Detection and Tracking
History search, Vehicle counting

Tampering Detection
Event alert

Restricted Area Detection
Event alert, Object counting

Cross Line Detection
Event alert, Object counting

EnGenius Cloud AI
Support

Storage

Storage Size
256GB on board

Retention Method
24/7 seamless, Auto Recycling

Retention Days
Based on video quality and bitrate: 22 days (Good 768kbps), 20 days (Better 1.5Mbps), 10 days (Best 2Mbps)

Storage Redundancy
Support EnGenius NVS and Cloud storage

System

LED Indicator
System power and status indicator

RTSP
Supported

Reset Button
Internal

Networking Interface
10/100 MbE RJ45 port

Power Method
PoE 802.3af Class 3

Max. Power Consumption
6.5W

Operating Temperature
-20°C ~ 50°C / -4°F ~ 122°F

Humidity
98%

Certifications
CE, FCC

Mechanical

Enclosure Material
Aluminum alloy, Polycarbonate

Weatherproofing
IP67

Resistance
IK10

Dimensions
Ø121.7 x 94.8 mm (Ø4.79 x 3.73")

Weight
525g / 18.5oz

Management Software

Web Browser
Chrome, Safari, Edge

Mobile App
Cloud To-Go on iOS and Android

Hardware Overview

Reset Button

Lens

Microphone

Light Sensor

IR LEDs

PoE In

LED Indicator

Features and specifications subject to change without notice. Trademarks and registered trademarks are the property of their respective owners. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at his/her own expense. Prior to installing any surveillance equipment, it is your responsibility to ensure the installation is in compliance with local, state and federal video and audio surveillance and privacy laws.

Version 1.1 03/25/2026