Nondimentionalization

seto

Sun 31$^{\text{st}}$ May, 2015 12:07 Noon

Force balance equation

The following force balance equation is considered here;

$$\boldsymbol{F}_{\text{H}} + \boldsymbol{F}_{\text{R}} = 0. \tag{1}$$

The hydrodynamic interaction is assumed to be linear form of velocities.

$$\boldsymbol{F}_{\text{H}} = -\boldsymbol{R} \cdot \boldsymbol{U}. \tag{2}$$

Representative quantities

From shear rate

Particle radius is commonly considered as the representative length in our particle simulations: $L^* = a$.

One way to give the representative particle velocity in a sheared suspension is

$$U_{\text{H}}^* = a\dot{\gamma}. \tag{3}$$

The typical hydrodynamic force is given by the typical velocity U_{H}^* and Stokes-drag form;

$$F_{\text{H}}^* = 6\pi\eta_0 a U_{\text{H}}^*. \tag{4}$$

Here, we indicate nondimensionalized variables in the hydrodynamic unit by using 'tilde', i.e., $\boldsymbol{F}_{\text{H}} = F_{\text{H}}^* \tilde{\boldsymbol{F}}_{\text{H}}$, etc.

[note] F_{H}^* is a function of shear rate $\dot{\gamma}$. Therefore, (1) it is not constant in the stress controlled simulation. (2) If system is not sheared, F_{H}^* is zero and useless.

From repulsive force

The repulsive force $\boldsymbol{F}_{\text{R}}$ is a function of particle-to-particle distance. We take the amplitude F_{R}^* to represent the typical strength:

$$\boldsymbol{F}_{\text{R}} = F_{\text{R}}^* \hat{\boldsymbol{F}}_{\text{R}}, \tag{5}$$

where 'hat' indicates nondimensionalized variables based on this repulsive force. The corresponding velocity can also be given via the Stokes-drag form;

$$U_R^* = \frac{F_R^*}{6\pi\eta_0 a}. \tag{6}$$

Hydrodynamic (or shear-rate) unit

In the hydrodynamic unit, the nondimensionalized force balance equation is

$$\frac{\boldsymbol{F}_H}{F_H^*} + \frac{\boldsymbol{F}_R}{F_H^*} = 0 \quad \Longrightarrow \quad -\boldsymbol{R}' \cdot \tilde{\boldsymbol{U}} + \tilde{\boldsymbol{F}}_R = 0 \tag{7}$$

where $\boldsymbol{R}' \equiv \boldsymbol{R}/6\pi\eta_0 a$.

In order to see the shear rate dependence, it is convenient to represent the typical repulsive force F_R^*.

$$-\tilde{\boldsymbol{R}} \cdot \tilde{\boldsymbol{U}} + \frac{1}{\alpha}\hat{\boldsymbol{F}}_R = 0 \tag{8}$$

This α indicates the competition between two forces:

$$\alpha \equiv \frac{\boldsymbol{F}_H^*}{\boldsymbol{F}_R^*} = \frac{\dot{\gamma}}{F_R^*/6\pi\eta_0 a^2} \tag{9}$$

The unit of time is

$$t_H^* \equiv \frac{L^*}{U_H^*} = \frac{1}{\dot{\gamma}}. \tag{10}$$

Therefore, the nondenominational time $\tilde{t}$ is shear strain (when shear rate is constant):

$$\tilde{t} = \frac{t}{t_H^*} = t\dot{\gamma} \tag{11}$$

The nondimensionalized shear rate is

$$\tilde{\dot{\gamma}} = \dot{\gamma}t_H^* = 1 \tag{12}$$

[note] We call this unit system "hydrodynamic". But, the essential origin for this unit system is the way to give typical velocity, i.e., $U^* = a\dot{\gamma}$. "Simple shear" unit would be more proper name.

Repulsive force unit

In the repulsive unit, the nondimensionalized force balance equation is

$$\frac{\boldsymbol{F}_H}{F_R^*} + \frac{\boldsymbol{F}_R}{F_R^*} = 0 \quad \Longrightarrow \quad -\boldsymbol{R}' \cdot \hat{\boldsymbol{U}} + \hat{\boldsymbol{F}}_R = 0 \tag{13}$$

2

The time unit is

$$t_R^* \equiv \frac{L^*}{U_R^*} = \frac{6\pi\eta_0 a^2}{F_R^*} \tag{14}$$

The nondimensionalized shear rate is

$$\hat{\dot{\gamma}} = \dot{\gamma} t_R^* = \alpha \tag{15}$$

In rate controlled simulations, the relation between the nondimensionalized time $\hat{t} \equiv t/t_R^*$ and shear strain is

$$\gamma \equiv \dot{\gamma} t = \dot{\gamma} t_R^* \hat{t} = \frac{F_H^*}{F_R^*} \hat{t} = \alpha \hat{t} \tag{16}$$

where α is defined in (9).

In stress controlled simulations, the strain is simply given by

$$\gamma = \int^t \dot{\gamma} dt = \int^t \alpha d\hat{t}. \tag{17}$$

Simulation data

Hydrodynamic (or shear-rate) unit

ND time	$\tilde{t}$
strain	$\gamma = \tilde{t}$
relative viscosity	$\eta_r = 6\pi\tilde{\sigma}$
ND shear rate	1
ND stress	$\tilde{\sigma}$

Repulsive force unit

ND time	$\hat{t}$
strain	γ
relative viscosity	$\eta_r = 6\pi\hat{\sigma}/\alpha$
ND shear rate	$\hat{\dot{\gamma}} = \alpha$
ND stress	$\hat{\sigma}$