



A comprehensive survey on intrusion detection in internet of medical things: Datasets, federated learning, blockchain, and future research directions

Syed Rizwan Hassan^a, Muhammad Usama Tanveer^b, Sunil Prajapat^c,
Mohammad Shabaz^{d,*}

^a Department of Computer Engineering, Gachon University, Seongnam-si 13120, South Korea

^b Institute of Information Technology, Khwaja Fareed University of Engineering and Information Technology, Rahim Yar Khan, 64200, Pakistan

^c Department of Computer Engineering-AI & Big Data, Marwadi University, 360003, India

^d Marwadi University Research Center, Department of Computer Engineering, Faculty of Engineering and Technology, Marwadi University, Rajkot, Gujarat 360003, India

ARTICLE INFO

Keywords:

Internet of medical things
Intrusion detection systems
Cybersecurity
Federated learning
Blockchain

ABSTRACT

The emerging Internet of Medical Things (IoMT) architecture enables real-time processing and monitoring of medical information. Its growing applications expose it to sophisticated cyber threats. Intrusion Detection Systems (IDS) have therefore become indispensable in ensuring confidentiality, integrity, and regulatory compliance. Existing surveys address the security issues, but they lack dataset analysis and integration of emerging approaches. This review presents a systematic review that classifies IoMT-IDSs across deployment strategies, response mechanisms, and evaluation metrics. We develop a multi-dimensional taxonomy that highlights the gaps and outlines a roadmap with federated IDS, blockchain validation, and explainable AI for secure healthcare.

1. Introduction

Internet of Medical Things (IoMT) has revolutionized contemporary healthcare scenarios by incorporating wearable devices, implantable systems, diagnostic devices, and distributed systems. It supports the continuous monitoring, early disease diagnosis, and personalized care [1]. The IoMT market size is expected to increase to USD 187.6 billion by 2028 [2]. Fig. 2 indicates the growing contribution of IoMT in digital health. Additionally, IoMT provides real-time patient monitoring, improved operational efficiency, and automation costs [3]. Nevertheless, its growing demand and cross-domain operations pose serious security threats. IoMT devices are resource-limited in nature; therefore, the traditional cryptographic or resource-intensive security protocols are not feasible [4].

The inclusion of heterogeneous communication technologies in IoMT further increases the security issues [5]. In blockchain-enabled IoMT (BC-IoMT), Distributed Denial of Service (DDoS) attacks are the most prevalent [6]. Federated learning (FL) frameworks provide secure distributed information transfer for intrusion detection systems (IDS), but are still compromised by model poisoning attacks [7]. According to

[8], the WannaCry ransomware attack of 2017 disrupted more than 80 hospitals in the United Kingdom (Fig. 1).

IDS solutions are used to monitor, analyze, and classify network or host activities, identifying potential anomalies or malicious activities. Akar et al. [9] proposed an LSTM model for detecting intrusions on IoMT, achieving an accuracy of 98 % in multi-class classification. Nonetheless, in [10] the authors emphasized that deep learning (DL) models are prone to high false alarm rates and need high resources, which makes them unsuitable in real-life applications. Similarly, the lack of explainability of the AI-driven IDSs was noted as a factor that lowers trust among healthcare practitioners [11]. Although reinforcement learning-based IDSs can enhance adaptive resilience to evolving IoMT threats but their computational complexity limits practical deployment [12].

A survey was presented in [13], which is more focused on IoT and did not discuss the IoMT-related issues. Authors in [14] presented the use of Machine Learning (ML) in IoMT security without taking into account the implementation architectures and the evaluation metrics. The survey in [15] focuses on ML-based IDS in the IoMT environment but does not consider the increased popularity of hybrid, federated, and

* Corresponding author.

E-mail addresses: syed9919@gachon.ac.kr (S.R. Hassan), muhammadusamatanveer99@gmail.com (M.U. Tanveer), sunilprajapat645@gmail.com (S. Prajapat), bhatsab4@gmail.com (M. Shabaz).

<https://doi.org/10.1016/j.ict.2025.11.005>

Received 21 September 2025; Received in revised form 29 October 2025; Accepted 15 November 2025

Available online 16 November 2025

2405-9595/© 2025 The Author(s). Published by Elsevier B.V. on behalf of The Korean Institute of Communications and Information Sciences. This is an open access article under the CC BY-NC-ND license (<http://creativecommons.org/licenses/by-nc-nd/4.0/>).




Fig. 1. Forecasted global IoMT market size.

blockchain-based IDS (BC-IDS) systems. Furthermore, [16] describes that the majority of IDS research utilizes general-purpose datasets (e.g., NSL-KDD and CICIDS2017), which do not contain biometric and physiological data. The dataset proposed in [17], which utilized Bluetooth, was among the first of its kind; however, the authors acknowledged that the IoMT domain still lacks dedicated datasets, raising concerns about the validity of IDS testing. These limitations provide a research gap that requires a comprehensive review of methodologies, datasets, evaluation metrics, and challenges in IoMT. Fig. 2 illustrates the role of IDS in IoMT, outlining key threats, infrastructures, and future research directions.

Recent IDS frameworks provide high accuracy with reduced latency. FL shows a significant degree of potential to support distributed IDSs [18]. However, its use in large-scale medical settings is mostly crucial. The federated reinforcement-based IDS proposed by [19] acknowledges that the trade-off between accuracy and computational overhead is a challenging task. The authors in [20] introduced blockchain (BC) technology to enhance tamper resistance in medical applications through immutable logging.

2. Related work and contributions

Early investigations by Wazid et al. [20] identified fundamental vulnerabilities in IoMT systems, reporting that over 60 % of medical devices lacked adequate security protocols. The WannaCry ransomware attack on the UK's National Health Service in 2017, which disrupted

over 19,000 medical procedures across 80 hospitals, served as a critical juncture that intensified academic and industrial focus on IoMT security mechanisms [21].

Several subsequent studies presented IoMT security from diverse perspectives. Khraisat et al. [13] conducted one of the first comprehensive reviews of IDSs in IoT environments, analyzing 127 papers published between 2010 and 2019. Their scope remained limited to general IoT applications with minimal healthcare-specific considerations. The study found that only 23 % of the reviewed IDS solutions considered the resource limitations inherent to medical devices. Similarly, Si-Ahmed et al. [15] focused specifically on ML-based intrusion detection methods for IoMT, reviewing 89 studies and revealing that 78 % of proposed solutions relied on traditional IT datasets rather than healthcare-specific traffic patterns. Their analysis demonstrated that detection accuracy rates varied significantly between general network and medical datasets, highlighting the inadequacy of existing evaluation methodologies [22].

The authors in [2], presents a review of 82 research articles on distributed architectures for intrusion detection, and identifies that only 31 % studies considered distributed computing paradigms for healthcare systems. Their work revealed critical gaps in FL applications. Naghib et al. [23] conducted a systematic literature review, focusing on challenges and opportunities in IoMT IDS. Still, their analysis lacked comprehensive coverage of emerging technologies.

The landscape of IoMT security research reveals several persistent limitations across existing surveys. First, most studies treat IoMT as a subset of general IoT systems, failing to address healthcare-specific regulatory requirements, patient safety considerations, and clinical workflow integration needs [6]. Second, evaluation methodologies remain fragmented, with 67 % of surveyed studies using datasets that inadequately represent real-world medical device communications and healthcare network behaviors [24–26]. Third, the rapid evolution of healthcare technologies, including 5G-enabled medical devices, edge computing infrastructures, and AI-driven clinical decision support systems, has outpaced the scope of existing surveys, creating knowledge gaps in contemporary security solutions [27,28].

The integration of advanced artificial intelligence (AI) techniques in IoMT IDS has emerged as a dominant research theme. Existing surveys provide limited analysis of the trade-offs between detection performance and resource constraints inherent in medical devices. Literature lacks comprehensive frameworks that address the convergence of FL, BC technology, and explainable AI in healthcare cybersecurity contexts. Furthermore, the absence of standardized evaluation metrics and healthcare-specific datasets continues to hinder meaningful comparison of proposed solutions and their clinical applicability.

2.1. Scope and distinctive contributions

This review presents a comprehensive multi-dimensional taxonomy of IoMT-IDS that integrates detection and deployment strategies with multiple response mechanisms. It also covers the emerging technology convergence, providing a more holistic classification framework than existing AI approaches. Furthermore, this review establishes the first systematic analysis of healthcare-specific datasets and their impact on IDS evaluation. Third, the paper introduces a novel mapping framework that correlates cyber threats with specific IoMT architectural layers and Central Intelligence Agency (CIA) security requirements, enabling precise threat modeling for healthcare networks. Fourth, this work provides the first comprehensive analysis of FL and BC integration in IoMT security, examining 45 recent studies that explore privacy-preserving collaborative detection mechanisms. Fifth, the paper addresses the critical gap in explainable AI applications for healthcare cybersecurity.

Finally, this review contributes a detailed examination of resource-constrained IDS design principles, addressing the unique challenges of deploying security mechanisms on battery-powered medical equipment with limited computational capabilities. Fig. 3 presents an overview of

A COMPREHENSIVE REVIEW ON INTRUSION DETECTION SYSTEMS IN THE INTERNET OF MEDICAL THINGS (IoMT)




Fig. 2. Overview of intrusion detection systems in IoMT.




Fig. 3. Distribution of selected research articles.

the reviewed papers, highlighting their quantity, publishing sources, and distribution over the years. A comparison of this review with the previous studies is shown in Table 1, which also highlights variations in approach, technological coverage, scope, and practical factors.

2.1.1. Key contributions

- A multi-dimensional taxonomy that categorizes IDS-IoMT based on detection methods, deployment architectures, response mechanisms, data sources, and technology integration approaches.
- A detailed healthcare-specific dataset analysis is presented that categorizes resource availability and identifies significant gaps.
- Novel correlation analysis linking cyber threats to specific IoMT layers and security requirements.
- Systematic analysis of distributed ledger technology applications in IoMT intrusion detection, covering consensus mechanisms, immutability features, and scalability challenges.
- Detailed analysis of interpretability needs in healthcare cybersecurity, addressing regulatory compliance and clinical decision support requirements.
- A comprehensive set of design rules that allow the creation of lightweight IDS that are optimized for battery-powered and computationally constrained medical devices.
- A methodical discovery of research deficiencies and research directions in advanced IoMT security IDSs, enabled by the convergence of technologies.

3. Methodology

This review followed Preferred Reporting Items of Systematic Reviews and Meta-Analyses (PRISMA) 2020 guidelines for methodological consistency and transparency.

3.1. Search strategy

The key databases that were searched included: IEEE Xplore Digital Library, PubMed/MEDLINE, Scopus, Web of Science, ACM Digital Library, and ScienceDirect. The study selection process, including identification, screening, and inclusion of relevant articles, is depicted in Fig. 4. The search string used was broad, including: (“Internet of Medical Things” or IoMT or medical IoT or healthcare IoT or medical devices network) and (intrusion detection or IDS or cybersecurity or network security or anomaly detection or threat detection or malware detection or cyber-attack detection). The timeframe of the search included January 2019 and October 2025. This timeframe was specifically




Fig. 4. PRISMA flow diagram.

Table 1
Comparison of related reviews with our proposed study.

Study Characteristics	[1] 2025	[2] 2023	[6] 2024	[13] 2019	[15] 2023	[23] 2025	[29] 2024	Our Work
Scope and coverage								
Healthcare-specific focus	●	✓	×	×	✓	✓	✓	✓
Multi-dimensional taxonomy	×	●	×	×	×	●	✓	✓
Resource-constraint analysis	×	×	×	●	×	●	✓	✓
Technological coverage								
FL integration	✓	×	✓	×	×	●	×	✓
BC-enhanced systems	×	×	✓	×	×	×	✓	✓
Explainable AI requirements	×	×	✓	×	×	●	✓	✓
Edge-fog-cloud paradigms	×	✓	●	×	×	●	×	✓
Methodology and evaluation								
Systematic methodology (PRISMA)	×	×	✓	●	●	✓	✓	✓
Dataset categorization analysis	×	×	●	×	●	×	●	✓
Performance metrics analysis	×	●	✓	●	✓	●	×	✓
Attack architecture correlation	×	×	●	×	×	×	✓	✓
Practical considerations								
Regulatory compliance discussion	×	●	●	×	×	●	✓	✓
Clinical integration challenges	×	×	×	×	×	●	✓	✓
Future research roadmap	✓	●	✓	●	●	✓	×	✓
Industry applicability framework	×	×	×	×	×	×	×	✓

Legend: ✓ = Comprehensive coverage, ● = Partial coverage, × = Not covered.

selected to focus on modern literature.

3.2. Inclusion criteria

Studies were included if they focused on intrusion detection specifically designed for IoMT environments. Original and peer-reviewed research with clear healthcare relevance, and provided sufficient methodological detail.

3.3. Study selection process

The multi-stage screening procedure began with [947 initially identified records. After removing 524 duplicates, 423 unique records underwent title and abstract screening. This resulted in 227 studies selected for full-text review. Following a detailed evaluation, studies were excluded for insufficient healthcare focus ($n = 55$), lack of intrusion detection components ($n = 32$), and theoretical contributions without validation ($n = 15$). The final corpus comprised 112 studies meeting all inclusion criteria, documented through a PRISMA flow diagram.

3.4. Data synthesis method

A mixed-methods approach combined quantitative analysis of performance metrics with qualitative thematic analysis. Quantitative synthesis examined detection accuracy distributions, computational efficiency trade-offs, and dataset utilization patterns. Qualitative synthesis identified recurring patterns, emerging trends, and knowledge gaps through iterative coding and thematic analysis.

4. Overview and security landscape

The IoMT, a subset of the broader Internet of Things (IoT), integrates medical devices, including wearable sensors, implantable devices, and hospital systems. To support the deployment of advanced healthcare applications, the IoMT framework utilizes cloud, fog, or edge computing infrastructures [30]. Unlike general IoT, IoMT is focused on clinical applications, providing real-time monitoring, diagnosis, and personalized treatment [29].

4.1. IoMT architecture

The IoMT paradigm integrates physical medical devices with digital connectivity to form intelligent healthcare ecosystems. The IoMT architecture is basically designed with three main layers [17], namely perception, network, and application layers, as shown in Fig. 5.

4.1.1. Perception layer

The perception layer contains all the physical medical devices and sensors that capture, generate, and initially process healthcare data [23]. Wearable devices are usually characterized by limited computing abilities, limited battery life, and a need to be continuously active for 24 h without compromising patient comfort and mobility [15]. These devices need to be highly reliable, safe, and energy efficient in nature due to the physiological importance they pose to the health of the patient. Their nature of weakness and life-sustaining roles make them appealing targets of cyber-attacks, thus the need to ensure high-security measures and effective backup systems [2].

Non-mobile medical equipment includes hospital-based equipment such as magnetic resonance imaging (MRI) scanners, computed tomography (CT) scanners, ventilators, infusion pumps, and patient monitoring equipment. Such tools tend to have better computational power than their wearable counterparts; however, they also have increased vulnerability to the drawbacks posed by legacy systems and heterogeneous security implementations, which are caused by long life cycles of operation and infrequent software updates [8]. The perception




Fig. 5. Three-Layered IoMT architecture.

layer is further complemented by environmental sensors, which include temperature sensors, air-quality sensors, and presence sensors that measure the healthcare environment and enable the optimization of patient-care processes and infection-control procedures [31,32].

4.1.2. Network layer

The network layer is the main communication infrastructure of the IoMT systems, where the efficient and secure transfer of information and data between the devices occurs [2]. The network layer uses various communication technologies to support the various needs and deployment scenarios of IoMT devices [14]. Short-range communication technologies such as Bluetooth Low Energy (BLE), Zigbee, and Wi-Fi protocols are normally adopted. BLE has been a leading technology, especially in wearable device designs, due to its unique low-power consumption properties that enable long battery life. On the contrary, the Wi-Fi standards will offer the necessary bandwidth increase needed to support data-intensive medical equipment [17].

Long-range communication technologies provide the ability to monitor patients remotely and provide telemedicine services [33]. The introduction of 5 G is a breakthrough in the communicative potential of the IoMT. It provides the ability to communicate with an extremely low latency that is ultra-high in nature. IoMT gateway constitutes the network layer infrastructure that works as strategic intermediary nodes, where information relayed by various devices in the perception layer is received, processed, and filtered preliminarily [34]. The network layer contains a wide range of architectural designs that are configured to achieve the best security, scalability, and performance in various healthcare deployment environments [35].

Distributed computing paradigms distribute the computation job across multiple tiers based on the latency requirements. The processed data is rendered into real-time critical alerts; intermediate analytics and aggregation of data occur at the fog node, and all data is stored on cloud infrastructure and processed with advanced analytics [14]. Mesh-based networking schemes enable direct device-to-device communication and other channels, thus significantly increasing the resilience and reliability of the network [35].

Software-Defined Networking (SDN) approaches provide a control plane and enable dynamically configuring network resources, thereby enabling the execution of adaptive security controls and informed resource allocation. These architectural paradigm combinations result in elastic and scalable network infrastructures that could support the full spectrum of IoMT applications and fulfill the reliability, security, and performance demands that are intrinsic in healthcare environments [16,

36]. Moreover, the network-layer design must allow addressing mixed Quality-of-Service (QoS) requirements of various medical applications, where delivery of life-saving alerts (immediately) is of greater significance than tolerable delays in simple health-monitoring information [37].

4.1.3. Application layer

The application layer comprises software applications, services, and user interfaces that process, analyze, and display healthcare data to end-users. It processes raw sensor data acquired by the perception layer and converts it into actionable information, which can be subjected to a clinical, administrative, and decision-making process.

The application layer is centered around the IoMT clinical applications. An example is Electronic Health Record (EHR) systems and Clinical Decision Support Systems (CDSS), designed to condense large amounts of patient data, which is obtained through a variety of means, and to support clinicians in their diagnostic and therapeutic decision-making processes [38]. Remote patient monitoring systems ensure that health is assessed continuously, and the telemedicine systems provide an opportunity to provide care abroad. The systems then integrate streams of information from different IoT devices to support clinical decisions. The other set of applications that can be seen in this layer are the patient-centric solutions. These solutions should be user-friendly and simultaneously ensure a high level of security and privacy, which is a key requirement when handling healthcare data [39].

The application layer provides real-time data processing and analytics for IoMT, enabling instant alerts, automated responses, and accurate decision-making [40]. IoMT security requires a comprehensive, multi-layered strategy integrating all system levels. The perception layer demands lightweight, energy-efficient protocols resilient to physical and cyber threats, while the network layer requires secure communication, intrusion detection, and data segmentation to prevent lateral movement within healthcare infrastructure [41]. The application layer must enforce strict access, privacy, and regulatory controls with audit and forensic capabilities. Coordinated multi-layer security ensures system-wide protection, preventing intrusions at one level from compromising the entire IoMT ecosystem [35]. The above tri-layer architecture is the basic model of IoMT security solutions, such as IDSs, which should be carefully designed and implemented [42]. Table 2 summarizes the key IoMT architectures, highlighting their emphases and security integration approaches.

5. Security requirements

Healthcare information is not only critical for clinical decision-making but also deeply personal, which makes ensuring its security and privacy imperative [43]. The CIA (Confidentiality, Integrity, and Availability) Triad remains the foundational framework for protecting IoMT environments [44,45]. Unauthorized disclosure of a patient’s data can lead to severe ethical, social, and legal consequences. The relationship between IoMT attack vectors and the CIA triad is illustrated in Fig. 6. Integrity is essential to guarantee the accuracy and trustworthiness of medical data throughout its lifecycle. Integrity attacks, such as false data injection, can destabilize entire healthcare services.

The authors in [38] list non-repudiation, authentication, authorization, and session resilience as the critical elements of IoMT security. Study in [35] suggested the CIANA model (Confidentiality, Integrity, Availability, Non-repudiation, Authentication) as a specialized extension to medical networks, the rationale being that the stakes are so high in the medical field that it requires more stringent requirements [44,45]. Table 3 presents a mapping of common IoMT attacks to their impact on confidentiality, integrity, and availability.

6. Intrusion detection process in IoMT

Fig. 7 describes the process of designing an IoMT IDS. The number of steps varies across different studies; mostly categorized into data preprocessing, feature selection, classification/attack detection, and hyperparameter tuning [11].

6.1. Data preprocessing

Data preprocessing is foundational because IoMT datasets are heterogeneous, noisy, incomplete, and imbalanced. Missing data




Fig. 6. CIA Triad mapping to IoMT attack vectors.

Table 2
Comparative Analysis of IoMT architecture implementations.

Ref.	Architecture Model	Perception Layer Focus	Network Technologies	Application Layer Emphasis	Security Integration
[2]	Cloud-Fog-Edge Paradigm	Heterogeneous Medical Devices	5 G, Wi-Fi, BLE	AI-Driven Analytics, Clinical Decision Support	Multi-Layer Security Framework
[3]	Sustainable IoMT Model	Energy-Efficient Sensors	LoRaWAN, Zigbee, 5G	Sustainable Healthcare Delivery	Green Security Protocols
[8]	Cyber-Physical Systems	Medical CPS Devices	Industrial Protocols	Attack Detection Systems	CPS-Specific Security Measures
[15]	ML-Integrated Architecture	Smart Medical Devices	Multi-Protocol Support	Machine Learning Services	ML-Based Intrusion Detection
[17]	Three-Layer (Device-Network-Cloud)	Wearable Devices, Medical Sensors	Wi-Fi, Bluetooth, Cellular	EHR Integration, Remote Monitoring	End-To-End Encryption, Authentication
[18]	Hierarchical Federated Model	Distributed Medical Devices	Dew-Cloud Communication	FL Applications	Privacy-Preserving Security
[23]	Comprehensive IoMT Model	All Device Categories	Multi-Technology Support	Full Application Spectrum	Holistic Security Approach
[36]	Security Focused Framework	Secured Medical Devices	Secure Communication Protocols	Privacy-Preserving Applications	Comprehensive Security Framework
[42]	Resource-Constrained Model	Low-Power Medical Devices	Energy-Efficient Protocols	Lightweight Applications	Resource-Optimized Security

Table 3
Mapping of Common IoMT Attacks to Security Requirements (CIA Triad).

Attack Type	Confidentiality	Integrity	Availability	Description/ Impact
Spoofing	✓	✓	–	Attacker impersonates devices or users, leading to stolen credentials and falsified data [3].
DDoS Attacks	–	–	✓	Floods IoMT servers and fog nodes with malicious traffic, preventing healthcare staff from accessing critical records [6].
Man-in-the-Middle (MitM)	✓	✓	–	Intercepts and alters communication between medical devices and servers, exposing private data and corrupting transmission [7].
Ransomware	✓	✓	✓	Encrypts patient records, halts device availability, and compromises confidentiality and integrity simultaneously [8].
Backdoor Attacks	✓	✓	–	Unauthorized access enables persistent manipulation of patient data and leakage of records [23].
Smurf Attack	–	–	✓	A DDoS attack using ICMP flooding disables IoMT devices and services, limiting accessibility [29].
False Data Injection	–	✓	–	Manipulation of medical data streams (e.g., heart rate, glucose levels) causes misdiagnosis and mistreatment [31].
U2R (User-to-Root)	✓	✓	–	Privilege escalation compromises confidentiality and alters clinical data.
SQL Injection / XSS	✓	✓	–	Exploitation of vulnerable medical applications exposes patient EHRs and corrupts data integrity [46].
SSH/FTP Brute Force	✓	–	✓	Attacker gains control of medical servers,

Table 3 (continued)

Attack Type	Confidentiality	Integrity	Availability	Description/ Impact
				locking users out of essential services [47].




Fig. 7. Process of intrusion detection in IoMT.

management methods include deletion [48], mean/median imputation [49], and advanced methods such as Expectation–Maximization [50]. Encoding techniques such as label encoding [51] and one-hot encoding converts categorical features into numerical form. Feature scaling is also critical to normalize the range of variables for ML algorithms, with Z-score normalization [9,52] and Min–Max scaling [53] being the most common approaches. Another persistent difficulty is how to resolve class imbalance: SMOTE-based oversampling [11], and cost-sensitive learning.

6.2. Feature selection

Reductions in dimensionality and redundancy are impossible without feature selection, since there are over 115 features of N-BaIoT data [48]. The methods are divided into filter-based, wrapper-based, embedded, and hybrid [18]. Filter methods, e.g., Pearson correlation [53] and Information Gain [54], do not depend on classifiers. Wrap techniques like Recursive Feature Elimination (RFE) [55] simplify subsets through the assistance of classifiers. Embedded routines use selection in the training, with LASSO regression [56] or tree-based importance ranking [57]. The hybrid strategies are combinations of evolutionary and statistical algorithms, such as the Grey Wolf Optimizer (GWO) [58], Particle Swarm Optimization (PSO) [12], and Harris Hawk Optimization (HHO) [59,60]. Such techniques are essential not only to the computational performance but also to preventing overfitting and facilitating the generalizability of IDS models.

6.3. Classification and attack detection

The most important phase of IDS is classification, in which models classify traffic or device behavior as benign or malicious. The most widely used ML algorithms are classified as Classical ML, such as Random Forest (RF), Decision Trees (DT), Support Vector Machines (SVM), and K-Nearest Neighbor (KNN) algorithms, as they are understandable and efficient [4]. Nevertheless, Deep Learning (DL) models, including CNNs, LSTMs, and stacked autoencoders, are becoming more and more popular since they can capture both temporal and spatial dependencies in the data of the IoMT [25]. Remarkably, there is an emergence of hybrid techniques: Researchers in [23] proposed Fusion Net that integrates RF, KNN, SVM, and MLP to improve the detection performance, and [24] introduced a fog-cloud ensemble IDS that uses LSTMs stacked on top of each other and fed into DTs.

6.4. Hyperparameter tuning

Hyperparameters have a strong impact on the performance of an IDS, and the most commonly used method is grid search [27]; Bayesian

optimization [61] and metaheuristic methods have also been studied, as well as Tree-structured Parzen estimators (TPE) [27,28].

As an example, [62] used genetic algorithms to optimize the hyperparameters of the XGBoost, thus significantly speeding up the process of malware detection. Similarly [63], applied the particle swarm optimization algorithm to deep neural network tuning, which attained an accuracy of 96 % and minimized convergence time. These adaptive tuning methods are required in lightweight IoMT environments, where the costs of the computations and the amount of energy are of the utmost priority [63]. Table 4 presents a summary of intrusion detection in IoMT, including applied techniques, datasets, and achieved performance results.

7. Cybersecurity threats in IoMT

Medical devices are particularly vulnerable due to their heterogeneity, resource constraints, and critical role in patient safety [22]. Cybersecurity threats in IoMT can be broadly categorized into DDoS attacks, ransomware, malware, Man-in-the-Middle (MitM) attacks, and injection-based attacks. Each class of attack exploits different vulnerabilities and imposes distinct consequences for the confidentiality, integrity, and availability of medical services [67].

7.1. Distributed denial of service (DDoS)

The DDoS attacks are among the most severe threats to IoMT infrastructures because they directly undermine the availability of critical medical systems. By overwhelming servers, gateways, or cloud–fog

nodes with malicious traffic, attackers prevent legitimate users from accessing essential health records, monitoring dashboards, or even device functions [7,45].

Industry reports confirm that over 34 % of cyberattacks on health-care in 2022 were DDoS-related, resulting in downtime costs of nearly USD 7.8 million per incident [6]. In the United States alone, DDoS disruptions accounted for more than 18 % of reported healthcare service outages between 2018 and 2022, illustrating the scale of the problem. Such attacks have been amplified by the emergence of botnets such as Mirai and Mozi, which hijack smart devices to generate high-volume traffic [26]. The 2016 Mirai attack, which infected over 600,000 devices, including medical IoT equipment, led to global service disruptions and highlighted the lack of security hardening at the device level [68].

Volumetric flooding attacks are based on bandwidth consumption, whereas protocol-based attacks are based on vulnerability of TCP/UDP handshakes, and application-level DDoS attacks are based on API and hospital portal overload [69]. The attacks are especially harmful to resource-limited IoMT devices, which cannot process malicious requests well [44].

Studies have tried to respond to these issues by developing high-end IDS and anomaly detectors. Study in [31] presented the DDoS detection model of BC-IoMT networks and obtained the detection accuracy of more than 98 % on simulated traffic datasets. Likewise, [21] designed an ensemble learning framework in a fog-cloud architecture that enhanced resilience to DDoS attacks that relied on botnets in intensive care monitoring systems.

The most recent developed anomaly-based IDS, that are tested on synthetic DDoS traces on IoMT, achieves an accuracy of more than 97 % [26,68,69]. Table 5 summarizes recent studies on DDoS attacks in IoMT environments, detailing the types of attacks, their impact on healthcare systems, and the corresponding detection solutions.

There are some important trends that are suggested by the collective evidence: To begin with, DDoS attacks are becoming more and more multi-vector as they nowadays involve volumetric, protocol, and application-level attacks. Second, the specifics of IoMT devices increase their susceptibility to botnets, as they can both be exploited and serve as

Table 4
Intrusion Detection Process in IoMT (Steps, Methods, and Studies).

Studies	Stage	Methods/ Techniques	Datasets Used	Performance
[11,49, 64]	Preprocessing	Missing data: deletion, imputation (mean/median, EM, MICE); Encoding: label, one-hot; Scaling: Min–Max, Z-score; Class imbalance: SMOTE, cost-sensitive	WUSTL-EHMS, ToN-IoT, Bot-IoT	Improved data quality; reduced bias; SMOTE enhanced minority class recall
[23,34, 45, 49]	Feature Selection	Filter: correlation, info gain; Wrapper: RFE, forward/backward; Embedded: LASSO, tree-based; Hybrid: GWO, PSO, HHO	ECU-IoHT, N-BaIoT, CICIDS2017	Reduced dimensionality; Improved Accuracy; Improved generalization
[23,64, 65]	Classification	ML: RF, DT, SVM, KNN; DL: CNN, LSTM, autoencoders; Hybrid ML–DL (Fusion Net, stacked ensembles)	N-BaIoT, WUSTL-EHMS, ToN-IoT	RF, DT, CNN improved accuracy; Hybrid IDSs reached greater accuracy
[1,49, 66]	Hyperparameter Tuning	Grid search, random search, Bayesian optimization, metaheuristics (GA, Firefly, PSO, TPE)	Malware PE, ARGUS, IoTID20	Accuracy improvement; faster convergence; reduced false acceptance rate

Table 5
Studies on DDoS attacks and detection in IoMT.

Study	Dataset / Context	Type of DDoS Attack	Impact on IoMT	Proposed Solution
[3]	Fog–cloud IoMT ICU monitoring	Botnet-driven DDoS on fog nodes	ICU patient data transmission failure	Ensemble IDS (RF + SVM + DT)
[6]	BC-IoMT testbed	Volumetric flooding on BC nodes	Service delays in validating medical transactions	ML-based IDS for BC-IoMT
[8]	Attack Detection for Medical Cyber-Physical Systems	IoT/IoMT device hijacking for large-scale DDoS	Global disruption of hospital services	Highlighted the lack of IoMT patching
[14]	IoMT simulation framework	Application-layer HTTP flooding	Blocked hospital EHR web portals	DL-IDS integrated with fog nodes
[20]	Review of IoMT malware attacks	Botnet-based volumetric attacks	Bandwidth exhaustion, device lockout	Suggested lightweight IDS
[21]	Industry report	Multiple DDoS vectors on healthcare	Avg. downtime cost per incident: USD 7.8M	A hybrid IDS with cloud backup
[27]	Anomaly-based IDS for IoMT	SYN flooding and UDP flooding	Disrupted connectivity of wearable devices	Anomaly-based ML IDS
[51]	IoMT wireless networks	ICMP flooding	Blocked telemetry from wearable sensors	IoMT-specific lightweight IDS

the source of DDoS attacks. Third, despite the accuracy rates of recent IDS models reaching more than 94–97 %, the issues of false positives reduction, the latency in real-time detection, and energy consumption are still unresolved. As a result, the research community focuses on the lightweight IDS designs that could be implemented at the edge and fog nodes and provide immediate mitigation that would not saturate the device itself.

7.2. Ransomware attacks

Ransomware has emerged as one of the most disruptive and costly forms of cyberattacks in healthcare and, by extension, in IoMT environments [69]. Unlike other cyber threats that may silently exfiltrate data or disrupt traffic temporarily, ransomware actively encrypts critical data or disables essential devices, demanding a ransom for restoration. This combination of a compromise of confidentiality and availability makes ransomware particularly insidious in the clinical setting [31,44]. According to [21], the median cost of data breaches in healthcare grew to USD 10.93 million in 2023, the highest across all sectors. The authors in [70] reported that ransomware attacks in healthcare increased by 94 % when compared with 2020 to 2022. In IoMT, ransomware can do the same by locking ventilators, pacemakers, or monitoring dashboards, causing hospitals to resort to manual systems, which significantly increases medical errors. The most infamous case was the 2017 WannaCry ransomware outbreak [71]. More recently, Ryuk and Conti ransomware families have targeted healthcare IoT/IoMT environments, using phishing campaigns and exploiting RDP vulnerabilities [72]. From a technical standpoint, ransomware in IoMT often leverages propagation vectors such as insecure APIs, unencrypted device communication, and outdated operating systems [17].

The BC-IoMT systems were initially thought to be resilient, but research has shown that infected edge or fog nodes can still spread ransomware across peer devices. Furthermore, [73] highlighted that real-time IDS solutions often fail in early detection of ransomware encryption patterns. Researchers are actively exploring countermeasures. Alalwany et al. (2025) developed a stacking ensemble deep learning model for IoMT ransomware detection, demonstrating real-time mitigation with over 99.3 % detection accuracy. In [74], a BC-based prevention model was presented, which used immutable logging to identify anomalous device behaviors and restore compromised states. Table 6 summarizes recent studies on ransomware attacks in IoMT environments. Ransomware is not a theoretical threat to the IoMT but a proven threat. The WannaCry attack has shown how such attacks can have a ripple effect, with the unavailability of the IoMT resulting in canceled surgeries and even life-threatening disruption.

7.3. Malware attacks

Malware attacks gain access to medical equipment, hospital

networks, and other connected systems to steal information, disrupt business, or destroy essential equipment [75]. Malware is typically not detected, but can be harmful to the confidentiality, integrity, or availability of sensitive health information [76]. Malware is available in different forms, including trojans, worms, spyware, and advanced persistent threats (APTs) [77]. One of the most important spheres that malware campaigns are always aimed at is healthcare. The U.S. Department of Health and Human Services reported that malware was used in nearly 60 % of cyberattacks related to the healthcare sector in 2022, with trojan and spyware being the most common [15]. Malware runs will presumably exploit device heterogeneity: one device may run a lightweight OS that can do little patching, whereas another may be running legacy Windows platforms, providing multiple attack vectors [19].

Several studies [34,43,78,79] have tried to address the issue of malware detection in IoMT with hybrid IDSs, which consolidate network- and device-level monitoring. Hady et al. [35] compared network-data-driven IDS with hybrid systems based on both medical and network data. Later on, authors in [80], even bettered this by proposing their own stacked autoencoder and XGBoost classifier and were able to achieve an accuracy of 98.9 % in detecting malware on the WUSTL EHMS 2020 and Malware PE headers datasets. Similarly [31], suggested a CNN-based model to classify malware in medical IoT. As highlighted by [31,32], traditional malware detection systems fail to keep up with new attack vectors like file-less malware, zero-day exploits, and so on, which cannot be detected through signature-based detection systems. More recent plans formulated to address these constraints combine metaheuristic methods with FL systems and thus enhance the resilience of distributed IoMT systems [81]. Table 7 summarizes recent studies on malware attacks in IoMT environments, outlining malware types, their impact on healthcare systems, proposed detection techniques, and reported performance outcomes.

7.4. Man-in-the-middle (MitM) attacks

MitM attacks have been identified as one of the major and increasing threats to the IoMT that mainly attack the confidentiality and integrity of sensitive health data that is transferred between devices, gateways, and the cloud/fog infrastructures [51]. In a MitM attack, an adversary captures and possibly modifies communication streams, and can therefore listen to patient records, tamper with sensor readings, or inject malicious instructions into medical equipment [2]. According to a 2022 survey of the state of healthcare cybersecurity, 28 % of healthcare IoMT network breaches involved some form of traffic interception or spoofing, making MitM one of the three most common attack vectors against healthcare IoMT networks [78]. To illustrate, authors in [82] discovered that the insecure connection of the Bluetooth of the smart medical devices allowed the ease of intercepting the glucose monitor readings, therefore compromising the privacy of the patients and the integrity of

Table 6
Ransomware attacks and detection in IoMT.

Study	Dataset Context	Attack Mechanism	Impact on IoMT Healthcare	Proposed Solution	Performance/Findings
[1]	Survey of FL-based IoMT security	Ransomware targeting EHRs	System-wide unavailability of cloud health records	FL IDS and anomaly-sharing across hospitals	Emphasized scalability; reduced communication overhead
[8]	NHS WannaCry case (2017)	Worm-based ransomware exploiting SMBv1	Cancellation of 19,000 medical procedures; 80 hospitals disrupted	Highlighted patching and IDS gaps	Losses estimated at >£92 M; demonstrated systemic IoMT risk
[13]	Global report	General ransomware in healthcare	Average breach cost = USD 10.93M	Advocated hybrid IDS and resilience training	Healthcare = the most targeted sector
[67]	BC-IoMT	Ransomware spread via fog nodes	Device/data unavailability; compromised BC transactions	BC-IDS and the prevention model	Improved detection, but dependent on node resilience
[50]	IoMT real-time environment	File encryption mimicking legitimate processes	Locked EHRs, medical data loss	Stacking ensemble DL IDS	Detection accuracy 99.3 %;
[54]	Industry stats	Ransomware campaigns across IoT/ IoMT	94 % increase in healthcare ransomware (2020–22)	Suggested proactive IDS + patching	Highlighted exponential risk growth
[59]	Federated IoMT IDS	Ransomware in distributed IoMT hospitals	Localized attacks spread across nodes	FL for anomaly detection	Accuracy 99.38 %; preserved privacy

Table 7

Malware attacks and detection techniques in IoMT.

Study	Dataset/Context	Malware Type / Attack Mechanism	Impact on IoMT/Healthcare	Proposed Solution	Performance/Findings
[3]	IoMT anomaly dataset	Malware binaries	Real-time IoMT communication disruption	CNN-based DL IDS	Achieved high recall and faster detection
[20]	Survey	IoMT-specific malware & zero-day exploits	Device hijacking, data theft	Proposed hybrid IDS framework	Identified a lack of datasets for zero-day malware
[80]	WUSTL EHMS 2020, Malware PE headers	Malware-injected executables	Device malfunction, EHR encryption bypass	Stacked Autoencoder + XGBoost	Accuracy: 98.9 %; faster convergence
[35]	IoMT hybrid datasets (network + medical)	General malware, trojans	Corrupted medical images, altered EHRs	Hybrid IDS combining medical & network data	Improved accuracy vs. network-only IDS
[66]	Healthcare 4.0 IoMT	Polymorphic malware	IDS evasion, evolving signatures	Metaheuristics + ML IDS	Accuracy: 99.69 %; improved adaptability

the clinical process. Similarly [83], mentioned that the MitM attacks may be employed to spy on the health data and to inject false medical instructions, which can cause the infusion pump overdose or the cardiac monitor to give a false alarm. MitM in IoMT has other implications as well, besides privacy violations.

By manipulating the real-time data feeds, hackers can change the vitals of patients, misdiagnose patients, or commit other unethical medical acts. In 2021, a MitM attack was simulated against wireless infusion pumps, where the adversary could alter insulin dosage by modifying communication packets, which may result in life-threatening conditions for diabetic patients [82]. The adverse consequences of MitM are not limited to the direct patient harm, since this method undermines compliance with regulatory requirements (HIPAA, GDPR, etc.) because unauthorized access and manipulation of data are considered a violation of legal and ethical protection [84].

To overcome MitM, researchers have studied cryptographic and ML-based IDS solutions. Authors in [82] introduced a tokenized FL-based IDS on a BC, where decentralized consensus was used to prevent tampering. Likewise [85,86], combined machine-learning with ensemble IDS models and demonstrated that it can be used to dynamically adapt to novel patterns of MitM attacks, achieving a substantial decrease in false negatives. The alternative solutions are lightweight anomaly detection algorithms implemented on fog nodes [87], which do not overload resource-constrained devices and monitor traffic integrity in real-time. The vulnerability of key exchange remains a problem in IoMT devices, with most of them using obsolete or fixed encryption. Also, real-time MitM attacks cannot be detected because malicious traffic resembles the legitimate encrypted packets, which makes false alarms a high possibility. The explicable IDS models are also urgent, as the medical professionals need to understand clear reasoning when the data integrity is put into question. Table 8 summarizes MitM attacks in IoMT, their impacts, detection strategies, and performance.

7.5. Injection-based attacks (SQL injection, XSS, etc.)

Injection-based attacks are also among the most persistent threats to connected systems, such as the IoMT. These attacks target the weaknesses in poorly sanitized inputs, weak authentication, and mis-configured middleware, which allow adversaries to execute malicious code or commands to healthcare systems. SQL injection (SQLi) [53] and XSS are the most common types of injection attacks on IoMT, where SQLi [88] is used to attack medical databases in the backend and XSS to manipulate web interfaces and steal session cookies, credentials, or inject malicious scripts. In IoMT, these attacks are particularly disastrous, as they can endanger Electronic Health Records (EHRs), cloud dashboards, and IoT-enabled hospital applications, which directly affect patient safety and institutional trust. In 2023, the Verizon Data Breach Investigations Report reveals that more than 22 % of healthcare web application attacks involved exploits that injected exploit code. Such weaknesses are compounded in IoMT since most of the devices use web-based dashboards and APIs to monitor and control, and thus are prone to injection attacks [89]. There are several works done on injection attacks in IoMT.

Authors in [53] have demonstrated how SQL injection could be used to access IoMT devices to disclose clinical information. Similarly [90], proved that XSS could be used to attack the IoMT web dashboards and gain control of physician sessions, and steal biometric streams. In an experimental study, Bhushan et al. [3] demonstrated that 70 % of the traditional IDS models are trained on traffic-level anomalies could be bypassed by injection attacks. A variety of mitigation strategies have been developed by researchers to tackle these risks. Pelekoudas-Oikonomou et al. [29] have designed BC-based edge security architectures that have input validation and immutability of records, and have reduced the injection vectors. Naghib et al. [23] supported the implementation of explainable AI models to detect injections in IoMT, claiming that explainable IDS tools may be used to make clinicians trust anomalous alerts in cases when patient dashboards act in a counterintuitive way. Moreover, the IDS driven by FL [1] has

Table 8

MitM Attacks and Detection Strategies in IoMT.

Study	Dataset/Context	Attack Mechanism	Impact on IoMT Healthcare	Proposed Solution	Performance/Findings
[7]	BC-based FL IoMT testbed	Traffic interception, spoofing	Patient privacy breach, tampered vitals	BC + FL-based IDS	Improved accuracy; reduced false acceptance rate
[8]	Industry analysis	General MitM in healthcare	Breach of HIPAA/GDPR compliance	Recommended cryptographic + IDS hybrid	Industry-level resilience insights
[17]	Smart healthcare Bluetooth dataset	Bluetooth MitM on wearables	Exfiltration of glucose readings	Secure Bluetooth IDS + novel dataset	Detected MitM with >90 % precision
[31]	Meta-learning IDS	Adaptive MitM injection	Misdiagnosis due to corrupted vitals	Meta-learning ensemble IDS	High adaptability; reduced false negative rate
[34]	Fog-cloud IoMT	Packet injection, replay	False alarms in ICU monitoring	Ensemble IDS (RF + SVM)	Improved accuracy by 15 % and decreases in time complexity by 32 %
[51]	Wireless infusion pump simulation	Data manipulation	Altered insulin dosage	Lightweight anomaly IDS	Improved framework covers all data and device security stages.

been demonstrated against injection vectors, with better scalability and privacy preservation in distributed IoMT infrastructures. Table 9 summarizes injection-based attacks in IoMT, their impacts, detection methods, and findings.

8. IDS classification frameworks

IDS have become complex and multidimensional systems incorporating a wide variety of operational models, detection processes, deployment designs, and analytical methods. The taxonomy is presented in Fig. 8, which provides a detailed categorization of the wide range of IoMT security solutions and thus allows researchers and practitioners to make informed decisions about the choice of the most suitable IDS implementation in particular contexts of healthcare and security needs.

8.1. Time aspects in prediction and detection

The attributes of time are the main factors that define the nature of the functioning of IDSs and delimit their applicability in healthcare settings [27,28].

8.1.1. Real-Time intrusion detection systems

The real-time IDSs provide immediate response by the real-time analysis of network traffic. The stacking ensemble deep-learning architecture described in [51] can be used to detect real-time intrusions in context of the IoMT networks with high efficacy rates on a range of attack types. The implementation indicates that deep-learning architectures can fulfill the high real-time performance demands that are typical of critical medical applications [2]. The study in [12] proposes a robust reinforcement learning based IDS that can thwart threats on the fly and, therefore, demonstrate how the latest AI-based approaches can meet the speed and accuracy requirements of medical settings. The ability of the system to dynamically adapt the detection strategies to changes in the threat patterns is a major improvement that the field of adaptive security response capabilities can achieve [21].

8.1.2. Offline intrusion detection systems

Offline systems offer a chance to perform heavy computation analysis methods that would not be possible in a real-time setting. In [92], authors investigated AI techniques for intrusion detection in IoMT using the offline analysis method by showing how batch processing can be used to realize the use of advanced analytical techniques, which are computationally intensive, and ensure high detection rates of various categories of threats [23].

8.1.3. Online and near-real-time systems

Online IDSs systems provide a balance of processing efficiency and a reasonable response time. Authors in [18] proposed a hierarchical FL dew-cloud-based intrusion detection in IoMT that exhibits the abilities of effective online processing and retains the advantages of distributed learning in healthcare networks. Online methods can be adapted to the

processing parameters of each healthcare organization to meet its unique operational demands [1]. Table 10 shows the IDSs based on time aspects.

9. Intrusion detection methods and techniques

The taxonomy of intrusion detection methods covers the underlying methods of detecting security threats in IoMT environments.

9.1. Signature-based detection methods

Signature-based detection systems detect threats by comparing observed activities with predefined signatures or patterns of known attacks. In [13], authors developed signature-based malware detection systems to be applied in IoMT environments and achieved high rates of successful malware detection. Signature-based systems are dependent on the completeness and up-to-date nature of signature databases, and therefore must be constantly updated to address new threats. Thamilarasu et al. [91] have proposed signature-based IDSs that take into consideration healthcare-specific signatures, and have presented how domain-specific signatures can enhance the detection of medical device environments.

9.2. Anomaly-based detection methods

IDSs that are based on anomalies create a model of normal system and network activity and then detect anomalies as possible security threats. This is particularly effective in the detection of new attacks and insider threats whose signatures are not known. Akar et al. [9] introduced an LSTM-based IDS that detects known and unknown attack patterns with high performance due to improved anomaly detection. Anomaly-based systems are prone to false alarms, and it is important to tune the system to meet the desired level of detection sensitivity and false alarms. Zachos et al. [69] proposed anomaly-based intrusion detection solutions to IoMT networks with adaptive baseline adjustment capabilities, which allow them to detect threats in a reliable and adaptable manner in the face of changes in legitimate patterns of healthcare operations.

9.3. Specification-based detection methods

Specification-based detection systems compare system activities with specifications of acceptable behaviors and report violations as possible security threats. This method is highly accurate in identifying the presence of certain kinds of attacks and has the added benefit of being interpretable, which is necessary in healthcare applications [44, 45]. Reputation-based detection systems assess the integrity of the network members based on past behavioral trends and the opinions of peers. Zaabar et al. [7] proposed IoMT intrusion detection based on BC-based reputation systems, where the trustworthiness of devices and users is rated using the distributed consensus mechanisms.

Table 9
Injection-based attacks and detection techniques in IoMT.

Study	Dataset	Injection Type	Impact on IoMT Healthcare	Proposed Solution	Findings
[1]	Federated IoMT networks	Injection attempts in cloud EHR	Data corruption & leakage	Federated IDS for injection anomalies	Scalable, privacy-preserving
[3]	Fog-cloud IoMT	SQLi & script injection	Manipulated patient records; bypassed IDS	Hybrid IDS integrating application logs	Improved detection over traffic-only IDS
[7]	IoMT web dashboard	Cross-Site Scripting (XSS)	Hijacked physician sessions; altered prescriptions	BC + FL IDS	Improved accuracy; reduced XSS exposure
[23]	AI IDS for IoMT	SQLi & XSS	Compromised web dashboards	Explainable AI anomaly detection	High accuracy + interpretability
[29]	BC-IoMT	General injection vectors	Altered IoMT BC transaction	BC-secured validation	Strong immutability, but high latency
[91]	IoMT hospital EHR database	SQL Injection	Unauthorized EHR access; privacy breach	Lightweight IDS for medical DB	Demonstrated SQLi exploitation risk




Fig. 8. Aspect-based classification.

Table 10
Time Aspects in IoMT Intrusion Detection Systems.

Studies	Time Mode	Processing Approach	Detection Latency	Context	Advantages	Limitations	Healthcare Suitability
[4]	Online	ML-based	5–8 s	IoMT networks	Practical deployment	Moderate accuracy	Routine monitoring
[8]	Offline	Systematic analysis	Post-incident	Medical CPS	Comprehensive forensics	No prevention	Compliance auditing
[12]	Real-time	Deep Reinforcement learning	<2 s	Healthcare networks	Adaptive blocking	Risk of disruption	Emergency response
[18]	Online	Hierarchical FL	5–10 s	ICU IoMT	Balanced performance	Batch update delays	General monitoring
[36]	Mixed	Framework analysis	Variable	Network security	Flexible approach	Implementation complexity	Framework design
[42]	Real-time	Resource-constrained	<3 s	Constrained devices	Energy efficient	Limited complexity	Wearable devices
[50]	Real-time	Stacking ensemble DL	<1 s	IoMT streams	Immediate response	High energy consumption	Critical care
[56]	Real-time	Swarm-neural	<1.5 s	IoMT framework	Bio-inspired	Algorithm complexity	Sensor networks
[63]	Online	Cloud-based hybrid	3–5 s	Cloud IoMT	Scalable processing	Network dependency	Cloud deployments
[92]	Offline	ML/DL analysis	Hours to days	IoMT survey	Thorough investigation	Delayed detection	Research analysis

9.3.1. Hybrid detection approaches

Hybrid detection systems combine two or more different methods of detection so that the advantages of the methods are combined. The meta-learning methods proposed [1,21] by improving the performance of the IDS by using ensemble techniques, thus showing that hybrid approaches can be used to develop better performance with reasonable operational overheads that can be deployed in the healthcare setting. Table 11 showed the intrusion detection methods in IoMT. Anomaly-based approaches are suitable for detecting novel threats, but signature-based ones are reliable for detecting known threats with

reduced computational demands.

10. IDS techniques and approaches

This is an in-depth survey of the various methods and mechanisms used in modern IoMT IDSs, including their advantages and disadvantages, as well as how they might be used in healthcare settings based on a systematic analysis of recent research publications.

Table 11
Intrusion detection methods in IoMT.

Study	Detection Method	Primary Technique	Dataset Used	Accuracy (%)	Precision (%)	Recall (%)	Adaptability
[2]	Hybrid approaches	AI-driven analysis	Multiple sources	Variable	Variable	Variable	High
[9]	Anomaly-based	LSTM neural networks	WUSTL EHMS	98.0	98.0	98.0	High
[32]	Hybrid	Meta-learning ensemble	Multiple datasets	93.4	-	-	Medium
[91]	Signature-based	Rule-based detection	IoMT prototypes	99.9 ~ 92.91	Variable	Variable	High
[92]	Mixed methods	ML/DL survey	Multiple datasets	99.98	99.96	99.99	Medium

10.1. Machine learning-based intrusion detection systems

ML algorithms have also become part of modern IoMT IDSs, allowing automatic learning of network-traffic patterns and device behaviors without explicitly programmed threat situations.

10.1.1. Supervised learning approaches

These methods make use of labeled training data to train predictive models that can make a distinction between normal and malicious network traffic. Binbusayyis et al. [27,28] performed a rigorous comparative study of supervised learning algorithms to detect anomalies in IoMT networks. It has been found that ensemble methods, and especially Random Forest, have a higher detection accuracy, and the computational requirements are sufficiently low to support implementation on resource-bound medical hardware [46]. The research in [47] highlights the importance of domain-specific feature selection and preprocessing strategies. The authors gave more emphasis to the significance of feature selection and the specific pre-processing approaches used for the healthcare network traffic, and observed that domain-specific optimizations can significantly enhance detection performance [48]. Balhareth and Ilyas (2024) combined intrusion detection mechanisms based on tree-based ML algorithms with high-quality, filter-based feature selection mechanisms that are specifically crafted to handle IoMT network traffic. This combination produced statistically significant gains in detection accuracy with a relatively small computational cost. These findings indicate that a carefully designed feature selection process can be used to effectively streamline the supervised learning task to the specificities of the healthcare-related traffic [49].

In [29] an intelligent framework based on Extreme Learning Machine algorithms and Bayesian optimization methods was proposed to detect cyber-attacks in IoMT. Their optimization-based solution has been able to train faster and have better generalization abilities without compromising the computational efficiency needed to be deployed in practice in healthcare [93]. Kulshrestha and Vijay Kumar (2024) have created machine learning-based IDSs that include the use of specific methods to deal with imbalanced data that are characteristic of healthcare settings. Table 12 presents a summary of the supervised learning approaches used for intrusion detection in IoMT systems. Decision tree models strike a perfect balance between accuracy and interpretability, whereas ensemble models are very robust in various attack settings. The difference in training times is a trade-off between mathematically advanced optimization procedures and performance demands.

10.1.2. Unsupervised learning approaches

Unsupervised learning has proven to have remarkable potential in IoMT security applications because medical device communication and healthcare workflows have a relatively predictable nature. Sarangi et al. [34] used feature-engineering techniques and a hybrid Principal Component Analysis-Grey Wolf Optimization (PCA-GWO) algorithm that minimizes the dimensions without losing the discriminatory ability

required to identify the threat precisely. They showed faster computational and stronger detection rates.

Recent advances in unsupervised learning of IoMT have been directed at the challenge of concept drift, where the typical patterns of operation change with time as a result of changes in clinical practice, updates in technology, or changes in operations [82]. Table 13 revealed that metaheuristic-optimized unsupervised approaches achieve the highest accuracy (99.9 %) while maintaining low false positive rates.

10.2. Deep learning-based intrusion detection systems

Deep learning has been suggested as a new technology that can be utilized in intrusion detection in the IoMT [81] as it provides an opportunity to automatically identify features in raw network data [77].

10.2.1. Convolutional neural network approaches

The effectiveness of CNN structures in the network security domain has been attributed to the fact that they automatically learn hierarchical feature representations of network. Faruqui et al. [73] developed a novel IoMT IDS based on the hybrid CNN-LSTM framework and found it to be more efficient than other methods in detecting various cyber-attacks on medical equipment. They integrated the spatial feature-extraction capability of the CNN and the temporal recognition capability of the LSTM to develop an efficient threat-detection system to address the time- and dynamics-related needs of the healthcare setting.

Gopala Krishnan et al. [54] suggested more secure IoMT devices through the combination of DL and network intrusion detection, using CNN designs to optimize real-time medical device traffic. This approach was shown to be more effective in detecting attacks in a wide range of attack scenarios.

Recent CNN-based advancements in intrusion detection of IoMT make use of transfer-learning methods that leverage existing trained models to improve detection accuracy, saving training time and data. These methods overcome the limited availability of labelled datasets on healthcare-security and can be highly successful in heterogeneous IoMT settings. Table 14 shows that stacked ensemble CNN methods are the most accurate (98.2 %), but they are also the most computationally intensive.

10.2.2. Long short-term memory and recurrent approaches

LSTM networks are adept at detecting temporal patterns and sequential dependencies in IoMT network traffic. They are suitable for detecting attacks with complex temporal patterns characteristic of advanced persistent threats and sophisticated attack campaigns against healthcare systems [73]. Authors in [9] have established a new LSTM called L2D2, which is designed to perform multi-class IDSs in the IoMT era, and has better performance in detecting different types of cyber-attacks due to its temporal pattern detection and sequential learning [91,96]. HIDS-IoMT is an IDS that is highly efficient and is implemented by Berguiga et al. [53] through DL, using the LSTM networks to offer a full device-level and network-level threat detection.

Table 12
Supervised Learning Approaches in IoMT IDS.

Studies	Algorithm Type	Primary Techniques	Dataset Used	Accuracy (%)	Precision (%)	Recall (%)	F1-Score (%)	Training Time (s)	Feature Engineering
[60]	Tree-based	Random Forest, XGBoost	IoMT traffic	98.79	97.94	99.90	99.09	120	Filter-based selection
[94]	Optimized ML	ELM + Bayesian	Healthcare datasets	99.03	99.03	99.03	99.03	95	Bayesian optimization
[72]	Multi-model	Multiple ML algorithms	Healthcare IoT	99.7	93.1	93.8	93.4	165	Attack-specific features
[4]	Imbalance-aware	ML with class balancing	IoMT networks	99.18	98.68	98.98	98.83	200	Imbalance handling
[74]	Rule-based ML	Feature selection + ML	Industrial IoT	98.12	98.0	92.4	91.8	190	Rule-based features

Table 13

Unsupervised learning approaches in IoMT IDS.

Studies	Approach Type	Core Technique	Anomaly Detection Method	Dataset Characteristics	Accuracy (%)	Adaptation Capability	Healthcare Integration
[27]	Statistical anomaly	Behavioral profiling	Statistical deviation	Custom IoMT traffic	96.5	Medium	IoMT-specific
[34]	Dimensionality reduction	PCA-GWO hybrid	Feature space anomalies	DNN-optimized	99.9	Medium	Architecture-specific
[76]	Hybrid unsupervised	Multi-technique	Combined anomalies	IoMT fog systems	High	High	Fog computing
[81]	Fuzzy clustering	Multi-modal analysis	Fuzzy-based detection	Multi-modal IoMT	92.95	High	Privacy-preserving
[66]	Metaheuristic	Optimization-based	Optimized clustering	Healthcare 4.0	99.69	Very High	Healthcare 4.0
[91]	Behavioral analysis	IoMT-specific patterns	Behavior deviation	IoMT prototypes	99.9	Low	Native IoMT
[95]	BC-based	Distributed anomaly	Consensus-based	E-health platform	-	High	BC integration

Table 14

Comprehensive analysis of CNN-based approaches.

Studies	CNN Architecture	Optimization Method	Input Data Type	Accuracy (%)	Memory Usage (MB)	Edge Compatibility	Healthcare Adaptation
[73]	CNN-LSTM	SafetyMed framework	Network traffic	97.63	245	Yes	IoMT-specific
[57]	Hybrid EHO—CNN	Elephant herding optimization	Traffic features	96.4	220	Yes	Architecture-optimized
[54]	Enhanced CNN	Deep learning optimization	Device communication	97.06	200	Yes	Real-time processing
[96]	Hybrid CNN	Healthcare framework	Medical data streams	99.19	260	Limited	Clinical integration
[49]	PSO—CNN	PSO	Sustainable IoMT	96.0	380	No	Sustainability-focused
[58]	Blended CNN	Edge-centric framework	Consumer edge data	98.53	150	Yes	Industrial IoMT
[55]	Stacking CNN	Enhanced scanning	Multi-grained data	91.0	290	Limited	Network-wide analysis
[53]	Intelligent CNN	Deep learning HIDS	Host-based data	99.92	320	Limited	Device-level security
[11]	SNN-enhanced	Spiking neural networks	AI-driven analysis	95.9	140	Yes	Energy-efficient
[50]	Stacking ensemble	Deep learning stack	Real-time streams	99.0	450	No	Ensemble optimization

Musikawan et al. [55] have proposed an improved multigradient scanning-based deep stacking networks, which consisted of more optimized LSTM modules to enhance the detection accuracy. These bi-directional LSTM solutions are especially beneficial to offline data analysis and forensic investigation, where an overall record of events across time can be studied exhaustively [54,55]. As shown in Table 15, the HIDS-LSTM model shows the most accurate result at 99.927 percent, with medium memory performance.

11. Federated learning-based intrusion detection systems

FL is a distributed approach that allows multiple healthcare institutions to learn together without violating data privacy. This solves the critical problem of limited labeled data of each healthcare organization.

11.1. Privacy-preserving distributed detection

Authors in [50] suggests a FL based IDS in the IoMT networks, which integrates the privacy-saving qualities of FL with permanence and

Table 15

LSTM and recurrent approaches.

Studies	LSTM Architecture	Temporal Features	Sequence Length	Accuracy (%)	Memory Efficiency	Learning Capability	Healthcare Focus
[9]	L2D2 multi-class	Advanced temporal patterns	Variable	98.0	High	Multi-class learning	IoMT-specific
[18]	Federated LSTM	Distributed sequences	Variable	99.31	Distributed	FL	Multi-institutional
[22]	Feature-LSTM	Selected sequences	Optimized length	99.7	High	Feature learning	Comprehensive selection
[76]	Fog-LSTM	Hierarchical sequences	Multi-tier	High	Medium	Fog computing	Lightweight systems
[53]	HIDS-LSTM	Device behavioral patterns	Short-medium	99.92	Medium	Intelligent adaptation	Device security
[55]	Enhanced stacking	Multi-grained sequences	Multi-scale	91.0	Medium	Deep stacking	Network analysis
[56]	Swarm-LSTM	Bio-inspired patterns	Short sequences	99.1	High	Swarm optimization	Framework security
[49]	PSO-LSTM	Optimized sequences	Sustainability-focused	96.0	Low	Particle optimization	Sustainable IoMT
[73]	CNN-LSTM Hybrid	Spatio-temporal patterns	Medium-long	97.63	Medium	Hybrid learning	Safety-focused
[96]	Hybrid LSTM	Healthcare sequences	Clinical patterns	99.19	Medium	Healthcare learning	Clinical integration

distributed trust of the BC technology. The use of hierarchical FL structures has proven to have tremendous potential in the case of large-scale IoMT implementations. In [18], authors suggested the use of complicated dew-cloud-based hierarchical FL based IDSs for the IoMT systems and demonstrated how hierarchical FL systems can be optimized. The hierarchical architecture can support their capability to organize the edge device, fog nodes, and the cloud infrastructure effectively, and their data locality and privacy requirements [63].

More advanced privacy preservation-based techniques in FL are based on differential privacy mechanisms, which add carefully controlled noise to model updates [47,49]. Secure aggregation protocols permit multiple parties to compute aggregate statistics without learning the individual contributions, and homomorphic encryption permits computation on encrypted data to be performed without decryption [90]. As shown in Table 16, FL combined with BC is more accurate (97.2) and provides strong privacy guarantees.

11.2. Decentralized learning architectures

Federated IoMT-IDS architectures solve the natural issues of distributed learning in healthcare environments, where connectivity, computing power, and operational priorities may differ significantly between participating institutions [29,33]. A recently proposed federated reinforcement-based fusion model, Fed-Inforce-Fusion [19], provides security and privacy assurances to IoMT networks in case of cyber-attacks, and demonstrates how federated architectures can be extended to incorporate reinforcement learning to boost the adaptive detection of network threats [90]. The strategy adopted on models that can be adjusted to changing patterns of threats without violating privacy [31,32].

A federated edge approach removes natural latency constraints of healthcare applications, although it still has the benefits of distributed learning in multiple healthcare centers. This has required the use of complex model synchronization and conflict-resolution algorithms [84]. Decentralized FL involves consensus mechanisms that allow participating healthcare organizations to reach an agreement on updating the model without infringing on personal autonomy [88]. Adaptive FL architectures include non-IID (non-independent and non-identically distributed) data-management functions, which are motivated by the heterogeneity of healthcare settings, where various institutions have diverse patient populations, medical equipment, and risk exposures [61]. These adaptive strategies are useful because they consider the

heterogeneity of healthcare data within different clinical settings [21].

The reinforcement-based architecture has the highest learning efficacy and, simultaneously, poses a tremendous complexity in deployment, as indicated in Table 17. In comparison, the resource-efficient architecture does impose even stricter requirements on the learning process but does not have too high deployment complexity. Though BC-based systems are more resilient to failure, they are generally less complex and less communicative [83].

12. Blockchain-Enhanced intrusion detection systems

The integration of BC technology with IoMT IDSs gives it revolutionary characteristics like immutability, decentralized trust, and a more robust security audit [88].

12.1. Immutability and audit trail capabilities

In [93], a detailed intrusion detection and prevention architecture is presented to offer end-to-end protection. Improved IDS deployments have already demonstrated the capability to detect distributed denial-of-service (DDoS) attacks in the BC-IoMT networks [6,81]. Advanced BC designs support other requirements of healthcare settings [29,33]. They provide BC-based security services to IoMT edge networks [97]. The audit trails will enable healthcare organizations to testify to adherence to security rules and permit comprehensive forensic investigations of security violations. Table 18 demonstrates the immutability and audit trail capabilities in BC-IoMT IDS. BC systems that deal with healthcare have a high rate of regulatory compliance and moderate integration needs.

12.2. Decentralized trust and consensus mechanisms

IoMT IDS incorporates BC to provide decentralized trust solutions, which are resilient to threat detection despite network components being attacked. These systems are based on decentralized consensus, instead of centralized control, and they are more reliable and transparent. FL models based on BC also combine privacy protection with decentralized trust, which enhances the scalability and operational efficiency of healthcare networks [20,98]. Smart contracts are automated responses and policy enforcement, which maintain the auditability and compliance of clinical settings [7,24–26].

In order to satisfy the real-time needs of healthcare, the mechanism

Table 16
Privacy-Preserving distributed detection in federated IoMT IDS.

Studies	Privacy Method	Participants	Bandwidth (MB/round)	Convergence Time (min)	Accuracy (%)	Privacy Guarantee	Healthcare Integration
[1]	Multiple Methods	Various configurations	1.5–5.0	25–70	94.5–97.8	Variable	Survey analysis
[18]	Secure Aggregation	Multi-tier hierarchy	3.2	38	99.31	Medium	Healthcare Ecosystem
[19]	Gradient Privacy	Multi institutional (CNNs; Edge-IoTSet)	4.1	65	97.2	Strong	Reinforcement Based
[21]	BC, Differential Privacy	(CNNs; Edge-IoTSet)	2.5	45	97.43 %	Strong	Multi institutional
[21]	BC, Differential Privacy	(BiLSTM; Edge-IoTSet)	2.5	45	96.02 %	Strong	Multi institutional
[21]	BC, Differential Privacy	(CNNs; TON-IoT)	2.5	45	98.21 %	Strong	Multi institutional
[21]	BC, Differential Privacy	(BiLSTM; TON-IoT)	2.5	45	97.42 %	Strong	Multi institutional
[33]	Edge Privacy	Multi-access Edge	2.1	35	93.4	Medium	Edge Computing
[59]	Homomorphic Encryption	Distributed IoMT	1.8	28	99.38	Very Strong	Resource Efficient

Table 17
Decentralized learning architectures in federated IoMT IDS.

Ref.	Architecture Type	Consensus Mechanism	Node Scalability	Fault Tolerance	Communication Efficiency	Learning Effectiveness	Deployment Complexity
[6]	Survey analysis	Various mechanisms	Variable	Variable	Variable	Variable	Variable
[29]	BC driven	Distributed consensus	Medium	Very High	Medium	High	Very High
[33]	Edge federated	Edge coordination	High	Medium	High	Medium	Medium
[31]	Hierarchical	Multi-tier aggregation	Very High	High	High	High	High
[76]	Fog federated	Fog aggregation	High	High	Medium	Medium	High
[59]	Reinforcement based	Gradient consensus	High	Very High	Medium	Very High	High
[70]	Resource efficient	Lightweight consensus	Very High	High	Very High	Medium	Medium
[93]	IoMT federated	BC consensus	Medium	High	Medium	High	High
[94]	Smart federated	Intelligent consensus	High	High	High	High	High
[95]	E-health federated	Healthcare consensus	Medium	Medium	Medium	Medium	Medium

Table 18
Immutability and Audit Trail Capabilities in BC-IoMT IDS.

Reference	BC Type	Consensus Mechanism	Immutability Strength	Audit Capabilities	Integration Complexity	Performance Impact	Regulatory Compliance
[6]	Consortium	PBFT	High	DDoS-focused	High	Medium	Standards-compliant
[7]	Hybrid	Multi-consensus	Very High	Federated audit	High	Medium	Multi-standard
[67]	Private	Proof of Authority	Very High	Comprehensive	Medium	Low	HIPAA-compliant
[21]	Consortium	Federated consensus	High	Learning audit	Very High	Medium	Privacy-compliant
[29]	Private	Proof of Stake	Very High	Edge-specific	Medium	Low	Healthcare-focused
[49]	Smart BC	Intelligent consensus	High	Smart audit	High	Medium	Smart standards
[68]	Consortium	Tendermint	High	IoMT-specific	High	Medium	Medical standards
[79]	Hybrid	Resilient consensus	Very High	TNN-enhanced	High	Medium	Resilient compliance
[95]	Private	Healthcare consensus	High	E-health audit	Medium	Low	E-health standards

of consensus is optimized to guarantee low latency and energy efficiency in emergency cases. Multi-signature and threshold signature schemes are methods used to involve stakeholders in collective and responsible decision-making, whereas Byzantine fault-tolerant protocols ensure the availability of the system against malicious nodes, ensuring that the system works continuously, and patient safety is ensured [99,100]. Table 19 indicates that authority-based consensus mechanisms are the most efficient in terms of decision speed and energy consumption, and

federated types are the most efficient in terms of multi-institutional scaling.

13. Datasets and evaluation metrics

The analysis of IDSs in the IoMT contexts is more complex because of the lack of healthcare-specific datasets. As a result, the research community has tackled this issue with an eclectic set of datasets, including

Table 19
Decentralized Trust and Consensus Mechanisms in BC-IoMT IDS.

Study	Consensus Type	Fault Tolerance	Trust Model	Decision Speed	Energy Efficiency	Scalability	Healthcare Alignment
[7]	Federated consensus	Byzantine tolerant	Distributed trust	Medium	Medium	High	Multi-institutional
[67]	Authority Based	High tolerance	Permissioned trust	Very Fast	High	Medium	Clinical integration
[21]	Federated Proof of Stake	High tolerance	Learning trust	Medium	High	High	Privacy-focused
[29]	Edge consensus	Edge tolerant	Edge trust	Very Fast	High	Medium	Edge computing
[68]	Smart contract	Fault tolerant	Programmable trust	Fast	Medium	Medium	IoMT-specific
[79]	Resilient consensus	Very high tolerance	Resilient trust	Medium	Medium	High	TNN-enhanced
[95]	Healthcare consensus	Medical tolerance	Healthcare trust	Fast	High	Medium	E-health platform
[98]	Intelligent consensus	AI-enhanced tolerance	Smart trust	Fast	Medium	High	Smart healthcare
[100]	Mobile consensus	Vehicle tolerance	Mobile trust	Fast	Medium	Medium	Mobile healthcare

both traditional network security benchmarks and more IoT-focused collections.

13.1. Dataset categories and characteristics

The dataset space considered in the analysis of IoMT intrusion detection includes three major groups: traditional IT/network security datasets, IoT-oriented datasets, and more recently introduced IoMT-specific datasets [34].

These types have different research purposes and attribute diverse levels of applicability to the real-life healthcare network contexts. Fig. 9 presents the frequency of datasets used across the reviewed literature, highlighting the most commonly employed IoMT datasets for cybersecurity studies.

13.1.1. Traditional IT and network security datasets

The foundation of the early research on IoMT intrusion detection has been based on conventionally available network security datasets. The NSL-KDD dataset, which is an adaptation of the original KDD [101] dataset, is an outdated and largely inapplicable dataset to modern healthcare network characteristics. To determine the applicability of machine learning techniques in intrusion detection in IoMT networks [41], have conducted a detailed comparative study of NSL-KDD and other standard datasets to reveal not only the feasibility of such practices, but also to demonstrate their inefficiency in applying traditional security datasets to new settings.

The CIC-IDS-2017 and CIC-IDS-2018 [102] are modern datasets in terms of network traffic and attacks. In [103], the CIC-IDS dataset is used in the development of their SafetyMed framework, showing how network security datasets can be adapted to the evaluation of IoMT intrusion detection.

UNSW-NB15 [102,103] is an alternative modern dataset that overcomes some of the limitations of older benchmark datasets by increasing the diversity of attack traffic. Some of the IoMT studies that have considered UNSW-NB15 as part of the evaluation framework include the study by [82,104] which used this data set to ensure the validity of their proposed particle swarm optimization and deep learning solution to identifying intrusion in IoMT environments, illustrating the limitations and opportunities of general network security data sets in healthcare settings.

13.1.2. IoT-Specific datasets

The ToN-IoT [105] dataset is one of the richest IoT security datasets with a variety of IoT device types and attacks that are more aligned with IoMT settings than those found in traditional IT datasets. Regarding the creation of anomaly-based IDSs in the context of an IoMT network [102, 103], offers a full assessment based on Internet of Things-specific datasets. Many researchers have taken BoT-IoT as a part of their evaluation systems, and they have adapted its features to correspond to the communication patterns and device behaviors typical of a clinical

environment.

13.1.3. Emerging IoMT-specific datasets

The BlueTrack dataset is specifically devoted to Bluetooth-based medical communications [41], which offers realistic evaluation conditions to wearable and implantable medical devices. Recently, Zubair et al. (2022) examined the security stance of smart healthcare settings by developing and using healthcare-specific Bluetooth datasets, thus demonstrating that protocol-oriented datasets are required to accurately evaluate IoMT security solutions. The Ecu-IoHT (Edge Computing unit of Internet of Health Things) dataset also adds to the existing collection of assessment resources in the healthcare sector since it includes edge-computing situations common to modern IoMT implementations.

13.1.4. Dataset utilization analysis

The analysis of the usage scheme of the datasets in the studies on the subject of IoMT intrusion detection shows that there are high patterns and biases, which are based on the availability of datasets, as well as their perceived relevance to the security issues associated with healthcare [106]. The use of conventional IT security datasets in most studies, although not relevant in most IoMT scenarios, highlights the continued nature of the difficulty of creating realistic and thorough evaluation data that is unique to healthcare settings. Table 20 presents the approaches used by the researchers in managing the limitations of the dataset when evaluating the IoMT.

14. Comparative performance analysis

Considering the performance metrics of different methods of IoMT intrusion detection, it is possible to note significant differences, not only in the actual performance achieved, but also in the metrics used. This variation can be explained by the fact that the research is heterogeneous, and the evaluation approaches used are different in the field. This has the negative effect of obstructing direct comparisons of methodologies, which explains the need to develop standardized evaluation frameworks and uniform metrics reporting practices. Table 21 describes the significant performance differences between multiple intrusion detection schemes.

15. Challenges and future directions

The development of intrusion detection solutions within the context of the IoMT presents several problematic aspects that must be addressed to create viable and effective cybersecurity solutions in healthcare.

15.1. Lightweight IDS for resource-constrained IoMT devices

The idea of developing lightweight security solutions that can be adapted to the needs of resource-constrained medical devices can be discussed as one of the most important issues of IoMT IDSs. Most medical devices, especially wearable and implantable systems, are subject to extreme computational, memory, and energy constraints that restrict the complexity of local security mechanisms that may be deployed. Zachos et al. [42] have solved this problem by designing anomaly-based IDSs tailored to resource-constrained devices in IoMT networks and showed how detection algorithms can be adapted to devices with low computational resources without compromising the effectiveness of detecting threats [91].

15.2. Explainability and interpretability of AI-Based systems

The explainable boosting ensemble framework suggested by Sohail et al. [24–26] to be used when the intrusion detection is applied to the IoMT, demonstrates that the sophisticated AI may be interpreted in a way that does not lead to a reduction in the detection level. The advanced deep learning and ensemble models are, however, inherently




Fig. 9. Frequency of Datasets used in the literature.

Table 20
Dataset Utilization Patterns in IoMT Intrusion Detection Research.

Ref.	Primary Dataset	Secondary Datasets	Dataset Category	Justification	Adaptation Method	Limitations Addressed
[9]	Multi-dataset	Various sources	Comprehensive	Algorithm robustness	Cross validation	Integration complexity
[17]	BlueTrack	Custom Bluetooth	Communication-specific	Protocol relevance	Direct deployment	Limited scope
[23]	Systematic review	All categories	Literature analysis	Complete overview	Classification approach	Review-based only
[40]	Literature survey	Multiple datasets	Survey analysis	Comprehensive review	Meta analysis	No direct evaluation
[42]	Custom IoMT	ToN-IoT	IoMT-specific	Real healthcare traffic	Direct application	Limited attack diversity
[53]	IoMT testbed	CIC-IDS-2018	Hybrid evaluation	Realistic scenarios	Protocol adaptation	Scalability constraints
[60]	Multiple IoT	Custom generated	IoT-focused	Device diversity	Feature engineering	Synthetic nature
[49]	UNSW-NB15	NSL-KDD	Mixed approach	Algorithm validation	Statistical normalization	Generic attack patterns
[64]	NSL-KDD	CIC-IDS-2017	Traditional IT	Benchmarking comparison	Feature mapping	Limited IoMT relevance
[73]	CIC-IDS-2017	UNSW-NB15	Modern network	Contemporary attacks	Traffic filtering	Healthcare context missing

Table 21
Performance Comparison of IoMT Intrusion Detection Systems.

Studies	Accuracy (%)	Precision (%)	Recall (%)	F1 – Score (%)	Energy Efficiency
[9]	98.0	98.0	98.0	98.0	110
[50]	99.0	99.0	99.0	98.0	200
[53]	99.92	99.91	99.91	99.95	120
[56]	99.1	99.1	99.1	-	90
[58]	98.53	98.59	99.42	99.00	85
[60]	98.79	97.94	99.90	99.09	35
[49]	96.0	96.0	95.0	95.0	180
[73]	97.63	98.47	97.00	97.73	150
[94]	99.03	99.03	99.03	99.03	25

black box, and the logic behind their decision-making process is unavailable to clinical staff, making them inappropriate for protecting medical safety. The research gap requiring specific consideration, in turn, is the creation of Explainable Artificial Intelligence (XAI) strategies that would be particularly sensitive to the needs of healthcare cybersecurity; these strategies should address the needs of balancing the complexity and sophistication of threat-detection systems with the need to clarify the logic behind their work in a manner that would satisfy both clinical and regulatory demands [83].

15.3. Data imbalance and dataset availability

One of the natural impediments to improvement and to experimenting with effective security practices is a deficiency of realistic and detailed datasets to investigate the field of IoMT intrusion detection. The health care environments also provide further constraints to data collection and exchange, as the privacy legislation, patient confidentiality, and sensitivity of medical systems limit access to real-life attack events that might be required in the research. In their study of the IoMT IDSs, Kharaisat and Alazab [39] also emphasized the importance of domain-specific data and found that the lack of real medical data compels researchers to work with generic IT or IoT data that do not reflect the specifics of medical device interaction and healthcare network functioning.

15.4. Integration with emerging technologies

The fast pace of networking and computing technology changes also poses both an opportunity and a challenge to IoMT IDSs, which demand

security solutions capable of integrating with new technologies such as 5 G networks, edge and fog computing networks, and Software-Defined Networking (SDN) [15,77,94] and Network Function Virtualization (NFV) [84] platforms. The high bandwidth and very low latency capabilities of 5 G networks enable new healthcare applications, but also create new attack surfaces and security issues that traditional IDSs cannot properly address. The paradigms of edge and fog computing have the potential to host security processing in a distributed computing environment, but these paradigms will require advanced coordination capabilities to ensure a coherent security policy and effective correlation of threats across distributed computing resources. Singh et al. (2018) address the compatibility of hierarchical FL structures built based on dew-cloud paradigms and distributed computing infrastructures.

15.5. Future research directions

The future of intrusion detection in smart healthcare lies in the combination of sophisticated technologies to eliminate the existing obstacles to provide a complete, flexible, and safe solution to future medical settings. Integration of FL with BC technology and a combination of privacy-preserving collaborative learning with fixed audit trails and decentralized authentication schemes are among them. Begum et al. [21] give an illustration of how FL using BC may be executed to attain effective intrusion detection, but comprehensive frameworks that implement these technologies are yet to be implemented [96].

The field of adversarial robust IDSs is a worthwhile field of research, especially in the wake of heightened cases of adversarial attacks aimed at beating the detection systems. Such powerful mechanisms should be able to include sophisticated defensive measures to overcome the attacks that take advantage of the weaknesses of machine-learning-based detection systems, but also satisfy the performance and efficiency needs of healthcare settings. Likewise, the development of regulatory-compliant security systems, which can be maintained by adapting healthcare regulations and a regulatory-compliant security system that may yet provide effective threat detection, is also a crucial research agenda [2].

Quantum abilities and a classical intrusion detection framework would simplify the modifications to data processing of the large-scale, high-dimensional data of the contemporary healthcare network and, at the same time, provide quantum-resistant security characteristics required by long-term security guarantees [3]. The future, possibly enhanced, approach is the creation of zero-trust safety designs tailored to the healthcare setting, including the continuous authentication and

authorization capability, not only urgent to healthcare applications but also fixable and meeting operational-efficiency needs [105].

16. Conclusion

This review provides a comprehensive analysis of intrusion detection in the Internet of Medical Things (IoMT), addressing critical gaps in datasets, interpretability, scalability, and resource constraints. By integrating BC validation, FL, and explainable AI, it highlights emerging solutions to enhance IoMT security. A multi-dimensional taxonomy, threat-architecture mapping, and dataset categorization offer structured guidance for researchers and practitioners. The proposed future research roadmap emphasizes lightweight, privacy-preserving, and interoperable IDS designs. Ultimately, this work contributes a unified reference framework to strengthen the resilience, trustworthiness, and regulatory compliance of next-generation digital healthcare systems.

Funding

No funding received.

Data availability

No data was used for the research described in the article.

CRediT authorship contribution statement

Syed Rizwan Hassan: Writing – original draft, Validation, Methodology. **Muhammad Usama Tanveer:** Writing – original draft, Visualization, Methodology. **Sunil Prajapat:** Writing – review & editing. **Mohammad Shabaz:** Writing – review & editing.

Declaration of competing interest

The author declares no conflict of interest, financial or otherwise.

References

- [1] R.P. Pinto, B.M.C. Silva, P.R.M. Inácio, Federated learning for anomaly detection on Internet of Medical Things: a survey, *Internet Things (Neth.)* 33 (2025) 101677, <https://doi.org/10.1016/j.iot.2025.101677>.
- [2] M.L. Hernandez-jaimas, A. Martinez-cruz, Internet of Things artificial intelligence for IoMT security : a review of intrusion detection systems , attacks , datasets and Cloud – Fog – Edge architectures, *Internet Thing.* 23 (2023) 100887, <https://doi.org/10.1016/j.iot.2023.100887>.
- [3] B. Bhushan, A. Kumar, A.K. Agarwal, A. Kumar, P. Bhattacharya, Towards a secure and sustainable internet of medical things (IoMT): requirements , design challenges, *Secur. Tech. Future Trend.* (2023).
- [4] P. Kulshrestha, T.V. Vijay Kumar, Machine learning based intrusion detection system for IoMT, *Int. J. Syst. Assur. Eng. Manag.* 15 (2024) 1802–1814, <https://doi.org/10.1007/s13198-023-02119-4>.
- [5] A. Aljuhani, A. Alamri, P. Kumar, A. Jolfaei, An intelligent and explainable SaaS-based intrusion detection system for resource-constrained IoMT, *IEEE Internet Things J.* 11 (2024) 25454–25463, <https://doi.org/10.1109/JIOT.2023.3327024>.
- [6] M. Akkal, S. Cherbal, K. Kharoubi, B. Annane, A. Gawanmeh, H. Lakhlef, An intrusion detection system for detecting DDoS attacks In blockchain-enabled IoMT networks, in: 2024 7th International Conference on Signal Processing and Information Security 2024, ICSPIS, 2024, <https://doi.org/10.1109/ICSPIS63676.2024.10812635>.
- [7] B. Zaabar, O. Cheikhrouhou, M. Abid, Intrusion detection system for IoMT through blockchain-based Federated Learning, in: Proceedings of the 2022 15th IEEE International Conference on Security of Information and Networks 2022, SIN, 2022, <https://doi.org/10.1109/SIN56466.2022.9970536>.
- [8] S.B. Weber, S. Stein, T. Schrader, Attack detection for medical cyber-physical systems – A systematic literature review, *IEEE Access.* 11 (2023) 41796–41815, <https://doi.org/10.1109/ACCESS.2023.3270225>.
- [9] G. Akar, S. Sahmoud, M. Onat, U. Cavusoglu, E. Malondo, L2D2: a novel LSTM model for multi-class intrusion detection systems in the era of IoMT, *IEEE Access.* 13 (2025) 7002–7013, <https://doi.org/10.1109/ACCESS.2025.3526883>.
- [10] R. Pakrooh, A. Jabbari, C. Fung, Deep learning-assisted security and privacy provisioning in the internet of medical things systems: a survey on recent advances, *IEEE Access.* 12 (2024) 40610–40621, <https://doi.org/10.1109/ACCESS.2024.3377561>.
- [11] M. Benmalek, A. Seddiki, K.D. Haouam, SNN-IoMT: a novel AI-driven model for intrusion detection in internet of medical things, *CMES - Comput. Model. Eng. Sci.* 143 (2025) 1157–1184, <https://doi.org/10.32604/cmcs.2025.062841>.
- [12] J.A. Shaikh, C. Wang, M.W.U. Sima, M. Arshad, M. Owais, D.S.M. Hassan, R. Alkanhel, M.S.A. Muthanna, A deep reinforcement learning-based robust intrusion Detection system for securing IoMT Healthcare Networks, *Front Med (Lausanne).* 12 (2025), <https://doi.org/10.3389/fmed.2025.1524286>.
- [13] A. Khraisat, I. Gondal, P. Vamplew, J. Kamruzzaman, Survey of intrusion detection systems: techniques, datasets and challenges, *Cybersecurity* 2 (2019), <https://doi.org/10.1186/s42400-019-0038-7>.
- [14] S.S. Hameed, A. Selamat, L.A. Latiff, S.A. Razak, O. Krejcar, H. Fujita, M.N. A. Sharif, S. Omatu, A hybrid lightweight system for early attack detection in the IoMT fog, *Sensors* 21 (2021), <https://doi.org/10.3390/s21248289>.
- [15] A. Si-Ahmed, M.A. Al-Garadi, N. Boustia, Survey of machine learning based intrusion detection methods for Internet of Medical Things, *Appl. Soft. Comput.* 140 (2023) 0–2, <https://doi.org/10.1016/j.asoc.2023.110227>.
- [16] J. Doménech, O. León, M.S. Siddiqui, J. Pegueroles, Evaluating and enhancing intrusion detection systems in IoMT: the importance of domain-specific datasets, *Internet Thing.* 32 (2025) 101631, <https://doi.org/10.1016/j.iot.2025.101631>.
- [17] M. Zubair, A. Ghubaihs, D. Unal, A. Al-Ali, T. Reimann, G. Alinier, M. Hammoudeh, J. Qadir, Secure bluetooth communication in Smart Healthcare Systems: a novel community dataset and intrusion detection system †, *Sensors* 22 (2022) 1–23, <https://doi.org/10.3390/s22218280>.
- [18] P. Singh, G.S. Gaba, A. Kaur, M. Hedabou, A. Gurtov, Dew-cloud-based hierarchical federated learning for intrusion detection in IoMT, *IEEE J. Biomed. Health Inf.* 27 (2023) 722–731, <https://doi.org/10.1109/JBHI.2022.3186250>.
- [19] I.A. Khan, I. Razzak, D. Pi, N. Khan, Y. Hussain, B. Li, T. Kousar, Fed-Inforce-Fusion: a federated reinforcement-based fusion model for security and privacy protection of IoMT networks against cyber-attacks, *Inf. Fusion.* 101 (2024) 102002, <https://doi.org/10.1016/j.inffus.2023.102002>.
- [20] M. Wazid, A.K. Das, J.J.P.C. Rodrigues, S. Shetty, Y. Park, IoMT malware detection approaches: analysis and research challenges, *IEEE Access.* 7 (2019) 182459–182476, <https://doi.org/10.1109/ACCESS.2019.2960412>.
- [21] K. Begum, M.A.I. Mozumder, M.-I. Joo, H.-C. Kim, BFLIDS: blockchain-driven federated learning for intrusion detection in IoMT networks, *Sensors* 24 (2024) 4591, <https://doi.org/10.3390/s24144591>.
- [22] M. Ur Rehman, R. Kalakoti, H. Bahsi, Comprehensive feature selection for machine learning-based intrusion detection in Healthcare IoMT networks, *Int. Conf. Inf. Syst. Secur. Priv.* 2 (2025) 248–259, <https://doi.org/10.5220/0013313600003899>.
- [23] A. Naghib, F.S. Gharehchopogh, A. Zamanifar, A comprehensive and systematic literature review on intrusion detection systems in the internet of medical things: current status, challenges, and opportunities, *Artif. Intell. Rev.* 58 (2025), <https://doi.org/10.1007/s10462-024-11101-w>.
- [24] F. Sohail, M.A.M. Bhatti, M. Awais, A. Iqtidar, Explainable boosting ensemble methods for intrusion detection in Internet of medical things (IoMT) applications, 4th International Conference on Digital Futures and Transformative Technologies, ICoDT2 2024 (2024). <https://doi.org/10.1109/ICoDT262145.2024.10740251>.
- [25] M. Puthin Krishna, S.R. Kumar, K. Palani Thanaraj, Intrusion Detection System for defending against DoS attacks in the IoMT ecosystem, 4th International Conference on Communication, Computing and Industry 6.0, C216 2023 (2023). <https://doi.org/10.1109/C21659362.2023.10430773>.
- [26] G. Zachos, G. Mantas, I. Essop, K. Porfyakis, J.C. Ribeiro, J. Rodriguez, Prototyping an anomaly-based intrusion detection system for Internet of medical Things networks, in: IEEE International Workshop on Computer Aided Modeling and Design of Communication Links and Networks, CAMAD 2022-Novem, 2022, pp. 179–183, <https://doi.org/10.1109/CAMAD55695.2022.9966912>.
- [27] G. Zachos, G. Mantas, K. Porfyakis, J. Manuel Camoes Sobral De Bastos, J. Rodriguez, Anomaly-based intrusion detection for IoMT Networks: design, implementation, dataset generation, and ML algorithms evaluation, *IEEE Access.* 13 (2025) 41994–42028, <https://doi.org/10.1109/ACCESS.2025.3547572>.
- [28] A. Binbusayyis, H. Alaskar, T. Vaiyapuri, M. Dinesh, An investigation and comparison of machine learning approaches for intrusion detection in IoMT network, *J. Supercomput.* 78 (2022) 17403–17422, <https://doi.org/10.1007/s11227-022-04568-3>.
- [29] F. Pelekoudas-oikonomou, G. Zachos, M. Papaioannou, M. De Ree, J.C. Ribeiro, G. Mantas, J. Rodriguez, Blockchain-Based Secur. Mech. IoMT Edge Netw. IoMT-Based Healthc. Monit. Syst., (2022).
- [30] S.R. Hassan, I. Ahmad, S. Ahmad, A. Alfaiy, M. Shafiq, Remote pain monitoring using fog computing for e-Healthcare: an efficient architecture, *Sensors* 20 (2020) 6574, <https://doi.org/10.3390/S20226574>, 2020, Vol. 20, Page 6574.
- [31] M. Alalhareth, S.C. Hong, Enhancing the internet of medical things (IoMT) security with Meta-Learning: a performance-driven approach for ensemble intrusion detection systems, *Sensors* 24 (2024), <https://doi.org/10.3390/s24113519>.
- [32] M. Alalhareth, S. Hong, Improv. Mutual Inf. Feature Sel. Tech., (2023).
- [33] G. Eric, A. Jurect, Intrusion detection in Internet of Things systems : a review on design approaches leveraging Multi-Access edge, *Sensors* 22 (2022) 1–33.
- [34] R.M. Swarna Priya, P.K.R. Maddikunta, M. Parimala, S. Koppu, T.R. Gadekallu, C. L. Chowdhary, M. Alazab, An effective feature engineering for DNN using hybrid PCA-GWO for intrusion detection in IoMT architecture, *Comput. Commun.* 160 (2020) 139–149, <https://doi.org/10.1016/j.comcom.2020.05.048>.
- [35] A.A. Hady, A. Ghubaihs, T. Salman, D. Unal, R. Jain, Intrusion detection system for Healthcare systems using medical and network data: a comparison study, *IEEE*

- Access. 8 (2020) 106576–106584, <https://doi.org/10.1109/ACCESS.2020.3000421>.
- [36] H.A. Tarish, R. Hassan, K.A.Z. Ariffin, M.M. Jaber, Network security framework for internet of medical things applications: a survey, *J. Intell. Syst.* 33 (2024), <https://doi.org/10.1515/jisys-2023-0220>.
- [37] N. Li, M. Xu, Q. Li, J. Liu, S. Bao, Y. Li, J. Li, H. Zheng, A review of security issues and solutions for precision health in Internet-of-medical-things systems, *Secur. Saf.* 2 (2023) 2022010, <https://doi.org/10.1051/sands/2022010>.
- [38] H. Nemat, H. Khadem, M.R. Eissa, J. Elliott, M. Benaissa, Blood glucose level prediction: advanced deep-ensemble learning approach, *IEEE J. Biomed. Health Inf.* 26 (2022) 2758–2769, <https://doi.org/10.1109/JBHI.2022.3144870>.
- [39] A. Khraisat, A. Alazab, A critical review of intrusion detection systems in the internet of things: techniques, deployment strategy, validation strategy, attacks, public datasets and challenges, *Cybersecurity* 4 (2021), <https://doi.org/10.1186/s42400-021-00077-7>.
- [40] Y. Zhang, D. Zhu, M. Wang, J. Li, J. Zhang, A comparative study of cyber security intrusion detection in healthcare systems, *Int. J. Crit. Infrastruct. Prot.* 44 (2024) 100658, <https://doi.org/10.1016/j.ijcip.2023.100658>.
- [41] I. Idriissi, M. Boukabous, M. Grari, M. Azizi, O. Moussaoui, An intrusion detection system using machine learning for internet of medical things, in: 2023. https://doi.org/10.1007/978-981-19-6223-3_66.
- [42] G. Zachos, I. Essop, G. Mantas, K. Porfyraakis, J.C. Ribeiro, Anom.-Based Intrusion Detect. Syst. Internet Med. Things Netw., (2021) 1–26.
- [43] P. Kumar, G.P. Gupta, R. Tripathi, An ensemble learning and fog-cloud architecture-driven cyber-attack detection framework for IoMT networks, *Comput Commun* 166 (2021) 110–124, <https://doi.org/10.1016/j.comcom.2020.12.003>.
- [44] G. Zachos, I. Essop, G. Mantas, K. Porfyraakis, J.C. Ribeiro, J. Rodriguez, An anomaly-based intrusion detection system for internet of medical things networks, *Electron. (Switz.)* 10 (2021), <https://doi.org/10.3390/electronics10212562>.
- [45] F. Akram, D. Liu, P. Zhao, N. Kryvinska, S. Abbas, M. Rizwan, Trustworthy intrusion detection in E-Healthcare Systems, *Front Public Health.* 9 (2021) 788347, <https://doi.org/10.3389/fpubh.2021.788347>.
- [46] M.A. Bassi, M.A. Lopez, L. Confalone, R.M. Gaudio, L. Lombardo, D. Lauritano, Enhanced Reader.Pdf, *Nature* 388 (2020) 539–547.
- [47] G. Zachos, I. Essop, G. Mantas, K. Porfyraakis, J.C. Ribeiro, Anom.-Based Intrusion Detect. Syst. Internet of, (2021) 1–25.
- [48] N. Sharma, P.G. Shambharkar, Multi-layered security architecture for IoMT systems: integrating dynamic key management, decentralized storage, and dependable intrusion detection framework, *Int. J. Mach. Learn. Cybern.* (2025), <https://doi.org/10.1007/s13042-025-02628-7>.
- [49] R. Chaganti, A. Mourade, V. Ravi, N. Vemprala, A. Dua, B. Bhushan, A particle swarm optimization and deep learning approach for intrusion detection system in internet of medical things, *Sustain. (Switz.)* 14 (2022) 1–18, <https://doi.org/10.3390/su141912828>.
- [50] E. Alalwany, B. Alsharif, Y. Alotaibi, A. Alfahaid, I. Mahgoub, M. Ilyas, Stacking ensemble deep learning for real-time intrusion detection in IoMT environments, *Sensors* 25 (2025), <https://doi.org/10.3390/s25030624>.
- [51] A. Ghubaihs, G.S. Member, T. Salman, G.S. Member, Recent Adv. Internet-of-Med.-Things (IoMT) Syst. Secur., 8 (2021) 8707–8718.
- [52] Y. Rbahi, M. Mahfoudi, Y. Balboul, M. Fattah, S. Mazer, M. Elbekkali, B. Bernoussi, Machine Learning and Deep learning methods for Intrusion Detection Systems in IoMT: a survey, 2022 2nd International Conference on Innovative Research in Applied Science, Engineering and Technology, IRASET 2022 (2022), <https://doi.org/10.1109/IRASET52964.2022.9738218>.
- [53] A. Berruiga, A. Harchay, A. Massaoudi, HIDS-IoMT: a deep learning-based intelligent intrusion detection system for the internet of medical things, *IEEE Access* 13 (2025) 32863–32882, <https://doi.org/10.1109/ACCESS.2025.3543127>.
- [54] D. Gopala Krishnan, M. Diviya, K.Jyoshika Shri, M. Subramanian, Enhanced security for IoMT devices: deep learning techniques for network intrusion detection, in: Proceedings - IEEE 5th International Conference on Communication, Computing and Industry 6.0 2024 2024, C2I6, 2024, <https://doi.org/10.1109/C2I663243.2024.10895169>.
- [55] P. Musikawan, Y. Kongsorot, P. Aimtongkham, C. So-In, Enhanced multigrained scanning-based deep stacking network for intrusion detection in IoMT networks, *IEEE Access* 12 (2024) 152482–152497, <https://doi.org/10.1109/ACCESS.2024.3480011>.
- [56] S. Nandy, M. Adhikari, M.A. Khan, V.G. Menon, S. Verma, An intrusion detection mechanism for secured IoMT framework based on swarm-Neural network, *IEEE J. Biomed. Health Inf.* 26 (2022) 1969–1976, <https://doi.org/10.1109/JBHI.2021.3101686>.
- [57] D. Praveena Anjelin, S.Ganesh Kumar, An effective classification using enhanced elephant herding optimization with convolution neural network for intrusion detection in IoMT architecture, *Clust. Comput* 27 (2024) 12341–12359, <https://doi.org/10.1007/s10586-024-04512-5>.
- [58] J.A. Alzubi, O.A. Alzubi, I. Qiqieh, A. Singh, A blended deep learning intrusion detection framework for consumable edge-centric IoMT industry, *IEEE Trans. Consum. Electron.* 70 (2024) 2049–2057, <https://doi.org/10.1109/TCE.2024.3350231>.
- [59] M. Fahim-Ul-Islam, A. Chakrabarty, M.G.R. Alam, S.S. Maidin, A resource-efficient federated learning framework for intrusion detection in IoMT networks, *IEEE Trans. Consum. Electron.* (2025), <https://doi.org/10.1109/TCE.2025.3544885>.
- [60] G. Balhareth, M. Ilyas, Optimized intrusion detection for IoMT networks with tree-based machine learning and filter-based feature selection, *Sensors* 24 (2024), <https://doi.org/10.3390/s24175712>.
- [61] M. Ramya, P. Sudhakaran, Y. Sivagnanam, C.S. Krishnan, Advanced intrusion detection technique (AIDT) for secure communication among devices in internet of medical things (IoMT), *EURASIP J. Wirel. Commun. Netw.* 2025 (2025), <https://doi.org/10.1186/s13638-025-02462-z>.
- [62] Y.K. Saheed, M.O. Arowolo, Efficient cyber attack detection on the internet of medical things-smart environment based on deep recurrent neural network and machine learning algorithms, *IEEE Access* 9 (2021) 161546–161554, <https://doi.org/10.1109/ACCESS.2021.3128837>.
- [63] A. Salehpour, M. Norouzi, M.A. Balafar, K. SamadZamini, A cloud-based hybrid intrusion detection framework using XGBoost and ADASYN-augmented random forest for IoMT, *IET Commun.* 18 (2024) 1371–1390, <https://doi.org/10.1049/cmu2.12833>.
- [64] A. Binbusayyis, H. Alaskar, T. Vaiyapuri, An investigation and comparison of machine learning approaches for intrusion detection in IoMT network, *J Supercomput* 78 (2022) 17403–17422, <https://doi.org/10.1007/s11227-022-04568-3>.
- [65] A. Khalid, A. Mehmood, A. Alabrah, B.F. Alkhamees, F. Amin, H. AlSalman, G. S. Choi, Breast cancer detection and prevention using machine learning, *Diagnostics* 13 (2023) 1–21, <https://doi.org/10.3390/diagnostics13193113>.
- [66] N. Savanović, A. Toskovic, A. Petrovic, M. Zivkovic, R. Damaševićius, L. Jovanovic, N. Bacanin, B. Nikolic, Intrusion detection in Healthcare 4.0 Internet of Things systems via Metaheuristics optimized Machine Learning, *Sustain. (Switz.)* 15 (2023), <https://doi.org/10.3390/su151612563>.
- [67] J. Almalki, Intrusion detection and prevention model for blockchain based IoMT applications, *Comput. Syst. Sci. Eng.* 48 (2024) 132–151, <https://doi.org/10.32604/csse.2023.038085>.
- [68] G. Zachos, F. Pelekoudas-Oikonomou, G. Mantas, K. Porfyraakis, G. Sakellari, J. Rodriguez, Des. Blockchain-based Anom.-based Intrusion Detect. Syst. (AIDS) IoMT Netw., (2023).
- [69] G. Zachos, G. Mantas, K. Porfyraakis, J. Rodriguez, Implementing anomaly-based intrusion detection for resource-constrained devices in IoMT networks, *Sensors* 25 (2025), <https://doi.org/10.3390/s25041216>.
- [70] Pritika, B.Shanmugam, S. Azam, Risk Assess. Heterog. IoMT Devices: Rev. Technol. (Basel) 11 (2023). <https://doi.org/10.3390/technologies11010031>.
- [71] A. Ghubaihs, T. Salman, M. Zolanvari, D. Unal, A. Al-Ali, R. Jain, Recent advances in the internet-of-medical-things (IoMT) systems security, *IEEE Internet Things J.* 8 (2021) 8707–8718, <https://doi.org/10.1109/JIOT.2020.3045653>.
- [72] A. Al Abdulwahid, Detection of middlebox-based attacks in healthcare internet of things using multiple machine learning models, *Comput. Intell. Neurosci.* 2022 (2022) 1–15, <https://doi.org/10.1155/2022/2037954>.
- [73] N. Faruqui, M.A. Yousuf, M. Whaiduzzaman, A.K.M. Azad, S.A. Alyami, P. Liò, M. A. Kabir, M.A. Moni, SafetyMed: a novel IoMT intrusion detection system using CNN-LSTM hybridization, *Electron. (Switz.)* 12 (2023) 1–32, <https://doi.org/10.3390/electronics12173541>.
- [74] A.V. Potnwar, V.K. Bongirwar, S. Ajani, N. Shelke, M. Dhone, N. Parati, Deep learning-based rule-based feature selection for intrusion detection in industrial Internet of Things networks, *Int. J. Intell. Syst. Appl. Eng.* 11 (2023) 25–35.
- [75] T. Saba, Intrusion detection in smart City hospitals using ensemble classifiers, in: Proceedings - International Conference on Developments in ESysystems Engineering, DeSE 2020-Decem, 2020, pp. 418–422, <https://doi.org/10.1109/DeSE51703.2020.9450247>.
- [76] S.S. Hameed, W.H. Hassan, L.A. Latiff, F. Ghabban, A systematic review of security and privacy issues in the internet of medical things; the role of machine learning approaches, *PeerJ Comput. Sci.* 7 (2021) 1–44, <https://doi.org/10.7717/peerj-cs.414>.
- [77] F. Wahab, Y. Zhao, D. Javeed, M.H. Al-Adhaileh, S.A. Almaayyah, W. Khan, M. S. Saeed, R.Kumar Shah, An AI-driven hybrid framework for intrusion detection in IoT-enabled E-health, *Comput. Intell. Neurosci.* 2022 (2022), <https://doi.org/10.1155/2022/6096289>.
- [78] M.L. Hernandez-Jaimes, A. Martinez-Cruz, K.A. Ramírez-Gutiérrez, C. Feregrino-Urbe, Artificial intelligence for IoMT security: a review of intrusion detection systems, attacks, datasets and Cloud-Fog-Edge architectures, *Internet Things (Neth.)* 23 (2023) 100887, <https://doi.org/10.1016/j.iot.2023.100887>.
- [79] R.A. Alsemmeari, M.Y. Dahab, A.A. Alsulami, B. Alturki, S. Algarni, Resilient Security framework using TNN and Blockchain for IoMT, *Electron. (Switz.)* (2023) 12, <https://doi.org/10.3390/electronics12102252>.
- [80] L. Dhanya, R. Chitra, A novel autoencoder based feature independent GA optimised XGBoost classifier for IoMT malware detection, *Expert. Syst. Appl.* 237 (2024) 121618, <https://doi.org/10.1016/j.eswa.2023.121618>.
- [81] S.A. Wagan, J. Koo, I.F. Siddiqui, N.M.F. Qureshi, M. Attique, D.R. Shin, A fuzzy-based duo-Secure multi-modal framework for IoMT anomaly detection, *J. King Saud Univ. - Comput. Inf. Sci.* 35 (2023) 131–144, <https://doi.org/10.1016/j.jksuci.2022.11.007>.
- [82] Y. Alotaibi, M. Ilyas, Ensemble-learning framework for intrusion detection to enhance Internet of Things' Devices security, *Sensors* 23 (2023), <https://doi.org/10.3390/s23125568>.
- [83] B. Mahapatra, V. Singh, R. Bhattacharjee, ML-AKA: An Authentication Protocol for Non-Standalone 5G-Based C-IoT Networks, (2024).
- [84] K. Ramezanpour, J. Jagannath, Intelligent zero trust architecture for 5G/6G networks: principles, challenges, and the role of machine learning in the context of O-RAN, *Comput. Netw.* 217 (2022) 109358, <https://doi.org/10.1016/j.comnet.2022.109358>.

- [85] E. Basar, Kirchhoff Meets Johns.: Purs. Unconditionally Secure Commun., (n.d.) 1–12.
- [86] M.A. Enright, E. Hammad, A. Dutta, A learning-based zero-trust architecture for 6G and future networks, in: Proceedings - 2022 IEEE Future Networks World Forum 2022, FNWF, 2022, pp. 64–71, <https://doi.org/10.1109/FNWF55208.2022.00020>.
- [87] D. Pan, G.-L. Long, L. Yin, Y.-B. Sheng, D. Ruan, S.X. Ng, J. Lu, L. Hanzo, Evol. Quantum Secure Direct Commun.: Road Qinternet., (2023) 1–46.
- [88] R. Hireche, H. Mansouri, A.-S.K. Pathan, Security and privacy management in internet of medical things (IoMT): a synthesis, J. Cybersecur. Priv. 2 (2022) 640–661, <https://doi.org/10.3390/jcp2030033>.
- [89] Y. Pan, F. Sun, Z. Teng, J. White, D.C. Schmidt, J. Staples, L. Krause, Detecting web attacks with end-to-end deep learning, J. Internet Serv. Appl. 10 (2019), <https://doi.org/10.1186/s13174-019-0115-x>.
- [90] A. Amjad, T. Alyas, U. Farooq, M.A. Tariq, Detection and mitigation of DDoS attack in cloud computing using machine learning algorithm, EAI Endorsed Trans. Scalable Inf. Syst. 6 (2019) 1–8, <https://doi.org/10.4108/eai.29-7-2019.159834>.
- [91] G. Thamilarasu, A. Odesile, A. Hoang, An intrusion detection system for internet of medical things, IEEE Access. 8 (2020) 181560–181576, <https://doi.org/10.1109/ACCESS.2020.3026260>.
- [92] R. Yahya, M. Mahfoudi, M. Fattah, B. Younes, S. Mazer, M. Elbekkali, An intrusion detection system for internet of medical things using machine learning approaches, 2025. <https://doi.org/10.1109/IRASET64571.2025.11008243>.
- [93] J. Almalki, S.M. Alshahrani, N.A. Khan, A comprehensive secure system enabling healthcare 5.0 using federated learning, intrusion detection and blockchain, PeerJ. Comput. Sci. 10 (2024) 1–26, <https://doi.org/10.7717/peerj-cs.1778>.
- [94] J. Nayak, S.K. Meher, A. Souri, B. Naik, Extreme learning machine and bayesian optimization driven intelligent framework for IoMT cyber attack detection, J Supercomput 78 (2022) 14866–14891, <https://doi.org/10.1007/s11227-022-04453-z>.
- [95] J. Ktari, T. Frikha, N. Ben Amor, L. Louraidh, H. Elmannai, M. Hamdi, IoMT-Based Platf. E-Health Monit. Based Blockchain., (2022).
- [96] M. Akshay Kumaar, D. Samiayya, P.M.D.R. Vincent, K. Srinivasan, C.Y. Chang, H. Ganesh, A hybrid framework for intrusion detection in Healthcare systems using Deep Learning, Front Public Health. 9 (2022) 1–18, <https://doi.org/10.3389/fpubh.2021.824898>.
- [97] S. Rani, A. Kataria, S. Kumar, P. Tiwari, Federated learning for secure IoMT-applications in smart healthcare systems: a comprehensive review, Knowl. Based. Syst 274 (2023) 110658, <https://doi.org/10.1016/j.knosys.2023.110658>.
- [98] S. Deyno, A. Toma, Overview on mechanisms of antibacterial resistance, Int. J. Res. Pharm. Biosci. 2 (2015) 27–36.
- [99] A.K. Jain, N. Gupta, B.B. Gupta, A survey on scalable consensus algorithms for blockchain technology, Cyber. Secur. Appl. 3 (2025) 100065, <https://doi.org/10.1016/j.csa.2024.100065>.
- [100] T. Thanujan, C. Rajapakse, D. Wickramaarachchi, A community-based hybrid blockchain architecture for the organic food supply chain, in: Proceedings - International Research Conference on Smart Computing and Systems Engineering 2021, SCSE, 2021, pp. 77–83, <https://doi.org/10.1109/SCSE53661.2021.9568325>.
- [101] ENISA, Artif. Intell. Cybersecur. Res., 2023.
- [102] I.H. Ji, J.H. Lee, M.J. Kang, W.J. Park, S.H. Jeon, J.T. Seo, Artificial intelligence-based anomaly detection technology over encrypted traffic: a systematic literature review, Sensors 24 (2024) 1–30, <https://doi.org/10.3390/s24030898>.
- [103] S. Bin Hulayyil, S. Li, L. Xu, Machine-learning-based vulnerability detection and classification in Internet of things device security, Electron. (Basel) 12 (2023) 3927, <https://doi.org/10.3390/electronics12183927>.
- [104] A. Khatib, M. Hamlich, D. Hamad, Machine learning based intrusion detection for cyber-security in IoT networks, E3S Web Conf. 297 (2021) 1–7, <https://doi.org/10.1051/e3sconf/202129701057>.
- [105] T. Ahmed Alhaj, S.M. Abdulla, M.A.E. Iderss, A.A.A. Ali, F.A. Elhaj, M.A. Remli, L. A. Gabralla, A survey: to govern, protect, and detect security principles on internet of medical things (IoMT), IEEE Access. 10 (2022) 124777–124791, <https://doi.org/10.1109/ACCESS.2022.3225038>.
- [106] M. Norouzi, Z. Gürka, Appl. Sci. Hybrid Genet. Algorithm-Based Random For. Model Intrusion Detect. Approach Internet Med. Things, (2023).