


Liquid-Cooled Edge Computing Workstations for Intelligent Transportation Systems in Singapore

Toward a Sustainable and Climate-Resilient Smart Nation Infrastructure

Email: info@dcdeeptech.com



Executive Summary

As Singapore advances its **Smart Nation 2.0** strategy and accelerates the implementation of the **Singapore Green Plan 2030**, national digital infrastructure is undergoing a structural transformation. Artificial intelligence (AI), the Internet of Things (IoT), and 5G connectivity are driving a fundamental shift of compute resources from centralized cloud data centers toward the data source itself—the **edge**.

In the context of **Intelligent Transportation Systems (ITS)**, this shift is mission-critical. Ultra-low-latency applications such as autonomous vehicle (AV)

coordination, real-time video analytics, and V2X communications require high-performance compute capabilities to be deployed directly at roadside infrastructure.

However, Singapore’s **tropical climate**—characterized by persistently high temperatures, extreme humidity, and corrosive urban atmospheres—poses severe challenges to conventional air-cooled edge computing hardware. These combined effects, referred to in this paper as the “**Tropical Penalty**,” significantly degrade energy efficiency, reliability, and lifecycle economics of traditional cooling architectures.

This white paper demonstrates that **sealed liquid-cooled edge workstations**, including **single-phase immersion cooling** and **fully enclosed conductive liquid cooling**, represent a technically and economically superior solution for Singapore’s next-generation ITS infrastructure. Through analysis of thermodynamics, corrosion mechanisms, standards compliance, and total cost of ownership (TCO), the paper establishes liquid cooling as a foundational enabler for sustainable, resilient, and scalable intelligent transportation systems.

1. Strategic Context: Smart Mobility Meets Sustainability

1.1 Smart Nation 2.0 and the Evolution of Digital Infrastructure

Since the launch of the Smart Nation initiative in 2014, Singapore has positioned itself as a global testbed for urban digital innovation. With the release of the **National AI Strategy 2.0 (NAIS 2.0)**, the national focus has shifted from technology adoption toward **global leadership in AI-driven systems**.

Within this vision, ITS plays a central role. Frameworks such as **Smart Mobility 2030**, led by the Land Transport Authority (LTA), emphasize real-time sensing, decentralized intelligence, and autonomous decision-making across the physical transportation network.

These requirements fundamentally exceed the capabilities of cloud-only computing models. For safety-critical scenarios—such as AV coordination at complex intersections—latency budgets below **10 milliseconds** necessitate **edge-resident compute infrastructure**.

1.2 Green Plan 2030 and the Decarbonization Imperative

Singapore's **Green Plan 2030** commits the nation to peak emissions by 2030 and net-zero emissions by 2050. The ICT sector, as a major energy consumer, is under increasing regulatory and societal pressure to reduce its carbon footprint.

IMDA's **Tropical Data Centre Standards (SS 697:2023)** explicitly recognize the inefficiency of conventional cooling approaches in tropical climates and encourage higher operating temperatures to reduce mechanical cooling demand.

However, the proliferation of **distributed edge nodes**—deployed in roadside cabinets, smart lampposts, and gantries—creates a new sustainability challenge. Unlike hyperscale data centers, these nodes cannot rely on centralized, precision air-conditioning systems. Continuing to use air-cooled designs risks creating thousands of energy-inefficient micro-sites that undermine national sustainability goals.

2. Edge Computing Requirements in Modern ITS

2.1 Compute Workload Characteristics

ITS edge nodes increasingly handle **AI inference-heavy workloads**, including:

- **Real-time video analytics** for traffic flow, incident detection, and enforcement
- **Cryptographic processing** for V2X message authentication
- **Multi-sensor fusion** combining camera, radar, and LiDAR data

These workloads demand GPU-class accelerators and high memory bandwidth, resulting in **power densities between 500 W and 1.5 kW per node**, often within highly constrained physical enclosures.

2.2 Physical and Acoustic Constraints

Urban roadside deployments impose strict limits on:

- **Footprint and form factor** (e.g., lamppost-mounted platforms)
- **Noise emissions**, especially in residential or mixed-use districts

High-speed fans required for air cooling not only consume significant power but also generate unacceptable noise levels, further limiting deployability.

3. Environmental Challenges: The “Tropical Penalty”

3.1 Humidity and Electrochemical Migration (ECM)

Singapore’s average relative humidity (~80–100%) creates ideal conditions for **electrochemical migration** on printed circuit boards. Under voltage bias, metal ions migrate across microscopic gaps, forming conductive dendrites that can cause catastrophic short circuits—particularly in modern fine-pitch electronics.

3.2 Corrosive Atmospheres: Sulfur and Salt

Roadside environments expose electronics to:

- **Sulfur-bearing gases** from traffic and industrial activity, accelerating silver sulfide corrosion
- **Marine salt aerosols**, which act as electrolytes and dramatically increase corrosion rates

Under ISA-71.04 classifications, many Singapore roadside environments approach **G3 or GX severity**, where unprotected air-cooled electronics may fail within one to two years.

3.3 Thermal Cycling and Condensation

Daily solar heating followed by tropical rainfall induces rapid thermal cycling in outdoor cabinets. This “breathing effect” draws moist, contaminated air into enclosures, leading to condensation on internal components—even in nominally sealed cabinets.

4. Limitations of Traditional Air Cooling

Air cooling is fundamentally an **open-loop system** that:

- Relies on continuous air exchange with the environment
- Suffers from filter clogging, corrosion ingress, and high maintenance frequency

- Experiences rapidly diminishing efficiency as ambient temperatures rise

Fan power consumption scales cubically with airflow demand, often accounting for **20% or more of total system power** in tropical conditions.

5. Liquid-Cooled Edge Architectures

5.1 Technology Comparison

Attribute	Air Cooling	Direct-to-Chip Liquid Cooling	Single-Phase Immersion
Heat removal capacity	Low	High	Very high
Environmental isolation	Poor	Partial	Complete
Noise	High	Moderate	Silent
Maintenance frequency	High	Medium	Very low
Typical PUE	>1.6	~1.2	<1.05

5.2 Why Single-Phase Immersion Excels

Single-phase immersion cooling submerges all electronic components in a dielectric fluid, delivering several decisive advantages:

- **Complete isolation** from humidity, oxygen, sulfur, and salt
- **Elimination of fans**, reducing failure points and noise
- **High thermal inertia**, providing resilience against transient power or pump failures
- **Longer hardware lifespan** due to reduced thermal stress and corrosion

For Singapore’s ITS edge deployments, sealed immersion or fully enclosed conductive liquid cooling architectures offer the highest robustness.

6. Reference Specifications for Tropical ITS Edge Nodes

- **Ingress Protection:** Minimum IP67 / IP68
 - **Cooling Medium:** Long-life dielectric fluid, high flash point, non-toxic
 - **Operating Temperature:** Designed for coolant temperatures up to 45–50 °C, aligned with SS 697
 - **Connectors:** Industrial-grade sealed connectors (e.g., M12), corrosion-protected contacts
 - **Maintenance Model:** “Replace-by-module” rather than on-site servicing
-

7. Total Cost of Ownership (TCO) Analysis

Despite higher upfront CapEx, liquid-cooled edge nodes deliver superior economics:

- **Energy savings:** ~40–50% per node annually
- **Maintenance reduction:** Near-zero routine servicing over multi-year periods
- **Extended hardware lifespan:** 20–50% longer service life

In Singapore’s high-energy-cost, high-labor-cost environment, TCO breakeven is typically achieved within **three years**.

8. Standards and Compliance Alignment

Liquid-cooled edge workstations align naturally with:

- **SS 697:2023** (Tropical Data Centre Standard)
- **IMDA IT Energy Efficiency Standards**
- **BCA Green Mark** sustainability criteria

Their fanless, low-energy, refrigerant-free design supports both regulatory compliance and national decarbonization objectives.

9. Conclusions and Recommendations

Key Conclusions

- **Air cooling has reached its practical limit** for high-density ITS edge compute in tropical climates
- **Sealed liquid cooling is the only architecture** that simultaneously solves heat, humidity, corrosion, and sustainability challenges
- **Economic viability is clear** when evaluated over full lifecycle costs

Strategic Recommendations

1. Incorporate **liquid cooling requirements** into future ITS and Smart Nation procurement specifications for >500 W edge nodes
2. Establish **tropical edge testbeds** to benchmark reliability and energy performance
3. Encourage **local-global partnerships** to develop Singapore-optimized liquid-cooled edge solutions