# Wiring, Printed - Component

**COMPANY**

**Dongguan HAYWAR Electronic Technology Co Ltd**
Floor 4, Building C, No.11, 7th Alley,Wenming Road
No.4 Industrial Area, Nance Community
Humen Town
Dongguan, Guangdong 523900 China

E508260

| Type | Cond Width Min mm | Min Edge mm | Cond Thk mic | SS/ DS/ DSO | Max Area Diam mm | Report date After 2022-01-01 | Surface Mount Technology | Assembly Solder Process Temp °C | Solder Process Cycles | Solder Limits °C | Solder Limits sec | Max Oper Temp °C | Flame Class | Meets UL796 DSR | C T I |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| **Single Layer Metal Base printed wiring boards** | | | | | | | | | | | | | | | |
| **HY-L** | 0.12 | 0.12 | 34 | SS | 50.8 | No | - | - | - | 288 | 20 | 90 | HB | All | 1 |
| **HY-M (ASP 1)** | 0.10 | 0.10 | 28 | SS | 50.8 | Yes | Yes | 260 | 3 | - | - | 90 | V-1 | All | * |
| **HY-S (ASP 1)** | 0.10 | 0.10 | 24 | SS | 50.8 | Yes | Yes | 260 | 3 | - | - | 130 | V-0 | All | * |

* - CTI marking is optional and may be marked on the printed wiring board.

(ASP 1) - Assembly Solder process evaluated to IPC-TM-650, 2.6.27 Thermal Stress Assembly Simulation.

Marking: Company name or file number and type designation. May be followed by a suffix to denote factory identification or flammability classification..

Last Updated on 2025-04-08

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must

appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2025 UL LLC."