

Cisco WSA First Time CLI Configuration:

```
WSA.cisco.com> interfaceconfig
```

Currently configured interfaces:

1. Management (192.168.1.100/24 on Management: WSA.cisco.com)

Choose the operation you want to perform:

- NEW - Create a new interface.
- EDIT - Modify an interface.
- DELETE - Remove an interface.
- DETAILS - Show details of an interface.

```
[>] edit
```

Enter the number of the interface you wish to edit.

```
[>] 1
```

Would you like to configure an IPv4 address for this interface (y/n)? [Y]>

IPv4 Address (Ex: 192.168.1.2):

```
[192.168.1.100]> 192.168.1.100
```

Netmask (Ex: "24", "255.255.255.0" or "0xffffffff00"):

```
[24]>
```

Would you like to configure an IPv6 address for this interface (y/n)? [N]>

Hostname:

```
[WSA.cisco.com]> wsa.cisco.com
```

Do you want to enable FTP on this interface? [N]>

Do you want to enable SSH on this interface? [Y]>

Which port do you want to use for SSH?

```
[22]>
```

Do you want to enable HTTP on this interface? [Y]>

Which port do you want to use for HTTP?

```
[8080]>
```

Do you want to enable HTTPS on this interface? [Y]>

Which port do you want to use for HTTPS?
[8443]>

You have not entered an HTTPS certificate. To assure privacy, run "certconfig" first. You may use the demo, but this will not be secure.
Do you really wish to use a demo certificate? [Y]>

Both HTTP and HTTPS are enabled for this interface, should HTTP requests redirect to the secure service? [Y]>

Currently configured interfaces:

1. Management (192.168.1.100/24 on Management: wsa.cisco.com)

Choose the operation you want to perform:

- NEW - Create a new interface.
 - EDIT - Modify an interface.
 - DELETE - Remove an interface.
 - DETAILS - Show details of an interface.
- []>

WSA.cisco.com> saveconfig

Do you want to mask the passphrase? Files with masked passphrases cannot be loaded using loadconfig command. [Y]>

Do you want the system to generate a name for the configuration file? [Y]>

