

zabbix 监控 windows下Mysql

环境

windows服务器

安装

1. 监控脚本

mysql监控需要自己写脚本监控，在linux下写一个脚本很容易，但是windows下却很少。我是从别处搜索来的脚本。脚本主要是使用了mysqlAdmin命令来获取管理信息。

- MySQL_Ping.vbs是用来查看mysql是否存活

```
Set objFS = CreateObject("Scripting.FileSystemObject")
Set objArgs = WScript.Arguments
str1 = getCommandOutput("E:\Program Files\MySQL\MySQL Server
5.5\bin\mysqladmin.exe -u用户 -p密码 --port=3306 ping")

If Instr(str1,"alive") > 0 Then
WScript.Echo 1
Else
WScript.Echo 0
End If

Function getCommandOutput(theCommand)

Dim objShell, objCmdExec
Set objShell = CreateObject("WScript.Shell")
Set objCmdExec = objShell.exec(thecommand)
getCommandOutput = objCmdExec.StdOut.ReadAll

end Function
```

其中的mysqlAdmin的路径需要自己修改，以及mysql用户和密码

- MySQL_Ext-Status_Script.vbs是获取一些额外的信息

```
Set objFS = CreateObject("Scripting.FileSystemObject")
Set objArgs = WScript.Arguments
str1 = getCommandOutput("E:\Program Files\MySQL\MySQL Server
5.5\bin\mysqladmin.exe -uroot -pvortex --port=3306 extended-status")
Arg = objArgs(0)
str2 = Split(str1,"|")
```

```

For i = LBound(str2) to UBound(str2)
If Trim(str2(i)) = Arg Then
WScript.Echo TRIM(str2(i+1))
Exit For
End If
next

Function getCommandOutput(theCommand)
Dim objShell, objCmdExec
Set objShell = CreateObject("WScript.Shell")
Set objCmdExec = objshell.exec(thecommand)
getCommandOutput = objCmdExec.StdOut.ReadAll
end Function

```

其中的mysqlAdmin的路径需要自己修改，以及mysql用户和密码

- Mysql_Version.vbs文件是用来查询mysql的版本

```

Set objFS = CreateObject("Scripting.FileSystemObject")
Set objArgs = WScript.Arguments
str1 = getCommandOutput("E:\Program Files\MySQL\MySQL Server 5.5\bin\mysql.exe
-V")

WScript.Echo str1

Function getCommandOutput(theCommand)
Dim objShell, objCmdExec
Set objShell = CreateObject("WScript.Shell")
Set objCmdExec = objshell.exec(thecommand)
getCommandOutput = objCmdExec.StdOut.ReadAll
end Function

```

其中的mysqlAdmin的路径需要自己修改，以及mysql用户和密码

2. 配置

修改zabbix_agentd.win.conf

```

UnsafeUserParameters=1

UserParameter=mysql.version,cscript /nologo C:\zabbix\conf\Mysql_Version.vbs
UserParameter=mysql.status[*],cscript /nologo C:\zabbix\conf\MySQL_Ext-
Status_Script.vbs $1
UserParameter=mysql.ping,cscript /nologo C:\zabbix\conf\MySql_Ping.vbs

```

- UnsafeUserParameters是允许参数中包含一个特殊字符，自定义脚本中往往都有，所以要设置为1
- UserParameter增加监控项，我们是调用前面的脚本监控。

3. 导入模板

导入监控模板

```
<?xml version="1.0" encoding="UTF-8"?>
<zabbix_export>
  <version>2.0</version>
  <date>2016-04-24T14:41:07Z</date>
  <groups>
    <group>
      <name>Templates</name>
    </group>
  </groups>
  <templates>
    <template>
      <template>Template App MySQL</template>
      <name>Template App MySQL</name>
      <description/>
      <groups>
        <group>
          <name>Templates</name>
        </group>
      </groups>
      <applications>
        <application>
          <name>MySQL</name>
        </application>
      </applications>
      <items>
        <item>
          <name>MySQL begin operations per second</name>
          <type>0</type>
          <snmp_community/>
          <multiplier>0</multiplier>
          <snmp_oid/>
          <key>mysql.status[Com_begin]</key>
          <delay>60</delay>
          <history>7</history>
          <trends>365</trends>
          <status>0</status>
          <value_type>0</value_type>
          <allowed_hosts/>
          <units>qps</units>
        </item>
      </items>
    </template>
  </templates>
</zabbix_export>
```

```

        <delta>1</delta>
        <snmpv3_contextname/>
        <snmpv3_securityname/>
        <snmpv3_securitylevel>0</snmpv3_securitylevel>
        <snmpv3_authprotocol>0</snmpv3_authprotocol>
        <snmpv3_authpassphrase/>
        <snmpv3_privprotocol>0</snmpv3_privprotocol>
        <snmpv3_privpassphrase/>
        <formula>1</formula>
        <delay_flex/>
        <params/>
        <ipmi_sensor/>
        <data_type>0</data_type>
        <authtype>0</authtype>
        <username/>
        <password/>
        <publickey/>
        <privatekey/>
        <port/>
        <description>It requires user parameter mysql.status[*],
which is defined in userparameter_mysql.conf.</description>
        <inventory_link>0</inventory_link>
        <applications>
            <application>
                <name>MySQL</name>
            </application>
        </applications>
        <valuemap/>
        <logtimefmt/>
    </item>
    <item>
        <name>MySQL bytes received per second</name>
        <type>0</type>
        <snmp_community/>
        <multiplier>0</multiplier>
        <snmp_oid/>
        <key>mysql.status[Bytes_received]</key>
        <delay>60</delay>
        <history>7</history>
        <trends>365</trends>
        <status>0</status>
        <value_type>0</value_type>
        <allowed_hosts/>
        <units>Bps</units>
        <delta>1</delta>

```

```

<snmpv3_contextname/>
<snmpv3_securityname/>
<snmpv3_securitylevel>0</snmpv3_securitylevel>
<snmpv3_authprotocol>0</snmpv3_authprotocol>
<snmpv3_authpassphrase/>
<snmpv3_privprotocol>0</snmpv3_privprotocol>
<snmpv3_privpassphrase/>
<formula>1</formula>
<delay_flex/>
<params/>
<ipmi_sensor/>
<data_type>0</data_type>
<authtype>0</authtype>
<username/>
<password/>
<publickey/>
<privatekey/>
<port/>
<description>The number of bytes received from all clients.

```





It requires user parameter mysql.status[*], which is defined in 
 userparameter_mysql.conf.</description>

```

<inventory_link>0</inventory_link>
<applications>
  <application>
    <name>MySQL</name>
  </application>
</applications>
<valuemap/>
<logtimefmt/>
</item>
<item>
  <name>MySQL bytes sent per second</name>
  <type>0</type>
  <snmp_community/>
  <multiplier>0</multiplier>
  <snmp_oid/>
  <key>mysql.status[Bytes_sent]</key>
  <delay>60</delay>
  <history>7</history>
  <trends>365</trends>
  <status>0</status>
  <value_type>0</value_type>
  <allowed_hosts/>

```

```

<units>Bps</units>
<delta>1</delta>
<snmpv3_contextname/>
<snmpv3_securityname/>
<snmpv3_securitylevel>0</snmpv3_securitylevel>
<snmpv3_authprotocol>0</snmpv3_authprotocol>
<snmpv3_authpassphrase/>
<snmpv3_privprotocol>0</snmpv3_privprotocol>
<snmpv3_privpassphrase/>
<formula>1</formula>
<delay_flex/>
<params/>
<ipmi_sensor/>
<data_type>0</data_type>
<authtype>0</authtype>
<username/>
<password/>
<publickey/>
<privatekey/>
<port/>
<description>The number of bytes sent to all clients.&#13;

```



It requires user parameter mysql.status[*], which is defined in userparameter_mysql.conf.</description>

```

<inventory_link>0</inventory_link>
<applications>
  <application>
    <name>MySQL</name>
  </application>
</applications>
<valuemap/>
<logtimefmt/>
</item>
<item>
  <name>MySQL commit operations per second</name>
  <type>0</type>
  <snmp_community/>
  <multiplier>0</multiplier>
  <snmp_oid/>
  <key>mysql.status[Com_commit]</key>
  <delay>60</delay>
  <history>7</history>
  <trends>365</trends>
  <status>0</status>
  <value_type>0</value_type>

```

```

        <allowed_hosts/>
        <units>qps</units>
        <delta>1</delta>
        <snmpv3_contextname/>
        <snmpv3_securityname/>
        <snmpv3_securitylevel>0</snmpv3_securitylevel>
        <snmpv3_authprotocol>0</snmpv3_authprotocol>
        <snmpv3_authpassphrase/>
        <snmpv3_privprotocol>0</snmpv3_privprotocol>
        <snmpv3_privpassphrase/>
        <formula>1</formula>
        <delay_flex/>
        <params/>
        <ipmi_sensor/>
        <data_type>0</data_type>
        <authtype>0</authtype>
        <username/>
        <password/>
        <publickey/>
        <privatekey/>
        <port/>
        <description>It requires user parameter mysql.status[*],
which is defined in userparameter_mysql.conf.</description>
        <inventory_link>0</inventory_link>
        <applications>
            <application>
                <name>MySQL</name>
            </application>
        </applications>
        <valuemap/>
        <logtimefmt/>
    </item>
    <item>
        <name>MySQL delete operations per second</name>
        <type>0</type>
        <snmp_community/>
        <multiplier>0</multiplier>
        <snmp_oid/>
        <key>mysql.status[Com_delete]</key>
        <delay>60</delay>
        <history>7</history>
        <trends>365</trends>
        <status>0</status>
        <value_type>0</value_type>
        <allowed_hosts/>

```

```

        <units>qps</units>
        <delta>1</delta>
        <snmpv3_contextname/>
        <snmpv3_securityname/>
        <snmpv3_securitylevel>0</snmpv3_securitylevel>
        <snmpv3_authprotocol>0</snmpv3_authprotocol>
        <snmpv3_authpassphrase/>
        <snmpv3_privprotocol>0</snmpv3_privprotocol>
        <snmpv3_privpassphrase/>
        <formula>1</formula>
        <delay_flex/>
        <params/>
        <ipmi_sensor/>
        <data_type>0</data_type>
        <authtype>0</authtype>
        <username/>
        <password/>
        <publickey/>
        <privatekey/>
        <port/>
        <description>It requires user parameter mysql.status[*],
which is defined in userparameter_mysql.conf.</description>
        <inventory_link>0</inventory_link>
        <applications>
            <application>
                <name>MySQL</name>
            </application>
        </applications>
        <valuemap/>
        <logtimefmt/>
    </item>
    <item>
        <name>MySQL insert operations per second</name>
        <type>0</type>
        <snmp_community/>
        <multiplier>0</multiplier>
        <snmp_oid/>
        <key>mysql.status[Com_insert]</key>
        <delay>60</delay>
        <history>7</history>
        <trends>365</trends>
        <status>0</status>
        <value_type>0</value_type>
        <allowed_hosts/>
        <units>qps</units>

```

```

        <delta>1</delta>
        <snmpv3_contextname/>
        <snmpv3_securityname/>
        <snmpv3_securitylevel>0</snmpv3_securitylevel>
        <snmpv3_authprotocol>0</snmpv3_authprotocol>
        <snmpv3_authpassphrase/>
        <snmpv3_privprotocol>0</snmpv3_privprotocol>
        <snmpv3_privpassphrase/>
        <formula>1</formula>
        <delay_flex/>
        <params/>
        <ipmi_sensor/>
        <data_type>0</data_type>
        <authtype>0</authtype>
        <username/>
        <password/>
        <publickey/>
        <privatekey/>
        <port/>
        <description>It requires user parameter mysql.status[*],
which is defined in userparameter_mysql.conf.</description>
        <inventory_link>0</inventory_link>
        <applications>
            <application>
                <name>MySQL</name>
            </application>
        </applications>
        <valuemap/>
        <logtimefmt/>
    </item>
    <item>
        <name>MySQL queries per second</name>
        <type>0</type>
        <snmp_community/>
        <multiplier>0</multiplier>
        <snmp_oid/>
        <key>mysql.status[Questions]</key>
        <delay>60</delay>
        <history>7</history>
        <trends>365</trends>
        <status>0</status>
        <value_type>0</value_type>
        <allowed_hosts/>
        <units>qps</units>
        <delta>1</delta>

```

```

        <snmpv3_contextname/>
        <snmpv3_securityname/>
        <snmpv3_securitylevel>0</snmpv3_securitylevel>
        <snmpv3_authprotocol>0</snmpv3_authprotocol>
        <snmpv3_authpassphrase/>
        <snmpv3_privprotocol>0</snmpv3_privprotocol>
        <snmpv3_privpassphrase/>
        <formula>1</formula>
        <delay_flex/>
        <params/>
        <ipmi_sensor/>
        <data_type>0</data_type>
        <authtype>0</authtype>
        <username/>
        <password/>
        <publickey/>
        <privatekey/>
        <port/>
        <description>It requires user parameter mysql.status[*],
which is defined in userparameter_mysql.conf.</description>
        <inventory_link>0</inventory_link>
        <applications>
            <application>
                <name>MySQL</name>
            </application>
        </applications>
        <valuemap/>
        <logtimefmt/>
    </item>
    <item>
        <name>MySQL rollback operations per second</name>
        <type>0</type>
        <snmp_community/>
        <multiplier>0</multiplier>
        <snmp_oid/>
        <key>mysql.status[Com_rollback]</key>
        <delay>60</delay>
        <history>7</history>
        <trends>365</trends>
        <status>0</status>
        <value_type>0</value_type>
        <allowed_hosts/>
        <units>qps</units>
        <delta>1</delta>
        <snmpv3_contextname/>

```

```

        <snmpv3_securityname/>
        <snmpv3_securitylevel>0</snmpv3_securitylevel>
        <snmpv3_authprotocol>0</snmpv3_authprotocol>
        <snmpv3_authpassphrase/>
        <snmpv3_privprotocol>0</snmpv3_privprotocol>
        <snmpv3_privpassphrase/>
        <formula>1</formula>
        <delay_flex/>
        <params/>
        <ipmi_sensor/>
        <data_type>0</data_type>
        <authtype>0</authtype>
        <username/>
        <password/>
        <publickey/>
        <privatekey/>
        <port/>
        <description>It requires user parameter mysql.status[*],
which is defined in userparameter_mysql.conf.</description>
        <inventory_link>0</inventory_link>
        <applications>
            <application>
                <name>MySQL</name>
            </application>
        </applications>
        <valuemap/>
        <logtimefmt/>
    </item>
    <item>
        <name>MySQL select operations per second</name>
        <type>0</type>
        <snmp_community/>
        <multiplier>0</multiplier>
        <snmp_oid/>
        <key>mysql.status[Com_select]</key>
        <delay>60</delay>
        <history>7</history>
        <trends>365</trends>
        <status>0</status>
        <value_type>0</value_type>
        <allowed_hosts/>
        <units>qps</units>
        <delta>1</delta>
        <snmpv3_contextname/>
        <snmpv3_securityname/>

```

```

        <snmpv3_securitylevel>0</snmpv3_securitylevel>
        <snmpv3_authprotocol>0</snmpv3_authprotocol>
        <snmpv3_authpassphrase/>
        <snmpv3_privprotocol>0</snmpv3_privprotocol>
        <snmpv3_privpassphrase/>
        <formula>1</formula>
        <delay_flex/>
        <params/>
        <ipmi_sensor/>
        <data_type>0</data_type>
        <authtype>0</authtype>
        <username/>
        <password/>
        <publickey/>
        <privatekey/>
        <port/>
        <description>It requires user parameter mysql.status[*],
which is defined in userparameter_mysql.conf.</description>
        <inventory_link>0</inventory_link>
        <applications>
            <application>
                <name>MySQL</name>
            </application>
        </applications>
        <valuemap/>
        <logtimefmt/>
    </item>
    <item>
        <name>MySQL slow queries</name>
        <type>0</type>
        <snmp_community/>
        <multiplier>0</multiplier>
        <snmp_oid/>
        <key>mysql.status[Slow_queries]</key>
        <delay>60</delay>
        <history>7</history>
        <trends>365</trends>
        <status>0</status>
        <value_type>3</value_type>
        <allowed_hosts/>
        <units/>
        <delta>0</delta>
        <snmpv3_contextname/>
        <snmpv3_securityname/>
        <snmpv3_securitylevel>0</snmpv3_securitylevel>

```

```

        <snmpv3_authprotocol>0</snmpv3_authprotocol>
        <snmpv3_authpassphrase/>
        <snmpv3_privprotocol>0</snmpv3_privprotocol>
        <snmpv3_privpassphrase/>
        <formula>1</formula>
        <delay_flex/>
        <params/>
        <ipmi_sensor/>
        <data_type>0</data_type>
        <authtype>0</authtype>
        <username/>
        <password/>
        <publickey/>
        <privatekey/>
        <port/>
        <description>It requires user parameter mysql.status[*],
which is defined in userparameter_mysql.conf.</description>
        <inventory_link>0</inventory_link>
        <applications>
            <application>
                <name>MySQL</name>
            </application>
        </applications>
        <valuemap/>
        <logtimefmt/>
    </item>
    <item>
        <name>MySQL status</name>
        <type>0</type>
        <snmp_community/>
        <multiplier>0</multiplier>
        <snmp_oid/>
        <key>mysql.ping</key>
        <delay>60</delay>
        <history>7</history>
        <trends>365</trends>
        <status>0</status>
        <value_type>3</value_type>
        <allowed_hosts/>
        <units/>
        <delta>0</delta>
        <snmpv3_contextname/>
        <snmpv3_securityname/>
        <snmpv3_securitylevel>0</snmpv3_securitylevel>
        <snmpv3_authprotocol>0</snmpv3_authprotocol>

```

```

        <snmpv3_authpassphrase/>
        <snmpv3_privprotocol>0</snmpv3_privprotocol>
        <snmpv3_privpassphrase/>
        <formula>1</formula>
        <delay_flex/>
        <params/>
        <ipmi_sensor/>
        <data_type>0</data_type>
        <authtype>0</authtype>
        <username/>
        <password/>
        <publickey/>
        <privatekey/>
        <port/>
        <description>It requires user parameter mysql.ping, which
is defined in userparameter_mysql.conf.&#13;
&#13;
0 - MySQL server is down&#13;
1 - MySQL server is up</description>
        <inventory_link>0</inventory_link>
        <applications>
            <application>
                <name>MySQL</name>
            </application>
        </applications>
        <valuemap>
            <name>Service state</name>
        </valuemap>
        <logtimefmt/>
    </item>
    <item>
        <name>MySQL update operations per second</name>
        <type>0</type>
        <snmp_community/>
        <multiplier>0</multiplier>
        <snmp_oid/>
        <key>mysql.status[Com_update]</key>
        <delay>60</delay>
        <history>7</history>
        <trends>365</trends>
        <status>0</status>
        <value_type>0</value_type>
        <allowed_hosts/>
        <units>qps</units>
        <delta>1</delta>

```

```

        <snmpv3_contextname/>
        <snmpv3_securityname/>
        <snmpv3_securitylevel>0</snmpv3_securitylevel>
        <snmpv3_authprotocol>0</snmpv3_authprotocol>
        <snmpv3_authpassphrase/>
        <snmpv3_privprotocol>0</snmpv3_privprotocol>
        <snmpv3_privpassphrase/>
        <formula>1</formula>
        <delay_flex/>
        <params/>
        <ipmi_sensor/>
        <data_type>0</data_type>
        <authtype>0</authtype>
        <username/>
        <password/>
        <publickey/>
        <privatekey/>
        <port/>
        <description>It requires user parameter mysql.status[*],
which is defined in userparameter_mysql.conf.</description>
        <inventory_link>0</inventory_link>
        <applications>
            <application>
                <name>MySQL</name>
            </application>
        </applications>
        <valuemap/>
        <logtimefmt/>
    </item>
    <item>
        <name>MySQL uptime</name>
        <type>0</type>
        <snmp_community/>
        <multiplier>0</multiplier>
        <snmp_oid/>
        <key>mysql.status[Uptime]</key>
        <delay>60</delay>
        <history>7</history>
        <trends>365</trends>
        <status>0</status>
        <value_type>3</value_type>
        <allowed_hosts/>
        <units>uptime</units>
        <delta>0</delta>
        <snmpv3_contextname/>

```

```

        <snmpv3_securityname/>
        <snmpv3_securitylevel>0</snmpv3_securitylevel>
        <snmpv3_authprotocol>0</snmpv3_authprotocol>
        <snmpv3_authpassphrase/>
        <snmpv3_privprotocol>0</snmpv3_privprotocol>
        <snmpv3_privpassphrase/>
        <formula>1</formula>
        <delay_flex/>
        <params/>
        <ipmi_sensor/>
        <data_type>0</data_type>
        <authtype>0</authtype>
        <username/>
        <password/>
        <publickey/>
        <privatekey/>
        <port/>
        <description>It requires user parameter mysql.status[*],
which is defined in userparameter_mysql.conf.</description>
        <inventory_link>0</inventory_link>
        <applications>
            <application>
                <name>MySQL</name>
            </application>
        </applications>
        <valuemap/>
        <logtimefmt/>
    </item>
    <item>
        <name>MySQL version</name>
        <type>0</type>
        <snmp_community/>
        <multiplier>0</multiplier>
        <snmp_oid/>
        <key>mysql.version</key>
        <delay>3600</delay>
        <history>7</history>
        <trends>365</trends>
        <status>0</status>
        <value_type>1</value_type>
        <allowed_hosts/>
        <units/>
        <delta>0</delta>
        <snmpv3_contextname/>
        <snmpv3_securityname/>

```

```

        <snmpv3_securitylevel>0</snmpv3_securitylevel>
        <snmpv3_authprotocol>0</snmpv3_authprotocol>
        <snmpv3_authpassphrase/>
        <snmpv3_privprotocol>0</snmpv3_privprotocol>
        <snmpv3_privpassphrase/>
        <formula>1</formula>
        <delay_flex/>
        <params/>
        <ipmi_sensor/>
        <data_type>0</data_type>
        <authtype>0</authtype>
        <username/>
        <password/>
        <publickey/>
        <privatekey/>
        <port/>
        <description>It requires user parameter mysql.version,
which is defined in userparameter_mysql.conf.</description>
        <inventory_link>0</inventory_link>
        <applications>
            <application>
                <name>MySQL</name>
            </application>
        </applications>
        <valuemap/>
        <logtimefmt/>
    </item>
</items>
<discovery_rules/>
<macros/>
<templates/>
<screens>
    <screen>
        <name>MySQL performance</name>
        <hsize>2</hsize>
        <vsize>1</vsize>
        <screen_items>
            <screen_item>
                <resourcetype>0</resourcetype>
                <width>500</width>
                <height>200</height>
                <x>0</x>
                <y>0</y>
                <colspan>1</colspan>
                <rowspan>1</rowspan>
            </screen_item>
        </screen_items>
    </screen>
</screens>

```

```

        <elements>0</elements>
        <valign>1</valign>
        <halign>0</halign>
        <style>0</style>
        <url/>
        <dynamic>0</dynamic>
        <sort_triggers>0</sort_triggers>
        <resource>
            <name>MySQL operations</name>
            <host>Template App MySQL</host>
        </resource>
        <max_columns>3</max_columns>
        <application/>
    </screen_item>
    <screen_item>
        <resourcetype>0</resourcetype>
        <width>500</width>
        <height>270</height>
        <x>1</x>
        <y>0</y>
        <colspan>1</colspan>
        <rowspan>1</rowspan>
        <elements>0</elements>
        <valign>1</valign>
        <halign>0</halign>
        <style>0</style>
        <url/>
        <dynamic>0</dynamic>
        <sort_triggers>0</sort_triggers>
        <resource>
            <name>MySQL bandwidth</name>
            <host>Template App MySQL</host>
        </resource>
        <max_columns>3</max_columns>
        <application/>
    </screen_item>
</screen_items>
</screen>
</screens>
</template>
</templates>
<triggers>
    <trigger>
        <expression>{Template App MySQL:mysql.ping.last(0)}=0</expression>
        <name>MySQL is down</name>
    </trigger>
</triggers>

```

```

        <url/>
        <status>0</status>
        <priority>2</priority>
        <description/>
        <type>0</type>
        <dependencies/>
    </trigger>
</triggers>
<graphs>
    <graph>
        <name>MySQL bandwidth</name>
        <width>900</width>
        <height>200</height>
        <yaxismin>0.0000</yaxismin>
        <yaxismax>100.0000</yaxismax>
        <show_work_period>1</show_work_period>
        <show_triggers>1</show_triggers>
        <type>0</type>
        <show_legend>1</show_legend>
        <show_3d>0</show_3d>
        <percent_left>0.0000</percent_left>
        <percent_right>0.0000</percent_right>
        <ymin_type_1>0</ymin_type_1>
        <ymin_type_1>0</ymin_type_1>
        <ymin_item_1>0</ymin_item_1>
        <ymin_item_1>0</ymin_item_1>
        <graph_items>
            <graph_item>
                <sortorder>0</sortorder>
                <drawtype>5</drawtype>
                <color>00AA00</color>
                <yaxisside>0</yaxisside>
                <calc_fnc>2</calc_fnc>
                <type>0</type>
                <item>
                    <host>Template App MySQL</host>
                    <key>mysql.status[Bytes_received]</key>
                </item>
            </graph_item>
            <graph_item>
                <sortorder>1</sortorder>
                <drawtype>5</drawtype>
                <color>3333FF</color>
                <yaxisside>0</yaxisside>
                <calc_fnc>2</calc_fnc>

```

```

        <type>0</type>
        <item>
            <host>Template App MySQL</host>
            <key>mysql.status[Bytes_sent]</key>
        </item>
    </graph_item>
</graph_items>
</graph>
<graph>
    <name>MySQL operations</name>
    <width>900</width>
    <height>200</height>
    <yaxismin>0.0000</yaxismin>
    <yaxismax>100.0000</yaxismax>
    <show_work_period>1</show_work_period>
    <show_triggers>1</show_triggers>
    <type>0</type>
    <show_legend>1</show_legend>
    <show_3d>0</show_3d>
    <percent_left>0.0000</percent_left>
    <percent_right>0.0000</percent_right>
    <ymin_type_1>0</ymin_type_1>
    <ymin_type_1>0</ymin_type_1>
    <ymin_item_1>0</ymin_item_1>
    <ymin_item_1>0</ymin_item_1>
    <graph_items>
        <graph_item>
            <sortorder>0</sortorder>
            <drawtype>0</drawtype>
            <color>C8C800</color>
            <yaxisside>0</yaxisside>
            <calc_fnc>2</calc_fnc>
            <type>0</type>
            <item>
                <host>Template App MySQL</host>
                <key>mysql.status[Com_begin]</key>
            </item>
        </graph_item>
        <graph_item>
            <sortorder>1</sortorder>
            <drawtype>0</drawtype>
            <color>006400</color>
            <yaxisside>0</yaxisside>
            <calc_fnc>2</calc_fnc>
            <type>0</type>

```

```

        <item>
            <host>Template App MySQL</host>
            <key>mysql.status[Com_commit]</key>
        </item>
    </graph_item>
    <graph_item>
        <sortorder>2</sortorder>
        <drawtype>0</drawtype>
        <color>C80000</color>
        <yaxisside>0</yaxisside>
        <calc_fnc>2</calc_fnc>
        <type>0</type>
        <item>
            <host>Template App MySQL</host>
            <key>mysql.status[Com_delete]</key>
        </item>
    </graph_item>
    <graph_item>
        <sortorder>3</sortorder>
        <drawtype>0</drawtype>
        <color>0000EE</color>
        <yaxisside>0</yaxisside>
        <calc_fnc>2</calc_fnc>
        <type>0</type>
        <item>
            <host>Template App MySQL</host>
            <key>mysql.status[Com_insert]</key>
        </item>
    </graph_item>
    <graph_item>
        <sortorder>4</sortorder>
        <drawtype>0</drawtype>
        <color>640000</color>
        <yaxisside>0</yaxisside>
        <calc_fnc>2</calc_fnc>
        <type>0</type>
        <item>
            <host>Template App MySQL</host>
            <key>mysql.status[Com_rollback]</key>
        </item>
    </graph_item>
    <graph_item>
        <sortorder>5</sortorder>
        <drawtype>0</drawtype>
        <color>00C800</color>

```

```

        <yaxisside>0</yaxisside>
        <calc_fnc>2</calc_fnc>
        <type>0</type>
        <item>
            <host>Template App MySQL</host>
            <key>mysql.status[Com_select]</key>
        </item>
    </graph_item>
    <graph_item>
        <sortorder>6</sortorder>
        <drawtype>0</drawtype>
        <color>C800C8</color>
        <yaxisside>0</yaxisside>
        <calc_fnc>2</calc_fnc>
        <type>0</type>
        <item>
            <host>Template App MySQL</host>
            <key>mysql.status[Com_update]</key>
        </item>
    </graph_item>
</graph_items>
</graph>
</graphs>
</zabbix_export>

```

命名为你想要的名字，然后导入就可以了。

4. 监控 新建一个主机，链接导入的模板就可以了。