

---

layout: post title: zabbix 监控windows下redis description: zabbix 监控 windows下redis tagline: image: date: 2017/03/06 categories: [linux] tags: [linux,zabbix,tocmat]

## zabbix 监控redis

---

### 环境

windows服务器

### 安装

#### 1. 配置

- 监控redis主要是使用redis的命令redis-cli.exe来监控。新建一个Redis\_Status.vbs脚本

```
Set objFS = CreateObject("Scripting.FileSystemObject")
Set objArgs = WScript.Arguments
str1 = getCommandOutput("E:\vortex\redis\redis-latest(3.0.501)\redis-cli.exe -h 127.0.0.1 -p "+objArgs(0)+" -a 123456 info")
Arg = objArgs(1)

str2 = Split(str1,vbCrLf)
For i = LBound(str2) to UBound(str2)

str3 = Split(str2(i),":")

If Trim(str3(0)) = Arg Then
WScript.Echo TRIM(str3(1))
Exit For
End If
next

Function getCommandOutput(theCommand)
Dim objShell, objCmdExec
Set objShell = CreateObject("WScript.Shell")
Set objCmdExec = objshell.exec(thecommand)
getCommandOutput = objCmdExec.StdOut.ReadAll
end Function
```

- 打开 zabbix\_agentd.win.conf文件，去除这行的注释

```
Include=c:\zabbix\zabbix_agentd.conf.d\*.conf
```

并且新建这个目录，在其下新建`redis.conf`,内容如下：

```
UserParameter=redis_stats[*],cscript /nologo C:\zabbix\conf\Redis_Status.vbs  
$1 $2
```

## 2. 导入模板

模板的内容如下：

```
<?xml version="1.0" encoding="UTF-8"?>  
<zabbix_export>  
  <version>3.0</version>  
  <date>2017-03-24T08:58:19Z</date>  
  <groups>  
    <group>  
      <name>Templates</name>  
    </group>  
  </groups>  
  <templates>  
    <template>  
      <template>Templates Redis_6379</template>  
      <name>Templates Redis_6379</name>  
      <description/>  
      <groups>  
        <group>  
          <name>Templates</name>  
        </group>  
      </groups>  
      <applications>  
        <application>  
          <name>Redis_6379</name>  
        </application>  
      </applications>  
      <items>  
        <item>  
          <name>port status_6379</name>  
          <type>0</type>  
          <snmp_community/>  
          <multiplier>0</multiplier>  
          <snmp_oid/>  
          <key>net.tcp.listen[6379]</key>  
          <delay>60</delay>  
          <history>7</history>
```

```

    <trends>365</trends>
    <status>0</status>
    <value_type>3</value_type>
    <allowed_hosts/>
    <units/>
    <delta>0</delta>
    <snmpv3_contextname/>
    <snmpv3_securityname/>
    <snmpv3_securitylevel>0</snmpv3_securitylevel>
    <snmpv3_authprotocol>0</snmpv3_authprotocol>
    <snmpv3_authpassphrase/>
    <snmpv3_privprotocol>0</snmpv3_privprotocol>
    <snmpv3_privpassphrase/>
    <formula>1</formula>
    <delay_flex/>
    <params/>
    <ipmi_sensor/>
    <data_type>0</data_type>
    <authtype>0</authtype>
    <username/>
    <password/>
    <publickey/>
    <privatekey/>
    <port/>
    <description/>
    <inventory_link>0</inventory_link>
    <applications>
      <application>
        <name>Redis_6379</name>
      </application>
    </applications>
    <valuemap/>
    <logtimefmt/>
  </item>
  <item>
    <name>Blocked clients_6379</name>
    <type>0</type>
    <snmp_community/>
    <multiplier>0</multiplier>
    <snmp_oid/>
    <key>redis_stats[6379,blocked_clients]</key>
    <delay>60</delay>
    <history>7</history>
    <trends>365</trends>
    <status>0</status>

```

```

<value_type>3</value_type>
<allowed_hosts/>
<units/>
<delta>0</delta>
<snmpv3_contextname/>
<snmpv3_securityname/>
<snmpv3_securitylevel>0</snmpv3_securitylevel>
<snmpv3_authprotocol>0</snmpv3_authprotocol>
<snmpv3_authpassphrase/>
<snmpv3_privprotocol>0</snmpv3_privprotocol>
<snmpv3_privpassphrase/>
<formula>1</formula>
<delay_flex/>
<params/>
<ipmi_sensor/>
<data_type>0</data_type>
<authtype>0</authtype>
<username/>
<password/>
<publickey/>
<privatekey/>
<port/>
<description/>
<inventory_link>0</inventory_link>
<applications>
  <application>
    <name>Redis_6379</name>
  </application>
</applications>
<valuemap/>
<logtimefmt/>
</item>
<item>
  <name>Connected clients_6379</name>
  <type>0</type>
  <snmp_community/>
  <multiplier>0</multiplier>
  <snmp_oid/>
  <key>redis_stats[6379,connected_clients]</key>
  <delay>60</delay>
  <history>7</history>
  <trends>365</trends>
  <status>0</status>
  <value_type>3</value_type>
  <allowed_hosts/>

```

```

    <units/>
    <delta>0</delta>
    <snmpv3_contextname/>
    <snmpv3_securityname/>
    <snmpv3_securitylevel>0</snmpv3_securitylevel>
    <snmpv3_authprotocol>0</snmpv3_authprotocol>
    <snmpv3_authpassphrase/>
    <snmpv3_privprotocol>0</snmpv3_privprotocol>
    <snmpv3_privpassphrase/>
    <formula>1</formula>
    <delay_flex/>
    <params/>
    <ipmi_sensor/>
    <data_type>0</data_type>
    <authtype>0</authtype>
    <username/>
    <password/>
    <publickey/>
    <privatekey/>
    <port/>
    <description/>
    <inventory_link>0</inventory_link>
    <applications>
        <application>
            <name>Redis_6379</name>
        </application>
    </applications>
    <valuemap/>
    <logtimefmt/>
</item>
<item>
    <name>Connected_slave_6380</name>
    <type>0</type>
    <snmp_community/>
    <multiplier>0</multiplier>
    <snmp_oid/>
    <key>redis_stats[6379,connected_slave]</key>
    <delay>60</delay>
    <history>7</history>
    <trends>365</trends>
    <status>0</status>
    <value_type>3</value_type>
    <allowed_hosts/>
    <units/>
    <delta>0</delta>

```

```

<snmpv3_contextname/>
<snmpv3_securityname/>
<snmpv3_securitylevel>0</snmpv3_securitylevel>
<snmpv3_authprotocol>0</snmpv3_authprotocol>
<snmpv3_authpassphrase/>
<snmpv3_privprotocol>0</snmpv3_privprotocol>
<snmpv3_privpassphrase/>
<formula>1</formula>
<delay_flex/>
<params/>
<ipmi_sensor/>
<data_type>0</data_type>
<authtype>0</authtype>
<username/>
<password/>
<publickey/>
<privatekey/>
<port/>
<description/>
<inventory_link>0</inventory_link>
<applications>
  <application>
    <name>Redis_6379</name>
  </application>
</applications>
<valuemap/>
<logtimefmt/>
</item>
<item>
  <name>Evicted_keys_6379</name>
  <type>0</type>
  <snmp_community/>
  <multiplier>0</multiplier>
  <snmp_oid/>
  <key>redis_stats[6379,evicted_keys]</key>
  <delay>60</delay>
  <history>7</history>
  <trends>365</trends>
  <status>0</status>
  <value_type>3</value_type>
  <allowed_hosts/>
  <units/>
  <delta>0</delta>
  <snmpv3_contextname/>
  <snmpv3_securityname/>

```

```

<snmpv3_securitylevel>0</snmpv3_securitylevel>
<snmpv3_authprotocol>0</snmpv3_authprotocol>
<snmpv3_authpassphrase/>
<snmpv3_privprotocol>0</snmpv3_privprotocol>
<snmpv3_privpassphrase/>
<formula>1</formula>
<delay_flex/>
<params/>
<ipmi_sensor/>
<data_type>0</data_type>
<authtype>0</authtype>
<username/>
<password/>
<publickey/>
<privatekey/>
<port/>
<description/>
<inventory_link>0</inventory_link>
<applications>
  <application>
    <name>Redis_6379</name>
  </application>
</applications>
<valuemap/>
<logtimefmt/>
</item>
<item>
  <name>Expired keys_6379</name>
  <type>0</type>
  <snmp_community/>
  <multiplier>0</multiplier>
  <snmp_oid/>
  <key>redis_stats[6379,expired_keys]</key>
  <delay>60</delay>
  <history>7</history>
  <trends>365</trends>
  <status>0</status>
  <value_type>3</value_type>
  <allowed_hosts/>
  <units/>
  <delta>0</delta>
  <snmpv3_contextname/>
  <snmpv3_securityname/>
  <snmpv3_securitylevel>0</snmpv3_securitylevel>
  <snmpv3_authprotocol>0</snmpv3_authprotocol>

```

```

    <snmpv3_authpassphrase/>
    <snmpv3_privprotocol>0</snmpv3_privprotocol>
    <snmpv3_privpassphrase/>
    <formula>1</formula>
    <delay_flex/>
    <params/>
    <ipmi_sensor/>
    <data_type>0</data_type>
    <authtype>0</authtype>
    <username/>
    <password/>
    <publickey/>
    <privatekey/>
    <port/>
    <description/>
    <inventory_link>0</inventory_link>
    <applications>
      <application>
        <name>Redis_6379</name>
      </application>
    </applications>
    <valuemap/>
    <logtimefmt/>
  </item>
  <item>
    <name>Last save time_6379</name>
    <type>0</type>
    <snmp_community/>
    <multiplier>0</multiplier>
    <snmp_oid/>
    <key>redis_stats[6379,last_save_time]</key>
    <delay>60</delay>
    <history>3</history>
    <trends>365</trends>
    <status>0</status>
    <value_type>3</value_type>
    <allowed_hosts/>
    <units>unixtime</units>
    <delta>0</delta>
    <snmpv3_contextname/>
    <snmpv3_securityname/>
    <snmpv3_securitylevel>0</snmpv3_securitylevel>
    <snmpv3_authprotocol>0</snmpv3_authprotocol>
    <snmpv3_authpassphrase/>
    <snmpv3_privprotocol>0</snmpv3_privprotocol>

```



```

        <snmpv3_privpassphrase/>
        <formula>1</formula>
        <delay_flex/>
        <params/>
        <ipmi_sensor/>
        <data_type>0</data_type>
        <authtype>0</authtype>
        <username/>
        <password/>
        <publickey/>
        <privatekey/>
        <port/>
        <description/>
        <inventory_link>0</inventory_link>
        <applications>
            <application>
                <name>Redis_6379</name>
            </application>
        </applications>
        <valuemap/>
        <logtimefmt/>
    </item>
    <item>
        <name>Role_6379</name>
        <type>0</type>
        <snmp_community/>
        <multiplier>0</multiplier>
        <snmp_oid/>
        <key>redis_stats[6379,role]</key>
        <delay>60</delay>
        <history>3</history>
        <trends>0</trends>
        <status>0</status>
        <value_type>1</value_type>
        <allowed_hosts/>
        <units/>
        <delta>0</delta>
        <snmpv3_contextname/>
        <snmpv3_securityname/>
        <snmpv3_securitylevel>0</snmpv3_securitylevel>
        <snmpv3_authprotocol>0</snmpv3_authprotocol>
        <snmpv3_authpassphrase/>
        <snmpv3_privprotocol>0</snmpv3_privprotocol>
        <snmpv3_privpassphrase/>
        <formula>1</formula>

```

```

        <delay_flex/>
        <params/>
        <ipmi_sensor/>
        <data_type>0</data_type>
        <authtype>0</authtype>
        <username/>
        <password/>
        <publickey/>
        <privatekey/>
        <port/>
        <description/>
        <inventory_link>0</inventory_link>
        <applications>
            <application>
                <name>Redis_6379</name>
            </application>
        </applications>
        <valuemap/>
        <logtimefmt/>
    </item>
    <item>
        <name>Request rate_6379</name>
        <type>0</type>
        <snmp_community/>
        <multiplier>0</multiplier>
        <snmp_oid/>
        <key>redis_stats[6379,total_commands_processed]</key>
        <delay>60</delay>
        <history>7</history>
        <trends>365</trends>
        <status>0</status>
        <value_type>3</value_type>
        <allowed_hosts/>
        <units/>
        <delta>1</delta>
        <snmpv3_contextname/>
        <snmpv3_securityname/>
        <snmpv3_securitylevel>0</snmpv3_securitylevel>
        <snmpv3_authprotocol>0</snmpv3_authprotocol>
        <snmpv3_authpassphrase/>
        <snmpv3_privprotocol>0</snmpv3_privprotocol>
        <snmpv3_privpassphrase/>
        <formula>1</formula>
        <delay_flex/>
        <params/>

```

```

        <ipmi_sensor/>
        <data_type>0</data_type>
        <authtype>0</authtype>
        <username/>
        <password/>
        <publickey/>
        <privatekey/>
        <port/>
        <description/>
        <inventory_link>0</inventory_link>
        <applications>
            <application>
                <name>Redis_6379</name>
            </application>
        </applications>
        <valuemap/>
        <logtimefmt/>
    </item>
    <item>
        <name>Connection rate_6379</name>
        <type>0</type>
        <snmp_community/>
        <multiplier>0</multiplier>
        <snmp_oid/>
        <key>redis_stats[6379,total_connections_received]</key>
        <delay>60</delay>
        <history>7</history>
        <trends>365</trends>
        <status>0</status>
        <value_type>3</value_type>
        <allowed_hosts/>
        <units/>
        <delta>1</delta>
        <snmpv3_contextname/>
        <snmpv3_securityname/>
        <snmpv3_securitylevel>0</snmpv3_securitylevel>
        <snmpv3_authprotocol>0</snmpv3_authprotocol>
        <snmpv3_authpassphrase/>
        <snmpv3_privprotocol>0</snmpv3_privprotocol>
        <snmpv3_privpassphrase/>
        <formula>1</formula>
        <delay_flex/>
        <params/>
        <ipmi_sensor/>
        <data_type>0</data_type>

```

```

    <authtype>0</authtype>
    <username/>
    <password/>
    <publickey/>
    <privatekey/>
    <port/>
    <description/>
    <inventory_link>0</inventory_link>
    <applications>
      <application>
        <name>Redis_6379</name>
      </application>
    </applications>
    <valuemap/>
    <logtimefmt/>
  </item>
  <item>
    <name>Uptime in seconds_6379</name>
    <type>0</type>
    <snmp_community/>
    <multiplier>0</multiplier>
    <snmp_oid/>
    <key>redis_stats[6379,uptime_in_seconds]</key>
    <delay>60</delay>
    <history>7</history>
    <trends>365</trends>
    <status>0</status>
    <value_type>3</value_type>
    <allowed_hosts/>
    <units>uptime</units>
    <delta>0</delta>
    <snmpv3_contextname/>
    <snmpv3_securityname/>
    <snmpv3_securitylevel>0</snmpv3_securitylevel>
    <snmpv3_authprotocol>0</snmpv3_authprotocol>
    <snmpv3_authpassphrase/>
    <snmpv3_privprotocol>0</snmpv3_privprotocol>
    <snmpv3_privpassphrase/>
    <formula>1</formula>
    <delay_flex/>
    <params/>
    <ipmi_sensor/>
    <data_type>0</data_type>
    <authtype>0</authtype>
    <username/>

```

```

    <password/>
    <publickey/>
    <privatekey/>
    <port/>
    <description/>
    <inventory_link>0</inventory_link>
    <applications>
      <application>
        <name>Redis_6379</name>
      </application>
    </applications>
    <valuemap/>
    <logtimefmt/>
  </item>
  <item>
    <name>Used memory_6379</name>
    <type>0</type>
    <snmp_community/>
    <multiplier>0</multiplier>
    <snmp_oid/>
    <key>redis_stats[6379,used_memory:]</key>
    <delay>60</delay>
    <history>7</history>
    <trends>365</trends>
    <status>0</status>
    <value_type>3</value_type>
    <allowed_hosts/>
    <units/>
    <delta>0</delta>
    <snmpv3_contextname/>
    <snmpv3_securityname/>
    <snmpv3_securitylevel>0</snmpv3_securitylevel>
    <snmpv3_authprotocol>0</snmpv3_authprotocol>
    <snmpv3_authpassphrase/>
    <snmpv3_privprotocol>0</snmpv3_privprotocol>
    <snmpv3_privpassphrase/>
    <formula>1</formula>
    <delay_flex/>
    <params/>
    <ipmi_sensor/>
    <data_type>0</data_type>
    <authtype>0</authtype>
    <username/>
    <password/>
    <publickey/>

```

```

    <privatekey/>
    <port/>
    <description/>
    <inventory_link>0</inventory_link>
    <applications>
      <application>
        <name>Redis_6379</name>
      </application>
    </applications>
    <valuemap/>
    <logtimefmt/>
  </item>
  <item>
    <name>Used_memory_rss_6379</name>
    <type>0</type>
    <snmp_community/>
    <multiplier>0</multiplier>
    <snmp_oid/>
    <key>redis_stats[6379,used_memory_rss]</key>
    <delay>60</delay>
    <history>7</history>
    <trends>365</trends>
    <status>0</status>
    <value_type>3</value_type>
    <allowed_hosts/>
    <units/>
    <delta>0</delta>
    <snmpv3_contextname/>
    <snmpv3_securityname/>
    <snmpv3_securitylevel>0</snmpv3_securitylevel>
    <snmpv3_authprotocol>0</snmpv3_authprotocol>
    <snmpv3_authpassphrase/>
    <snmpv3_privprotocol>0</snmpv3_privprotocol>
    <snmpv3_privpassphrase/>
    <formula>1</formula>
    <delay_flex/>
    <params/>
    <ipmi_sensor/>
    <data_type>0</data_type>
    <authtype>0</authtype>
    <username/>
    <password/>
    <publickey/>
    <privatekey/>
    <port/>

```

```

        <description/>
        <inventory_link>0</inventory_link>
        <applications>
            <application>
                <name>Redis_6379</name>
            </application>
        </applications>
        <valuemap/>
        <logtimefmt/>
    </item>
</items>
<discovery_rules/>
<macros/>
<templates/>
<screens/>
</template>
</templates>
<triggers>
    <trigger>
        <expression>{Templates
Redis_6379:net.tcp.listen[6379].count(#3,0,&quot;eq&quot;)}=3</expression>
        <name>Redis port 6379 is not running</name>
        <url/>
        <status>0</status>
        <priority>4</priority>
        <description/>
        <type>0</type>
        <dependencies/>
    </trigger>
</triggers>
<graphs>
    <graph>
        <name>Redis key_6379</name>
        <width>900</width>
        <height>200</height>
        <yaxismin>0.0000</yaxismin>
        <yaxismax>100.0000</yaxismax>
        <show_work_period>1</show_work_period>
        <show_triggers>1</show_triggers>
        <type>0</type>
        <show_legend>1</show_legend>
        <show_3d>0</show_3d>
        <percent_left>0.0000</percent_left>
        <percent_right>0.0000</percent_right>
        <ymin_type_1>0</ymin_type_1>

```

```

<ymax_type_1>0</ymax_type_1>
<ymin_item_1>0</ymin_item_1>
<ymax_item_1>0</ymax_item_1>
<graph_items>
  <graph_item>
    <sortorder>0</sortorder>
    <drawtype>0</drawtype>
    <color>C80000</color>
    <yaxisside>0</yaxisside>
    <calc_fnc>2</calc_fnc>
    <type>0</type>
    <item>
      <host>Templates Redis_6379</host>
      <key>redis_stats[6379,evicted_keys]</key>
    </item>
  </graph_item>
  <graph_item>
    <sortorder>1</sortorder>
    <drawtype>0</drawtype>
    <color>00C800</color>
    <yaxisside>0</yaxisside>
    <calc_fnc>2</calc_fnc>
    <type>0</type>
    <item>
      <host>Templates Redis_6379</host>
      <key>redis_stats[6379,expired_keys]</key>
    </item>
  </graph_item>
</graph_items>
</graph>
<graph>
  <name>Redis Last_save_time_6379</name>
  <width>900</width>
  <height>200</height>
  <yaxismin>0.0000</yaxismin>
  <yaxismax>100.0000</yaxismax>
  <show_work_period>1</show_work_period>
  <show_triggers>1</show_triggers>
  <type>0</type>
  <show_legend>1</show_legend>
  <show_3d>0</show_3d>
  <percent_left>0.0000</percent_left>
  <percent_right>0.0000</percent_right>
  <ymin_type_1>0</ymin_type_1>
  <ymax_type_1>0</ymax_type_1>

```



```

    <ymin_item_1>0</ymin_item_1>
    <ymin_item_1>0</ymin_item_1>
    <ymax_item_1>0</ymax_item_1>
    <graph_items>
      <graph_item>
        <sortorder>0</sortorder>
        <drawtype>0</drawtype>
        <color>C80000</color>
        <yaxisside>0</yaxisside>
        <calc_fnc>2</calc_fnc>
        <type>0</type>
        <item>
          <host>Templates Redis_6379</host>
          <key>redis_stats[6379,last_save_time]</key>
        </item>
      </graph_item>
    </graph_items>
  </graph>
  <graph>
    <name>Redis Port Connections_6379</name>
    <width>900</width>
    <height>200</height>
    <yaxismin>0.0000</yaxismin>
    <yaxismax>100.0000</yaxismax>
    <show_work_period>1</show_work_period>
    <show_triggers>0</show_triggers>
    <type>0</type>
    <show_legend>1</show_legend>
    <show_3d>0</show_3d>
    <percent_left>0.0000</percent_left>
    <percent_right>0.0000</percent_right>
    <ymin_type_1>0</ymin_type_1>
    <ymin_type_1>0</ymin_type_1>
    <ymin_item_1>0</ymin_item_1>
    <ymin_item_1>0</ymin_item_1>
    <ymax_item_1>0</ymax_item_1>
    <ymax_item_1>0</ymax_item_1>
    <graph_items>
      <graph_item>
        <sortorder>0</sortorder>
        <drawtype>0</drawtype>
        <color>EE0000</color>
        <yaxisside>0</yaxisside>
        <calc_fnc>4</calc_fnc>
        <type>0</type>
        <item>
          <host>Templates Redis_6379</host>
          <key>redis_stats[6379,blocked_clients]</key>

```

```

        </item>
    </graph_item>
    <graph_item>
        <sortorder>1</sortorder>
        <drawtype>0</drawtype>
        <color>BBBB00</color>
        <yaxisside>0</yaxisside>
        <calc_fnc>4</calc_fnc>
        <type>0</type>
        <item>
            <host>Templates Redis_6379</host>
            <key>redis_stats[6379,total_connections_received]</key>
        </item>
    </graph_item>
    <graph_item>
        <sortorder>2</sortorder>
        <drawtype>0</drawtype>
        <color>CC00CC</color>
        <yaxisside>0</yaxisside>
        <calc_fnc>4</calc_fnc>
        <type>0</type>
        <item>
            <host>Templates Redis_6379</host>
            <key>redis_stats[6379,total_commands_processed]</key>
        </item>
    </graph_item>
    <graph_item>
        <sortorder>3</sortorder>
        <drawtype>0</drawtype>
        <color>00CCCC</color>
        <yaxisside>0</yaxisside>
        <calc_fnc>4</calc_fnc>
        <type>0</type>
        <item>
            <host>Templates Redis_6379</host>
            <key>redis_stats[6379,connected_slave]</key>
        </item>
    </graph_item>
    <graph_item>
        <sortorder>4</sortorder>
        <drawtype>0</drawtype>
        <color>009900</color>
        <yaxisside>0</yaxisside>
        <calc_fnc>4</calc_fnc>
        <type>0</type>

```

```

        <item>
            <host>Templates Redis_6379</host>
            <key>redis_stats[6379,connected_clients]</key>
        </item>
    </graph_item>
</graph_items>
</graph>
<graph>
    <name>Redis Port status_6379</name>
    <width>900</width>
    <height>200</height>
    <yaxismin>0.0000</yaxismin>
    <yaxismax>100.0000</yaxismax>
    <show_work_period>1</show_work_period>
    <show_triggers>1</show_triggers>
    <type>0</type>
    <show_legend>1</show_legend>
    <show_3d>0</show_3d>
    <percent_left>0.0000</percent_left>
    <percent_right>0.0000</percent_right>
    <ymin_type_1>0</ymin_type_1>
    <ymin_type_1>0</ymin_type_1>
    <ymin_item_1>0</ymin_item_1>
    <ymin_item_1>0</ymin_item_1>
    <graph_items>
        <graph_item>
            <sortorder>0</sortorder>
            <drawtype>0</drawtype>
            <color>C80000</color>
            <yaxisside>0</yaxisside>
            <calc_fnc>2</calc_fnc>
            <type>0</type>
            <item>
                <host>Templates Redis_6379</host>
                <key>net.tcp.listen[6379]</key>
            </item>
        </graph_item>
    </graph_items>
</graph>
<graph>
    <name>Redis Uptime_in_seconds_6379</name>
    <width>900</width>
    <height>200</height>
    <yaxismin>0.0000</yaxismin>
    <yaxismax>100.0000</yaxismax>

```

```

    <show_work_period>1</show_work_period>
    <show_triggers>1</show_triggers>
    <type>0</type>
    <show_legend>1</show_legend>
    <show_3d>0</show_3d>
    <percent_left>0.0000</percent_left>
    <percent_right>0.0000</percent_right>
    <ymin_type_1>0</ymin_type_1>
    <ymin_type_1>0</ymin_type_1>
    <ymin_item_1>0</ymin_item_1>
    <ymin_item_1>0</ymin_item_1>
    <graph_items>
      <graph_item>
        <sortorder>0</sortorder>
        <drawtype>0</drawtype>
        <color>C80000</color>
        <yaxisside>0</yaxisside>
        <calc_fnc>2</calc_fnc>
        <type>0</type>
        <item>
          <host>Templates Redis_6379</host>
          <key>redis_stats[6379,uptime_in_seconds]</key>
        </item>
      </graph_item>
    </graph_items>
  </graph>
  <graph>
    <name>Redis Used memory_6379</name>
    <width>900</width>
    <height>200</height>
    <yaxismin>0.0000</yaxismin>
    <yaxismax>100.0000</yaxismax>
    <show_work_period>1</show_work_period>
    <show_triggers>1</show_triggers>
    <type>0</type>
    <show_legend>1</show_legend>
    <show_3d>0</show_3d>
    <percent_left>0.0000</percent_left>
    <percent_right>0.0000</percent_right>
    <ymin_type_1>0</ymin_type_1>
    <ymin_type_1>0</ymin_type_1>
    <ymin_item_1>0</ymin_item_1>
    <ymin_item_1>0</ymin_item_1>
    <graph_items>
      <graph_item>

```

```

        <sortorder>0</sortorder>
        <drawtype>0</drawtype>
        <color>C80000</color>
        <yaxisside>0</yaxisside>
        <calc_fnc>2</calc_fnc>
        <type>0</type>
        <item>
            <host>Templates Redis_6379</host>
            <key>redis_stats[6379,used_memory:]</key>
        </item>
    </graph_item>
    <graph_item>
        <sortorder>1</sortorder>
        <drawtype>0</drawtype>
        <color>00C8C8</color>
        <yaxisside>0</yaxisside>
        <calc_fnc>2</calc_fnc>
        <type>0</type>
        <item>
            <host>Templates Redis_6379</host>
            <key>redis_stats[6379,used_memory_rss]</key>
        </item>
    </graph_item>
</graph_items>
</graph>
</graphs>
</zabbix_export>

```

3. 监控 新建一个host，链接该模板便可。