

000
001
002
003
004
005
006
007
008
009
010
011
012
013
014
015
016
017
018
019
020
021
022
023
024
025
026
027
028
029
030
031
032
033
034
035
036
037
038
039
040
041
042
043
044
045
046
047
048
049
050
051
052
053

THE COOPER UNION
ALBERT NERKEN SCHOOL OF ENGINEERING

A Deep Partitioned Autoencoder
for De-Noising Live Audio

by
Ethan Lusterman

A thesis submitted in partial fulfillment
of the requirements for the degree of
Master of Engineering

September 2016

Professor Sam Keene, Advisor

054 THE COOPER UNION FOR THE
055
056 ADVANCEMENT OF SCIENCE AND ART
057
058
059
060

061 ALBERT NERKEN SCHOOL OF ENGINEERING
062
063
064
065
066
067
068
069

070 This thesis was prepared under the direction of the Can-
071 didate's Thesis Advisor and has received approval. It was
072 submitted to the Dean of the School of Engineering and
073 the full Faculty, and was approved as partial fulfillment of
074 the requirements for the degree of Master of Engineering.
075
076
077
078
079
080
081
082
083
084
085
086

087 _____
088 Dean, School of Engineering Date
089
090
091
092
093
094

095 _____
096 Prof. Sam Keene, Thesis Advisor Date
097
098
099
100
101
102
103
104
105
106
107

108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161

Acknowledgements

Ack example

162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215

Abstract

Abstract

216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269

Contents

1	Introduction	1
2	Background	2
2.1	Machine Learning	2
2.1.1	Regression	3
2.1.2	Overfitting and Curse of Dimensionality	3
2.1.3	Loss functions and Regularization	3
2.1.4	Gradient Stuff?	3
2.2	Neural Networks	3
2.2.1	Dense Layer	3
2.2.2	Convolutional Layer	3
2.2.3	Nonlinearity Choice	3
2.3	Signals and Systems	3
2.3.1	Signals	3
2.3.2	Convolution	4
2.3.3	Frequency Transforms	5
2.3.4	Windowing and Perfect Reconstruction	6
2.3.5	Window Size and Frequency v. Time Resolution Tradeoff	7
2.3.6	Noise and Signal-to-Noise Ratio	7
2.3.7	Magnitude and Phase Spectrum	7
3	System Description	8
4	Results	9
5	Conclusions and Future Work	10
5.1	Conclusions	10
5.2	Future Work	10
5.2.1	Models	10
5.2.2	Data	10

270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323

List of Figures

324	Table of Nomenclature
325	
326	
327	
328	
329	
330	
331	
332	
333	
334	
335	
336	
337	
338	
339	
340	
341	
342	
343	
344	
345	
346	
347	
348	
349	
350	
351	
352	
353	
354	
355	
356	
357	
358	
359	
360	
361	
362	
363	
364	
365	
366	
367	
368	
369	
370	
371	
372	
373	
374	
375	
376	
377	

1 Introduction

Advances in smartphone technology have led to smaller devices with more powerful audio hardware, allowing for common consumers to make higher quality recordings. However, recorded speech and music are subject to noisy conditions, often hampering intelligibility and listenability. The goal of denoising audio recordings is to improve intelligibility and perceived quality. A variety of applications of audio denoising exist, including listening to a recording of a band or an artist’s live performance in a noisy crowd, or listening to a recorded conversation or speech under noisy conditions.

A common technique for denoising involves the use of deep neural networks (DNN). [PARIS] Advances in parallel graphics processing units (GPU) and in machine learning algorithms have allowed for training deeper networks faster, utilizing more hidden layers with more neurons.

Prior work in denoising audio has involved access to noise-free training data. Since common consumers do not often have access to clean audio, we seek to denoise without the use of clean audio.

In this thesis, we compare several neural network architectures and problem scenarios, ranging from data input types, level of noise, depth of network, training objectives, and more. In Chapter 2, we present background information on machine learning, neural networks, and signal processing as well as prior work in audio denoising. In Chapter 3, we detail all considered network architectures. In Chapter 4, we compare results from different data inputs, levels of noise, network architectures, and training objectives and discuss methods of evaluation. Finally, we make conclusions and recommendations for future work in Chapter 5.

2 Background

2.1 Machine Learning

Machine learning involves the use of computer algorithms to make decisions based on training data. Generally, this falls into categorizing input data (classification) or determining a mathematical function to determine a continuous output given an input (regression). Popular classification examples include recognizing handwritten digits (MNIST) as well as determining whether an image contains a cat or a dog. (REF) An example of a regression problem is determining the temperature given a set of input features (humidity, latitude, longitude, date, etc.).

Problems where training data contain input data vectors as well as the correct output vectors (targets) are known as supervised learning problems. Training a model to denoise audio where noise was introduced to the clean audio would be a supervised learning problem. On the other hand, training a model to denoise audio where the underlying clean signal is not known is an unsupervised learning problem. Different loss functions and neural network architectures can be exploited to accomplish denoising without the clean data.

For the purposes of this thesis, we use machine learning to determine an underlying nonlinear function that removes noise from time slices of audio (i.e. regression). These slices can then be pieced back together through overlap-add resynthesis. To clarify, this is a general linear model that maps an input noisy audio vector $y[n] = x[n] + N[n]$ to $\tilde{x}[n]$, a target denoised audio vector, where $x[n]$ is the underlying clean signal and $N[n]$ is the additive background noise.

2.1.1 Regression

A classical regression technique is linear regression, where one or more independent variables x_i are used to determine a scalar dependent variable y . The case of a single independent variable x is known as simple linear regression. On the other hand, the case of estimating A canonical example would be estimating a sine wave $x[n]$ given noisy samples

2.1.2 Overfitting and Curse of Dimensionality

2.1.3 Loss functions and Regularization

2.1.4 Gradient Stuff?

2.2 Neural Networks

2.2.1 Dense Layer

2.2.2 Convolutional Layer

2.2.3 Nonlinearity Choice

2.3 Signals and Systems

Domain knowledge of discrete audio signals and systems better informs our decisions for an audio denoising system, so some background information on signals and systems as it pertains to this thesis is detailed below.

2.3.1 Signals

We deal exclusively with discrete-time audio signals in this thesis. A discrete-time audio signal $x[n]$ is represented as a sequence of numbers (samples), where each integer-valued slot n in the sequence corresponds to a unit of time based on the sampling frequency f_s . This comes from sampling the continuous-time audio signal $x_c(t)$:

$$x[n] = x_c(nT) \quad (1)$$

where $T = 1/f_s$. For example, a 1-second speech signal sampled at 8kHz has 8000 samples. Furthermore, digital signals also have discrete valued sample amplitudes. For the purposes of this thesis, the bit depths of computers we use for analysis are high enough to allow for perfect reconstruction between continuous-time signals and digital signals.

We also assume signals collected have been properly sampled according to the Nyquist-Shannon sampling theorem, which states that a discrete-time signal must be sampled at at least twice the highest frequency present in the signal to prevent aliasing of different frequencies. For example, speech signals generally have information up to 8kHz, so many speech signals are sampled at 16kHz. Music is more complex in that signals often span up to about 20kHz, so CD quality recordings are often sampled at 44.1kHz or higher. For this thesis, we use recordings sampled at 44.1kHz or lower.

2.3.2 Convolution

The discrete-time convolution operation takes two sequences $x[n]$ and $h[n]$ and outputs a third sequence $y[n] = x[n] * h[n]$:

$$y[n] = \sum_{k=-\infty}^{\infty} x[k]h[n-k] \quad (2)$$

Convolution is commutative, so $x[n] * h[n] = h[n] * x[n]$ holds true.

A linear, time-invariant (LTI) system is characterized by its impulse response $h[n]$, which allows us to determine samples $y[n]$ when $x[n]$ is subject to $h[n]$. For the purposes of this thesis, our underlying clean signal $x[n]$ might be

subject to the conditions of an acoustic environment $h[n]$ and crowd noise $N[n]$:

$$y[n] = h[n] * x[n] + N[n] \quad (3)$$

In this scenario, our system would attempt to recover $h[n] * x[n]$ and possibly even $x[n]$ if the acoustic environment were deemed “noisy enough” due to echo and reverberation.

One of our proposed systems also incorporates convolutional neural networks (CNN) which use convolutions between frames of samples instead of simple linear combinations (discussed later).

2.3.3 Frequency Transforms

In some of our proposed systems, we use a frequency transformed version of the input signal as a preprocessing step to the system input. While no new information is gained from transforming the input, networks often respond better to determining the value of the magnitude of varying frequencies at a time slice instead of the individual time samples.

The frequency transform we use in this thesis is the discrete-time Fourier transform (DTFT). A sequence of N discrete-time samples is transformed into another sequence of N samples where each index then corresponds to a frequency bin. The DTFT $X[k]$ of a signal $x[n]$ is given by the following:

$$X[k] = \sum_{n=0}^{N-1} x[n] W_N^{kn} \quad (4)$$

where the twiddle factor W_N is given by $W_N = e^{-j(2\pi/N)}$. Then the reconstruction of $x[n]$ from $X[k]$ is given by:

$$x[n] = \frac{1}{N} \sum_{k=0}^{N-1} X[k] W_N^{-kn} \quad (5)$$

In this thesis, we also exploit the main duality between the time and frequency domain using the convolution theorem, which states that convolution in time is equivalent to multiplication in frequency and vice versa:

$$\mathcal{F}\{h[n] * x[n]\} = H[k]X[k] \quad (6)$$

$$\mathcal{F}^{-1}\{H[k] * X[k]\} = h[n]x[n] \quad (7)$$

This allows us to effectively treat our network as a non-linear filter that can denoise small time/frequency slices of our noisy signal, which can then be pieced back together using overlap-add resynthesis. We detail this in the next section.

2.3.4 Windowing and Perfect Reconstruction

To window a signal is to multiply a window function $w[n]$ by the frame, i.e. $w[n]x[n]$ over the frame length N . Because we are training a network to denoise small segments of a larger audio signal, we window the signal segments. This accommodates the finite-length requirement of the DTFT and helps to prevent spectral leakage. [DSPBOOK]

Also, to be able to properly reconstruct our signal, we use a window function and corresponding overlapping frame percentage to accomplish perfect reconstruction. The corresponding overlapping frame percentage is set such that the window sums to a constant for all time. For example, a rectangular window $w[n] = 1$ over an interval of length N has an overlap of 0% to sum to a constant 1 for all time. Another popular window is the Hanning window, defined over an interval N by the following:

$$w[n] = \frac{1}{2} \left(1 - \cos \left(\frac{2\pi n}{N-1} \right) \right) \quad (8)$$

For the Hann window, the perfect reconstruction overlap is a frame length of $N = 50\%$.

2.3.5 Window Size and Frequency v. Time Resolution Tradeoff

2.3.6 Noise and Signal-to-Noise Ratio

Since we are trying to denoise audio signals, we must discuss how we measure noise. One of the most common measures of degradation of signal quality from additive noise is signal-to-noise ratio (SNR), defined as the ratio of signal variance to noise variance. [DSP] For the signal $y[n] = x[n] + N[n]$, where $x[n]$ is the signal of interest and $N[n]$ is the additive noise, the SNR is defined as

$$SNR = \frac{\sigma_x^2}{\sigma_n^2} \quad (9)$$

where σ^2 refers to the variance of the signal in question over some time interval. For the purposes of this thesis, we achieve desired a desired SNR for a simulation by scaling the noise to match the variance to the signal, then scaling the noise or the signal to achieve the desired SNR.

2.3.7 Magnitude and Phase Spectrum

756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809

3 System Description

810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863

4 Results

864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917

5 Conclusions and Future Work

5.1 Conclusions

While more work is needed, deep partitioned neural network architectures using time and frequency data seem promising in long-term solutions for denoising speech and music signals.

5.2 Future Work

5.2.1 Models

Make network deeper. Consider gradual partitioning instead of hard.

5.2.2 Data

Get more data. Consider different noise levels and types of signals.

References

- [1] A. Krizhevsky, I. Sutskever, and G. E. Hinton, “Imagenet classification with deep convolutional neural networks,” in *Advances in Neural Information Processing Systems 25*, F. Pereira, C. Burges, L. Bottou, and K. Weinberger, Eds. Curran Associates, Inc., 2012, pp. 1097–1105. [Online]. Available: <http://papers.nips.cc/paper/4824-imagenet-classification-with-deep-convolutional-neural-networks.pdf>
- [2] C. Szegedy, W. Liu, Y. Jia, P. Sermanet, S. Reed, D. Anguelov, D. Erhan, V. Vanhoucke, and A. Rabinovich, “Going deeper with convolutions,” *CoRR*, vol. abs/1409.4842, 2014. [Online]. Available: <http://arxiv.org/abs/1409.4842>
- [3] I. Sutskever, J. Martens, G. Dahl, and G. Hinton, “On the importance of initialization and momentum in deep learning,” in *Proceedings of the 30th International Conference on Machine Learning (ICML-13)*, 2013, pp. 1139–1147.
- [4] K. He, X. Zhang, S. Ren, and J. Sun, “Delving deep into rectifiers: Surpassing human-level performance on imagenet classification,” *CoRR*, vol. abs/1502.01852, 2015. [Online]. Available: <http://arxiv.org/abs/1502.01852>
- [5] G. E. Hinton, N. Srivastava, A. Krizhevsky, I. Sutskever, and R. Salakhutdinov, “Improving neural networks by preventing co-adaptation of feature detectors,” *CoRR*, vol. abs/1207.0580, 2012. [Online]. Available: <http://arxiv.org/abs/1207.0580>
- [6] D. R. Wilson and T. R. Martinez, “The general inefficiency of batch training for gradient descent learning,” *Neural Netw.*, vol. 16, no. 10, pp. 1429–1451, Dec. 2003. [Online]. Available: [http://dx.doi.org/10.1016/S0893-6080\(03\)00138-2](http://dx.doi.org/10.1016/S0893-6080(03)00138-2)
- [7] G. E. Dahl, T. N. Sainath, and G. E. Hinton, “Improving deep neural networks for lvcsr using rectified linear units and dropout,” in *Acoustics, Speech and Signal Processing (ICASSP), 2013 IEEE International Conference on*. IEEE, 2013, pp. 8609–8613.
- [8] M. D. Zeiler and R. Fergus, “Visualizing and understanding convolutional networks,” *CoRR*, vol. abs/1311.2901, 2013. [Online]. Available: <http://arxiv.org/abs/1311.2901>

- [9] S. Geman, E. Bienenstock, and R. Doursat, “Neural networks and the bias/variance dilemma,” *Neural computation*, vol. 4, no. 1, pp. 1–58, 1992.
- [10] X. Glorot and Y. Bengio, “Understanding the difficulty of training deep feedforward neural networks,” in *International conference on artificial intelligence and statistics*, 2010, pp. 249–256.
- [11] N. Srivastava, G. Hinton, A. Krizhevsky, I. Sutskever, and R. Salakhutdinov, “Dropout: A simple way to prevent neural networks from overfitting,” *Journal of Machine Learning Research*, vol. 15, pp. 1929–1958, 2014. [Online]. Available: <http://jmlr.org/papers/v15/srivastava14a.html>
- [12] J. Luo, “Frequently asked questions,” Hatfield Marine Science Center, 2014. [Online]. Available: <https://www.kaggle.com/c/datasciencebowl/data>
- [13] K. Fukushima, “Neocognitron: A self-organizing neural network model for a mechanism of pattern recognition unaffected by shift in position,” *Biological Cybernetics*, vol. 36, no. 4, pp. 193–202, 1980. [Online]. Available: <http://dx.doi.org/10.1007/BF00344251>
- [14] Y. LeCun, B. Boser, J. S. Denker, D. Henderson, R. E. Howard, W. Hubbard, and L. D. Jackel, “Backpropagation applied to handwritten zip code recognition,” *Neural computation*, vol. 1, no. 4, pp. 541–551, 1989.
- [15] X. Glorot, A. Bordes, and Y. Bengio, “Deep sparse rectifier networks,” in *Proceedings of the 14th International Conference on Artificial Intelligence and Statistics. JMLR W&CP Volume*, vol. 15, 2011, pp. 315–323.
- [16] Y. Nesterov *et al.*, “Gradient methods for minimizing composite objective function,” 2007.
- [17] A. Krogh and J. A. Hertz, “A simple weight decay can improve generalization,” in *ADVANCES IN NEURAL INFORMATION PROCESSING SYSTEMS 4*. Morgan Kaufmann, 1992, pp. 950–957.
- [18] R. Collobert, K. Kavukcuoglu, and C. Farabet, “Torch7: A matlab-like environment for machine learning,” in *BigLearn, NIPS Workshop*, no. EPFL-CONF-192376, 2011.
- [19] T. Salimans, I. J. Goodfellow, W. Zaremba, V. Cheung, A. Radford, and X. Chen, “Improved techniques for training gans,” *CoRR*, vol. abs/1606.03498, 2016. [Online]. Available: <http://arxiv.org/abs/1606.03498>

1026 [20] A. Radford, L. Metz, and S. Chintala, “Unsupervised repre-
1027 sentation learning with deep convolutional generative adversarial
1028 networks,” *CoRR*, vol. abs/1511.06434, 2015. [Online]. Available:
1029 <http://arxiv.org/abs/1511.06434>
1030
1031
1032 [21] E. L. Denton, S. Chintala, A. Szlam, and R. Fergus, “Deep
1033 generative image models using a laplacian pyramid of adversarial
1034 networks,” *CoRR*, vol. abs/1506.05751, 2015. [Online]. Available:
1035 <http://arxiv.org/abs/1506.05751>
1036
1037
1038 [22] Y. Li, K. Swersky, and R. S. Zemel, “Generative moment matching
1039 networks,” *CoRR*, vol. abs/1502.02761, 2015. [Online]. Available:
1040 <http://arxiv.org/abs/1502.02761>
1041
1042
1043 [23] J. Johnson, A. Alahi, and F. Li, “Perceptual losses for real-time
1044 style transfer and super-resolution,” *CoRR*, vol. abs/1603.08155, 2016.
1045 [Online]. Available: <http://arxiv.org/abs/1603.08155>
1046
1047
1048 [24] L. A. Gatys, A. S. Ecker, and M. Bethge, “A neural algorithm of
1049 artistic style,” *CoRR*, vol. abs/1508.06576, 2015. [Online]. Available:
1050 <http://arxiv.org/abs/1508.06576>
1051
1052
1053 [25] A. Makhzani, J. Shlens, N. Jaitly, and I. J. Goodfellow, “Adversarial
1054 autoencoders,” *CoRR*, vol. abs/1511.05644, 2015. [Online]. Available:
1055 <http://arxiv.org/abs/1511.05644>
1056
1057
1058 [26] L. Chen, G. Papandreou, I. Kokkinos, K. Murphy, and A. L. Yuille,
1059 “Semantic image segmentation with deep convolutional nets and fully
1060 connected crfs,” *CoRR*, vol. abs/1412.7062, 2014. [Online]. Available:
1061 <http://arxiv.org/abs/1412.7062>
1062
1063
1064 [27] F. Yu and V. Koltun, “Multi-scale context aggregation by dilated
1065 convolutions,” *CoRR*, vol. abs/1511.07122, 2015. [Online]. Available:
1066 <http://arxiv.org/abs/1511.07122>
1067
1068
1069 [28] D. P. Kingma and J. Ba, “Adam: A method for stochastic
1070 optimization,” *CoRR*, vol. abs/1412.6980, 2014. [Online]. Available:
1071 <http://arxiv.org/abs/1412.6980>
1072
1073
1074 [29] I. J. Goodfellow, J. Pouget-Abadie, M. Mirza, B. Xu, D. Warde-Farley,
1075 S. Ozair, A. C. Courville, and Y. Bengio, “Generative adversarial
1076 networks,” *CoRR*, vol. abs/1406.2661, 2014. [Online]. Available:
1077 <http://arxiv.org/abs/1406.2661>
1078
1079

1080 [30] Y. A. LeCun, L. Bottou, G. B. Orr, and K.-R. Müller, “Efficient back-
1081 prop,” in *Neural networks: Tricks of the trade*. Springer, 1998, pp. 9–48.
1082
1083
1084 [31] A. G. Baydin, B. A. Pearlmutter, and A. A. Radul, “Automatic differ-
1085 entiation in machine learning: a survey,” *CoRR*, vol. abs/1502.05767,
1086 2015. [Online]. Available: <http://arxiv.org/abs/1502.05767>
1087
1088 [32] J. Bergstra, O. Breuleux, F. Bastien, P. Lamblin, R. Pascanu, G. Des-
1089 jardins, J. Turian, D. Warde-Farley, and Y. Bengio, “Theano: A cpu and
1090 gpu math compiler in python,” in *Proceedings of the 9th Python in Sci-
1091 ence Conference*, S. van der Walt and J. Millman, Eds., 2010, pp. 3 –
1092 10.
1093
1094
1095 [33] M. Abadi, A. Agarwal, P. Barham, E. Brevdo, Z. Chen, C. Citro,
1096 G. S. Corrado, A. Davis, J. Dean, M. Devin, S. Ghemawat, I. J.
1097 Goodfellow, A. Harp, G. Irving, M. Isard, Y. Jia, R. Józefowicz,
1098 L. Kaiser, M. Kudlur, J. Levenberg, D. Mané, R. Monga, S. Moore,
1099 D. G. Murray, C. Olah, M. Schuster, J. Shlens, B. Steiner, I. Sutskever,
1100 K. Talwar, P. A. Tucker, V. Vanhoucke, V. Vasudevan, F. B. Viégas,
1101 O. Vinyals, P. Warden, M. Wattenberg, M. Wicke, Y. Yu, and
1102 X. Zheng, “Tensorflow: Large-scale machine learning on heterogeneous
1103 distributed systems,” *CoRR*, vol. abs/1603.04467, 2016. [Online].
1104 Available: <http://arxiv.org/abs/1603.04467>
1105
1106
1107 [34] G. Cybenko, “Approximation by superpositions of a sigmoidal function,”
1108 *Mathematics of control, signals and systems*, vol. 2, no. 4, pp. 303–314,
1109 1989.
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133