

Markov Renewal Processes – Basics

Definition: The stochastic process $\{(X_n, T_n)\}$ is called a *Markov renewal process* with state space E if

$$P\{X_{n+1} = j, T_{n+1} - T_n \leq t \mid X_0, \dots, X_n; T_0, \dots, T_n\} = P\{X_{n+1} = j, T_{n+1} - T_n \leq t \mid X_n\}$$

for all $n=0, 1, \dots, j \in E$, and $t \geq 0$.

We will always assume (1) the process is time homogeneous and (2) E is discrete.

Definition: The family of probabilities $Q = \{Q(i, j, t): i, j \in E, \text{ and } t \geq 0\}$ is called a *semi-Markov kernel* and is defined by

$$P\{X_{n+1} = j, T_{n+1} - T_n \leq t \mid X_n = i\} = Q(i, j, t).$$

Definition: The process $\{Y(t)\}$ defined by

$$Y(t) = X_n \text{ for } T_n \leq t < T_{n+1} \text{ and } Y(t) = \Delta \text{ if } t \geq \sup \{T_n : n=0, 1, \dots\},$$

is called a *semi-Markov process*, where Δ is a state not in E .

Two properties of a Markov renewal process:

1. $\{X_n\}$ is a Markov chain.
2. $P\{T_{n+1} - T_n \leq t \mid X_0, X_1, \dots; T_0, \dots, T_n\} = P\{T_{n+1} - T_n \leq t \mid X_n, X_{n+1}\}$

Examples

1. A Markov process forms a Markov renewal process. Or, one could also say that a semi-Markov process is a generalization of a Markov process.
2. *Counters of Type I:* Arrivals to a particle counter form a Poisson process with rate λ . An arriving particle which finds the counter free gets registered and locks it for a random duration with distribution function ψ . Arrivals during a locked period have no effect. Define State 0 to be the state when the counter is unlocked and let State 1 be when the counter is locked. Let $T_0=0, T_1, T_2$, etc. be the successive instants of changes in the state of the counter and let X_n be the state immediately after T_n . Then $\{(X_n, T_n)\}$ is a Markov renewal process with state space $E = \{0, 1\}$. The semi-Markov process $\{Y(t)\}$ associated with $\{(X_n, T_n)\}$ represents the state of the counter at time t . The semi-Markov kernel for this process is relatively simple.
3. *M/G/1 Queueing System.* An M/G/1 system represents a single-server queueing system with a Poisson arrival process with rate λ and independent service times with the common distribution ϕ . Let $T_0=0, T_1, T_2$, etc. be the successive instants of departures, and let X_n be the number of customers left behind by the n^{th} departure. Then $\{(X_n, T_n)\}$ is a Markov renewal process with state space $E = \{0, 1, \dots\}$. The semi-Markov kernel for this process is more complex than the previous example, but we do have $Q(i,j,t) = 0$ for $i - j \geq 2$.

Consider example 4 after example 3 has been discussed

4. *G/M/1 Queueing System.* A G/M/1 system represents a single-server queueing system with the arrival process being a renewal process with ϕ being the distribution of inter-arrival times and independent service times governed by an exponential distribution with mean rate μ . Let $T_0=0, T_1, T_2$, etc. be the successive instants of arrivals, and let X_n be the number of customers just **before** the n^{th} arrival. Then $\{(X_n, T_n)\}$ is a Markov renewal process with state space $E = \{0, 1, \dots\}$. The semi-Markov kernel for this process is more complex than the previous example, but we do have $Q(i,j,t) = 0$ for $j - i \geq 2$.