

## PHL451 – Prolog Exercise

In order to complete these exercises please use the SWISH prolog app available at:

<https://swish.swi-prolog.org>

Cut and past the following program in to the program area of the SWISH interface:

```
female(pam).  
female(liz).  
female(ann).  
female(pat).  
male(tom).  
male(bob). male(jim).  
parent(pam,bob).  
parent(tom,bob).  
parent(tom,liz).  
parent(bob,ann).  
parent(bob,pat). parent(pat,jim).
```

(a) Once you have loaded the program pose the following queries:

```
?- female(ann).  
?- female(jim).  
?- parent(X,bob).  
?- parent(tom,X).  
?- parent(X,ann),parent(X,pat).
```

What are the answers to these queries? Beware, for some queries here might be more than one answer. To get all the answers type a ';' and carriage return at the question mark.

(b) Now, using the parent predicate formulate the following Prolog queries:

1. Who is Pat's parent?
2. Does Liz have a child?
3. Who is Pat's grandparent?

(c) Given the above facts, extend the program by writing rules defining the following predicates:

```
sister(X,Y) -- X is the sister of Y.  
son(X,Y) -- X is the son of Y. father(X,Y)  
-- X is the father of Y. grandmother(X,Y)  
-- X is the grandmother of Y.
```

Hint: The following predicate might come in handy: `different(X,Y):- not(X=Y)`.  
Demonstrate that your program works by posing the following queries:

4. `?- sister(X,pat).`
5. `?- sister(X,Y).`
6. `?- son(jim,X).`
7. `?- father(X,bob).`
8. `?- grandmother(X,ann).`
9. `?- ancestor(X,jim).`

Hand in the source code of your prolog program and a proof of the program execution.

**Extra Credit:** create a rule that defines,

`ancestor(X,Y)` -- X is an ancestor of Y.

Hint: use recursion.