



LSS: Linear Shamir's
Secret Sharing —
A Pragmatic
Framework for Dynamic
and Resilient
Threshold Signatures
with Live Secret Resharing

Zech Kallim

Lux Industries

2024

Abstract

We present **LSS** (Linear Secret Sharing), a pragmatic MPC framework for dynamic threshold signatures that wraps both CGGMP21 (threshold ECDSA) and FROST (threshold Schnorr/EdDSA) under a unified interface with *live membership changes*. The protocol’s principal innovation is coordinator-driven verifiable resharing via Joint Verifiable Secret Sharing (JVSS), enabling transition from (t, n) to $(t', n \pm k)$ without reconstructing the master key or interrupting signing operations.

LSS solves three critical operational challenges absent from prior threshold signature literature: (1) *dynamic resharing* — live expansion and contraction of the signing group without downtime or key reconstruction; (2) *automated fault tolerance* — node eviction, state rollback to previously certified shard generations, and persistence-backed recovery; and (3) *multi-chain adaptation* — a unified **SignerAdapter** interface providing native signature production for 20+ blockchains (XRPL, Ethereum, Bitcoin, Solana, Cosmos, Polkadot, TON, Sui, Aptos, Cardano, and others).

The framework supports Protocol I (Localized Nonce Blinding) and Protocol II (Collaborative Nonce Blinding), achieving sub-25ms signing latency with 100% test coverage and Byzantine fault tolerance up to $t - 1$ malicious parties. Post-quantum security is provided via integration with Ringtail lattice-based threshold signatures at 128/192/256-bit security levels.

Production-deployed in the Lux Teleport omnichain bridge securing cross-chain assets across 270+ connected blockchains.

Contents

1	Introduction	2
2	Preliminaries	3
2.1	Shamir’s Secret Sharing	3
2.2	Linearity Property	3
2.3	Joint Verifiable Secret Sharing (JVSS)	3
3	LSS Protocol	3
3.1	Architecture	3
3.2	Dynamic Resharing Protocol	3
3.3	Fault Tolerance and Rollback	5
3.4	Protocol Variants	5
4	Multi-Chain Adaptation	5
5	Post-Quantum Extension	6
6	Security Analysis	6
7	Performance	6
8	Deployment	6
9	Conclusion	7

1 Introduction

Threshold signature schemes enable a group of n parties to collectively produce signatures under a shared public key, such that any subset of t or more parties can sign while any subset of $t - 1$ or fewer cannot. Two dominant protocols exist:

- **CGGMP21** [5]: Threshold ECDSA with identifiable aborts, producing standard (r, s, v) signatures compatible with Ethereum, Bitcoin, and all secp256k1 chains.
- **FROST** [4]: Two-round Schnorr threshold signatures for Ed25519 and BIP-340 Taproot, compatible with Solana, TON, Cosmos, Polkadot, and Bitcoin Taproot.

Both protocols assume a *static* signer set: the participants are fixed at key generation time and cannot be changed without generating a new key pair. This is operationally infeasible for production systems requiring 24/7 uptime, where nodes must be rotated for maintenance, security incidents, or capacity changes.

Our Contribution. LSS solves this by providing a *live resharing* protocol that enables:

1. Adding new signers to an existing group without downtime.
2. Removing signers (including compromised nodes) without key reconstruction.
3. Changing the threshold t while maintaining the same public key.
4. Automatic rollback to previous shard generations on signing failure.
5. Unified multi-chain support through pluggable **SignerAdapter** interface.

The key insight is that Shamir’s Secret Sharing [1] is *linear*: shares of a secret s under polynomial $f(x)$ of degree $t - 1$ can be *re-shared* into a new polynomial $g(x)$ of degree $t' - 1$ distributed to a potentially different set of n' participants, without ever reconstructing s in the clear. JVSS [2] makes this verifiable.

2 Preliminaries

2.1 Shamir’s Secret Sharing

Definition 1 ((t, n) -Shamir Sharing). *A dealer chooses a random polynomial $f(x) = s + a_1x + a_2x^2 + \dots + a_{t-1}x^{t-1}$ over $\mathbb{Z}_q$ where $f(0) = s$ is the secret. Share i is $s_i = f(i)$ for $i \in \{1, \dots, n\}$. Any t shares determine f (and thus s) via Lagrange interpolation; any $t - 1$ shares reveal no information about s .*

2.2 Linearity Property

The critical property enabling LSS is linearity:

$$f(x) + g(x) = (s_f + s_g) + (a_1^f + a_1^g)x + \dots \quad (1)$$

If parties hold shares of f and independently generate shares of a polynomial g with $g(0) = 0$, the sum produces a fresh sharing of the same secret s_f under a new polynomial. This enables:

- **Refresh**: Same (t, n) , new polynomial, same secret.
- **Reshare**: New (t', n') , new polynomial, same secret.

2.3 Joint Verifiable Secret Sharing (JVSS)

JVSS [2] adds verifiability: each party publishes Pedersen commitments $C_k = g^{a_k}h^{b_k}$ for each coefficient of their polynomial. Other parties verify their shares against these commitments. A complaint mechanism handles malicious dealers.

3 LSS Protocol

3.1 Architecture

LSS operates as a wrapper around CGGMP21 and FROST:

Component	Purpose
Suite	Unified entry point, protocol selection
WithCMP(pool)	CMP/CGGMP21 backend for ECDSA
WithFROST(pool)	FROST backend for Schnorr/EdDSA
Coordinator	Manages resharing ceremonies
Dealer	Distributes JVSS shares during reshare
Rollback	Maintains generation history
SignerAdapter	Chain-specific signature formatting

3.2 Dynamic Resharing Protocol

Algorithm 1 LSS Dynamic Reshare: $(t, n) \rightarrow (t', n')$

Require: Current config C_{old} with shares $\{s_i\}_{i \in P_{old}}$, new set P_{new} , new threshold t'

Ensure: New config C_{new} with shares $\{s'_j\}_{j \in P_{new}}$, same public key Y

- 1: **Phase 1: Coordinator Preparation**
 - 2: Coordinator broadcasts $(P_{new}, t', \text{generation}_{k+1})$ to all parties in $P_{old} \cup P_{new}$
 - 3: Each old party $p_i \in P_{old}$ generates resharing polynomial $g_i(x)$ of degree $t' - 1$
 - 4: $g_i(0) = \lambda_i \cdot s_i$ where λ_i is Lagrange coefficient for P_{old} subset
 - 5: **Phase 2: Verifiable Distribution (JVSS)**
 - 6: **for all** $p_i \in P_{old}$ **do**
 - 7: Compute commitments $\{C_{i,k} = g^{a_{i,k}}\}_{k=0}^{t'-1}$ and broadcast
 - 8: **for all** $p_j \in P_{new}$ **do**
 - 9: Send share $g_i(j)$ privately to p_j
 - 10: **end for**
 - 11: **end for**
 - 12: **Phase 3: Verification and Aggregation**
 - 13: **for all** $p_j \in P_{new}$ **do**
 - 14: Verify each received share against commitments
 - 15: File complaint if verification fails
 - 16: Aggregate: $s'_j = \sum_{i \in P_{old}} g_i(j)$
 - 17: **end for**
 - 18: **Phase 4: Certification**
 - 19: All parties verify $Y' = Y$ (public key unchanged)
 - 20: Coordinator certifies generation $k + 1$, stores C_{new} in persistence layer
 - 21: Previous generation k retained for rollback
-

Theorem 1 (Reshare Correctness). *After protocol execution, the new shares $\{s'_j\}_{j \in P_{new}}$ form a valid (t', n') -Shamir sharing of the same secret $s = f(0)$, and the group public key $Y = g^s$ is unchanged.*

Proof. By linearity of Lagrange interpolation:

$$s'_j = \sum_{i \in P_{old}} g_i(j) = \sum_{i \in P_{old}} \lambda_i \cdot s_i \cdot L_{i,j}(t')$$

At $j = 0$:

$$\sum_{i \in P_{old}} g_i(0) = \sum_{i \in P_{old}} \lambda_i \cdot s_i = s$$

since $\sum \lambda_i s_i$ is Lagrange interpolation of f at $x = 0$. The new polynomial has degree $t' - 1$, so any t' shares suffice to recover s . The public key $Y = g^s$ is unchanged since s is unchanged. $\square$ $\square$

3.3 Fault Tolerance and Rollback

Definition 2 (Generation History). *LSS maintains a chain of certified shard generations: $C_0 \rightarrow C_1 \rightarrow \dots \rightarrow C_k$. If signing under generation k fails (node eviction, timeout, abort), the coordinator rolls back to C_{k-1} and retries.*

Theorem 2 (Rollback Safety). *If generation C_{k-1} was certified (all parties confirmed valid shares), then rollback to C_{k-1} preserves the ability to sign with the original secret key s .*

3.4 Protocol Variants

Protocol I: Localized Nonce Blinding. Each party generates their own blinding factor for nonce computation. Lower latency (~ 8 ms) but requires an honest majority assumption for nonce generation.

Protocol II: Collaborative Nonce Blinding. Nonce blinding is jointly computed via another round of JVSS. Higher latency (~ 25 ms) but secure against dishonest majority up to $t - 1$ corruptions.

4 Multi-Chain Adaptation

LSS provides a unified `SignerAdapter` interface for chain-specific signature formatting:

```
[language=Go,basicstyle=] type SignerAdapter interface ChainType() string FormatSignature(r, s *big.Int,
v byte) ([]byte, error) DeriveAddress(pubkey []byte) (string, error) ValidateTransaction(tx []byte) error
```

5 Post-Quantum Extension

LSS integrates with Ringtail [6] lattice-based threshold signatures for post-quantum security. Ringtail uses Learning With Errors (LWE) to provide threshold signatures secure against quantum computers:

- **128-bit security:** $n = 512, q = 2^{32}$, signature ~ 4 KB
- **192-bit security:** $n = 768, q = 2^{48}$, signature ~ 6 KB
- **256-bit security:** $n = 1024, q = 2^{64}$, signature ~ 8 KB

The hybrid deployment uses classical (FROST/CMP) for day-to-day signing and Ringtail for finality certificates (via Quasar consensus [7]), ensuring both current efficiency and quantum-future safety.

Chain	Backend	Sig Format	Latency
Ethereum/EVM	CMP (ECDSA)	(r, s, v) 65B	12ms
Bitcoin	FROST (Schnorr)	(R, s) 64B	8ms
Bitcoin Taproot	FROST Taproot	BIP-340 64B	8ms
Solana	FROST (Ed25519)	Ed25519 64B	8ms
TON	FROST (Ed25519)	Ed25519 64B	8ms
Cosmos	FROST (Ed25519)	Ed25519 64B	8ms
XRPL	CMP (ECDSA)	DER-encoded	12ms
Polkadot	FROST (Ed25519)	Sr25519/Ed25519	8ms
Cardano	FROST (Ed25519)	Ed25519 64B	8ms
Sui	FROST (Ed25519)	Ed25519 64B	8ms
Aptos	FROST (Ed25519)	Ed25519 64B	8ms
NEAR	FROST (Ed25519)	Ed25519 64B	8ms
Stellar	FROST (Ed25519)	Ed25519 64B	8ms
Tezos	FROST (Ed25519)	Ed25519 64B	8ms
Algorand	FROST (Ed25519)	Ed25519 64B	8ms
StarkNet	CMP (Stark)	Stark ECDSA	15ms
TRON	CMP (ECDSA)	(r, s, v) 65B	12ms

Table 1: Multi-chain signing via LSS adapters

6 Security Analysis

Theorem 3 (LSS Security). *The LSS resharing protocol preserves the security of the underlying threshold scheme (CGGMP21 or FROST). Specifically:*

1. *An adversary corrupting $< t'$ parties after reshare cannot forge signatures.*
2. *An adversary corrupting $< t$ parties before reshare AND $< t'$ parties after reshare cannot forge (even with shares from both generations).*
3. *The secret s is never reconstructed in the clear during resharing.*

Theorem 4 (Forward Security). *After a successful reshare from generation k to $k+1$, shares from generation k provide no advantage to an adversary attacking generation $k+1$, even if the adversary obtains all n shares from generation k after the reshare completes.*

7 Performance

Operation	3-of-5	5-of-7	10-of-15
Key Generation	12ms	28ms	82ms
Signing (Protocol I)	8ms	12ms	25ms
Signing (Protocol II)	15ms	22ms	40ms
Reshare	45ms	95ms	280ms
Rollback	< 1 ms	< 1 ms	< 1 ms

Table 2: Performance benchmarks (Apple M1 Max, Go 1.22)

8 Deployment

LSS is production-deployed in the Lux Teleport omnichain bridge, where it provides:

- 2-of-3 default threshold for bridge MPC signing.
- Live signer rotation with 7-day timelock (users can exit during rotation).

- Automatic rollback on signing failure (coordinator detects abort, reverts to certified generation).
- Multi-chain signing for 270+ connected blockchains via unified adapter interface.
- Zero downtime during maintenance — nodes rotate one at a time without interrupting bridge operations.

9 Conclusion

LSS bridges the gap between theoretical threshold signature schemes and production operational requirements. By exploiting the linearity of Shamir’s Secret Sharing, LSS enables live membership changes, automatic fault recovery, and unified multi-chain signing under a single framework wrapping both CGGMP21 and FROST. The integration with Ringtail post-quantum signatures provides a smooth upgrade path to quantum-resistant operations.

All source code is open-source at github.com/luxfi/threshold/protocols/lss.

References

- [1] A. Shamir, “How to Share a Secret,” *Communications of the ACM*, vol. 22, no. 11, pp. 612–613, 1979.
- [2] T. P. Pedersen, “Non-Interactive and Information-Theoretic Secure Verifiable Secret Sharing,” in *CRYPTO*, 1991.
- [3] P. Feldman, “A Practical Scheme for Non-Interactive Verifiable Secret Sharing,” in *FOCS*, 1987.
- [4] C. Komlo and I. Goldberg, “FROST: Flexible Round-Optimized Schnorr Threshold Signatures,” in *SAC*, 2020.
- [5] R. Canetti *et al.*, “UC Non-Interactive, Proactive, Threshold ECDSA with Identifiable Aborts,” in *ACM CCS*, 2020.
- [6] Z. Kelling, “Ringtail: Post-Quantum Lattice-Based Threshold Signatures,” Lux Industries, 2024.
- [7] Z. Kelling and V. Seesahai, “Quasar Consensus: Hybrid BLS + Ringtail Dual-Signature Finality,” Lux Industries, 2022.
- [8] R. Gennaro, S. Jarecki, H. Krawczyk, and T. Rabin, “Secure Distributed Key Generation for Discrete-Log Based Cryptosystems,” *Journal of Cryptology*, vol. 20, no. 1, pp. 51–83, 2007.
- [9] P. Wuille *et al.*, “BIP-340: Schnorr Signatures for secp256k1,” 2020.
- [10] Z. Kelling and V. Seesahai, “Lux Teleport: Sovereign Omnichain Liquidity,” Lux Industries, 2022.