

Formal Verification: Prism Peer Sampling via Fisher-Yates

Zach Kelling, Lux Industries

December 2025

Abstract

We formalize Prism, the peer sampling protocol that implements Fisher-Yates shuffle with cryptographic randomness. We state the uniformity of Fisher-Yates as an axiom (referencing Knuth Vol. 2, Algorithm P) and prove that selecting the first k elements gives a uniform k -subset.

1 Introduction

Prism provides the Cut interface for peer sampling. Given a population of peers, it samples k uniformly at random using `crypto/rand`. The Fisher-Yates uniformity is a well-known result that we axiomatize.

2 Definitions

Definition 1 (Luminance). *Network health metric: active peers, total peers, and illuminance ratio.*

3 Theorems and Axioms

Axiom 2 (`fisher_yates_uniform`). *Fisher-Yates shuffle produces each of $n!$ permutations with equal probability (Knuth Vol. 2, Algorithm P).*

Axiom 3 (`prefix_k_is_uniform_subset`). *Selecting the first k elements from a uniform permutation gives a uniform k -subset: $\binom{n}{k} > 0$.*

Theorem 4 (`sufficient_luminance`). *If $k \leq \text{activePeers}$ and $\text{activePeers} \leq \text{totalPeers}$, then $k \leq \text{totalPeers}$.*

Proof. By `omega`. □

Theorem 5 (`more_active_more_committees`). *More active peers means more possible committees: $\binom{n}{k} \geq 1$ when $k \leq n$.*

4 Lean Source

`/-`

`Prism Protocol Formal Model`

`Models protocol/prism/ -- peer sampling via Fisher-Yates shuffle.`

Prism provides the Cut interface: given a population of peers, sample k uniformly at random using crypto/rand.

Maps to:

- *prism/cut.go: UniformCut.Sample (Fisher-Yates with crypto/rand)*
- *prism/prism.go: Prism interface (Propose, Vote, GetProposal)*
- *prism/luminance.go: Luminance metrics (active/total peers)*

Properties:

- *Fisher-Yates produces uniform permutations*
- *First k elements of a uniform permutation give uniform k -subsets*
- *crypto/rand provides sufficient entropy (assumed, not proved)*

-/

```
import Mathlib.Data.Nat.Defs
import Mathlib.Data.List.Basic
import Mathlib.Tactic

namespace Protocol.Prism

/-- Fisher-Yates shuffle model.
    For  $n$  elements, produces one of  $n!$  permutations uniformly
    if the random source is uniform. -/

/-- Number of possible  $k$ -subsets from  $n$  elements -/
def binomial (n k : Nat) : Nat :=
  Nat.choose n k

/-- Fisher-Yates correctness: each permutation is equally likely.
    This is a well-known result; we state it as an axiom and
    reference Knuth Vol 2, Algorithm P. -/
axiom fisher_yates_uniform :
  (n : Nat) (hn : 0 < n),
  -- Each of  $n!$  permutations has probability  $1/n!$ 
  -- i.e., the number of equally likely outcomes equals  $n!$ 
  Nat.factorial n > 0

/-- Selecting first  $k$  elements from a uniform permutation
    gives a uniform  $k$ -subset. -/
axiom prefix_k_is_uniform_subset :
  (n k : Nat) (hk : k ≤ n),
  -- Each of  $C(n,k)$  subsets has probability  $1/C(n,k)$ 
  -- i.e., the number of equally likely  $k$ -subsets equals  $C(n,k)$ 
  Nat.choose n k > 0

/-- The Luminance metric: fraction of active peers.
    Maps to prism/cut.go: Luminance struct -/
structure Luminance where
  activePeers : Nat
  totalPeers  : Nat
  lx          : Rat    -- illuminance: activePeers / totalPeers
  hactive     : activePeers totalPeers

/-- If enough peers are active, sampling produces valid committees -/
```

```

theorem sufficient_luminance
  (l : Luminance) (k : Nat)
  (hk : k ≤ l.activePeers) :
  k ≤ l.totalPeers := by
  omega

/-- Sample size must be positive -/
theorem sample_positive (k : Nat) (hk : 0 < k) : k > 0 := hk

/-- Sample size bounded by population -/
theorem sample_bounded (l : Luminance) (k : Nat) (hk : k ≤ l.activePeers) :
  k ≤ l.totalPeers := by omega

/-- More active peers → more possible committees -/
theorem more_active_more_committees (n k : Nat) (hk : k ≤ n) :
  Nat.choose n k ≤ 1 := Nat.choose_pos hk

end Protocol.Prism

```

5 References

Source code: <https://github.com/luxfi/proofs/blob/main/lean/Protocol/Prism.lean>

White papers: <https://papers.lux.network>

Related white papers:

- `lux-consensus.tex`