

fheCRDT: Conflict-Free Replicated Data Types over Encrypted State

Lux Partners
research@lux.network

January 2025

Abstract

We introduce fheCRDT, the first framework combining Conflict-free Replicated Data Types (CRDTs) with Fully Homomorphic Encryption. fheCRDTs enable eventually consistent distributed systems where replicas synchronize encrypted state without decryption, achieving both strong privacy and high availability. We formalize the theory of homomorphic CRDT operations, prove that lattice properties are preserved under encryption, and demonstrate practical implementations for counters, sets, registers, and sequences. Our evaluation shows fheCRDTs achieve 500 merge operations per second in geo-distributed deployments with convergence time under 500ms.

1 Introduction

Distributed systems face the CAP theorem: consistency, availability, and partition tolerance cannot all be achieved simultaneously. CRDTs elegantly sidestep this by ensuring all replicas *eventually converge* through mathematically guaranteed conflict resolution.

Definition 1.1 (CRDT [4]). A state-based CRDT is a tuple $(S, \sqcup, \perp, q)$ where:

- $(S, \sqcup)$ is a join-semilattice with least element $\perp$
- $q : S \rightarrow V$ is a query function returning values in V

Problem: Existing CRDTs operate on plaintext, exposing sensitive data across all replicas.

Our Solution: fheCRDTs perform merge operations homomorphically, keeping data encrypted at all replicas while preserving eventual consistency.

1.1 Contributions

1. **Formal Framework:** Theory of CRDTs over encrypted domains with preservation proofs
2. **fheCRDT Primitives:** Encrypted G-Counter, PN-Counter, G-Set, OR-Set, LWW-Register
3. **Optimizations:** Delta-state compression for encrypted deltas
4. **Evaluation:** Geo-distributed deployment across 5 continents

2 Background

2.1 Lattice Theory

Definition 2.1 (Join-Semilattice). A join-semilattice $(S, \sqcup)$ satisfies for all $a, b, c \in S$:

$$a \sqcup a = a \quad (\text{idempotent}) \quad (1)$$

$$a \sqcup b = b \sqcup a \quad (\text{commutative}) \quad (2)$$

$$(a \sqcup b) \sqcup c = a \sqcup (b \sqcup c) \quad (\text{associative}) \quad (3)$$

These properties ensure replicas converge regardless of merge order.

2.2 FHE Preliminaries

□

For our construction, we require an FHE scheme supporting:

- Addition: $\text{Enc}(a) \boxplus \text{Enc}(b) = \text{Enc}(a + b)$
- Comparison: $\text{Enc}(a) \boxtimes_{<} \text{Enc}(b) = \text{Enc}(\mathbf{1}[a < b])$
- Selection: $\text{FHE.select}(\text{Enc}(c), \text{Enc}(a), \text{Enc}(b)) = \text{Enc}(c?a : b)$

3 fheCRDT Theory

3.1 Definition

Definition 3.1 (fheCRDT). An fheCRDT is a tuple $(\tilde{\sigma}, \oplus_{\text{enc}}, \tilde{\perp}, q)$ where:

- $\tilde{\sigma} = \{\text{Enc}(\text{pk}, \sigma) : \sigma \in S\}$ is the set of encrypted states
- $\oplus_{\text{enc}} : \tilde{\sigma} \times \tilde{\sigma} \rightarrow \tilde{\sigma}$ is the encrypted merge
- $\tilde{\perp} = \text{Enc}(\text{pk}, \perp)$ is the encrypted initial state
- $q : \tilde{\sigma} \times \text{sk} \rightarrow V$ is the query requiring decryption

3.2 Homomorphic Lattice Preservation

For fheCRDT validity, encrypted merge must preserve lattice properties:

Theorem 3.2 (Lattice Preservation). *If $(S, \sqcup)$ is a join-semilattice and $\oplus_{\text{enc}}$ is defined as:*

$$\text{Enc}(\text{pk}, a) \oplus_{\text{enc}} \text{Enc}(\text{pk}, b) \triangleq \text{Enc}(\text{pk}, a \sqcup b)$$

then $(\tilde{\sigma}, \oplus_{\text{enc}})$ is also a join-semilattice.

Proof. We verify each property:

Idempotence:

$$\text{Enc}(a) \oplus_{\text{enc}} \text{Enc}(a) = \text{Enc}(a \sqcup a) = \text{Enc}(a) \quad (4)$$

Commutativity:

$$\begin{aligned} \text{Enc}(a) \oplus_{\text{enc}} \text{Enc}(b) &= \text{Enc}(a \sqcup b) = \text{Enc}(b \sqcup a) = \text{Enc}(b) \oplus_{\text{enc}} \text{Enc}(a) \\ &= \text{FHE.max}(\text{FHE.gt}(a, b), a, b) \end{aligned} \quad (5)$$

Associativity:

$$\begin{aligned} (\text{Enc}(a) \oplus_{\text{enc}} \text{Enc}(b)) \oplus_{\text{enc}} \text{Enc}(c) &= \text{Enc}((a \sqcup b) \sqcup c) \\ &= \text{Enc}(a \sqcup (b \sqcup c)) \end{aligned} \quad (6)$$

$$\begin{aligned} &= \text{Enc}(a) \oplus_{\text{enc}} (\text{Enc}(b) \oplus_{\text{enc}} \text{Enc}(c)) \\ &= \text{FHE.select}(\text{FHE.gt}(a, b), a, b) \end{aligned} \quad (7)$$

$$\sigma = (P, N) \quad \text{where } P, N \text{ are G-Counters} \quad (8)$$

3.3 Convergence Guarantee

Theorem 3.3 (Encrypted Convergence). *Let $R_1, \dots, R_k$ be replicas with encrypted states $\tilde{\sigma}_1, \dots, \tilde{\sigma}_k$. After all pairwise merges complete:*

$$\forall i, j : \tilde{\sigma}_i = \tilde{\sigma}_j = \text{Enc} \left(\bigsqcup_{r=1}^k \sigma_r \right)$$

where $\sigma_r = \text{Dec}(\text{sk}, \tilde{\sigma}_r)$.

4 fheCRDT Implementations

4.1 Encrypted G-Counter

The G-Counter (grow-only counter) tracks increments per replica.

Definition 4.1 (G-Counter State).

$$\sigma = \{r_1 \mapsto c_1, \dots, r_n \mapsto c_n\} \quad \text{where } c_i \in \mathbb{Z}_{\geq 0}$$

Plaintext operations:

$$\text{increment}(\sigma, r) = \sigma[r \mapsto \sigma[r] + 1] \quad (9)$$

$$\text{query}(\sigma) = \sum_r \sigma[r] \quad (10)$$

$$\sigma_1 \sqcup \sigma_2 = \{r \mapsto \max(\sigma_1[r], \sigma_2[r])\} \quad (11)$$

Encrypted operations:

$$\text{incr_enc}(\tilde{\sigma}, r) = \tilde{\sigma}[r \mapsto \tilde{\sigma}[r] \boxplus \text{Enc}(1)] \quad (12)$$

$$\text{qu_enc}(\tilde{\sigma}, \text{sk}) = \text{Dec} \left(\text{sk}, \bigoplus_r \tilde{\sigma}[r] \right) \quad (13)$$

$$\tilde{\sigma}_1 \oplus_{\text{enc}} \tilde{\sigma}_2 = \{r \mapsto \text{FHE.max}(\tilde{\sigma}_1[r], \tilde{\sigma}_2[r])\} \quad (14)$$

4.2 Encrypted PN-Counter

The PN-Counter supports both increments and decrements.

$$\begin{aligned} &= \text{Enc}(a) \oplus_{\text{enc}} (\text{Enc}(b) \oplus_{\text{enc}} \text{Enc}(c)) \\ &= \text{FHE.select}(\text{FHE.gt}(a, b), a, b) \end{aligned} \quad (7)$$

$$\sigma = (P, N) \quad \text{where } P, N \text{ are G-Counters} \quad (8)$$

Algorithm 1 Encrypted G-Counter Merge**Require:** Encrypted states $\tilde{\sigma}_1, \tilde{\sigma}_2$ **Ensure:** Merged encrypted state $\tilde{\sigma}$

```

1: for each replica  $r$  do
2:    $\text{ct}_{\text{cmp}} \leftarrow \text{FHE.gt}(\tilde{\sigma}_1[r], \tilde{\sigma}_2[r])$ 
3:    $\tilde{\sigma}[r] \leftarrow \text{FHE.select}(\text{ct}_{\text{cmp}}, \tilde{\sigma}_1[r], \tilde{\sigma}_2[r])$ 
4: end for
5: return  $\tilde{\sigma}$ 

```

Encrypted operations:

$$\text{increment}(\tilde{\sigma}) = (\tilde{P}[r] \boxplus \text{Enc}(1), \tilde{N}) \quad (15)$$

$$\text{decrement}(\tilde{\sigma}) = (\tilde{P}, \tilde{N}[r] \boxplus \text{Enc}(1)) \quad (16)$$

$$\text{query}(\tilde{\sigma}, \text{sk}) = \text{Dec} \left(\bigoplus_r \tilde{P}[r] \right) - \text{Dec} \left(\bigoplus_r \tilde{N}[r] \right) \quad (17)$$

4.3 Encrypted G-Set

The G-Set (grow-only set) tracks element membership.

Definition 4.3 (Encrypted G-Set State).

$$\tilde{\sigma} = \{h_1 \mapsto \tilde{f}_1, \dots, h_m \mapsto \tilde{f}_m\}$$

where $h_i = \text{Hash}(e_i)$ and $\tilde{f}_i = \text{Enc}(\mathbf{1}[e_i \in S])$.

Encrypted operations:

$$\tilde{\text{add}}(\tilde{\sigma}, e) = \tilde{\sigma}[\text{Hash}(e) \mapsto \text{Enc}(1)] \quad (18)$$

$$\tilde{\sigma}_1 \oplus_{\text{enc}} \tilde{\sigma}_2 = \{h \mapsto \tilde{\sigma}_1[h] \vee_{\text{enc}} \tilde{\sigma}_2[h]\} \quad (19)$$

where $\vee_{\text{enc}}$ is encrypted OR via $a \vee b = a + b - a \cdot b$.

4.4 Encrypted OR-Set

The OR-Set (observed-remove set) supports both additions and removals.

Definition 4.4 (OR-Set State). Each element e has a set of unique tags:

$$\sigma[e] = \{t_1, t_2, \dots\} \quad (\text{tags from add operations})$$

Element $e \in S$ iff $|\sigma[e]| > 0$.

Encrypted add:

$$\tilde{\text{add}}(\tilde{\sigma}, e) = \tilde{\sigma}[e] \cup \{\text{Enc}(\text{unique_tag}())\} \quad (20)$$

Encrypted remove:

$$\tilde{\text{remove}}(\tilde{\sigma}, e) = \tilde{\sigma}[e \mapsto \emptyset] \quad (21)$$

Encrypted merge:

$$(\tilde{\sigma}_1 \oplus_{\text{enc}} \tilde{\sigma}_2)[e] = \tilde{\sigma}_1[e] \cup \tilde{\sigma}_2[e] \quad (22)$$

4.5 Encrypted LWW-Register

The Last-Writer-Wins Register resolves conflicts via timestamps.

Definition 4.5 (LWW-Register State).

$$\sigma = (t, v) \quad \text{timestamp } t, \text{ value } v$$

Encrypted merge:

$$\tilde{\sigma}_1 \oplus_{\text{enc}} \tilde{\sigma}_2 = \text{FHE.select}(\text{FHE.gt}(\tilde{t}_1, \tilde{t}_2), \tilde{\sigma}_1, \tilde{\sigma}_2) \quad (23)$$

5 Optimizations**5.1 Delta-State fheCRDTs**

Full state synchronization is expensive. We compute encrypted deltas:

Definition 5.1 (Encrypted Delta).

$$\tilde{\delta}_{i \rightarrow j} = \tilde{\sigma}_i \boxminus_{\delta} \tilde{\sigma}_{\text{last_sync}}$$

For G-Counters, $\boxminus_{\delta}$ computes per-replica differences:

$$\tilde{\delta}[r] = \tilde{\sigma}_i[r] \boxminus \tilde{\sigma}_{\text{last}}[r]$$

Theorem 5.2 (Delta Correctness).

$$\tilde{\sigma}_j \oplus_{\text{enc}} \tilde{\delta}_{i \rightarrow j} = \tilde{\sigma}_j \oplus_{\text{enc}} \tilde{\sigma}_i$$

5.2 Batched Bootstrapping

FHE comparisons require bootstrapping. We batch across merges:

Algorithm 2 Batched fheCRDT Merge

Require: States $\tilde{\sigma}_1, \dots, \tilde{\sigma}_k$ to merge

- 1: comparisons $\leftarrow \square$
- 2: **for** $i = 1$ to $k - 1$ **do**
- 3: **for** each replica r **do**
- 4: comparisons.append($((\tilde{\sigma}_i[r], \tilde{\sigma}_{i+1}[r]))$)
- 5: **end for**
- 6: **end for**
- 7: results $\leftarrow$ BatchBootstrap(comparisons) ▷ Amortized cost
- 8: Reconstruct merged states from results

6 Security Analysis

6.1 Privacy Model

Definition 6.1 (Replica Privacy). An fheCRDT scheme provides replica privacy if for any two states σ_0, σ_1 with $q(\sigma_0) = q(\sigma_1)$:

$$\{\text{Enc}(\text{pk}, \sigma_0)\} \approx_c \{\text{Enc}(\text{pk}, \sigma_1)\}$$

Theorem 6.2 (fheCRDT Privacy). *Under IND-CPA security of the underlying FHE scheme, fheCRDTs provide replica privacy.*

6.2 Merge Integrity

Theorem 6.3 (Merge Soundness). *For any PPT adversary $\mathcal{A}$ producing $\tilde{\sigma}^* \notin \{\tilde{\sigma}_1 \oplus_{\text{enc}} \dots \oplus_{\text{enc}} \tilde{\sigma}_k\}$:*

$$\Pr[\text{Verify}(\tilde{\sigma}^*) = 1] \leq \text{negl}(\lambda)$$

7 Evaluation

7.1 Microbenchmarks

Table 1: fheCRDT Operation Latency

CRDT Type	Merge (ms)	State Size	Distributed counter aggregation across organizations:
G-Counter (10 replicas)	2	2.5 KB	500
PN-Counter	4	5 KB	250
G-Set (1K elements)	15	128 KB	65
OR-Set (1K elements)	25	256 KB	40
LWW-Register	3	64 bytes	330

7.2 Geo-Distributed Deployment

We deploy across 5 AWS regions (US-East, US-West, EU-West, AP-South, AP-Southeast):

Table 2: Geo-Distributed Performance

Metric	Value
Average merge latency	180 ms
Convergence time	450 ms
Throughput	500 ops/sec
Availability during partitions	99.99%

7.3 Comparison

Table 3: Distributed Systems Comparison

System	Privacy	Consistency	Availability
Plain CRDT	X	Eventual	High
Encrypted DB	At-rest	Strong	Medium
MPC	Full	Strong	Low
fheCRDT	Full	Eventual	High

8 Applications

8.1 Encrypted Collaborative Documents

Real-time collaboration on encrypted text using sequence CRDTs:

- Character-level operations (insert, delete)
- Conflict-free concurrent edits
- Only document owners decrypt content

8.2 Privacy-Preserving Analytics

- Each organization maintains local encrypted counters
- Periodic merge reveals only aggregate statistics
- Individual contributions remain private

9 Related Work

CRDTs Shapiro et al. [4] formalized CRDTs; Kleppmann’s Automerge [1] provides practical implementations.

Encrypted Databases CryptDB [2] and Mylar [3] provide encryption but require server-side decryption.

MPC Secure multi-party computation provides privacy but requires synchronization, sacrificing availability.

10 Conclusion

fheCRDTs bridge privacy and distributed systems, enabling coordination-free replication of encrypted state. Our framework achieves 500 ops/sec while providing cryptographic privacy impossible with traditional CRDTs. This opens new possibilities for privacy-preserving collaborative applications.

References

- [1] Martin Kleppmann et al. Automerge: A JSON-like data structure for building collaborative applications. <https://automerge.org>, 2023.
- [2] Raluca Ada Popa et al. CryptDB: Protecting confidentiality with encrypted query processing. In *SOSP*, 2011.
- [3] Raluca Ada Popa et al. Building web applications on top of encrypted data using Mylar. In *NSDI*, 2014.
- [4] Marc Shapiro, Nuno Preguiça, Carlos Baquero, and Marek Zawirski. Conflict-free replicated data types. *SSS*, 2011.