

A


B

C


D

E


Top Copper (Scale 1)




Signal Layer 1 (Scale 1)



Layer 1 (Scale 1)



Bottom Layer (Scale 1)

**FABRICATION NOTES:**

Fabricate per IPC-6011 & IPC-6012 CLASS 2
Inspect per IPC-A-600 CLASS 2
Test per IPC-TM-650

- * PCB has 4 copper layers
- * Copper thicknesses are finished and include base foil plus Cu plating on plated layers.
- * PCB thickness: 63mil +/- 3mil
- * Min. trace width/clearance: 0.1mm/0.1mm
- * Min. hole drill/ring: 8mil/16mil
- * Soldermask gang relief is allowed for pads in same footprint, if footprint is NSMD.
- * Silkscreen, non-conductive epoxy ink, color: white
- * Solder mask color: black
- * Remove silkscreen as needed to prevent ink on any exposed copper
- * Surface finish: ENIG
- * Hole dimensions are finished size, +/-3mil
- * Linear board dimension tolerance: +/-10mil
- * Bow, twist, warp not to exceed 0.75% of greatest diagonal span
- * PCB shall be UL Recognized printed wiring board (ZPMV2), minimum flammability rating 94V-0
- * PCB shall be marked with fabricator company or trade name, UL mark, and date code using legend ink on secondary side
- * All PCBs shall be electrically tested for opens and shorts per gerber. Test marking shall be marked on secondary side.

Fabricator shall panelize the PCB using mouse bites and tab routing. V-scoring not allowed.

Controlled impedance differential pairs shall be within +/-10% for 100ohm targets, and +/-10% for 90ohm targets. See Sheet 3 for transmission line details and location of 90ohm differential pairs.

Title: BW1098OAK	
Number: DXXXX	Revision: =revision
Date: 21/04/2021	Sheet: 1 of 3
Drawn by: Brian Weinstein	PROPRIETARY AND CONFIDENTIAL

LUXonjs

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF LUXONIS HOLDING CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION IS PROHIBITED.


A

B

C

D

E

A	B	C	D	E																																																																													
	<p>Layer Stack Legend</p>  <table border="1"> <thead> <tr> <th>Layer</th> <th>Thickness</th> <th>Type</th> <th>Gerber</th> <th>Df</th> <th>Dk</th> </tr> </thead> <tbody> <tr> <td>Top Overlay</td> <td></td> <td>Legend</td> <td>GTO</td> <td></td> <td></td> </tr> <tr> <td>Top Mask</td> <td>0.71mil(0.018mm)</td> <td>Solder Mask</td> <td>GTS</td> <td>4,2</td> <td></td> </tr> <tr> <td>Top Copper</td> <td>1.40mil(0.036mm)</td> <td>Signal</td> <td>GTL</td> <td></td> <td></td> </tr> <tr> <td></td> <td>7.09mil(0.180mm)</td> <td>Dielectric</td> <td></td> <td>0,02</td> <td>4,2</td> </tr> <tr> <td>Signal Layer 1</td> <td>1.40mil(0.036mm)</td> <td>Signal</td> <td>G1</td> <td></td> <td></td> </tr> <tr> <td></td> <td>43.31mil(1.100mm)</td> <td>Dielectric</td> <td></td> <td>0,02</td> <td>4,2</td> </tr> <tr> <td>Layer 1</td> <td>1.40mil(0.036mm)</td> <td>Signal</td> <td>G2</td> <td></td> <td></td> </tr> <tr> <td></td> <td>7.09mil(0.180mm)</td> <td>Dielectric</td> <td></td> <td>0,02</td> <td>4,2</td> </tr> <tr> <td>Bottom Layer</td> <td>1.40mil(0.036mm)</td> <td>Signal</td> <td>GBL</td> <td></td> <td></td> </tr> <tr> <td>Bottom Solder</td> <td>0.71mil(0.018mm)</td> <td>Solder Mask</td> <td>GBS</td> <td>4,2</td> <td></td> </tr> <tr> <td>Bottom Overlay</td> <td></td> <td>Legend</td> <td>GBO</td> <td></td> <td></td> </tr> <tr> <td colspan="5">Total thickness: 64.50mil(1.638mm)</td></tr> </tbody> </table>	Layer	Thickness	Type	Gerber	Df	Dk	Top Overlay		Legend	GTO			Top Mask	0.71mil(0.018mm)	Solder Mask	GTS	4,2		Top Copper	1.40mil(0.036mm)	Signal	GTL				7.09mil(0.180mm)	Dielectric		0,02	4,2	Signal Layer 1	1.40mil(0.036mm)	Signal	G1				43.31mil(1.100mm)	Dielectric		0,02	4,2	Layer 1	1.40mil(0.036mm)	Signal	G2				7.09mil(0.180mm)	Dielectric		0,02	4,2	Bottom Layer	1.40mil(0.036mm)	Signal	GBL			Bottom Solder	0.71mil(0.018mm)	Solder Mask	GBS	4,2		Bottom Overlay		Legend	GBO			Total thickness: 64.50mil(1.638mm)							
Layer	Thickness	Type	Gerber	Df	Dk																																																																												
Top Overlay		Legend	GTO																																																																														
Top Mask	0.71mil(0.018mm)	Solder Mask	GTS	4,2																																																																													
Top Copper	1.40mil(0.036mm)	Signal	GTL																																																																														
	7.09mil(0.180mm)	Dielectric		0,02	4,2																																																																												
Signal Layer 1	1.40mil(0.036mm)	Signal	G1																																																																														
	43.31mil(1.100mm)	Dielectric		0,02	4,2																																																																												
Layer 1	1.40mil(0.036mm)	Signal	G2																																																																														
	7.09mil(0.180mm)	Dielectric		0,02	4,2																																																																												
Bottom Layer	1.40mil(0.036mm)	Signal	GBL																																																																														
Bottom Solder	0.71mil(0.018mm)	Solder Mask	GBS	4,2																																																																													
Bottom Overlay		Legend	GBO																																																																														
Total thickness: 64.50mil(1.638mm)																																																																																	
	<p>Drill Table</p> <table border="1"> <thead> <tr> <th>Symbol</th> <th>Count</th> <th>Hole Size</th> <th>Plated</th> <th>Hole Tolerance</th> </tr> </thead> <tbody> <tr> <td>✳</td> <td>133</td> <td>8.00mil(0.203mm)</td> <td>Plated</td> <td></td> </tr> <tr> <td>✳</td> <td>251</td> <td>10.00mil(0.254mm)</td> <td>Plated</td> <td></td> </tr> <tr> <td>+</td> <td>4</td> <td>23.62mil(0.600mm)</td> <td>Plated</td> <td></td> </tr> <tr> <td>☒</td> <td>2</td> <td>33.86mil(0.860mm)</td> <td>Plated</td> <td></td> </tr> <tr> <td>○</td> <td>3</td> <td>41.34mil(1.050mm)</td> <td>Plated</td> <td></td> </tr> <tr> <td>◊</td> <td>1</td> <td>70.87mil(1.800mm)</td> <td>Non-Plated</td> <td></td> </tr> <tr> <td>☆</td> <td>2</td> <td>82.68mil(2.100mm)</td> <td>Non-Plated</td> <td></td> </tr> <tr> <td>□</td> <td>2</td> <td>108.27mil(2.750mm)</td> <td>Plated</td> <td></td> </tr> <tr> <td>☒</td> <td>4</td> <td>118.11mil(3.000mm)</td> <td>Plated</td> <td></td> </tr> <tr> <td colspan="2">402 Total</td><td></td><td></td><td></td></tr> </tbody> </table>	Symbol	Count	Hole Size	Plated	Hole Tolerance	✳	133	8.00mil(0.203mm)	Plated		✳	251	10.00mil(0.254mm)	Plated		+	4	23.62mil(0.600mm)	Plated		☒	2	33.86mil(0.860mm)	Plated		○	3	41.34mil(1.050mm)	Plated		◊	1	70.87mil(1.800mm)	Non-Plated		☆	2	82.68mil(2.100mm)	Non-Plated		□	2	108.27mil(2.750mm)	Plated		☒	4	118.11mil(3.000mm)	Plated		402 Total																													
Symbol	Count	Hole Size	Plated	Hole Tolerance																																																																													
✳	133	8.00mil(0.203mm)	Plated																																																																														
✳	251	10.00mil(0.254mm)	Plated																																																																														
+	4	23.62mil(0.600mm)	Plated																																																																														
☒	2	33.86mil(0.860mm)	Plated																																																																														
○	3	41.34mil(1.050mm)	Plated																																																																														
◊	1	70.87mil(1.800mm)	Non-Plated																																																																														
☆	2	82.68mil(2.100mm)	Non-Plated																																																																														
□	2	108.27mil(2.750mm)	Plated																																																																														
☒	4	118.11mil(3.000mm)	Plated																																																																														
402 Total																																																																																	
		<p>Title: BW1098OAK</p> <p>Number: DXXXX Revision: =revision</p> <p>Date: 21/04/2021 Sheet: 2 of 3</p> <p>Drawn by: Brian Weinstein</p>	<p>LUXonjs</p> <p>PROPRIETARY AND CONFIDENTIAL</p> <p>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF LUXONIS HOLDING CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION IS PROHIBITED.</p>																																																																														


A

B


C

D

E



90 OHM (+/-10%) DIFF PAIRS



100 OHM (+/-10%) DIFF PAIRS

Transmission Line Structure Table

Impedance Id	Target Impedance	Calculated Impedance	Trace layer	Lower Trace Width	Upper Trace Width	Gap	Reference layers
1	100	101.48	Top Copper	5.0mil(0.127mm)	4.2mil(0.106mm)	4.0mil(0.102mm)	Signal Layer 1
2	90	91.35	Top Copper	7.0mil(0.178mm)	6.2mil(0.157mm)	4.0mil(0.102mm)	Signal Layer 1
3	100	101.48	Bottom Layer	5.0mil(0.127mm)	4.2mil(0.106mm)	4.0mil(0.102mm)	Layer 1
4	90	91.35	Bottom Layer	7.0mil(0.178mm)	6.2mil(0.157mm)	4.0mil(0.102mm)	Layer 1

Title: **BW1098OAK**

Number: DXXXX Revision: =revisi
on

Date: 21/04/2021 Sheet: 3 of 3

Drawn by: Brian Weinstein

LUXonjs

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF LUXONIS HOLDING CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION IS PROHIBITED.

A

B

C

D

E