









Today and Tomorrow HPC


Today's Top HPC Systems Used to do Simulations

- Climate
- Combustion
- Nuclear Reactors
- Catalysis
- Electric Grid
- Fusion
- Stockpile
- Supernovae
- Materials
- Digital Twins
- Accelerators
- ...



Today's Top HPC Systems Used to do Simulations

- Climate
- Combustion
- Nuclear Reactors
- Catalysis
- Electric Grid
- Fusion
- Stockpile
- Supernovae
- Materials
- Digital Twins
- Accelerators
- ...



Usually 3-D PDE's

Sparse matrix computations, not dense

HPCG Top 10, November 2022

Rank	Site	Computer	Cores	HPL Rmax (Pflop/s)	TOP500 Rank	HPCG (Pflop/s)	Fraction of Peak
1	RIKEN Center for Computational Science Japan	Fugaku, Fujitsu A64FX 48C 2.2GHz, Tofu D, Fujitsu	7,630,848	442	2	16.0	3.0%
2	DOE/SC/ORNL USA	Frontier, HPE Cray EX235a, AMD 3rd EPYC 64C, 2 GHz, AMD Instinct MI250X, Slingshot 10	8,730,112	1,102	1	14.1	0.8%
3	EuroHPC/CSC	LUMI, HPE Cray EX235a, AMD Zen-3 (Milan) 64C 2GHz, Mellanox HDR100 Infiniband	2,174,070	204	3	3.41	0.2%

Think of a race car that has the potential of 200 MPH but only goes 2 MPH! 

Rank	Site	Computer	Cores	HPL Rmax (Pflop/s)	TOP500 Rank	HPCG (Pflop/s)	Fraction of Peak
4	DOE/NNSA/LLNL USA	Frontier, HPE Cray EX235a, AMD 3rd EPYC 64C, 2 GHz, AMD Instinct MI250X, Slingshot 10	8,730,112	1,102	1	14.1	0.8%
5	EuroHPC/CINECA Italy	Leonardo, BullSequana XH2000, Xeon Platinum 8358 32C 2.6GHz, NVIDIA A100 SXM4 40 GB, Quad-rail NVIDIA HDR100 Infiniband	1,463,616	175	4	2.57	1.0%
6	DOE/SC/LBNL USA	Perlmutter, HPE Cray EX235n, AMD EPYC 7763 64C 2.45GHz, NVIDIA A100 SXM4 40 GB, Slingshot-10	761,856	70.9	8	1.91	2.0%
7	DOE/NNSA/LLNL USA	Sierra, S922LC, IBM POWER9 20C 3.1 GHz, Mellanox EDR, NVIDIA Volta V100, IBM	1,572,480	94.6	6	1.80	1.4%
8	NVIDIA USA	Selene, DGX SuperPOD, AMD EPYC 7742 64C 2.25 GHz, Mellanox HDR, NVIDIA Ampere A100	555,520	63.5	9	1.62	2.0%
9	Forschungszentrum Juelich (FZJ) Germany	JUWELS Booster Module, Bull Sequana XH2000 , AMD EPYC 7402 24C 2.8GHz, Mellanox HDR InfiniBand, NVIDIA Ampere A100, Atos	449,280	44.1	12	1.28	1.8%
10	Saudi Aramco Saudi Arabia	Dammam-7, Cray CS-Storm, Xeon Gold 6248 20C 2.5GHz, InfiniBand HDR 100, NVIDIA Volta V100, HPE	672,520	22.4	20	0.88	1.6%

AI/ML Takeoff


Recently we have seen AI & ML take off

- AI and ML have been around for a long time as research efforts.
- Why Now?
 - Flood of available data (especially with the Internet)
 - Increasing computational power
 - Growing progress in available algorithms and theory developed by researchers.
 - Increasing support from industries.


Machine Learning in Computational Science

Many fields are beginning to adopt machine learning to augment modeling and simulation methods

- Climate
 - Biology
 - Drug Design
 - Epidemiology
 - Materials
 - Cosmology
 - High-Energy Physics



#84517548




Deep Learning Needs Small Matrix Operations

Matrix Multiply is the time-consuming part.

Convolution Layers and Fully Connected L

There are many GEMM's of small matrices
point



Emergence of AI-Specific Hardware Ecosystem

MYTHIC

DEEPhi

GRAPHCORE

thinci™

深 鑑 科 技

aws

RAIN
NEUROMORPHICS

WAVE®
COMPUTING

Google

intel®

Baidu 百度

flexlogix
Technologies, Inc.

cerebras

SambaNova
SYSTEMS


XILINX

Fully Connected
Classification


Numerical representations

- Today many options for arithmetic precision (IEEE Standard)

Type	Size	Range	$u = 2^{-t}$
half	16 bits	$10^{\pm 5}$	$2^{-11} \approx 4.9 \times 10^{-4}$
single	32 bits	$10^{\pm 38}$	$2^{-24} \approx 6.0 \times 10^{-8}$
double	64 bits	$10^{\pm 308}$	$2^{-53} \approx 1.1 \times 10^{-16}$
quadruple	128 bits	$10^{\pm 4932}$	$2^{-113} \approx 9.6 \times 10^{-35}$




IEEE FP16



Google Bfloat16


Future HPC Systems Will be Customized...

- You will be able to dial up what you need in your computer for your application mix ...




Future HPC Systems Will be Customized...

- You will be able to dial up what you need in your computer for your application mix ...



Future HPC Systems Will be Customized...

- You will be able to dial up what you need in your computer for your application mix ...



High performance Programming

What do you mean by performance

- What is a **xflop/s**?

xflop/s is a rate of execution, some number of floating-point operations per second. Whenever this term is used, it will refer to **64-bit floating-point operations** and the operations will be either addition or multiplication.

- What is the **theoretical peak performance**?

The theoretical peak is a paper computation to determine the theoretical peak rate of execution of floating-point operations for the machine. The theoretical peak performance is determined by *counting the number of floating-point additions and multiplications (in full precision) that can be completed during a period of time*.

- For example, an Intel Skylake processor at **2.1 GHz** can complete **32 floating point operations per cycle per core** or a theoretical peak performance of **67.2 GFlop/s** per core or **1.61 Tflop/s** for the socket of 24 cores.

Example: DGEMM Performance

Speedups from performance engineering a program that multiplies two 4K-by-4K floating point matrices (**D**ouble-precision **G**eneral **M**atrix-**M**atrix) running on a dual-socket Intel Xeon E5-2666 v3 system

Version	Implementation	Absolute speedup	Relative speedup
1	Python	1	1
2	Java	11	10.8
3	C	47	4.4
4	Parallel loop	366	7.8
5	Divide and conquer	6'727	18.4
6	Vectorization	23'224	3.5
7	AVX intrinsics	62'806	2.7

Software does not have “good enough” performance by default.

[There's plenty of room at the Top: What will drive computer performance after Moore's law?

<https://dx.doi.org/10.1126/science.aam9744>

Single-Node HPC

- How to improve performance of an application running on a single node?
- We need to:
 1. Measure actual application performance
 2. Understand the hardware architecture executing the application
 3. Identify bottleneck: (memory bound/compute bound/resource underutilization)
 4. (possibly) solve bottlenecks
 5. Goto 1

Single-Node HPC

- How to write high-performance applications running on a single node?
 1. Optimize Algorithms & Data Structures
 - Use efficient algorithms
 - Choose appropriate data structures (e.g., hash tables for fast lookups, trees for sorted data).
 2. Memory Optimization
 - Optimize CPU cache usage (**data locality, avoid cache misses**).
 - Maximize data reuse
 3. Exploit hardware parallelism
 - Exploit hardware accelerated instructions (e.g x86 AVX extensions)
 - Utilize multi-core CPUs with threading

Optimize Algorithms

An example with sorting:


Version	1000 elements	10000 elements	100000 elements
quicksort	67 us	458 us	3993 us
counting sort	36 us	57 us	837 us

Why is faster:

complexity is linear with the max value. Be aware, it works only with integers with limited range

Optimize Memory

- Data movement has a big impact
- **Operational Intensity:** Performance comes from balancing floating point execution (**Flops/sec**) with memory->CPU transfer rate (**Words/sec**)
 - “Best” balance would be 1 flop per word-transferred
- Today’s systems are close to 100 flops/sec per word-transferred
 - Imbalanced: Over provisioned for Flops



Graph from Mark Gates

Plot for 64-bit floating point data movement & operations
(Bandwidth from CPU or GPU memory to registers)

Optimize Memory

An example with DGEMM:

Version	Implementation	Absolute speedup	Relative speedup
4	Parallel loop	366	7.8
5	Divide and conquer	6'727	18.4

Why is faster:

Instead of accessing entire rows or columns, subdivide matrices into blocks.

Requires more memory accesses but improves locality of accesses

Exploit hardware parallelism

- **Types of Parallelism:**
 - Data parallelism: Same task on different data.
 - Thread parallelism: different threads cooperate to execute an algorithm.
- **Programming Models:**
 - Data parallelism is usually exploited with specialized instructions
 - Thread parallelism is usually exploited with OpenMP for (single) HPC node

Data Parallelism

An example with DGEMM:

Version	Implementation	Absolute speedup	Relative speedup
5	Divide and conquer	6'727	18.4
6	Vectorization	23'224	3.5

Why is faster:

Exploits SIMD (Single Instruction multiple Data) CPU extension. The same operation is applied to multiple data at the same time

Thread Parallelism

An example with DGEMM:

Version	Implementation	Absolute speedup	Relative speedup
3	C	47	4.4
4	Parallel loop	366	7.8

Why is faster:

Execute the multiplication on multiple cores.

Warning: you need to be aware of data races and false sharing