Overview Package Class Use Tree Deprecated Index Help

Prev ClassNext ClassFramesNo FramesAll Classes

Summary: Nested | Field | Constr | Method Detail: Field | Constr | Method

gui.sub

# Class DisplayAppointmentConfirmationUI

### All Implemented Interfaces:

java.awt.event.ActionListener, java.awt.image.lmageObserver, java.awt.MenuContainer, java.io.Serializable, java.util.EventListener, javax.accessibility.Accessible, javax.swing.RootPaneContainer, javax.swing.WindowConstants

```
public class DisplayAppointmentConfirmationUI
extends javax.swing.JDialog
implements java.awt.event.ActionListener
```

DisplayAppointmentConfirmationUI shows information about a patient's appointment when a patient in the table is clicked.

#### See Also:

Serialized Form

## **Nested Class Summary**

## Nested classes/interfaces inherited from class java.awt.Dialog

java.awt.Dialog.ModalExclusionType, java.awt.Dialog.ModalityType

# Nested classes/interfaces inherited from class java.awt.Window

java.awt.Window.Type

# Nested classes/interfaces inherited from class java.awt.Component

java.awt.Component.BaselineResizeBehavior

### **Field Summary**

### Fields inherited from class java.awt.Dialog

DEFAULT MODALITY TYPE

## Fields inherited from class java.awt.Component

BOTTOM ALIGNMENT, CENTER ALIGNMENT, LEFT ALIGNMENT, RIGHT ALIGNMENT, TOP ALIGNMENT

### Fields inherited from interface javax.swing.WindowConstants

DISPOSE ON CLOSE, DO NOTHING ON CLOSE, EXIT ON CLOSE, HIDE ON CLOSE

## Fields inherited from interface java.awt.image.lmageObserver

ABORT, ALLBITS, ERROR, FRAMEBITS, HEIGHT, PROPERTIES, SOMEBITS, WIDTH

## **Method Summary**

#### Methods

Modifier and Type	Method and Description
void	<pre>actionPerformed(java.awt.event.ActionEvent e)</pre>
	Closes the window once the user hits the "OK" button.
static void	ShowDialog(java.awt.Component owner, data.Appointment appt)
	Makes the pop up window visible when a patient from the table is selected.

## Methods inherited from class javax.swing.JDialog

getAccessibleContext, getContentPane, getDefaultCloseOperation, getGlassPane,
getGraphics, getJMenuBar, getLayeredPane, getRootPane, getTransferHandler,
isDefaultLookAndFeelDecorated, remove, repaint, setContentPane,
setDefaultCloseOperation, setDefaultLookAndFeelDecorated, setGlassPane, setJMenuBar,
setLayeredPane, setLayout, setTransferHandler, update

## Methods inherited from class java.awt.Dialog

addNotify, getModalityType, getTitle, hide, isModal, isResizable, isUndecorated, setBackground, setModal, setModalityType, setOpacity, setResizable, setShape, setTitle, setUndecorated, setVisible, show, toBack

## Methods inherited from class java.awt.Window

addPropertyChangeListener, addPropertyChangeListener, addWindowFocusListener, addWindowListener, addWindowStateListener, applyResourceBundle, applyResourceBundle, createBufferStrategy, createBufferStrategy, dispose, getBackground, getBufferStrategy,

getFocusableWindowState, getFocusCycleRootAncestor, getFocusOwner, getFocusTraversalKeys, getIconImages, getInputContext, getListeners, getLocale, getModalExclusionType, getMostRecentFocusOwner, getOpacity, getOwnedWindows, getOwner, getOwnerlessWindows, getShape, getToolkit, getType, getWarningString, getWindowFocusListeners, getWindowListeners, getWindows, getWindowStateListeners, isActive, isAlwaysOnTop, isAlwaysOnTopSupported, isAutoRequestFocus, isFocusableWindow, isFocusCycleRoot, isFocused, isLocationByPlatform, isOpaque, isShowing, isValidateRoot, pack, paint, postEvent, removeNotify, removeWindowFocusListener, removeWindowListener, removeWindowStateListener, reshape, setAlwaysOnTop, setAutoRequestFocus, setBounds, setBounds, setCursor, setFocusableWindowState, setFocusCycleRoot, setIconImage, setIconImages, setLocation, setLocation, setLocationByPlatform, setLocationRelativeTo, setMinimumSize, setModalExclusionType, setSize, setSize, setType, toFront

### Methods inherited from class java.awt.Container

add, add, add, add, add, addContainerListener, applyComponentOrientation, areFocusTraversalKeysSet, countComponents, deliverEvent, doLayout, findComponentAt, findComponentAt, getAlignmentY, getComponent, getComponentAt, getComponentAt, getComponentSorder, getComponentAt, getComponentCount, getComponents, getComponentZOrder, getContainerListeners, getFocusTraversalPolicy, getInsets, getLayout, getMaximumSize, getMinimumSize, getMousePosition, getPreferredSize, insets, invalidate, isAncestorOf, isFocusCycleRoot, isFocusTraversalPolicyProvider, isFocusTraversalPolicySet, layout, list, locate, minimumSize, paintComponents, preferredSize, print, printComponents, remove, removeAll, removeContainerListener, setComponentZOrder, setFocusTraversalKeys, setFocusTraversalPolicy, setFocusTraversalPolicyProvider, setFont, transferFocusDownCycle, validate

### Methods inherited from class java.awt.Component

action, add, addComponentListener, addFocusListener, addHierarchyBoundsListener, addHierarchyListener, addInputMethodListener, addKeyListener, addMouseListener, addMouseMotionListener, addMouseWheelListener, bounds, checkImage, checkImage, contains, contains, createImage, createImage, createVolatileImage, createVolatileImage, disable, dispatchEvent, enable, enable, enableInputMethods, firePropertyChange, firePropertyChange, firePropertyChange, firePropertyChange, firePropertyChange, firePropertyChange, getBaseline, getBaselineResizeBehavior, getBounds, getBounds, getColorModel, getComponentListeners, getComponentOrientation, getCursor, getDropTarget, getFocusListeners, getFocusTraversalKeysEnabled, getFont, getFontMetrics, getForeground, getGraphicsConfiguration, getHeight, getHierarchyBoundsListeners, getHierarchyListeners, getIgnoreRepaint, getInputMethodListeners, getInputMethodRequests, getKeyListeners, getLocation, getLocation, getLocationOnScreen, getMouseListeners, getMouseMotionListeners, getMousePosition, getMouseWheelListeners, getName, getParent, getPeer, getPropertyChangeListeners, getPropertyChangeListeners, getSize, getSize, getTreeLock, getWidth, getX, getY, gotFocus, handleEvent, hasFocus, imageUpdate, inside, isBackgroundSet, isCursorSet, isDisplayable, isDoubleBuffered, isEnabled, isFocusable, isFocusOwner, isFocusTraversable, isFontSet, isForegroundSet, isLightweight, isMaximumSizeSet, isMinimumSizeSet, isPreferredSizeSet, isValid, isVisible, keyDown, keyUp, list, list, location, lostFocus, mouseDown, mouseDrag, mouseEnter, mouseExit, mouseMove, mouseUp, move, nextFocus, paintAll, prepareImage, prepareImage, printAll, remove, removeComponentListener, removeFocusListener, removeHierarchyBoundsListener, removeHierarchyListener, removeInputMethodListener, removeKeyListener, removeMouseListener, removeMouseMotionListener, removeMouseWheelListener, removePropertyChangeListener, removePropertyChangeListener, repaint, repaint, requestFocus, requestFocusInWindow, resize, resize, revalidate, setComponentOrientation, setDropTarget, setEnabled, setFocusable, setFocusTraversalKeysEnabled, setForeground, setIgnoreRepaint, setLocale, setMaximumSize, setName, setPreferredSize, show, size, toString, transferFocus,

transferFocusBackward, transferFocusUpCycle

## Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, wait, wait, wait

### **Method Detail**

### **ShowDialog**

Makes the pop up window visible when a patient from the table is selected.

#### Parameters:

owner - - the component that owns this pane (the AppointmentConfirmationListener)

appt - - the appointment information

### actionPerformed

public void actionPerformed(java.awt.event.ActionEvent e)

Closes the window once the user hits the "OK" button.

### Specified by:

actionPerformed in interface java.awt.event.ActionListener

Overview Package Class Use Tree Deprecated Index Help

Prev Class Next Class Frames No Frames All Classes

Summary: Nested | Field | Constr | Method Detail: Field | Constr | Method