

# reachability analysis for continuous one counter automata

---

Lars Van Roy

*dept. of Mathematics and Computer Science*

*University of Antwerp*

`lars.vanroy@student.uantwerpen.be`

August 24, 2021

## **Problem overview**

---

- Reachability analysis

- Reachability analysis
  - Are all conditional statements satisfiable

# Problem overview I

- Reachability analysis
  - Are all conditional statements satisfiable
- Explore set of values that a counter can have

# Problem overview I

- Reachability analysis
  - Are all conditional statements satisfiable
- Explore set of values that a counter can have
- Analysis of one-counter continuous automata

# Problem overview I

- Reachability analysis
  - Are all conditional statements satisfiable
- Explore set of values that a counter can have
- Analysis of one-counter continuous automata
- Only applicable to simple functions

- Only applicable to simple functions



- Only applicable to simple functions
  - Supported comparisons:  $\leq$ ,  $<$ ,  $=$ ,  $\neq$ ,  $>$ ,  $\geq$

- Only applicable to simple functions
  - Supported comparisons:  $\leq, <, ==, \neq, >, \geq$
  - Supported operations:  $+, -, =$

- Only applicable to simple functions
  - Supported comparisons:  $\leq$ ,  $<$ ,  $==$ ,  $\neq$ ,  $>$ ,  $\geq$
  - Supported operations:  $+$ ,  $-$ ,  $=$
  - Restrictions only apply for counters

- Only applicable to simple functions
  - Supported comparisons:  $\leq$ ,  $<$ ,  $=$ ,  $\neq$ ,  $>$ ,  $\geq$
  - Supported operations:  $+$ ,  $-$ ,  $=$
  - Restrictions only apply for counters
  - Counter must be of type integer


- Only applicable to simple functions
  - Supported comparisons:  $\leq$ ,  $<$ ,  $==$ ,  $\neq$ ,  $>$ ,  $\geq$
  - Supported operations:  $+$ ,  $-$ ,  $=$
  - Restrictions only apply for counters
  - Counter must be of type integer
  - Conditions and operations on counters can be performed with
    - Parameters
    - Constants

- Only applicable to simple functions
  - Supported comparisons:  $\leq$ ,  $<$ ,  $=$ ,  $\neq$ ,  $>$ ,  $\geq$
  - Supported operations:  $+$ ,  $-$ ,  $=$
  - Restrictions only apply for counters
  - Counter must be of type integer
  - Conditions and operations on counters can be performed with
    - Parameters
    - Constants
  - There can only be one consecutive counter

# Approach

---

# Approach






- Interval representing possible counter values

# Reachability intervals

- Interval representing possible counter values
- Tracked for each of the nodes


# Reachability intervals

- Interval representing possible counter values
- Tracked for each of the nodes




# Reachability intervals

- Interval representing possible counter values
- Tracked for each of the nodes




# Reachability intervals

- Interval representing possible counter values
- Tracked for each of the nodes




# Reachability intervals

- Interval representing possible counter values
- Tracked for each of the nodes



# Reachability intervals

- Interval representing possible counter values
- Tracked for each of the nodes



## Successor function

---



- Approach for non-parametric automata

- Approach for non-parametric automata
- Evaluate the reachability intervals iteratively

- Approach for non-parametric automata
- Evaluate the reachability intervals iteratively
- Acceleration to prevent infinite loops

## Successor function II

$$\begin{aligned} succ_i(p, q) := & \bigcup \{ (R_i(p, q) + (o, z]) \cap \tau(q) \mid (p, z, q) \in T, z > o \} \\ & \cup \bigcup \{ (R_i(p, q) + [z, o)) \cap \tau(q) \mid (p, z, q) \in T, z < o \} \\ & \cup \bigcup \{ (R_i(p, q) + [o, o]) \cap \tau(q) \mid (p, o, q) \in T, z = o \} \end{aligned}$$

1. Generate the next interval for the edge going from p to q
2. Apply the edge operation to the current interval
3. Ensure that the interval is within the node bounds

## Successor function II

$$\begin{aligned} \text{succ}_i(p, q) &:= \bigcup \{ (R_i(p, q) + (o, z]) \cap \tau(q) \mid (p, z, q) \in T, z > o \} \\ &\quad \cup \bigcup \{ (R_i(p, q) + [z, o)) \cap \tau(q) \mid (p, z, q) \in T, z < o \} \\ &\quad \cup \bigcup \{ (R_i(p, q) + [o, o]) \cap \tau(q) \mid (p, o, q) \in T, z = o \} \end{aligned}$$

1. Generate the next interval for the edge going from p to q
2. Add the operation interval to the current reachability interval
  - operation interval =  $(o, 1] * z$
3. Ensure that the interval is within the node bounds

## Successor function II

$$\begin{aligned} \text{succ}_i(p, q) := & \bigcup \{(R_i(p, q) + (o, z]) \cap \tau(q) \mid (p, z, q) \in T, z > o\} \\ & \cup \bigcup \{(R_i(p, q) + [z, o)) \cap \tau(q) \mid (p, z, q) \in T, z < o\} \\ & \cup \bigcup \{(R_i(p, q) + [o, o]) \cap \tau(q) \mid (p, o, q) \in T, z = o\} \end{aligned}$$

1. Generate the next interval for the edge going from p to q
2. Add the operation interval to the current reachability interval
  - operation interval =  $(o, 1] * z$
3. Ensure that the interval is within the node bounds

## Successor function II

$$\begin{aligned} \text{succ}_i(p, q) := & \bigcup \{ (R_i(p, q) + (0, z]) \cap \tau(q) \mid (p, z, q) \in T, z > 0 \} \\ & \cup \bigcup \{ (R_i(p, q) + [z, 0)) \cap \tau(q) \mid (p, z, q) \in T, z < 0 \} \\ & \cup \bigcup \{ (R_i(p, q) + [0, 0]) \cap \tau(q) \mid (p, 0, q) \in T, z = 0 \} \end{aligned}$$

1. Generate the next interval for the edge going from p to q
2. Add the operation interval to the current reachability interval
  - operation interval =  $(0, 1] * z$
3. Ensure that the interval is within the node bounds

- Iteratively update intervals until no more changes occur




## Successor function III

- Iteratively update intervals until no more changes occur
- Only apply the *succ* function to non-empty intervals


## Successor function IV

```
1 int func() {  
2     for (int i; i < 11;) {  
3         if (i == 12) {  
4             return -1;  
5         }  
6         i += 2;  
7     }  
8     return 0;  
9 }
```




# Successor function V

p	q	$R_0$
$l_1$	$l_2$	$[0, 0]$
$l_2$	$l_3$	$\emptyset$
$l_3$	$l_4$	$\emptyset$
$l_3$	$l_6$	$\emptyset$
$l_6$	$l_7$	$\emptyset$
$l_7$	$l_2$	$\emptyset$
$l_7$	$l_8$	$\emptyset$




# Successor function V

p	q	$R_0$	$R_1$
$l_1$	$l_2$	$[0, 0]$	$[0, 0]$
$l_2$	$l_3$	$\emptyset$	$[0, 0]$
$l_3$	$l_4$	$\emptyset$	$\emptyset$
$l_3$	$l_6$	$\emptyset$	$\emptyset$
$l_6$	$l_7$	$\emptyset$	$\emptyset$
$l_7$	$l_2$	$\emptyset$	$\emptyset$
$l_7$	$l_8$	$\emptyset$	$\emptyset$




# Successor function V

p	q	$R_0$	$R_1$	$R_2$
$l_1$	$l_2$	$[0, 0]$	$[0, 0]$	$[0, 0]$
$l_2$	$l_3$	$\emptyset$	$[0, 0]$	$[0, 0]$
$l_3$	$l_4$	$\emptyset$	$\emptyset$	$\emptyset$
$l_3$	$l_6$	$\emptyset$	$\emptyset$	$[0, 0]$
$l_6$	$l_7$	$\emptyset$	$\emptyset$	$\emptyset$
$l_7$	$l_2$	$\emptyset$	$\emptyset$	$\emptyset$
$l_7$	$l_8$	$\emptyset$	$\emptyset$	$\emptyset$




# Successor function V

p	q	$R_0$	$R_1$	$R_2$	$R_3$
$l_1$	$l_2$	$[0, 0]$	$[0, 0]$	$[0, 0]$	$[0, 0]$
$l_2$	$l_3$	$\emptyset$	$[0, 0]$	$[0, 0]$	$[0, 0]$
$l_3$	$l_4$	$\emptyset$	$\emptyset$	$\emptyset$	$\emptyset$
$l_3$	$l_6$	$\emptyset$	$\emptyset$	$[0, 0]$	$[0, 0]$
$l_6$	$l_7$	$\emptyset$	$\emptyset$	$\emptyset$	$(0, 2]$
$l_7$	$l_2$	$\emptyset$	$\emptyset$	$\emptyset$	$\emptyset$
$l_7$	$l_8$	$\emptyset$	$\emptyset$	$\emptyset$	$\emptyset$



# Successor function V

p	q	$R_0$	$R_1$	$R_2$	$R_3$	$R_4$
$l_1$	$l_2$	$[0, 0]$	$[0, 0]$	$[0, 0]$	$[0, 0]$	$[0, 0]$
$l_2$	$l_3$	$\emptyset$	$[0, 0]$	$[0, 0]$	$[0, 0]$	$[0, 0]$
$l_3$	$l_4$	$\emptyset$	$\emptyset$	$\emptyset$	$\emptyset$	$\emptyset$
$l_3$	$l_6$	$\emptyset$	$\emptyset$	$[0, 0]$	$[0, 0]$	$[0, 0]$
$l_6$	$l_7$	$\emptyset$	$\emptyset$	$\emptyset$	$(0, 2]$	$(0, 2]$
$l_7$	$l_2$	$\emptyset$	$\emptyset$	$\emptyset$	$\emptyset$	$(0, 2]$
$l_7$	$l_8$	$\emptyset$	$\emptyset$	$\emptyset$	$\emptyset$	$\emptyset$



# Acceleration

---



- Accelerate by moving bounds of an interval closer to fix point


- Accelerate by moving bounds of an interval closer to fix point
- The full loop must be discovered

- Accelerate by moving bounds of an interval closer to fix point
- The full loop must be discovered
- Select interval closest to its bound

- Accelerate by moving bounds of an interval closer to fix point
- The full loop must be discovered
- Select interval closest to its bound
- Set interval bound equal to the node/automaton bound


## Acceleration II

p	q	$R_4$
$l_1$	$l_2$	$[0, 0]$
$l_2$	$l_3$	$[0, 0]$
$l_3$	$l_4$	$\emptyset$
$l_3$	$l_6$	$[0, 0]$
$l_6$	$l_7$	$(0, 2]$
$l_7$	$l_2$	$(0, 2]$
$l_7$	$l_8$	$\emptyset$




## Acceleration II

p	q	$R_4$	$R_5$
$l_1$	$l_2$	$[0, 0]$	$[0, 0]$
$l_2$	$l_3$	$[0, 0]$	$[0, 0]$
$l_3$	$l_4$	$\emptyset$	$\emptyset$
$l_3$	$l_6$	$[0, 0]$	$[0, 0]$
$l_6$	$l_7$	$(0, 2]$	$(0, 2]$
$l_7$	$l_2$	$(0, 2]$	$(0, 10]$
$l_7$	$l_8$	$\emptyset$	$\emptyset$




# Acceleration II

p	q	$R_4$	$R_5$	$R_6$
$l_1$	$l_2$	$[0, 0]$	$[0, 0]$	$[0, 0]$
$l_2$	$l_3$	$[0, 0]$	$[0, 0]$	$(0, 10]$
$l_3$	$l_4$	$\emptyset$	$\emptyset$	$\emptyset$
$l_3$	$l_6$	$[0, 0]$	$[0, 0]$	$[0, 0]$
$l_6$	$l_7$	$(0, 2]$	$(0, 2]$	$(0, 2]$
$l_7$	$l_2$	$(0, 2]$	$(0, 10]$	$(0, 10]$
$l_7$	$l_8$	$\emptyset$	$\emptyset$	$\emptyset$



## Acceleration II


p	q	$R_4$	$R_5$	$R_6$	$R_7$
$l_1$	$l_2$	$[0, 0]$	$[0, 0]$	$[0, 0]$	$[0, 0]$
$l_2$	$l_3$	$[0, 0]$	$[0, 0]$	$(0, 10]$	$(0, 10]$
$l_3$	$l_4$	$\emptyset$	$\emptyset$	$\emptyset$	$\emptyset$
$l_3$	$l_6$	$[0, 0]$	$[0, 0]$	$[0, 0]$	$(0, 10]$
$l_6$	$l_7$	$(0, 2]$	$(0, 2]$	$(0, 2]$	$(0, 2]$
$l_7$	$l_2$	$(0, 2]$	$(0, 10]$	$(0, 10]$	$(0, 10]$
$l_7$	$l_8$	$\emptyset$	$\emptyset$	$\emptyset$	$\emptyset$






# Acceleration II

p	q	$R_4$	$R_5$	$R_6$	$R_7$	$R_8$
$l_1$	$l_2$	$[0, 0]$	$[0, 0]$	$[0, 0]$	$[0, 0]$	$[0, 0]$
$l_2$	$l_3$	$[0, 0]$	$[0, 0]$	$(0, 10]$	$(0, 10]$	$(0, 10]$
$l_3$	$l_4$	$\emptyset$	$\emptyset$	$\emptyset$	$\emptyset$	$\emptyset$
$l_3$	$l_6$	$[0, 0]$	$[0, 0]$	$[0, 0]$	$(0, 10]$	$(0, 10]$
$l_6$	$l_7$	$(0, 2]$	$(0, 2]$	$(0, 2]$	$(0, 2]$	$(0, 12]$
$l_7$	$l_2$	$(0, 2]$	$(0, 10]$	$(0, 10]$	$(0, 10]$	$(0, 10]$
$l_7$	$l_8$	$\emptyset$	$\emptyset$	$\emptyset$	$\emptyset$	$\emptyset$



# Acceleration II

p	q	$R_5$	$R_6$	$R_7$	$R_8$	$R_9$
$l_1$	$l_2$	$[0, 0]$	$[0, 0]$	$[0, 0]$	$[0, 0]$	$[0, 0]$
$l_2$	$l_3$	$[0, 0]$	$[0, 10]$	$(0, 10]$	$(0, 10]$	$(0, 10]$
$l_3$	$l_4$	$\emptyset$	$\emptyset$	$\emptyset$	$\emptyset$	$\emptyset$
$l_3$	$l_6$	$[0, 0]$	$[0, 0]$	$[0, 10]$	$(0, 10]$	$(0, 10]$
$l_6$	$l_7$	$(0, 2]$	$(0, 2]$	$(0, 2]$	$(0, 12]$	$(0, 12]$
$l_7$	$l_2$	$(0, 10]$	$(0, 10]$	$(0, 10]$	$(0, 10]$	$(0, 10]$
$l_7$	$l_8$	$\emptyset$	$\emptyset$	$\emptyset$	$\emptyset$	$[11, 12]$



# Shortcomings

- Does not work with variables

# Shortcomings

- Does not work with variables
- Can result in false positives

## **SAT problem**

---

- Convert to a satisfiability problem

- Convert to a satisfiability problem
- Can handle variables

- Convert to a satisfiability problem
- Can handle variables
- Try to guess rather than compute



- conditions

- conditions
  - The initial interval needs to be  $[0, 0]$


- conditions
  - The initial interval needs to be  $[0, 0]$
  - The successor function needs to be applicable to all intervals

- conditions
  - The initial interval needs to be  $[0, 0]$
  - The successor function needs to be applicable to all intervals
  - Loops will be self satisfying

- conditions
  - The initial interval needs to be  $[0, 0]$
  - The successor function needs to be applicable to all intervals
  - Loops will be self satisfying
    - One predecessor not part of loop


# SAT problem III

p	q	configuration
$l_1$	$l_2$	$[o, o]$
$l_2$	$l_3$	$\emptyset$
$l_3$	$l_4$	$\emptyset$
$l_3$	$l_6$	$\emptyset$
$l_6$	$l_7$	$\emptyset$
$l_7$	$l_2$	$\emptyset$
$l_7$	$l_8$	$\emptyset$




# SAT problem III

p	q	configuration
$l_1$	$l_2$	$[0, 0]$
$l_2$	$l_3$	$[0, 0]$
$l_3$	$l_4$	$\emptyset$
$l_3$	$l_6$	$[0, 0]$
$l_6$	$l_7$	$(0, 2]$
$l_7$	$l_2$	$(0, 2]$
$l_7$	$l_8$	$\emptyset$



# SAT problem III


p	q	configuration
$l_1$	$l_2$	$[0, 0]$
$l_2$	$l_3$	$(1, 10)$
$l_3$	$l_4$	$\emptyset$
$l_3$	$l_6$	$(1, 10)$
$l_6$	$l_7$	$(1, 12)$
$l_7$	$l_2$	$(1, 12)$
$l_7$	$l_8$	$[11, 12]$





# SAT problem III

p	q	configuration
$l_1$	$l_2$	$[0, 0]$
$l_2$	$l_3$	$(0, 10]$
$l_3$	$l_4$	$\emptyset$
$l_3$	$l_6$	$(0, 10]$
$l_6$	$l_7$	$(0, 12]$
$l_7$	$l_2$	$(0, 12]$
$l_7$	$l_8$	$[11, 12]$



- Requires a large amount of variables

## SAT problem IV

- Requires a large amount of variables
  - Four variables per interval

- Requires a large amount of variables
  - Four variables per interval
  - Two variables per node condition

- Requires a large amount of variables
  - Four variables per interval
  - Two variables per node condition
  - Three variables per edge

- Requires a large amount of variables
  - Four variables per interval
  - Two variables per node condition
  - Three variables per edge
- Slower than the first approach

- Requires a large amount of variables
  - Four variables per interval
  - Two variables per node condition
  - Three variables per edge
- Slower than the first approach
- Can give false positives

- Requires a large amount of variables
  - Four variables per interval
  - Two variables per node condition
  - Three variables per edge
- Slower than the first approach
- Can give false positives
- Only use SAT in case parameters are present



## Use case: Xrdp

---

## Use case: Xrdp

- Graphical login to remote machines using RDP

## Use case: Xrdp

- Graphical login to remote machines using RDP
- Medium-sized C project
  - 94 458 lines of code
  - 1 328 functions

## Use case: Xrdp

- Graphical login to remote machines using RDP
- Medium-sized C project
  - 94 458 lines of code
  - 1 328 functions
- Analysed 73.42% of the functions

## Use case: Xrdp

- Graphical login to remote machines using RDP
- Medium-sized C project
  - 94 458 lines of code
  - 1 328 functions
- Analysed 73.42% of the functions
- 33 Convertible functions

## Use case: Xrdp

- Graphical login to remote machines using RDP
- Medium-sized C project
  - 94 458 lines of code
  - 1 328 functions
- Analysed 73.42% of the functions
- 33 Convertible functions
- 2 Parametric automata

# Manual verification

---

- Introduce dead code in xrdp



- Introduce dead code in xrdp
- 7 different types of dead code

- Introduce dead code in xrdp
- 7 different types of dead code
- Test suite with 115 tests

## Conclusion

---

# Conclusion

- The proposed approach is capable of identifying dead code

# Conclusion

- The proposed approach is capable of identifying dead code
- No false negatives

# Conclusion

- The proposed approach is capable of identifying dead code
- No false negatives
- Need for a different compiler

# Conclusion

- The proposed approach is capable of identifying dead code
- No false negatives
- Need for a different compiler
- Further optimizations to the code constraints should be considered