Do More Text Views Help? A Leakage-Aware Evaluation of Text Representations for Sequential Recommendation

Anonymous Author(s)

Abstract

Text features are widely used to enrich sequential recommenders, but comparisons of lexical TF-IDF against TF-anchored LLM augmentations (single-view TF+LLM or multi-prompt TF+MV) are often conducted under evaluation protocols that permit temporal overlap. We conduct a leakage-aware controlled study of ID-only, cutoff-fit TF-IDF, TF+LLM (a single Qwen2.5-7B view added to the TF-IDF base), and TF+MV (four prompt views added to the TF-IDF base) under full-ranking global temporal splitting (GTS) on three Amazon datasets, using GTS-Last as the primary protocol, GTS-Random as a robustness check, and clean leave-one-out (LOO) as a contrast. Three findings emerge. First, evaluation protocol changes conclusions: across the evaluated settings, text consistently improves over ID-only on warm targets, but the relative ordering of TF-IDF, TF+LLM, and TF+MV changes across Last, Random, and LOO, even when Last and Random evaluate the same trained checkpoints. Second, no text representation is robustly dominant across temporal windows; temporal shift reduces absolute performance while preserving near-ties among text variants. Third, additional prompt views provide limited marginal value because they are highly redundant: inter-view CKA reaches 0.82–0.94, the concatenated representation uses only 53–55% of its nominal effective rank, and leave-one-view-out has negligible downstream effect. In contrast, TF-IDF is geometrically distinct from LLM views (CKA $\approx$ 0.19), suggesting a potentially complementary lexical–semantic axis that is not captured by adding more prompt views. These results suggest that evaluation protocol and representation redundancy should be diagnosed before attributing gains to increasingly complex LLM text pipelines.

CCS Concepts

• **Information systems** → **Recommender systems**; *Content ranking*.

Keywords

Sequential Recommendation, Text Features, Temporal Evaluation, Multi-View Redundancy, Leakage-Aware Protocol

1 Introduction

Sequential recommendation predicts a user's next item from historical interactions [**?** **?** **?**]. Item text—titles, descriptions, and LLM-generated semantics—is a standard way to enrich ID embeddings and enable cross-domain transfer [**?** **?**]. A natural working hypothesis is that *richer text always helps*: LLM embeddings should beat bag-of-words, and multiple prompt-based views should beat a single view.

This hypothesis is widely held. Recent work shows that pretrained language representations can improve text-enhanced recommendation and transferability [**?** **?** **?**], feature-level attention exploits item attributes and text [**?**], and multi-view prompt strategies are increasingly adopted to capture complementary item facets such as function, audience, and style. Practitioners building production recommenders face a concrete decision: should they invest in LLM inference and multi-prompt pipelines for text features, or does a lightweight bag-of-words baseline suffice? The answer depends critically on how the comparison is evaluated—a consideration that is seldom examined in text-enhanced recommendation papers.

This hypothesis rests on fragile evaluation foundations. Most text-enhanced sequential recommenders are validated with leave-one-out (LOO) splits that, as shown by **?**] and **?**], allow temporal overlap between training and test, yielding higher absolute metrics and potentially distorting model comparisons. In a deployment scenario, a recommender must predict items that a user will interact with *in the future*, not reconstruct a randomly held-out historical interaction. Global temporal split (GTS) better simulates this deployment constraint, but introduces additional design choices: the *target-selection mode* (Last, Random, Successive, or All interactions per user in the test window) itself changes effective task difficulty and can alter model rankings [**?**]. Prior work has studied split effects in general [**?** **?**]; we show that these effects are *specifically decisive* for the TF-IDF vs. TF+LLM vs. TF+MV comparison.

Text features also require preprocessing—vocabulary construction, IDF weighting, SVD projection, and LLM embedding whitening—each of which must respect the temporal boundary. If these statistics are computed on the full item set (including future items), the resulting features carry information unavailable at training time, introducing a form of leakage orthogonal to the train/test split itself. We therefore enforce strict *cutoff-fit* controls throughout: all text preprocessing is fit only on items appearing before the training cutoff.

We compare five variants—ID, TF-IDF, TF+LLM, TF+MV, and an adapted UniSRec baseline [**?**]—on three Amazon datasets under GTS-Last (primary), GTS-Random (robustness check), and clean LOO (contrast), plus an equal-horizon Early temporal window. We name variants by their full feature composition: the LLM-based variants *augment* the lexical TF-IDF base rather than replace it; a base-free LLM-only variant is evaluated separately in Section 7. We diagnose multi-view behavior with CKA [**?**], effective rank [**?**], and leave-one-view-out (LOVO).

Research questions.

RQ1 *Protocol effect.* Do clean LOO, GTS-Last, and GTS-Random change the absolute gains and relative ranking of TF-IDF, TF+LLM, and TF+MV?

RQ2 *Temporal robustness.* Can the conclusions drawn under the Main temporal window (80% cutoff) survive when the training window shrinks (Early, 60% cutoff)?

RQ3 *Multi-view redundancy.* Why do four prompt views (TF+MV) not reliably outperform a single view (TF+LLM) or even TF-IDF alone, and where does potential complementarity lie?

Contributions.

(1) A leakage-aware comparison on three datasets showing that evaluation protocol changes text-representation rankings. Within GTS, Last vs. Random on the same trained checkpoints yields different winners (**target effect**); switching from GTS to LOO changes both training data and targets (**split effect**). Text consistently beats ID, but *which* text is best is protocol-sensitive.

(2) Cross-window evidence that no single text variant dominates: under a matched-protocol equal-horizon Early window (60% cutoff, same valid/test span as Main), absolute MRR drops and the Main-window ranking is not preserved, yet text variants remain within 0.001 of each other.

(3) A triangulated redundancy analysis (CKA + effective rank + LOVO) spanning raw 3584-d Qwen hidden states through 64-d post-whitening, jointly explaining limited multi-view gains, while identifying lexical–semantic dissimilarity (TF vs. LLM, CKA 0.18–0.20) as a potential complementarity axis.

2 Related Work

Text-enhanced sequential recommendation. Early systems fused bag-of-words or review text with collaborative filtering [**?** **?**]. Modern approaches encode titles and descriptions with pretrained language models for cross-domain transfer [**?** **?** **?** **?**]. UniSRec learns transferable item representations from text and adapts them via a lightweight MoE [**?**]; VQ-Rec quantizes textual embeddings for transfer [**?**]; P5 casts recommendation as language modeling [**?**]; TALLRec aligns LLMs to ranking via instruction tuning [**?**]. These systems typically report LOO or loosely specified temporal protocols. We do *not* propose a new architecture; we ask whether stronger text encoders and more views remain advantageous once temporal leakage is controlled under a fixed backbone.

LLM-based item representations. Beyond architecture papers, a growing practice is to treat LLM embeddings as drop-in item features—either as a single view (title/description) or as multiple prompt-conditioned views that supposedly capture complementary facets (function, audience, style). This practice is motivated by the intuition that different prompts can elicit diverse semantic aspects of an item (e.g., "describe the function" vs. "describe the target audience"), thereby increasing feature coverage. However, when all views are produced by the *same* pretrained encoder applied to the *same* item text, the diversity of the resulting representations depends on how much the encoder's internal representations actually change in response to different instructions—a question that has received little empirical attention in the recommendation literature. Our study isolates this representation choice from architectural novelty: the same SASRec backbone and fusion pipeline are held fixed while only the text source changes (TF-IDF alone, TF+LLM, or TF+MV).

Evaluation protocols and temporal leakage. Sampled metrics distort rankings [**?**]; LOO vs. time-based splits change absolute scores and can alter model selection [**?** **?** **?**]. **?**] showed that seemingly minor protocol choices can cause large shifts in relative rankings of sequential models. Within GTS, target-selection mode matters: **?**] show that Successive best approximates online next-item prediction but is expensive; Last is a deterministic low-cost proxy; Random has the highest rank-correlation with Successive (we average three sampling seeds because Random is non-deterministic); and All packs multiple items into one ground-truth set, introducing task mismatch and the weakest correlation with Successive. Beyond sequential recommendation, the impact of temporal protocols has also been documented in session-based [**?**] and general collaborative filtering settings [**?**], confirming that protocol sensitivity is not a niche issue but a systemic concern across recommendation paradigms. We specialize this finding to text representations: protocol changes conclusions *precisely because* TF-IDF, TF+LLM, and TF+MV respond differently to distribution shift. Matching validation and test target modes (both Last, or both Random) is also recommended for reliable model selection [**?**]; our Early-window experiments keep this alignment.

Multi-view learning and representation redundancy. Multi-view theory holds that views must be *useful and complementary*; more views do not guarantee benefit [**?**]. In computer vision, **?**] introduced CKA (Centered Kernel Alignment) to measure representational similarity of Gram structures across network layers and architectures; it can detect structural redundancy even when instance-level pairwise cosine is moderate or near zero. In NLP, **?**] revealed that contextual word embeddings from different layers of the same pretrained model are highly anisotropic and occupy a narrow cone in embedding space, a form of geometric redundancy. Effective rank (the entropy of normalized singular values) [**?**] provides a complementary diagnostic, quantifying how much of a representation's nominal dimensionality is actually used. These tools have been applied to analyze network depth [**?**] and embedding quality [**?**], but to our knowledge have not been jointly deployed to diagnose *multi-prompt* redundancy in recommendation. We combine CKA, effective rank, and LOVO—not any single measure alone—to explain limited multi-view gains.

Information geometry of embeddings. Singular-value concentration and anisotropy are known failure modes of pretrained text embeddings [**?**]. When multiple views are generated from the same encoder, these geometric properties propagate: each view inherits its similar spectral structure, and concatenation does not proportionally expand the effective subspace. Our effective-rank analysis connects this literature to sequential recommendation: concatenating four prompt views that share the same encoder yields ER/dim $\approx$0.53, whereas a lexical TF-IDF SVD of the same dimension retains ER/dim $\approx$0.98.

3 Controlled Study Setup

3.1 Temporal Protocols

GTS-Last (primary). Interactions are globally ordered by timestamp (RecBole TS [**?**]). Main uses the first 80% for training, the next 10% for validation, and the last 10% for testing. Early uses the first 60% for training, the next 10% for validation, and the next 10% for testing; the final 20% is unused, so the evaluation window is shifted earlier while validation/test horizon lengths remain fixed. After sequential augmentation, each user contributes only their chronologically last test interaction (one target per user)—the deterministic last-item proxy studied by **?**].

GTS-Random (robustness check). Same checkpoints; each user contributes one uniformly random test interaction. We average over three target-sampling seeds (42, 123, 456) for stability; cross-seed std per checkpoint is 0.001–0.003. Random has the highest rank-correlation with Successive [**?**] and serves as a cross-check.

Clean LOO (contrast). Per-user leave-one-out with no global time cutoff: for each user, all but the final two interactions are used for training, the penultimate interaction for validation, and the final interaction for test (RecBole LS split). Included only to quantify the protocol gap; *not* used for primary conclusions.

GTS-All (appendix). All post-cutoff targets per user; relegated to Appendix A due to task-mismatch concerns [**?**].

Leakage controls. TF-IDF vocabulary/IDF, SVD projection, and LLM center/whitening are fit only on items appearing before the training cutoff. Evaluation filters users with ≥ 5 training interactions. Main tables report *warm-target* results: the test target must belong to the training-time item catalog, which is also the candidate set at inference. Last and Random are evaluated on the *same eligible-user set* per dataset (users with at least 5 training interactions and a test-window interaction: Beauty 4,520, Toys 4,873, Grocery 4,152); the two modes differ only in which target interaction is selected. Because the warm filter applies to the *selected* target, the warm sub-cohort differs slightly between modes (e.g., Beauty: 3,137 warm users under Last vs. 3,054–3,083 across Random sampling seeds). To confirm that this second-order difference does not drive our conclusions, Appendix D restricts both modes to the intersection of their warm cohorts (users warm under Last *and* under Random): the method ordering is unchanged in every dataset and both modes, so Last-vs.-Random contrasts are target-selection effects on a fixed user population. All-target and unseen diagnostics appear in Appendix E.

3.2 Text Representations and Models

All variants share a SASRec [**?**] backbone (d=256, 2 layers, 2 attention heads).

- **ID**: ID embeddings only.
- **TF**: train-cutoff TF-IDF → SVD 256-d → lightweight projection head + InfoNCE alignment [**?**].
- **TF+LLM**: the TF-IDF base of TF *plus* a single Qwen2.5-7B [**?**] item embedding (train-cutoff centered and whitened); both sources are fused by the same pipeline.
- **TF+MV**: the TF-IDF base *plus* four prompt views (Description / Function / Audience / Style) → per-view 64-d projections → 256-d concatenation → shared projection.
- **UniSRec** [**?**]: the original UniSRec architecture (MoE adaptor over item-text embeddings) trained from scratch on each dataset with no cross-domain pretraining; for leakage parity, its item-text inputs are replaced by the same cutoff-fit whitened Qwen2.5-7B embeddings, under the identical evaluation filter. We therefore treat it as a *UniSRec backbone adapted to our cutoff-fit features*, not as the original pretrained UniSRec.

The variant names make the feature composition explicit: the LLM-based variants *augment* the lexical base rather than replace it, so RQ1 compares incremental augmentation of a fixed TF-IDF base, not three independent representation families. A base-free LLM-only variant is evaluated in Section 7. All text variants use two-phase training: Phase A (text-head warmup via InfoNCE), then Phase B (joint BPR [**?**] + InfoNCE fine-tuning). Hyperparameters and cutoff-fit preprocessing for the Early window are frozen from Main (no re-tuning).

3.3 Datasets

We evaluate on three Amazon review categories [**? ?**]. Tables use the short names Beauty, Toys, and Grocery:

- **Beauty**: 1.21M users, 259K items, 2.02M interactions.
- **Toys & Games**: 1.28M users, 336K items, 2.25M interactions.
- **Grocery & Gourmet Food**: 768K users, 172K items, 1.30M interactions.

Grocery is included as a same-platform replication of the Beauty/Toys protocol, not as evidence of domain diversity.

3.4 Evaluation Details

Full-ranking Hit@10, NDCG@10, MRR@10 [**?**]. Main tables: MRR@10, mean±sample-std over 3 seeds (42, 2024, 2026); NDCG and Hit are reported as secondary metrics. All runs on a single NVIDIA RTX 5090; per-model training: 15–65 min.

4 RQ1: Protocol Changes Rankings

Table 1 and Figure 1 report the protocol contrast. No text representation wins everywhere; instead, the relative ordering shifts with the target-selection protocol:

- **GTS-Last**: among the controlled SASRec-based variants, point estimates favor TF+MV on Beauty and Grocery (.0064 / .0058); on Toys TF+MV ≈ TF (.0042 / .0040), with all text margins often within one std (Table 3); the adapted UniSRec baseline is strongest on Grocery (.0107).
- **GTS-Random** (3 sample-seed avg): TF leads on Toys (.0113 vs. TF+MV .0108, within one std of TF+MV); Beauty is a tie (TF .01239, TF+MV .01244, both round to .0124); Grocery is a tie (TF .0087, TF+MV .0089).
- **LOO**: absolute MRR is 4–7× higher than GTS-Last; ranking becomes TF+LLM ≈ TF+MV ≈ TF.

Last vs. Random is a **target-selection** effect on the same trained GTS checkpoints; LOO vs. GTS is a **split/training-protocol** effect (different training data and models).

Table 1: Protocol contrast — warm-target MRR@10 (3 training-seed mean±std; users with ≥ 5 training interactions; GTS-Random additionally averaged over 3 target-sampling seeds). Bold: highest value in the row (exact ties both bold). UniSRec is an adapted external baseline and is strongest on Grocery. Among the SASRec-based variants: Last favors TF+MV on Beauty/Grocery (Toys TF+MV ≈ TF); Random: TF ≈ TF+MV; LOO: TF+LLM ≈ TF+MV ≈ TF.

Dataset	Protocol	ID	TF	TF+LLM	TF+MV	UniSRec
Beauty	GTS-Last	.0032±.0006	.0053±.0004	.0060±.0004	**.0064**±.0003	.0052±.0002
	GTS-Rand	.0074±.0005	**.01239**±.0002	.01201±.0002	**.01244**±.0002	.0096±.0001
	LOO	.0175±.0004	.0251±.0002	**.0254**±.0004	.0253±.0004	.0239±.0002
Toys	GTS-Last	.0031±.0002	.0040±.0005	.0035±.0002	**.0042**±.0006	.0040±.0008
	GTS-Rand	.0076±.0002	**.0113**±.0004	.0108±.0007	.0108±.0009	.0085±.0003
	LOO	.0152±.0005	.0247±.0006	**.0258**±.0012	**.0258**±.0028	.0196±.0010
Grocery	GTS-Last	.0030±.0012	.0046±.0006	.0047±.0005	.0058±.0007	**.0107**±.0002
	GTS-Rand	.0050±.0012	.0087±.0011	.0076±.0004	.0089±.0008	**.0121**±.0002




Figure 1: Protocol contrast on Beauty and Toys. GTS-Last/Random: warm MRR@10 (3 training seeds; Random further averaged over 3 target-sampling seeds); LOO is clean leave-one-out, shown for contrast only. Bar heights are *point estimates*; text-variant gaps within one seed-level std should be read as ties (≈), not as a deterministic winner. Absolute scores and rankings shift with the protocol: LOO is 4–7× higher than Last, and among the text variants the leading method changes between Last, Random, and LOO (e.g., Toys Last TF+MV ≈ TF > TF+LLM > ID; LOO TF+LLM ≈ TF+MV ≈ TF; per-row orderings in Table 1).

A plausible account of the LOO gap. The 4–7× higher absolute scores under LOO are not merely an additive shift; they also change the relative ordering among text methods. LOO permits temporal overlap: a user's training interactions include items from the same time period as the test target, effectively allowing the model to "memorize" co-occurrence patterns that would not exist under a strict temporal cutoff. A plausible explanation is that this overlap disproportionately benefits representations capturing fine-grained semantic similarity (TF+LLM and TF+MV), because overlapping items provide richer co-occurrence signal for semantic features than for lexical ones. Under GTS, where training and evaluation interactions are separated by a global temporal cutoff, this advantage vanishes and the broader lexical coverage of TF-IDF becomes competitive.

Table 2: GTS-Last warm NDCG@10 and Hit@10 (3-seed mean±std). Bold: highest value in the row (same rule as Table 1). Among the SASRec-based variants, NDCG agrees with MRR. UniSRec is strongest on Hit@10 (all three datasets) and on Grocery NDCG.

Dataset	Metric	ID	TF	TF+LLM	TF+MV	UniSRec
Beauty	NDCG	.0047±.0007	.0074±.0006	.0080±.0009	**.0087**±.0003	.0081±.0003
	Hit	.0098±.0013	.0146±.0013	.0146±.0029	.0167±.0011	**.0180**±.0007
Toys	NDCG	.0046±.0004	.0056±.0006	.0046±.0002	.0057±.0011	**.0066**±.0013
	Hit	.0098±.0013	.0108±.0011	.0084±.0004	.0108±.0027	**.0154**±.0030
Grocery	NDCG	.0048±.0019	.0062±.0004	.0063±.0005	.0077±.0007	**.0160**±.0003
	Hit	.0107±.0041	.0117±.0009	.0117±.0007	.0136±.0007	**.0338**±.0007

Table 3: Per-seed GTS-Last warm MRR@10 (seeds 42 / 2024 / 2026). Variance is visible; TF+MV's lead is small and seed-dependent.

Dataset	Seed	ID	TF	TF+LLM	TF+MV	UniSRec
Beauty	42	.0038	.0049	**.00627**	**.00629**	.0050
	2024	.0032	.0052	.0055	**.0066**	.0054
	2026	.0026	.0057	**.0063**	.0061	.0051
Toys	42	.0033	**.0045**	.0037	.0035	.0044
	2024	.0030	.0038	.0032	.0042	**.0045**
	2026	.0029	.0036	.0036	**.0048**	.0031

Why do Last and Random disagree? Under GTS-Last, each user's single evaluation target is their *chronologically last* test interaction; under GTS-Random, it is uniformly sampled from the test window. A text representation that "wins" under one target mode can "lose" under another, even with identical model weights. One plausible hypothesis is that Last over-represents recently popular or niche items while Random draws a broader mix, but we treat that only as an association: the solid claim is that changing target selection on the same checkpoints changes the winner. This is not an artifact of the two modes scoring slightly different warm cohorts: restricting both to their intersecting warm users preserves the pattern (Appendix D).

Implications. The *same checkpoints* (same trained weights), evaluated on the same eligible users, produce different winners when evaluated with Last vs. Random target selection—a protocol artifact of target choice. Claims of text-representation superiority are therefore unreliable without specifying the target mode. All text methods outperform ID-only under every protocol we evaluate (+13–100% relative under GTS-Last, wider under Random). Our data thus support a narrow claim (text beats ID) and not a broad one (a single best text representation).

UniSRec as external baseline. Under identical GTS-Last, min-5, and warm-target filters, UniSRec scores 0.0052 (Beauty) and 0.0040 (Toys), between ID and TF on Beauty and tied with TF on Toys, but it dominates on Grocery (0.0107, nearly 2× the next best). Table 2 shows that NDCG@10 largely agrees with MRR rankings under GTS-Last, while Hit@10 elevates UniSRec across all three datasets,

Table 4: Main (80% cutoff) vs. Early (60% cutoff) on Beauty — GTS-Last warm MRR@10 (3-seed mean±std). Early: first 60% train, next 10% valid, next 10% test (final 20% unused). Fusion and cutoff-fit embeddings matched to Main; hyperparameters frozen. The Main row matches Table 1. Point estimates: TF+MV on Main, TF-IDF on Early (within one std of TF+MV).

Window	TF	TF+LLM	TF+MV
Main	.0053±.0004	.0060±.0004	**.0064**±.0003
Early60-EQ	**.0042**±.0005	.0037±.0003	.0039±.0003

Table 5: All-target catalog-level context (valid→test, Main GTS), *not* a direct explanation of warm-target MRR. Unseen targets are absent from the train catalog and never enter the warm scores of Tables 1 and 4. Reported as associations with catalog shift, not causal claims.

Dataset	Unseen targets	Pop mean (V→T)	Pop median (V→T)
Beauty	31.9%	112.8 → 101.8	21 → 15
Toys	40.8%	144.7 → 119.1	18 → 11
Grocery	29.6%	87.3 → 76.9	16 → 12

Table 6: All-target popularity-bucket composition (valid→test, Main GTS; head ≥10, mid 3–9, low 1–2 train interactions). Catalog-level context only: unseen items are excluded by the warm filter and do not enter warm MRR.

Dataset	Split	Head	Mid	Low	Unseen
Beauty	Valid	63.1%	15.9%	9.7%	11.3%
	Test	56.6%	14.9%	10.7%	17.8%
Toys	Valid	60.1%	16.3%	10.6%	13.0%
	Test	52.3%	15.5%	11.0%	21.3%

so metric choice interacts with protocol. We therefore treat MRR as the primary ranking metric and report NDCG/Hit for completeness. UniSRec's apparent ranking is protocol-sensitive: also scoring users with fewer than 5 training interactions inflates GTS-Last MRR into the 0.02 range (Appendix F). The choice of minimum interaction threshold, candidate scope (warm vs. full), and target mode can each independently shift where an external baseline appears to rank.

5 RQ2: Temporal Robustness

To isolate the effect of training-window size from test-horizon length, Early uses the first 60% for training, the next 10% for validation, and the next 10% for testing; the final 20% is unused. Thus the evaluation window is shifted earlier while validation/test horizon lengths remain fixed (the same 10% spans as Main).

Table 4 reports GTS-Last warm MRR@10 for both windows under the same cutoff-fit protocol. Absolute scores drop from Main to Early for every variant. The within-window ranking is *not* invariant: point estimates favor TF+MV on Main and TF-IDF on Early (.0042 vs. TF+MV .0039 and TF+LLM .0037, within one std of




Figure 2: Representation analysis on Beauty (3 random item subsamples of 3,000 each, mean±std). (a) Pairwise CKA: LLM views show high mutual similarity (0.84–0.94); TF–LLM CKA is low (≈0.20). (b) Effective rank: 4-view concat 136/256 (53%) vs. TF-IDF 250/256 (98%).

Table 7: Inter-view CKA (3 subsamples of 3K items, mean±std). All LLM view pairs exceed 0.82; TF-IDF vs. any LLM view stays within 0.18–0.20.

View Pair	Beauty	Toys
Description–Function	.846 ± .001	.834 ± .001
Description–Audience	.860 ± .001	.856 ± .002
Description–Style	.914 ± .000	.904 ± .001
Function–Audience	.940 ± .000	.921 ± .001
Function–Style	.843 ± .001	.818 ± .002
Audience–Style	.859 ± .001	.838 ± .002
TF-IDF vs. LLM view (range)	.196–.201	.184–.189

TF+MV). All three remain within 0.001 of each other. TF-IDF also degrades less than TF+LLM/TF+MV when the cutoff recedes, so the Main-window "TF+MV slightly ahead" pattern does not survive as a temporal fact. The Main→Early drop in Table 4 is measured on warm targets only. Tables 5–6 provide all-target *catalog-level context* (unseen share, popularity) for the same global cutoffs; they are not a direct explanation of warm-MRR degradation, because unseen items never enter those scores (Appendix E).

No single text variant dominates once the temporal window is varied.

TF-IDF robustness under shift. Despite catalog shift, TF-IDF exhibits the smallest Main-to-Early drop among the three text variants (Table 4); we treat this as an empirical robustness observation rather than evidence for a causal mechanism. The catalog-level shift statistics (Tables 5–6) co-occur with the Main→Early drop but do not explain the warm ranking pattern.

6 RQ3: Why Limited Multi-View Gain

We address RQ3 with three complementary analyses, none of which is sufficient alone: CKA captures structural similarity but cannot by itself prove task-irrelevance [**?**], effective rank measures dimensionality utilization, and LOVO measures downstream impact.

Table 8: Effective rank (Beauty/Toys, 3 subsamples). 4-view concat occupies only 53–55% of its nominal dimensionality.

Representation	Dim	ER (Beauty)	ER (Toys)
Single LLM view (avg)	64	63.7 (99.5%)	63.6 (99.4%)
4-view concat	256	136.1 (**53.2%**)	141.2 (**55.2%**)
TF-IDF (SVD)	256	249.9 (97.6%)	251.4 (98.2%)

Table 9: Leave-one-view-out (LOVO; zero-mask, 3-seed mean) under GTS-Last warm, matching Table 1. Δ: warm MRR@10 change vs. the full 4-view model. Maximum |Δ| is 0.00032 (Style on Beauty).

Dataset	Full MRR	−Desc	−Func	−Aud	−Style
Beauty	.00636	−.00021	−.00030	−.00027	−.00032
Toys	.00417	−.00017	+.00005	−.00007	−.00025

(1) High inter-view CKA.. Table 7 and Figure 2(a) show that all six LLM view pairs have CKA ≥ 0.82 (Beauty 0.84–0.94; Toys 0.82–0.92). The four prompt views, generated from the same encoder applied to the same item text with different instructions, encode highly similar relational structures. In contrast, TF-IDF vs. any LLM view yields CKA 0.196–0.201 (Beauty) and 0.184–0.189 (Toys)—a qualitatively different regime indicating substantial representational dissimilarity.

(2) Pairwise cosine vs. CKA.. Mean pairwise cosine between prompt views is often moderate or near zero (e.g., Description–Function ≈ −0.01 on Beauty), while Function–Audience reaches ≈ 0.42. This does *not* contradict high CKA: cosine measures instance-level alignment of vectors, whereas CKA compares Gram-matrix geometry across the item set [**?**]. Views can have low average cosine yet still induce nearly isomorphic similarity structures, which is the regime we observe for prompt-based paraphrasing. We therefore treat CKA as the primary similarity diagnostic and use cosine only as a complementary check, never as standalone proof of redundancy.

(3) Low effective rank of concatenated views. Table 8 and Figure 2(b) show that concatenating four 64-d views into 256 dimensions yields effective rank of only 136 (Beauty) and 141 (Toys), occupying 53–55% of the available capacity. Nearly half the nominal dimensions carry redundant structure. TF-IDF at the same 256-d has effective rank ≥250 (97–98%), utilizing almost all capacity. Concatenating prompt views therefore expands the subspace far less than the dimension count suggests.

(4) Negligible LOVO impact. Table 9 shows that zeroing any single view has minimal downstream effect under GTS-Last warm: maximum |Δ| = 0.00032 (≈5% of the full TF+MV score). Full MRR matches Table 1's TF+MV column. Per-seed signs can flip, so we do not treat any prompt as uniquely necessary.

Where is redundancy already present? To disentangle prompt-induced from preprocessing-induced redundancy, we compare CKA at two stages: *pre-whitening* (SVD-projected + centered, 64-d per view, without ZCA whitening) and *post-whitening* (the final model-input embeddings). On Beauty, mean pairwise CKA is 0.96 ± 0.001 pre-whitening and 0.88 ± 0.001 post-whitening; on Toys, 0.96 ± 0.001 and 0.87 ± 0.001 respectively. CKA is *already extremely high before whitening* (Table 10): whitening *reduces* mean inter-view CKA by 0.08 (Beauty) and 0.10 (Toys), and raises concatenated effective rank from 99/256 (39%) to 136/256 (53%) on Beauty and from 104/256 to 140/256 on Toys.

Table 10: Pre- vs. post-whitening audit (3 item-subsamples, mean). CKA is already ≥0.94 before whitening; whitening lowers CKA and raises concat effective rank, so redundancy is not a whitening artifact. Subsamples are drawn independently of Table 8, hence the ±1 difference in the Toys post-whitening rank.

Dataset	Stage	Pairwise CKA	Concat ER/256
Beauty	Pre-whiten (SVD+center)	0.94–0.99	99 (39%)
	Post-whiten (TS fit)	0.84–0.94	136 (53%)
Toys	Pre-whiten (SVD+center)	0.94–0.98	104 (41%)
	Post-whiten (TS fit)	0.82–0.92	140 (55%)

To trace redundancy further upstream, we compute inter-view CKA directly on the raw 3584-d Qwen hidden states *before any SVD projection.* Mean pairwise CKA at 3584-d is 0.961 on Beauty and 0.963 on Toys (3-trial random subsample of 3000 items, $\sigma < 0.002$). Redundancy is therefore already present in the raw Qwen outputs before SVD or whitening under our prompt design, rather than an artifact of SVD truncation. We cannot separate encoder geometry from the shared item text or from limited prompt divergence: even at this stage the four views yield near-isomorphic relational structures. Whitening partially decorrelates the views but cannot remove this structural overlap. Expanding view dimensionality to 4×256 is thus *not* justified—the bottleneck is source redundancy, not projection capacity (Table 11).

Synthesis. The three diagnostics agree: prompt views encode overlapping semantics, which produces dimensionality collapse and negligible per-view contribution. The observed geometry is consistent with insufficient view complementarity for views derived from a single source via semantic paraphrasing [**?**]. The potential complementarity in our system lies between lexical TF-IDF and semantic LLM views (CKA 0.18–0.20), suggesting representational dissimilarity that is not harvested by naive multi-prompt stacking: the TF+MV model replicates similar semantic structures four times instead of further exploiting the lexical–semantic axis it already contains.

7 Discussion and Limitations

Why does TF-IDF alone match TF+MV?. Why can a bag-of-words representation match or exceed the four-view variant under GTS-Random? We see two contributing factors. First, TF-IDF captures *lexical diversity*: the vocabulary of product titles and descriptions spans tens of thousands of unique tokens, and SVD-projected TF-IDF retains nearly all available capacity (ER/dim ≈0.98; Table 8). Each dimension contributes distinct information. Second, the four LLM views suffer from *semantic homogeneity*: because the same

pretrained encoder processes the same item text with only minor instruction changes, the resulting representations share highly similar relational geometry (CKA 0.82–0.94). Concatenating four such views nominally quadruples dimensionality but effectively adds only ∼50% new capacity. TF-IDF does not capture richer semantics than an LLM, but its *geometric diversity per dimension* is far higher. This geometric diversity per dimension is a practical advantage under GTS-Random, where TF-IDF matches or exceeds TF+MV on warm targets (Table 1) even though the concatenated LLM views occupy only about half of their nominal rank (Table 8).

LLM-only (no TF-IDF base) ablation. Because TF+LLM and TF+MV augment the TF-IDF base, one may ask how much the LLM views achieve on their own. We train a variant using only a single Qwen2.5-7B view with *no* TF-IDF base (same architecture, same two-phase pipeline). Under the main protocol (GTS-Last, warm targets, users with ≥ 5 training interactions, train-catalog candidates), this LLM-only variant scores .0046 ± .0001 on Beauty and .0018 ± .0007 on Toys—below the TF+LLM column in Table 1 (.0060 / .0035) and below ID-only on Toys. The lexical base is therefore load-bearing, not a "free init": all of our text gains are gains of TF-IDF-anchored pipelines, which is why we name the variants TF+LLM and TF+MV rather than LLM and MV.

Single-view hybrid: dropping three of the four views. To test whether the lexical–semantic dissimilarity identified in RQ3 (TF–LLM CKA 0.18–0.20) is what carries the useful signal, we train a hybrid that keeps the TF-IDF base and a *single* LLM view inside the multi-view architecture (per-view projection + concatenation; no extra prompt views), under the same cutoff-fit protocol and training seeds as Table 1. Under GTS-Last warm, the hybrid scores .0070 ± .0006 (Beauty) and .0049 ± .0011 (Toys), vs. TF+MV .0064 ± .0003 / .0042 ± .0006; under GTS-Random (3 sampling seeds) it scores .0128 ± .0003 and .0114 ± .0008, vs. TF+MV .01244 ± .0002 / .0108 ± .0009. The hybrid thus matches or slightly exceeds the four-view model on both datasets under both target modes while using one prompt view instead of four; the margins are within roughly one seed-level std, so we read this as *no loss from dropping three views* plus a consistent small edge, not as a large additive gain. This is consistent with the redundancy analysis: extra prompt views add little beyond a single view, while the lexical–semantic pair carries the useful signal. Low TF–LLM CKA by itself licenses only *geometric dissimilarity*; the hybrid provides the ranking-level evidence.

Practitioner implications.

(1) Report text-representation comparisons under GTS with explicit target mode. LOO can reverse rankings and yield 4–7× higher absolute metrics.
(2) Start with cutoff-fit TF-IDF as a strong baseline. Under GTS-Random it stays within one std of TF+MV on all three datasets and leads on Toys; under GTS-Last on the Main window it may trail TF+LLM/TF+MV, but Table 4 shows that an earlier cutoff can reverse that ranking. Given its negligible preprocessing cost relative to LLM inference, TF-IDF should be the first text baseline evaluated.

Table 11: Recommendation-stage parameter count and online scoring cost (seed 42; *offline text encoding excluded*). TF+MV adds <1% parameters.

Model	Params (M)	ms/sample
ID / TF / TF+LLM / TF+MV	67.2 / 67.4 / 67.6 / 67.7	0.02
UniSRec	67.7	0.04

Beauty; Toys is ∼87M due to larger vocab (ranking identical).

(3) A single LLM view typically matches four prompt views; diagnose redundancy (e.g., via CKA and effective rank) before investing in multi-view pipelines.
(4) Adding more prompt views from the same encoder yields negligible gains. Geometric diversity between representation families (lexical TF-IDF vs. semantic LLM) is the more useful axis: in our runs, a TF-IDF + single-LLM-view hybrid matched or slightly exceeded TF+MV under both GTS-Last and GTS-Random. Such claims should be verified under GTS-Last/Random rather than assumed from low CKA or from GTS-All validation scores.
(5) Do not overclaim a single "best" text representation across protocols; report Last and Random (or Successive) side by side, as rankings can reverse between target modes.

Limitations.

- **Warm-target scope.** Our models lack content-only zero-shot fallback; warm-target evaluation is thus the fairest comparison, but it excludes 28–35% of eligible users' last test targets (and 30–41% of all post-cutoff targets).
- **Static metadata.** We use fixed product titles/descriptions; temporally evolving text (e.g., reviews, trending tags) could change the TF/LLM balance.
- **Amazon-only domain.** All three datasets are Amazon subcategories. Grocery is a same-platform replication, not a solution to domain diversity.
- **GTS-Random reproducibility.** We average GTS-Random over three target-sampling seeds (42, 123, 456). Cross-seed standard deviation of warm MRR@10 per checkpoint is 0.001–0.003, indicating moderate but non-negligible sensitivity to target sampling [**?**].
- **Redundancy locus.** Our redundancy audit spans three stages—raw 3584-d Qwen hidden states, 256-d SVD-projected, and 64-d post-whitening—showing that redundancy is already present in the raw Qwen outputs before SVD/whitening under our prompt design (Section 6). However, only a single LLM (Qwen2.5-7B) is tested, and we cannot isolate encoder geometry from shared item text or prompt similarity; other architectures or more divergent prompts may exhibit different inter-view structure.
- **Successive protocol. ?**] identify Successive—scoring every test interaction in chronological order—as the closest offline analogue of online next-item prediction, and treat Last/Random as cheaper proxies with high rank-correlation to it. We report Last and Random; full Successive scoring at sampled-user scale remains future work.

Cost analysis. Table 11 confirms multi-view failure is not a capacity issue: all variants have effectively the same recommendation-stage parameter budget and online scoring cost. The practical cost gap lies in *offline text encoding*, which the table deliberately excludes: cutoff-fit TF-IDF +SVD takes about a minute on CPU for the Beauty catalog (259K items, measured), whereas each Qwen2.5-7B view requires a one-time GPU inference pass over the catalog, and multi-view multiplies that pass by the number of prompts. Feature-side cost, not model-side cost, is where TF-IDF, TF+LLM, and TF+MV differ.

8 Conclusion

We conducted a leakage-aware controlled study of text representations for sequential recommendation, structured as an empirical investigation rather than a model-proposal paper. Three conclusions follow from our experiments.

(1) **Protocol matters.** The relative ordering of TF-IDF, TF+LLM, and TF+MV depends on the GTS target mode. Text features consistently outperform ID-only, but which text is best requires specifying the evaluation protocol. Among the SASRec-based variants under GTS-Last, point estimates favor TF+MV on Beauty and Grocery, while Toys is TF+MV ≈ TF (the adapted UniSRec baseline is strongest on Grocery); under GTS-Random, TF-IDF catches up and overtakes it on Toys, with no gap exceeding one std. This shift is driven entirely by target selection, not by model changes.

(2) **No text variant is consistently dominant.** Under a matched-protocol equal-horizon Early window (60% cutoff, same valid/test span as Main), absolute MRR drops and the Main ranking is not preserved (TF-IDF leads narrowly), yet text variants remain within 0.001 of each other. Text helps, but which text helps most depends as much on the evaluation window as on the representation.

(3) **Multi-view gains are limited by inter-view redundancy.** CKA, effective rank, and LOVO jointly show that prompt views encode overlapping semantics; potential complementarity lies between lexical and semantic features (CKA 0.18–0.20), not between different prompt instructions applied to the same encoder. Consistently, a hybrid that keeps the TF-IDF base and a single LLM view matches or slightly exceeds TF+MV under both GTS-Last and GTS-Random (Section 7): the prompt-view budget is better spent on the lexical–semantic pair than on additional prompts.

Text-enhanced sequential recommendation is increasingly treated as an LLM upgrade problem—more parameters, more prompts, and more views are assumed to monotonically improve quality. Our evidence suggests the community should first lock the temporal protocol, then diagnose representation redundancy, before investing in additional prompt views or fusion modules. The practical default under leakage-aware evaluation is: report GTS-Last (and Random as a check), keep cutoff-fit TF-IDF as a mandatory baseline, and treat multi-view LLM features as a hypothesis to be tested—not a free upgrade.

Future directions. Five questions remain open. (1) **Richer lexical–semantic fusion.** Our single-view hybrid matches or slightly exceeds TF+MV under GTS-Last/Random; whether more sophisticated fusion (e.g., gating, cross-attention) can turn the lexical–semantic pair into larger, significant gains remains open. (2) **Cross-architecture redundancy audit.** Our raw 3584-d audit confirms the redundancy locus in Qwen2.5-7B. Testing whether the same inter-view collapse holds for decoder-only vs. encoder-only LLMs (e.g., Mistral, BERT-large) would clarify whether this is a general transformer property or specific to the Qwen family. (3) **GTS-Successive evaluation** at sampled-user scale, to validate Last/Random as proxies for online next-item prediction [**?**]. (4) **Non-Amazon domains** with reliable timestamps, to test whether protocol sensitivity generalizes beyond product catalogs. (5) **Instruction-diverse prompts** that enforce semantic divergence (e.g., attribute extraction vs. sentiment summarization) to test whether complementarity can be engineered at the prompt level.

Ethical Considerations

This work uses public Amazon review datasets with no personally identifiable attributes beyond standard user/item IDs. Potential concerns include reinforcing popularity bias under temporal shift and inheriting biases from LLM-generated text features. We mitigate the former by reporting warm-target stratified diagnostics and the latter by treating multi-view LLM features as an empirical object of study rather than a recommended default. No human subjects were involved.

A GTS-All Results

Main tables use GTS-Last (one last target per user). GTS-All evaluates all post-cutoff targets (Beauty: 4,520 users → 12,001 samples, avg 2.65/user; Toys: 4,873 users → 13,186, avg 2.71/user).

Table 12: GTS-All warm MRR@10 (3-seed mean; cutoff-fit checkpoints for all columns). TF leads or ties TF+MV under All, unlike GTS-Last.

Dataset	ID	TF	TF+LLM	TF+MV	UniSRec
Beauty	.0156	**.02411**	.0237	**.02413**	.0180
Toys	.0118	**.0191**	.0180	.0184	.0139

Under GTS-All, TF leads or ties TF+MV on both datasets, closer to the GTS-Random picture than to GTS-Last, where TF+MV leads narrowly among the SASRec-based variants. Per **?**], All has the lowest rank-correlation with Successive and introduces task mismatch, which is why we relegate it to appendix and do not treat these rankings as a main-protocol result.

B Grocery Per-Seed Breakdown

Grocery replicates the Beauty/Toys pattern under the same search budget: among the SASRec-based variants, TF+MV leads narrowly on Last, and TF and TF+MV stay within one std of each other on Random. We treat it as same-platform replication, not a domain-diversity claim.

Table 13: Grocery warm MRR@10 per training seed under GTS-Last and GTS-Random (Random averaged over target-sampling seeds {42, 123, 456}**).**

Protocol	Seed	ID	TF	TF+LLM	TF+MV
GTS-Last	42	.0027	.0038	.0049	**.0052**
	2024	.0019	.0049	.0050	**.0058**
	2026	.0043	.0050	.0041	**.0065**
GTS-Rand	42	.0044	.0075	.0073	**.0088**
	2024	.0041	**.0095**	.0080	.0082
	2026	.0063	.0091	.0075	**.0097**

C GTS-Random Target-Sampling Seeds

Main-table GTS-Random numbers average three target-sampling seeds {42, 123, 456} on the same checkpoints (no retraining). Table 14 reports each seed after averaging the three training seeds. Cross-seed std of warm MRR@10 is typically 0.001–0.003; seed 456 is systematically lower, which is why a single Random seed would overstate TF's Beauty lead (0.0138 vs. 3-seed 0.01239).

Table 14: GTS-Random warm MRR@10 by target-sampling seed (mean over training seeds 42/2024/2026).

Dataset	Sample seed	ID	TF	TF+LLM	TF+MV	UniSRec
Beauty	42	.0081	**.0138**	.0133	.0134	.0098
	123	.0080	.0134	.0128	**.0141**	.0103
	456	.0063	**.0101**	.0099	.0098	.0087
Toys	42	.0096	**.0146**	.0140	.0141	.0103
	123	.0066	**.0091**	.0089	.0085	.0078
	456	.0065	**.0101**	.0095	.0098	.0075

D Last vs. Random on Intersecting Users

Last and Random score the same eligible users, but the warm filter applies to the *selected* target, so the two warm sub-cohorts do not coincide exactly (Section 3.1). In principle the Last-vs.-Random ranking differences could therefore be partly a cohort-composition artifact rather than a pure target-selection effect. We rule this out by re-scoring both modes on the *intersection* of their warm cohorts—users whose Last target *and* whose Random target both lie in the train catalog—using the same checkpoints and a single forward pass per checkpoint, so that per-user ranks are identical to those behind the main tables. The intersection retains 2,846–2,858 users on Beauty (63% of eligible), 2,651–2,686 on Toys (54%), and 2,671–2,678 on Grocery (64%), varying only with the Random sampling seed.

Table 15 reports warm MRR@10 on the intersection alongside the full warm cohorts of Tables 1 and 2. Two observations hold in all six dataset×mode blocks. First, restricting to the intersection changes absolute scores by at most .0014 (largest on Beauty Random, where dropping the Last-only warm users lowers TF from .0124 to .0110) and leaves the ordering of ID, TF-IDF, TF+LLM, and TF+MV untouched. Second, and more importantly, the Last→Random shifts we rely on survive on the identical user set: point estimates favor TF+MV under Last on Beauty and Grocery, with Toys TF+MV ≈ TF, whereas under Random TF-IDF closes to within one std on Beauty (.0110 vs. .0113) and Grocery (.0083 vs. .0087) and overtakes TF+MV on Toys (.0110 vs. .0105). Random also remains roughly twice as easy as Last for every variant. Both effects are thus attributable to target selection alone.

Table 15: Warm MRR@10 on intersecting users (warm under both Last and Random) vs. the full warm cohorts used in the main tables. Mean±std over 3 training seeds; Random additionally averages target-sampling seeds {42, 123, 456}**. Bold: best variant per dataset within each mode (comparing full-warm columns).**

		Last		Random	
Dataset	Variant	Intersect.	Full warm	Intersect.	Full warm
Beauty	ID	.0033±.0006	.0032±.0005	.0066±.0004	.0074±.0004
	TF-IDF	.0054±.0003	.0053±.0003	.0110±.0002	**.0124**±.0002
	TF+LLM	.0063±.0004	.0060±.0003	.0107±.0003	.0120±.0001
	TF+MV	.0065±.0003	**.0064**±.0002	.0113±.0002	**.0124**±.0002
Toys	ID	.0032±.0001	.0031±.0001	.0073±.0001	.0076±.0001
	TF-IDF	.0039±.0005	.0040±.0004	.0110±.0003	**.0113**±.0003
	TF+LLM	.0035±.0002	.0035±.0002	.0106±.0005	.0108±.0006
	TF+MV	.0040±.0004	**.0042**±.0005	.0105±.0008	.0108±.0008
Grocery	ID	.0031±.0010	.0030±.0010	.0047±.0010	.0050±.0010
	TF-IDF	.0049±.0005	.0046±.0005	.0083±.0010	.0087±.0009
	TF+LLM	.0050±.0004	.0047±.0004	.0071±.0002	.0076±.0003
	TF+MV	.0063±.0005	**.0058**±.0005	.0087±.0007	**.0089**±.0006

E All-Target and Cross-Attention

All-target evaluation. Including unseen test items (absent from train catalog) decreases absolute MRR uniformly but preserves ranking order. Unseen-target shares among all test targets: Beauty 31.9%, Toys 40.8%, Grocery 29.6%. These targets never enter the warm-target scores of the main tables; they quantify how much of the deployment-time traffic warm evaluation excludes, not why warm MRR degrades (Tables 5–6 are the same all-target catalog context). Without content-only zero-shot capability, all models score near-zero on unseen items; warm-target scope is the fairest comparison.

Cross-attention (negative result). A sequence-level cross-attention module attending to text-view features was tested but improves and degrades per-user performance roughly equally; it is excluded from the main method.

F UniSRec Detailed Results

UniSRec [**?**] is highly sensitive to the evaluation filter: when users with fewer than 5 training interactions are retained, its MRR@10 reaches 0.0204–0.0208 (Beauty) and 0.0162–0.0164 (Toys). Under the shared protocol (users with at least 5 training interactions):

[†]GTS-Random averaged over target-sampling seeds {42, 123, 456} (same protocol as Table 1). All three columns are warm-target MRR@10 on the same cutoff-fit checkpoints.

Dataset	GTS-All	GTS-Last	GTS-Random†
Beauty	.0180±.0001	.0052±.0002	.0096±.0001
Toys	.0139±.0003	.0040±.0008	.0085±.0003

Under fair comparison, UniSRec sits between ID and TF on Beauty MRR and ties TF on Toys, consistent with its use of a single LLM view without the alignment warmup that benefits our TF+LLM/TF+MV variants. On Hit@10 under GTS-Last, UniSRec is stronger (Table 2), suggesting backbone differences affect metrics differently.